

# TEST REPORT

**Application No.:** GZCR2506000909LM  
**Applicant:** SHENZHEN BETTERLIFE PHOTOELECTRIC TECHNOLOGY CO., LTD.  
**Address of Applicant:** 2nd Floor, Building C, Shitoushan Industrial Zone, Zhoushi Road, Shiyang Town, Baoan District, Shenzhen, Guangdong, China  
**Manufacturer:** SHENZHEN BETTERLIFE PHOTOELECTRIC TECHNOLOGY CO., LTD.  
**Address of Manufacturer:** 2nd Floor, Building C, Shitoushan Industrial Zone, Zhoushi Road, Shiyang Town, Baoan District, Shenzhen, Guangdong, China  
**Factory:** SHENZHEN BETTERLIFE PHOTOELECTRIC TECHNOLOGY CO., LTD.  
**Address of Factory:** 2nd Floor, Building C, Shitoushan Industrial Zone, Zhoushi Road, Shiyang Town, Baoan District, Shenzhen, Guangdong, China  
**Product Name:** Garden Light  
**Model No.:** MOD01RGB, MOD01RG, MOD01RB, MOD01GB, MOD24RGB, MOD24RG, MOD24RB, MOD24GB, MOD32RGB, MOD32RG, MOD32RB, MOD32GB, OD01RGB, OD01RG, OD01RB, OD01GB, OD24RGB, OD24RG, OD24RB, OD24GB, OD32RGB, OD32RG, OD32RB, OD32GB, MODX01RB, MODX01GB, MODX01RG, MODX707RG, MODX717RG, MODX727RG, MODX737RG, MODX747RG, MODX757RG, MODX767RG, MODX777RG, MODX787RG, MODX797RG, MH-R30, MH-R50, MH-H90 MODX01RG, MODX\*RG(\*=02-30)  
 OD01RG, OD02RG, OD06RG, OD08RG, OD12RG, OD16RG, OD18RG, OD22RG, OD24RG, OD26RG, OD28RG, OD32RG, OD36RG, OD38RG, ODX01RG, ODX02RG, ODX06RG, ODX08RG, ODX12RG, OD16XRG, ODX18RG, ODX22RG, ODX26RG, ODX28RG, ODX32RG, ODX36RG, ODX38RG, MODF01RB ♣  
 ♣ Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.  
**Standard(s):** 47 CFR Part 15, Subpart C 15.231  
**Date of Receipt:** 2025-06-24  
**Date of Test:** 2025-07-01 to 2025-07-28  
**Date of Issue:** 2025-08-18

<b>Test Result:</b>	<b>Pass*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.

*Ricky Liu*

Ricky Liu  
Manager





SGS-CSTC Standards Technical Services Co., Ltd.  
Guangzhou Branch Testing Center EEC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663  
 中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgs.com.cn  
 t (86-20) 82155555 sgs.china@sgs.com

Revision Record			
Version	Report No.	Date	Remark
01	GZCR250600090902	2025-08-18	Original

Authorized for issue by:				
				
		Michael Huang/Project Engineer		
				
		Vico Cui/Reviewer		



## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.231	N/A	47 CFR Part 15 Subpart C 15.203	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
20dB Bandwidth	47 CFR Part 15, Subpart C 15.231	ANSI C63.10 (2020) Section 6.9	47 CFR Part 15 Subpart C 15.231(c)	Pass
Radiated Emissions below 1GHz		ANSI C63.10 (2020) Section 6.4&6.5	47 CFR Part 15C Section 15.231(e) and 15.209	Pass**
Dwell Time (15.231(a))		ANSI C63.10 (2020) Section 7.5	47 CFR Part 15 Subpart C 15.231(a2)	Pass
Field Strength of the Fundamental Signal (15.231(b))		ANSI C63.10 (2020) Section 6.5	47 CFR Part 15 Subpart C 15.231(b)	Pass
Radiated Emissions above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15C Section 15.231(e) and 15.209	Pass**

\*\* : The EUT passed Radiated Emissions below 1GHz and Radiated Emissions above 1GHz tests after modifications.

### Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Guangzhou Branch (EMC Laboratory)

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663  
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn  
t (86-20) 82155555 sgs.china@sgs.com

### ♣ Declaration of EUT Family Grouping:

Model No.:

MOD01RGB, MOD01RG, MOD01RB, MOD01GB, MOD24RGB, MOD24RG, MOD24RB, MOD24GB, MOD32RGB, MOD32RG, MOD32RB, MOD32GB, OD01RGB, OD01RG, OD01RB, OD01GB, OD24RGB, OD24RG, OD24RB, OD24GB, OD32RGB, OD32RG, OD32RB, OD32GB, MODX01RB, MODX01GB, MODX01RGB, MODX707RG, MODX717RG, MODX727RG, MODX737RG, MODX747RG, MODX757RG, MODX767RG, MODX777RG, MODX787RG, MODX797RG, MH-R30, MH-R50, MH-H90  
MODX01RG, MODX\*RG(\*=02-30)

OD01RG, OD02RG, OD06RG, OD08RG, OD12RG, OD16RG, OD18RG, OD22RG, OD24RG, OD26RG, OD28RG, OD32RG, OD36RG, OD38RG, ODX01RG, ODX02RG, ODX06RG, ODX08RG, ODX12RG, OD16XRG, ODX18RG, ODX22RG, ODX26RG, ODX28RG, ODX32RG, ODX36RG, ODX38RG, MODF01RB

According to the declaration from the applicant, the electrical circuit design, layout, components used and internal wiring were identical for all models, with only difference being the model name.

Only the model MOD01RGB was tested in this report.



## 3 Contents

	Page
1 Cover Page .....	1
2 Test Summary .....	3
3 Contents .....	5
4 General Information .....	7
4.1 Details of E.U.T. ....	7
4.2 Description of Support Units .....	7
4.3 Measurement Uncertainty .....	8
4.4 Test Location .....	8
4.5 Test Facility .....	9
4.6 Deviation from Standards .....	9
4.7 Abnormalities from Standard Conditions .....	9
5 Equipment List .....	10
6 Radio Spectrum Technical Requirement .....	12
6.1 Antenna Requirement .....	12
6.1.1 Test Requirement: .....	12
6.1.2 Conclusion .....	12
7 Radio Spectrum Matter Test Results .....	13
7.1 20dB Bandwidth .....	13
7.1.1 E.U.T. Operation .....	13
7.1.2 Test Mode Description .....	13
7.1.3 Test Setup Diagram .....	13
7.1.4 Measurement Procedure and Data .....	14
7.2 Radiated Emissions below 1GHz .....	15
7.2.1 E.U.T. Operation .....	16
7.2.2 Test Mode Description .....	16
7.2.3 Test Setup Diagram .....	16
7.2.4 Measurement Procedure and Data .....	17
7.3 Dwell Time (15.231(a)) .....	20
7.3.1 E.U.T. Operation .....	20
7.3.2 Test Mode Description .....	20
7.3.3 Test Setup Diagram .....	20
7.3.4 Measurement Procedure and Data .....	21
7.4 Field Strength of the Fundamental Signal (15.231(b)) .....	22
7.4.1 E.U.T. Operation .....	22
7.4.2 Test Mode Description .....	22
7.4.3 Test Setup Diagram .....	23
7.4.4 Measurement Procedure and Data .....	23
7.5 Radiated Emissions above 1GHz .....	26
7.5.1 E.U.T. Operation .....	26
7.5.2 Test Mode Description .....	26
7.5.3 Test Setup Diagram .....	27



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)



7.5.4	Measurement Procedure and Data .....	27
8	Test Setup Photo .....	30
9	EUT Constructional Details (EUT Photos) .....	31



## 4 General Information

### 4.1 Details of E.U.T.

Power supply: DC 4V (Supply power for the LED POWER SUPPLY as below) for Light unit (Receiver)  
 Controller power (B/O): DC 3V = 1 X 3V"CR2025" button cell (Transmitter)  
 (1) LED POWER SUPPLY  
 Model: RKPO-UK0401000IP20-1  
 Input: AC 100-240V 50/60Hz 0.3A  
 Output: DC 4V, 1.0A, 4.0W  
 (2) LED POWER SUPPLY  
 Model: RKPO-DE0401000IP44-1  
 Input: AC 220-240V 50/60Hz 0.1A  
 Output: DC 4.0V, 1.0A, 4.0W

Cable(s): 2 Pins, AC input  
 2 wires x about 2m unscreened DC output cable.  
 (The LED POWER SUPPLY output cable to EUT).

Test Voltage: DC 4 V

Operation Frequency: 433.92 MHz

Channel Numbers: 1

Modulation Type: ASK

Antenna Type: PCB antenna

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

### 4.2 Description of Support Units

The EUT has been tested as an independent unit.



#### 4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
20dB Bandwidth	$\pm 0.274\%$
Radiated Emissions below 1GHz	$\pm 5.14\text{dB}$ (30MHz-1GHz; 3m) $\pm 4.90\text{dB}$ (30MHz-1GHz; 10m)
Dwell Time (15.231(a))	$\pm 0.029\%$
Field Strength of the Fundamental Signal (15.231(b))	$\pm 5.14\text{dB}$ (30MHz-1GHz; 3m) $\pm 4.90\text{dB}$ (30MHz-1GHz; 10m)
Radiated Emissions above 1GHz	$\pm 4.88\text{ dB}$ ( 1GHz-6 GHz) $\pm 5.06\text{ dB}$ (6GHz-18GHz) $\pm 5.30\text{dB}$ (18GHz-40GHz)
<p>Remark:</p> <p>The <math>U_{\text{lab}}</math> (lab Uncertainty) is less than <math>U_{\text{cisp}} ( \text{CISPR Uncertainty})</math> or <math>U_{\text{ETSI}} (\text{ETSI Uncertainty})</math>.</p> <p>Emission decision rule:</p> <ul style="list-style-type: none"> <li>– Compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit, marked as Pass in the report.</li> <li>– Non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit, marked as Fail in the report.</li> </ul>	

#### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,  
No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou,  
Guangdong, China 510663

Tel: +86 20 82155555

No tests were sub-contracted.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Guangzhou Branch EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663  
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn  
t (86-20) 82155555 sgs.china@sgs.com



#### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **FCC Recognized Accredited Test Firm(Registration No.: 486818)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

- **ISED (Registration No.: 4620B, CAB identifier: CN0052)**

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

- **VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)**

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

#### 4.6 Deviation from Standards

None

#### 4.7 Abnormalities from Standard Conditions

The EUT passed Radiated Emissions below 1GHz and Radiated Emissions above 1GHz tests after modifications.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Guangzhou Branch EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663  
中国·广东·广州高新技术产业开发区科学城科珠路198号

t (86-20) 82155555 www.sgsgroup.com.cn  
t (86-20) 82155555 sgs.china@sgs.com

## 5 Equipment List

20dB Bandwidth					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
MXA Signal Analyzer (10Hz-8.4GHz)	Agilent Technologies	N9020A	SEM004-10	2024-12-03	2025-12-02
MI CABLE	SGS-EMC	0.8M	EMC2136	2023-11-02	2025-11-01

Radiated Emissions below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
966 Anechoic Chamber	Shenzhen C.R.T	CRTSGSSAC966	EMC2230	2025-03-22	2028-03-21
EMI Test Receiver(1Hz-8GHz)	Rohde & Schwarz	ESW8	EMC2229	2024-12-03	2025-12-02
Amplifier(9k-1000MHz)	SONOMA	310	EMC2237	2024-12-03	2025-12-02
Trilog Broadband Antenna (25MHz-2GHz)	Schwarzbeck Mess-Elektronik	VULB 9168	EMC2238	2025-03-24	2027-03-23
Coaxial Cable	Mirco-COAX UTIFLEX ve	LA2-C125-8000	EMC2239	2024-12-04	2026-12-03
Test Software E3	Audix	Ver.6.191211	GZE100-81	N/A	N/A
Active Loop Antenna-RED	ETS-Lindgren	6502	EMC2190	2024-04-08	2026-04-07

Dwell Time (15.231(a))					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
MXA Signal Analyzer (10Hz-8.4GHz)	Agilent Technologies	N9020A	SEM004-10	2024-12-03	2025-12-02
MI CABLE	SGS-EMC	0.8M	EMC2136	2023-11-02	2025-11-01

Field Strength of the Fundamental Signal (15.231(b))					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
966 Anechoic Chamber	Shenzhen C.R.T	CRTSGSSAC966	EMC2230	2025-03-22	2028-03-21
EMI Test Receiver(1Hz-8GHz)	Rohde & Schwarz	ESW8	EMC2229	2024-12-03	2025-12-02
Amplifier(9k-1000MHz)	SONOMA	310	EMC2237	2024-12-03	2025-12-02
Trilog Broadband Antenna (25MHz-2GHz)	Schwarzbeck Mess-Elektronik	VULB 9168	EMC2238	2025-03-24	2027-03-23
Coaxial Cable	Mirco-COAX UTIFLEX ve	LA2-C125-8000	EMC2239	2024-12-04	2026-12-03
Test Software E3	Audix	Ver.6.191211	GZE100-81	N/A	N/A



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Guangzhou Branch (EMC Laboratory)

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663  
中国·广东·广州高新技术产业开发区科学城科珠路198号

t (86-20) 82155555 www.sgsgroup.com.cn  
t (86-20) 82155555 sgs.china@sgs.com

Radiated Emissions above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
1-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2024-10-14	2025-10-13
EMI Test Receiver (10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2024-09-02	2025-09-01
Chamber cable (Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2024-08-19	2026-08-18
Horn Antenna (1-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2025-05-13	2027-05-12
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2023-12-20	2026-12-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2025-06-03	2026-06-02



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Guangzhou Branch (CMAA, CNAS, EEC Laboratory)

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663  
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn  
t (86-20) 82155555 sgs.china@sgs.com

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

#### 6.1.2 Conclusion

15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement.

Antenna location: Refer to Internal photos



## 7 Radio Spectrum Matter Test Results

### 7.1 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.231(c)

Test Method: ANSI C63.10 (2020) Section 6.9

Limit:

Frequency range(MHz)	Limit
70-900	No wider than 0.25% of the center frequency
Above 900	No wider than 0.5% of the center frequency

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C


Humidity: 69.7 % RH

Atmospheric Pressure: 1008 mbar

#### 7.1.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Operation(433.92MHz):Keep the wireless remote controller EUT works normally.

#### 7.1.3 Test Setup Diagram





### 7.1.4 Measurement Procedure and Data



## 7.2 Radiated Emissions below 1GHz

Test Requirement 47 CFR Part 15C Section 15.231(e) and 15.209

Test Method: ANSI C63.10 (2020) Section 6.4&6.5

Test Distance: 3m

Limit:

For Restricted bands

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

For Other bands

Fundamental Frequency MHz	Field Strength of Fundamental (μV/m @ 3 m)	Field Strength of Harmonics and Spurious Emissions (μV/m @ 3 m)
40.66 to 40.70	2,250	225
70 to 130	1,250	125
130 to 174	**1,250 to 3,750	**125 to 375
174 to 260	3,750	375
260 to 470	**3,750 to 12,500	**375 to 1,250
Above 470	12,500	1,250
<b>Detector:</b>	Peak for pre-scan QP for 30MHz to 1000 MHz: 120 kHz resolution bandwidth Peak for Above 1 GHz: 1 MHz resolution bandwidth	

\*\* linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows:

for the band 130-174 MHz, uV/m at 3 meters = 56.81818(F) - 6136.3636;

for the band 260-470 MHz, uV/m at 3 meters = 41.6667(F) - 7083.3333.

The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.



The fundamental frequency of the EUT is 433.92 MHz

The limit for average or QP field strength dBuV/m for the fundamental emission= 80.83 dBuV/m

No fundamental is allowed in the restricted bands.

The limit for average field strength dBuV/m for the spurious emission=60.83 dBuV/m. Spurious in the restricted bands must be less than 60.83 dBuV/m or 15.209, whichever limit permits a higher field strength.

### 7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 24.8 °C


Humidity: 49.7 % RH

Atmospheric Pressure: 1008 mbar

### 7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Operation(433.92MHz):Keep the wireless remote controller EUT works normally.

### 7.2.3 Test Setup Diagram



## 7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.


Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 2) Scan from 9kHz to 1GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.





Test Mode: 00; Polarity: Horizontal




Site : 966 Chamber  
Job :  
Model :  
Power :  
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	63.983	27.75	18.37	0.43	32.77	13.78	40.00	-26.22	HORIZONTAL	QP
2	169.005	29.15	18.68	0.72	32.79	15.76	43.52	-27.76	HORIZONTAL	QP
3	325.596	30.51	20.02	1.01	32.87	18.67	46.02	-27.35	HORIZONTAL	QP
4	605.659	32.14	25.85	1.43	32.68	26.74	46.02	-19.28	HORIZONTAL	QP
5	833.317	31.98	29.14	1.68	31.54	31.26	46.02	-14.76	HORIZONTAL	QP
6	869.130	61.93	28.53	1.74	31.41	60.79	60.83	-0.04	HORIZONTAL	QP





Test Mode: 00; Polarity: Vertical



Site : 966 Chamber  
Job :  
Model :  
Power :  
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	43.506	26.36	19.53	0.36	32.78	13.47	40.00	-26.53	VERTICAL	QP
2	54.643	26.81	19.48	0.40	32.78	13.91	40.00	-26.09	VERTICAL	QP
3	163.182	29.27	19.01	0.71	32.78	16.21	43.52	-27.31	VERTICAL	QP
4	352.943	31.30	20.27	1.08	32.88	19.77	46.02	-26.25	VERTICAL	QP
5	742.259	32.77	27.60	1.58	31.72	30.23	46.02	-15.79	VERTICAL	QP
6	869.130	51.81	28.53	1.74	31.41	50.67	60.83	-10.16	VERTICAL	QP



### 7.3 Dwell Time (15.231(a))

Test Requirement 47 CFR Part 15, Subpart C 15.231(a2)

Test Method: ANSI C63.10 (2020) Section 7.5

Limit:

Device type	Limit
Manually operated transmitter	The switch automatically deactivate the transmitter within not more than 5 seconds of being released
Automatically activated transmitter	Cease transmission within 5 seconds after activation
Periodic transmissions to determine system integrity of transmitters used in security or safety applications	The total transmission time does not exceed 2 seconds per hour

#### 7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C

Humidity: 69.7 % RH


Atmospheric Pressure: 1008 mbar

#### 7.3.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
--------------------------	--------------	-------------

Final test	00	TX mode_Operation(433.92MHz):Keep the wireless remote controller EUT works normally.
------------	----	--

#### 7.3.3 Test Setup Diagram



### 7.3.4 Measurement Procedure and Data



## 7.4 Field Strength of the Fundamental Signal (15.231(b))

Test Requirement 47 CFR Part 15, Subpart C 15.231(b)

Test Method: ANSI C63.10 (2020) Section 6.5

Limit:

Fundamental Frequency MHz	Field Strength of Fundamental ( $\mu\text{V/m}$ @ 3 m)	Field Strength of Harmonics and Spurious Emissions ( $\mu\text{V/m}$ @ 3 m)
40.66 to 40.70	2,250	225
70 to 130	1,250	125
130 to 174	**1,250 to 3,750	**125 to 375
174 to 260	3,750	375
260 to 470	**3,750 to 12,500	**375 to 1,250
Above 470	12,500	1,250
<b>Detector:</b>	Peak for pre-scan	
	QP for 30MHz to 1000 MHz: 120 kHz resolution bandwidth	
	Peak for Above 1 GHz: 1 MHz resolution bandwidth	

\*\* linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows:

for the band 130-174 MHz,  $\mu\text{V/m}$  at 3 meters =  $56.81818(F) - 6136.3636$ ;

for the band 260-470 MHz,  $\mu\text{V/m}$  at 3 meters =  $41.6667(F) - 7083.3333$ .]

The fundamental frequency of the EUT is 433.92 MHz

The limit for average or QP field strength dB $\mu\text{V/m}$  for the fundamental emission = 80.83 dB $\mu\text{V/m}$

No fundamental is allowed in the restricted bands.

### 7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 25.6 °C

Humidity: 50.9 % RH

Atmospheric Pressure: 1008 mbar


### 7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
<b>Final test</b>	00	TX mode_Operation(433.92MHz):Keep the wireless remote controller EUT works normally.





### 7.4.3 Test Setup Diagram




### 7.4.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
  - For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
  - The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
  - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
  - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
  - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
  - If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
  - The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.
- Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor



Test Mode: 00; Polarity: Vertical




Site : 966 Chamber  
Job :  
Model :  
Power :  
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	433.065	60.95	22.32	1.19	32.93	51.53	46.02	5.51	VERTICAL	QP



Test Mode: 00; Polarity: Horizontal



Site : 966 Chamber  
 Job :  
 Model :  
 Power :  
 Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	433.065	70.55	22.32	1.19	32.93	61.13	46.02	15.11	HORIZONTAL	QP



## 7.5 Radiated Emissions above 1GHz

Test Requirement 47 CFR Part 15C Section 15.231(e) and 15.209

Test Method: ANSI C63.10 (2020) Section 6.6

Limit:

For Restricted bands

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 960	500	3
Remark: Radiated emission limits in this band is based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.		

For Other bands

Fundamental Frequency MHz	Field Strength of Fundamental (μV/m @ 3 m)	Field strength of spurious emissions (μV/m @ 3 m)
Above 470	12,500	1,250
<b>Detector:</b>	Peak for pre-scan	
	Peak for Above 1 GHz: 1 MHz resolution bandwidth	

### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 26.9 °C

Humidity: 65.3 % RH


Atmospheric Pressure: 1008 mbar

### 7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
<b>Final test</b>	00	TX mode_Operation(433.92MHz):Keep the wireless remote controller EUT works normally.



### 7.5.3 Test Setup Diagram



### 7.5.4 Measurement Procedure and Data

- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.


Remark:

- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.





Test Mode: 00; Polarity: Vertical




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1297.103	52.84	25.59	2.58	38.60	42.41	74.00	-31.59	VERTICAL	Peak
2	2065.729	47.61	26.74	3.15	37.80	39.70	74.00	-34.30	VERTICAL	Peak
3	2664.019	48.02	28.02	3.58	37.74	41.88	74.00	-32.12	VERTICAL	Peak
4	4456.315	45.24	30.87	4.61	37.45	43.27	74.00	-30.73	VERTICAL	Peak
5	7200.309	45.89	35.80	5.93	37.17	50.45	74.00	-23.55	VERTICAL	Peak
6	10698.510	36.34	40.39	7.35	37.05	47.03	74.00	-26.97	VERTICAL	Peak





Test Mode: 00; Polarity: Horizontal



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1297.103	53.64	25.59	2.58	38.60	43.21	74.00	-30.79	HORIZONTAL	Peak
2	2359.478	48.05	27.59	3.43	37.77	41.30	74.00	-32.70	HORIZONTAL	Peak
3	2694.998	48.06	28.10	3.60	37.73	42.03	74.00	-31.97	HORIZONTAL	Peak
4	4667.241	45.19	31.17	4.70	37.41	43.65	74.00	-30.35	HORIZONTAL	Peak
5	7541.114	45.85	36.75	6.04	37.19	51.45	74.00	-22.55	HORIZONTAL	Peak
6	10156.140	38.41	39.40	7.23	37.09	47.95	74.00	-26.05	HORIZONTAL	Peak



## 8 Test Setup Photo

Refer to Setup Photos for GZCR250600090902



## 9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for GZCR2506000909LM

- End of the Report -

