

RF Test Data for Bluetooth LE

(Conducted Measurements)

General Description of EUT	
Product Name:	MINI projector
Test Model:	P10
Sample ID:	202204-0018_01-02#
Environmental Conditions	
Temperature:	25℃
Relative Humidity:	55%
Test Voltage:	AC 120V
Test Engineer:	Huangjianping
Note: For a more detailed features description, please refer to the report TBR-C-202204-0018-21	

Contents


1. DTS Bandwidth.....	3
1.1. Test Result.....	3
1.2. Test Graphs	4
2. Occupied Channel Bandwidth.....	6
2.1. Test Result.....	6
2.2. Test Graphs	7
3. Maximum conducted output power.....	9
3.1. Test Result.....	9
3.2. Test Graphs	10
4. Maximum power spectral density	12
4.1. Test Result.....	12
4.2. Test Graphs	13
5. Band edge measurements	15
5.1. Test Result.....	15
5.2. Test Graphs	16
6. Conducted Spurious Emission.....	18
6.1. Test Result.....	18
6.2. Test Graphs	19
7. Duty Cycle	25
7.1. Test Result.....	25
7.2. Test Graphs	26
8. Emissions in Restricted Bands.....	28
8.1. Test Result.....	28
8.2. Test Graphs	29

1. DTS Bandwidth


1.1. Test Result

Test Mode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.67	2401.67	2402.34	0.5	PASS
		2440	0.66	2439.67	2440.33	0.5	PASS
		2480	0.66	2479.68	2480.34	0.5	PASS
BLE_2M	Ant1	2402	0.96	2401.45	2402.40	0.5	PASS
		2440	1.12	2439.45	2440.57	0.5	PASS
		2480	1.13	2479.44	2480.57	0.5	PASS


1.2. Test Graphs




BLE_1M_Ant1_2402




BLE_1M_Ant1_2440




BLE_1M_Ant1_2480



BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480

2. Occupied Channel Bandwidth


2.1. Test Result

Test Mode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.035	2401.497	2402.531	---	---
		2440	1.039	2439.493	2440.531	---	---
		2480	1.047	2479.485	2480.531	---	---
BLE_2M	Ant1	2402	2.074	2400.985	2403.059	---	---
		2440	2.062	2438.989	2441.051	---	---
		2480	2.07	2478.985	2481.055	---	---


2.2. Test Graphs




BLE_1M_Ant1_2402




BLE_1M_Ant1_2440




BLE_1M_Ant1_2480



BLE_2M_Ant1_2402



BLE_2M_Ant1_2440




BLE_2M_Ant1_2480


3. Maximum conducted output power

3.1. Test Result


Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-3.6	≤30	PASS
		2440	-3.78	≤30	PASS
		2480	-3.55	≤30	PASS
BLE_2M	Ant1	2402	1.69	≤30	PASS
		2440	1.26	≤30	PASS
		2480	1.31	≤30	PASS

3.2. Test Graphs






BLE_2M_Ant1_2402



BLE_2M_Ant1_2440




BLE_2M_Ant1_2480

4. Maximum power spectral density


4.1. Test Result

Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-18.66	≤8.00	PASS
		2440	-19.07	≤8.00	PASS
		2480	-19.21	≤8.00	PASS
BLE_2M	Ant1	2402	-15.38	≤8.00	PASS
		2440	-15.16	≤8.00	PASS
		2480	-16.15	≤8.00	PASS


4.2. Test Graphs




BLE_1M_Ant1_2402




BLE_1M_Ant1_2440




BLE_1M_Ant1_2480



BLE_2M_Ant1_2402



BLE_2M_Ant1_2440




BLE_2M_Ant1_2480

5. Band edge measurements


5.1. Test Result

Test Mode	Antenna	ChName	Channel	Ref.Level[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	-3.87	-48.52	≤ -23.87	PASS
		High	2480	-3.84	-45.91	≤ -23.84	PASS
BLE_2M	Ant1	Low	2402	1.37	-30.5	≤ -18.63	PASS
		High	2480	0.95	-46.28	≤ -19.05	PASS


5.2. Test Graphs




BLE_1M_Ant1_Low_2402



BLE_1M_Ant1_High_2480



BLE_2M_Ant1_Low_2402




BLE_2M_Ant1_High_2480

6. Conducted Spurious Emission


6.1. Test Result

Test Mode	Antenna	Channel	Freq. Range [MHz]	Ref. Level [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	-3.99	-3.99	---	PASS
			30~1000	-3.99	-52.62	≤-23.99	PASS
			1000~26500	-3.99	-37.34	≤-23.99	PASS
		2440	Reference	-4.23	-4.23	---	PASS
			30~1000	-4.23	-53.59	≤-24.23	PASS
			1000~26500	-4.23	-36.96	≤-24.23	PASS
		2480	Reference	-3.98	-3.98	---	PASS
			30~1000	-3.98	-53.05	≤-23.98	PASS
			1000~26500	-3.98	-40.84	≤-23.98	PASS
BLE_2M	Ant1	2402	Reference	1.22	1.22	---	PASS
			30~1000	1.22	-53.69	≤-18.78	PASS
			1000~26500	1.22	-31.42	≤-18.78	PASS
		2440	Reference	0.83	0.83	---	PASS
			30~1000	0.83	-53.23	≤-19.17	PASS
			1000~26500	0.83	-33.28	≤-19.17	PASS
		2480	Reference	0.87	0.87	---	PASS
			30~1000	0.87	-52.97	≤-19.13	PASS
			1000~26500	0.87	-37.36	≤-19.13	PASS


6.2.Test Graphs



BLE_1M_Ant1_2402_0~Reference




BLE_1M_Ant1_2402_30~1000




BLE_1M_Ant1_2402_1000~26500




BLE_1M_Ant1_2440_0~Reference




BLE_1M_Ant1_2440_30~1000




BLE_1M_Ant1_2440_1000~26500



BLE_1M_Ant1_2480_0~Reference




BLE_1M_Ant1_2480_30~1000




BLE_1M_Ant1_2480_1000~26500



BLE_2M_Ant1_2402_0~Reference




BLE_2M_Ant1_2402_30~1000




BLE_2M_Ant1_2402_1000~26500




BLE_2M_Ant1_2440_0~Reference




BLE_2M_Ant1_2440_30~1000




BLE_2M_Ant1_2440_1000~26500



BLE_2M_Ant1_2480_0~Reference



BLE_2M_Ant1_2480_30~1000




BLE_2M_Ant1_2480_1000~26500

7. Duty Cycle


7.1. Test Result

Test Mode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Limit	Verdict
BLE_1M	Ant1	2402	0.42	0.63	66.67	---	---
		2440	0.42	0.63	66.67	---	---
		2480	0.42	0.63	66.67	---	---
BLE_2M	Ant1	2402	0.24	0.63	38.10	---	---
		2440	0.23	0.62	37.10	---	---
		2480	0.24	0.62	38.71	---	---


7.2.Test Graphs




BLE_1M_Ant1_2402




BLE_1M_Ant1_2440




BLE_1M_Ant1_2480



BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480