

## FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2A6T2-X96Q

### Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

### Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: *f* is frequency in MHz

\* = Power density limit is applicable at frequencies greater than 100 MHz

### Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: *f* = frequency in MHz

\* = Plane-wave equivalent power density

## MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

## Test Result of RF Exposure Evaluation

	Modes& Channel Freq. (MHz)	Tune up Produce power	Maximum peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/cm <sup>2</sup> )	Limit (mW / cm <sup>2</sup> )	Result
BLE	GFSK& HCH	4±1	5	3.1623	0.8395 (-0.76dBi)	0.0005	1	Pass
2.4G WIFI	802.11b&2 412	23±1	24	251.188 6	1.1324 (0.54dBi)	0.0566	1	Pass
5.2GWIFI	802.11a20 &5240	15±1	16	39.8107	1.2764 (1.06dBi)	0.0101	1	Pass
5.8GWIFI	802.11ax4 0&5755	14±1	15	31.6228	1.5136 (1.8dBi)	0.0095	1	Pass

BT+WIFI supported simultaneous transmission:

BLE+2.4GWIFI:  $\sum$  MPE Ratio = 0.0005/1+0.0566/1=0.0571≤1,

BLE+5GWIFI:  $\sum$  MPE Ratio = 0.0005/1+0.0101/1=0.0106≤1,

So passed.