

FCC TEST REPORT

FCC ID: 2A6T2-X98S500

Report Number : ZKT-220915L6883-01

Date of Test : Sep. 02, 2022 -- Sep. 28, 2022

Date of issue : Sep. 28, 2022

Total number of pages : 65

Test Result : PASS

Testing Laboratory : Shenzhen ZKT Technology Co., Ltd.

Address : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : SHENZHEN AMEDIA TECHNOLOGY CO., LTD

Address : Room 201, Building 2, Stech Park, Gaofeng community, Dalang Street, Longhua District, Shenzhen, China

Manufacturer's name : SHENZHEN AMEDIA TECHNOLOGY CO., LTD

Address : Room 201, Building 2, Stech Park, Gaofeng community, Dalang Street, Longhua District, Shenzhen, China

Test specification:

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2013
KDB558074 D0115.247 Meas Guidance v 05r02

Test procedure : /

Non-standard test method : N/A

Test Report Form No. : TRF-EL-112_V0

Test Report Form(s) Originator : ZKT Testing

Master TRF : Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name : TV Stick

Trademark : /

Model/Type reference : X98S500


Ratings : DC 5V from USB port or adapter

Testing procedure and testing location:


Testing Laboratory **Shenzhen ZKT Technology Co., Ltd.**

Address 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature).....: Alen He



Reviewer (name + signature).....: Joe Liu



Approved (name + signature) Lake Xie



Table of Contents

	Page
1. VERSION	5
2. TEST SUMMARY	6
2.1 TEST FACILITY	6
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 Test Setup Configuration	9
3.3 Support Equipment	9
3.4 Test Mode	10
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
4. EMC EMISSION TEST	13
4.1 Conducted emissions	13
4.1.1 POWER LINE CONDUCTED EMISSION Limits	13
4.1.2 TEST PROCEDURE	13
4.1.3 DEVIATION FROM TEST STANDARD	13
4.1.4 TEST SETUP	14
4.1.5 EUT OPERATING CONDITIONS	14
4.1.6 Test Result	15
4.2 Radiated emissions	17
4.2.1 Radiated Emission Limits	17
4.2.2 TEST PROCEDURE	17
4.2.3 DEVIATION FROM TEST STANDARD	18
4.2.4 TEST SETUP	18
4.2.5 EUT OPERATING CONDITIONS	19
4.2.6 TEST RESULTS	20
5. RADIATED BAND EMISSION MEASUREMENT	27
5.1 Test Requirement:	27
5.2 TEST PROCEDURE	27
5.3 DEVIATION FROM TEST STANDARD	28
5.4 TEST SETUP	28
5.5 EUT OPERATING CONDITIONS	28
5.6 TEST RESULT	29
6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	31
6.1 Limit	31
6.2 Test Setup	31
6.3 Test procedure	31
6.4 DEVIATION FROM STANDARD	31
6.5 Test Result	31
7. 20DB BANDWIDTH	43
7.1 Test Setup	43
7.2 Limit	43
7.3 Test procedure	43

7.4 DEVIATION FROM STANDARD	43
7.5 Test Result	43
8. MAXIMUM PEAK OUTPUT POWER	47
8.1 Block Diagram Of Test Setup	47
8.2 Limit.	47
8.3 Test procedure	47
8.4 DEVIATION FROM STANDARD	47
8.5 Test Result	47
9. HOPPING CHANNEL SEPARATION	48
9.1 Test Setup	48
9.2 Test procedure	48
9.3 DEVIATION FROM STANDARD	48
9.4 Test Result	48
10.NUMBER OF HOPPING FREQUENCY	50
10.1 Test Setup	50
10.2 Test procedure	50
10.3 DEVIATION FROM STANDARD	50
10.4 Test Result	51
11. DWELL TIME	53
11.1 Test Setup	53
11.2 Test procedure	53
11.3 DEVIATION FROM STANDARD	53
11.4 Test Result	54
12. ANTENNA REQUIREMENT	58
13. TEST SETUP PHOTO	59
14. EUT CONSTRUCTIONAL DETAILS	61

1. VERSION

Report No.	Version	Description	Approved
ZKT-220915L6883-01	Rev.01	Initial issue of report	Sep. 28, 2022

2. TEST SUMMARY

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
15.203/15.247 (c)	Antenna Requirement	PASS	
15.207	AC Power Line Conducted Emission	PASS	
15.247 (b)(1)	Conducted Peak Output Power	PASS	
15.247 (a)(1)	20dB Occupied Bandwidth	PASS	
15.247 (a)(1)	Carrier Frequencies Separation	PASS	
15.247 (a)(1)(iii)	Hopping Channel Number	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205/15.209	Radiated Emission	PASS	
15.247(d)	Band Edge	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street,
Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power conducted	$\pm 0.16\text{dB}$
3	Spurious emissions conducted	$\pm 0.21\text{dB}$
4	All emissions radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	TV Stick
Model No.:	X98S500
Hardware Version:	DM916_428_V1.1
Software Version:	SecureCRT
Sample(s) Status:	Engineer sample
Channel numbers:	79
Channel separation:	2402MHz~2480MHz
Modulation technology:	GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type:	FPC antenna
Antenna gain:	1.5dBi
Power supply:	DC 5V from USB port or adapter

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		


Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:


Test channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

3.2 Test Setup Configuration


Conducted Emission



Radiated Emission



Conducted Spurious



3.3 Support Equipment

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	adapter	HUAWEI	HW-100100C01	/	SDOC
2	PC	HP	HP40	/	SDOC


Item	Shielded Type	Ferrite Core	Length	Note
1	HDMI		20CM	
2	TYPR-C		50CM	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3.4 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	BT Test Tool 
Power level setup	<10dBm

3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	Oct. 18, 2021	Oct. 17, 2022
2	Spectrum Analyzer (1GHz-40GHz)	R&S	FSQ	100363	Oct. 17, 2021	Oct. 16, 2022
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	Oct. 18, 2021	Oct. 17, 2022
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	N/A	Oct. 17, 2021	Oct. 16, 2022
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	Oct. 17, 2021	Oct. 16, 2022
6	Loop Antenna	TESEQ	HLA6121	58357	Oct. 17, 2021	Oct. 16, 2022
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	060747	Oct. 17, 2021	Oct. 16, 2022
8	Amplifier (1GHz-26.5GHz)	Agilent	8449B	3008A00315	Oct. 18, 2021	Oct. 17, 2022
9	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Oct. 18, 2021	Oct. 17, 2022
10	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Oct. 18, 2021	Oct. 17, 2022
11	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Oct. 18, 2021	Oct. 17, 2022
12	ESG Signal Generator	Agilent	E4421B	N/A	Oct. 18, 2021	Oct. 17, 2022
13	Signal Generator	Agilent	N5182A	N/A	Oct. 22, 2021	Oct. 21, 2022
14	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	Oct. 17, 2021	Oct. 16, 2022
15	MWRF Power Meter Test system	MW	MW100-RPC B	N/A	Oct. 22, 2021	Oct. 21, 2022
16	D.C. Power Supply	LongWei	TPR-6405D	N/A	\	\
17	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	\	\
18	RF Software	MW	MTS8310	V2.0.0.0	\	\
19	Turntable	MF	MF-7802BS	N/A	\	\
20	Antenna tower	MF	MF-7802BS	N/A	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Oct. 22, 2021	Oct. 21, 2022
2	LISN	CYBERTEK	EM5040A	E185040014 9	Oct. 22, 2021	Oct. 21, 2022
3	Test Cable	N/A	C01	N/A	Oct. 18, 2021	Oct. 17, 2022
4	Test Cable	N/A	C02	N/A	Oct. 18, 2021	Oct. 17, 2022
5	EMI Test Receiver	R&S	ESCI3	101393	Oct. 17, 2021	Oct. 16, 2022
6	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	\	\

4. EMC EMISSION TEST

4.1 Conducted emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- The EUT was placed 0.1 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 Test Result

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1539	52.59	9.75	62.34	65.78	-3.44	QP	
2		0.1620	24.79	9.75	34.54	55.36	-20.82	AVG	
3		0.3420	19.49	9.86	29.35	49.15	-19.80	AVG	
4		0.3620	37.44	9.86	47.30	58.68	-11.38	QP	
5		1.5500	29.70	9.69	39.39	56.00	-16.61	QP	
6		1.8260	17.17	9.66	26.83	46.00	-19.17	AVG	
7		6.1380	28.32	9.64	37.96	60.00	-22.04	QP	
8		6.2260	14.00	9.63	23.63	50.00	-26.37	AVG	
9		15.6980	17.26	9.64	26.90	50.00	-23.10	AVG	
10		15.7500	30.46	9.64	40.10	60.00	-19.90	QP	
11		24.0780	28.96	9.47	38.43	60.00	-21.57	QP	
12		24.0780	16.55	9.47	26.02	50.00	-23.98	AVG	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor

4.2 Radiated emissions

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 Radiated Emission Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


4.2.6 TEST RESULTS

Between 9KHz – 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Horizontal
Test Voltage:	DC 5.0V	Test mode	BT



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 5.0V	Test mode	BT



Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

1GHz~25GHz

GFSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804	54.15	30.55	5.77	24.66	54.03	74.00	-19.97	Pk
V	4804	41.78	30.55	5.77	24.66	41.66	54.00	-12.34	AV
V	7206	54.56	30.33	6.32	24.55	55.10	74.00	-18.90	Pk
V	7206	40.83	30.33	6.32	24.55	41.37	54.00	-12.63	AV
V	9608	51.29	30.85	7.45	24.69	52.58	74.00	-21.42	Pk
V	9608	36.67	30.85	7.45	24.69	37.96	54.00	-16.04	AV
H	4804	56.32	30.55	5.77	24.66	56.20	74.00	-17.80	Pk
H	4804	41.51	30.55	5.77	24.66	41.39	54.00	-12.61	AV
H	7206	53.55	30.33	6.32	24.55	54.09	74.00	-19.91	Pk
H	7206	40.60	30.33	6.32	24.55	41.14	54.00	-12.86	AV
H	9608	49.77	30.85	7.45	24.69	51.06	74.00	-22.94	Pk
H	9608	37.79	30.85	7.45	24.69	39.08	54.00	-14.92	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882	56.03	30.55	5.77	24.66	55.91	74.00	-18.09	Pk
V	4882	39.50	30.55	5.77	24.66	39.38	54.00	-14.62	AV
V	7323	54.54	30.33	6.32	24.55	55.08	74.00	-18.92	Pk
V	7323	39.66	30.33	6.32	24.55	40.20	54.00	-13.80	AV
V	9764	51.94	30.85	7.45	24.69	53.23	74.00	-20.77	Pk
V	9764	38.94	30.85	7.45	24.69	40.23	54.00	-13.77	AV
H	4882	56.69	30.55	5.77	24.66	56.57	74.00	-17.43	Pk
H	4882	39.99	30.55	5.77	24.66	39.87	54.00	-14.13	AV
H	7323	54.34	30.33	6.32	24.55	54.88	74.00	-19.12	Pk
H	7323	39.66	30.33	6.32	24.55	40.20	54.00	-13.80	AV
H	9764	51.93	30.85	7.45	24.69	53.22	74.00	-20.78	Pk
H	9764	38.60	30.85	7.45	24.69	39.89	54.00	-14.11	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2480MHz									
V	4960	54.77	30.55	5.77	24.66	54.65	74.00	-19.35	Pk
V	4960	41.87	30.55	5.77	24.66	41.75	54.00	-12.25	AV
V	7440	52.82	30.33	6.32	24.55	53.36	74.00	-20.64	Pk
V	7440	39.02	30.33	6.32	24.55	39.56	54.00	-14.44	AV
V	9920	49.84	30.85	7.45	24.69	51.13	74.00	-22.87	Pk
V	9920	37.96	30.85	7.45	24.69	39.25	54.00	-14.75	AV
H	4960	55.22	30.55	5.77	24.66	55.10	74.00	-18.90	Pk
H	4960	39.29	30.55	5.77	24.66	39.17	54.00	-14.83	AV
H	7440	54.25	30.33	6.32	24.55	54.79	74.00	-19.21	Pk
H	7440	39.10	30.33	6.32	24.55	39.64	54.00	-14.36	AV
H	9920	52.01	30.85	7.45	24.69	53.30	74.00	-20.70	Pk
H	9920	38.95	30.85	7.45	24.69	40.24	54.00	-13.76	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

$\pi/4$ -DQPSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804	56.07	30.55	5.77	24.66	55.95	74.00	-18.05	Pk
V	4804	39.29	30.55	5.77	24.66	39.17	54.00	-14.83	AV
V	7206	53.68	30.33	6.32	24.55	54.22	74.00	-19.78	Pk
V	7206	39.52	30.33	6.32	24.55	40.06	54.00	-13.94	AV
V	9608	51.48	30.85	7.45	24.69	52.77	74.00	-21.23	Pk
V	9608	37.97	30.85	7.45	24.69	39.26	54.00	-14.74	AV
H	4804	56.64	30.55	5.77	24.66	56.52	74.00	-17.48	Pk
H	4804	39.78	30.55	5.77	24.66	39.66	54.00	-14.34	AV
H	7206	53.02	30.33	6.32	24.55	53.56	74.00	-20.44	Pk
H	7206	38.97	30.33	6.32	24.55	39.51	54.00	-14.49	AV
H	9608	52.00	30.85	7.45	24.69	53.29	74.00	-20.71	Pk
H	9608	37.91	30.85	7.45	24.69	39.20	54.00	-14.80	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882	53.92	30.55	5.77	24.66	53.80	74.00	-20.20	Pk
V	4882	42.00	30.55	5.77	24.66	41.88	54.00	-12.12	AV
V	7323	52.77	30.33	6.32	24.55	53.31	74.00	-20.69	Pk
V	7323	40.36	30.33	6.32	24.55	40.90	54.00	-13.10	AV
V	9764	50.21	30.85	7.45	24.69	51.50	74.00	-22.50	Pk
V	9764	36.61	30.85	7.45	24.69	37.90	54.00	-16.10	AV
H	4882	55.57	30.55	5.77	24.66	55.45	74.00	-18.55	Pk
H	4882	40.98	30.55	5.77	24.66	40.86	54.00	-13.14	AV
H	7323	53.94	30.33	6.32	24.55	54.48	74.00	-19.52	Pk
H	7323	39.90	30.33	6.32	24.55	40.44	54.00	-13.56	AV
H	9764	50.66	30.85	7.45	24.69	51.95	74.00	-22.05	Pk
H	9764	37.67	30.85	7.45	24.69	38.96	54.00	-15.04	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2480MHz									
V	4960	54.94	30.55	5.77	24.66	54.82	74.00	-19.18	Pk
V	4960	42.09	30.55	5.77	24.66	41.97	54.00	-12.03	AV
V	7440	53.13	30.33	6.32	24.55	53.67	74.00	-20.33	Pk
V	7440	40.43	30.33	6.32	24.55	40.97	54.00	-13.03	AV
V	9920	50.17	30.85	7.45	24.69	51.46	74.00	-22.54	Pk
V	9920	38.56	30.85	7.45	24.69	39.85	54.00	-14.15	AV
H	4960	55.40	30.55	5.77	24.66	55.28	74.00	-18.72	Pk
H	4960	41.54	30.55	5.77	24.66	41.42	54.00	-12.58	AV
H	7440	53.16	30.33	6.32	24.55	53.70	74.00	-20.30	Pk
H	7440	41.05	30.33	6.32	24.55	41.59	54.00	-12.41	AV
H	9920	50.52	30.85	7.45	24.69	51.81	74.00	-22.19	Pk
H	9920	38.20	30.85	7.45	24.69	39.49	54.00	-14.51	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

8-DPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804	56.20	30.55	5.77	24.66	56.08	74.00	-17.92	Pk
V	4804	39.92	30.55	5.77	24.66	39.80	54.00	-14.20	AV
V	7206	52.80	30.33	6.32	24.55	53.34	74.00	-20.66	Pk
V	7206	40.86	30.33	6.32	24.55	41.40	54.00	-12.60	AV
V	9608	50.80	30.85	7.45	24.69	52.09	74.00	-21.91	Pk
V	9608	37.21	30.85	7.45	24.69	38.50	54.00	-15.50	AV
H	4804	54.18	30.55	5.77	24.66	54.06	74.00	-19.94	Pk
H	4804	41.84	30.55	5.77	24.66	41.72	54.00	-12.28	AV
H	7206	53.73	30.33	6.32	24.55	54.27	74.00	-19.73	Pk
H	7206	38.94	30.33	6.32	24.55	39.48	54.00	-14.52	AV
H	9608	51.70	30.85	7.45	24.69	52.99	74.00	-21.01	Pk
H	9608	37.89	30.85	7.45	24.69	39.18	54.00	-14.82	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882	54.55	30.55	5.77	24.66	54.43	74.00	-19.57	Pk
V	4882	39.72	30.55	5.77	24.66	39.60	54.00	-14.40	AV
V	7323	54.38	30.33	6.32	24.55	54.92	74.00	-19.08	Pk
V	7323	40.60	30.33	6.32	24.55	41.14	54.00	-12.86	AV
V	9764	51.16	30.85	7.45	24.69	52.45	74.00	-21.55	Pk
V	9764	38.58	30.85	7.45	24.69	39.87	54.00	-14.13	AV
H	4882	56.31	30.55	5.77	24.66	56.19	74.00	-17.81	Pk
H	4882	41.91	30.55	5.77	24.66	41.79	54.00	-12.21	AV
H	7323	53.60	30.33	6.32	24.55	54.14	74.00	-19.86	Pk
H	7323	40.10	30.33	6.32	24.55	40.64	54.00	-13.36	AV
H	9764	50.32	30.85	7.45	24.69	51.61	74.00	-22.39	Pk
H	9764	37.48	30.85	7.45	24.69	38.77	54.00	-15.23	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960	54.23	30.55	5.77	24.66	54.11	74.00	-19.89	Pk
V	4960	40.78	30.55	5.77	24.66	40.66	54.00	-13.34	AV
V	7440	54.61	30.33	6.32	24.55	55.15	74.00	-18.85	Pk
V	7440	39.75	30.33	6.32	24.55	40.29	54.00	-13.71	AV
V	9920	52.24	30.85	7.45	24.69	53.53	74.00	-20.47	Pk
V	9920	36.89	30.85	7.45	24.69	38.18	54.00	-15.82	AV
H	4960	55.43	30.55	5.77	24.66	55.31	74.00	-18.69	Pk
H	4960	41.16	30.55	5.77	24.66	41.04	54.00	-12.96	AV
H	7440	53.87	30.33	6.32	24.55	54.41	74.00	-19.59	Pk

H	7440	39.92	30.33	6.32	24.55	40.46	54.00	-13.54	AV
H	9920	52.44	30.85	7.45	24.69	53.73	74.00	-20.27	Pk
H	9920	37.78	30.85	7.45	24.69	39.07	54.00	-14.93	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. RADIATED BAND EMISSION MEASUREMENT

5.1 Test Requirement:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Detec tor Type	Resul t
GFSK	Low Channel: 2402MHz									
	H	2390.00	55.66	30.22	4.85	23.98	54.27	74.00	PK	PASS
	H	2390.00	38.00	30.22	4.85	23.98	36.61	54.00	AV	PASS
	H	2400.00	54.31	30.22	4.85	23.98	52.92	74.00	PK	PASS
	H	2400.00	39.59	30.22	4.85	23.98	38.20	54.00	AV	PASS
	V	2390.00	51.19	30.22	4.85	23.98	49.80	74.00	PK	PASS
	V	2390.00	41.95	30.22	4.85	23.98	40.56	54.00	AV	PASS
	V	2400.00	53.10	30.22	4.85	23.98	51.71	74.00	PK	PASS
	V	2400.00	39.14	30.22	4.85	23.98	37.75	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	48.92	30.22	4.85	23.98	47.53	74.00	PK	PASS
	H	2483.50	37.91	30.22	4.85	23.98	36.52	54.00	AV	PASS
	H	2500.00	53.62	30.22	4.85	23.98	52.23	74.00	PK	PASS
	H	2500.00	40.08	30.22	4.85	23.98	38.69	54.00	AV	PASS
	V	2483.50	56.26	30.22	4.85	23.98	54.87	74.00	PK	PASS
	V	2483.50	40.59	30.22	4.85	23.98	39.20	54.00	AV	PASS
	V	2500.00	55.53	30.22	4.85	23.98	54.14	74.00	PK	PASS
	V	2500.00	40.48	30.22	4.85	23.98	39.09	54.00	AV	PASS
$\pi/4$ -DQPSK	Low Channel: 2402MHz									
	H	2390.00	53.16	30.22	4.85	23.98	51.77	74.00	PK	PASS
	H	2390.00	38.70	30.22	4.85	23.98	37.31	54.00	AV	PASS
	H	2400.00	54.22	30.22	4.85	23.98	52.83	74.00	PK	PASS
	H	2400.00	38.76	30.22	4.85	23.98	37.37	54.00	AV	PASS
	V	2390.00	51.59	30.22	4.85	23.98	50.20	74.00	PK	PASS
	V	2390.00	41.79	30.22	4.85	23.98	40.40	54.00	AV	PASS
	V	2400.00	51.69	30.22	4.85	23.98	50.30	74.00	PK	PASS
	V	2400.00	38.67	30.22	4.85	23.98	37.28	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	47.61	30.22	4.85	23.98	46.22	74.00	PK	PASS
	H	2483.50	35.41	30.22	4.85	23.98	34.02	54.00	AV	PASS
	H	2500.00	47.94	30.22	4.85	23.98	46.55	74.00	PK	PASS
	H	2500.00	39.25	30.22	4.85	23.98	37.86	54.00	AV	PASS
	V	2483.50	57.77	30.22	4.85	23.98	56.38	74.00	PK	PASS
	V	2483.50	43.86	30.22	4.85	23.98	42.47	54.00	AV	PASS
	V	2500.00	54.44	30.22	4.85	23.98	53.05	74.00	PK	PASS
	V	2500.00	40.52	30.22	4.85	23.98	39.13	54.00	AV	PASS

8-DPSK	Low Channel: 2402MHz									
	H	2390.00	54.17	30.22	4.85	23.98	52.78	74.00	PK	PASS
	H	2390.00	37.57	30.22	4.85	23.98	36.18	54.00	AV	PASS
	H	2400.00	53.71	30.22	4.85	23.98	52.32	74.00	PK	PASS
	H	2400.00	40.71	30.22	4.85	23.98	39.32	54.00	AV	PASS
	V	2390.00	53.64	30.22	4.85	23.98	52.25	74.00	PK	PASS
	V	2390.00	41.98	30.22	4.85	23.98	40.59	54.00	AV	PASS
	V	2400.00	52.75	30.22	4.85	23.98	51.36	74.00	PK	PASS
	V	2400.00	37.43	30.22	4.85	23.98	36.04	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	47.05	30.22	4.85	23.98	45.66	74.00	PK	PASS
	H	2483.50	39.71	30.22	4.85	23.98	38.32	54.00	AV	PASS
	H	2500.00	47.94	30.22	4.85	23.98	46.55	74.00	PK	PASS
	H	2500.00	36.55	30.22	4.85	23.98	35.16	54.00	AV	PASS
	V	2483.50	58.98	30.22	4.85	23.98	57.59	74.00	PK	PASS
	V	2483.50	42.22	30.22	4.85	23.98	40.83	54.00	AV	PASS
V	2500.00	57.98	30.22	4.85	23.98	56.59	74.00	PK	PASS	
V	2500.00	42.67	30.22	4.85	23.98	41.28	54.00	AV	PASS	
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										


6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 Limit

Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.2 Test Setup



6.3 Test procedure

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.


6.4 DEVIATION FROM STANDARD

No deviation.


6.5 Test Result

GFSK mode:


Test channel:	Lowest channel
---------------	----------------



Test channel:	Middle channel
---------------	----------------




Test channel:	Highest channel
---------------	-----------------




$\pi/4$ -DQPSK


Test channel:	Lowest channel
---------------	----------------



Test channel:	Middle channel
---------------	----------------




Test channel:	Highest channel
---------------	-----------------




8-DPSK mode:


Test channel:	Lowest channel
---------------	----------------




Test channel:	Middle channel
---------------	----------------




Test channel:	Highest channel
---------------	-----------------




GFSK No-hopping Band edge-left side




GFSK Hopping Band edge-left side




GFSK No-hopping Band edge-right side




GFSK Hopping Band edge-right side




$\pi/4$ -DQPSK No-hopping Band edge-left side




$\pi/4$ -DQPSK Hopping Band edge-left side




$\pi/4$ -DQPSK No-hopping Band edge-right side




$\pi/4$ -DQPSK Hopping Band edge-right side




8-DPSK No-hopping Band edge-left side




8-DPSK Hopping Band edge-left side



8-DPSK No-hopping Band edge-right side




8-DPSK Hopping Band edge-right side



7. 20DB BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013

7.1 Test Setup



7.2 Limit

N/A

7.3 Test procedure

1. Set RBW = 30 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 DEVIATION FROM STANDARD

No deviation.

7.5 Test Result

Mode	Test channel	20dB Emission Bandwidth (MHz)	Result
GFSK	Lowest	0.9458	Pass
	Middle	0.9459	
	Highest	0.9457	
$\pi/4$ -DQPSK	Lowest	1.283	Pass
	Middle	1.287	
	Highest	1.289	
8-DPSK	Lowest	1.295	Pass
	Middle	1.294	
	Highest	1.296	

Test plots

GFSK Low Channel



GFSK Middle Channel



GFSK High Channel



$\pi/4$ -DQPSK Low Channel



$\pi/4$ -DQPSK Middle Channel



$\pi/4$ -DQPSK High Channel



8-DPSK Low Channel



8-DPSK Middle Channel



8-DPSK High Channel



8. Maximum Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Limit:	21

8.1 Block Diagram Of Test Setup



8.2 Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.
For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

8.3 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3MHz. VBW = 3MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

8.4 DEVIATION FROM STANDARD

No deviation.

8.5 Test Result

Mode	Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK	Lowest	6.43	21	Pass
	Middle	6.22		
	Highest	5.47		
$\pi/4$ -DQPSK	Lowest	8.04	21	Pass
	Middle	7.83		
	Highest	7.01		
8-DPSK	Lowest	8.67	21	Pass
	Middle	8.39		
	Highest	7.55		

9. Hopping Channel Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)

9.1 Test Setup



9.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz , Span = 3.0MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 Test Result

Modulation	Test Channel	Separation (MHz)	Limit(MHz)	Result
GFSK	Low	1.23	0.631	PASS
$\pi/4$ -DQPSK	Low	1.15	0.855	PASS
8-DPSK	Low	0.99	0.863	PASS


Test plots GFSK Low Channel



$\pi/4$ -DQPSK Low Channel




8-DPSK Low Channel



10.NUMBER OF HOPPING FREQUENCY

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels

10.1 Test Setup



10.2 Test procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

10.3 DEVIATION FROM STANDARD


No deviation.

10.4 Test Result


Test Plots:
79 Channels in total
GFSK



$\pi/4$ -DQPSK




8-DPSK



11. DWELL TIME

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second

11.1 Test Setup



11.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0Hz;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

11.3 DEVIATION FROM STANDARD

No deviation.

11.4 Test Result


Frequency	Packet	Burst Width [ms/hop/ch]	Dwell time(ms)	Limit(ms)	Result
2441MHz	DH1	0.365	116.800	400	Pass
2441MHz	DH3	1.623	259.680	400	Pass
2441MHz	DH5	2.872	306.356	400	Pass
2441MHz	2DH1	0.341	109.120	400	Pass
2441MHz	2DH3	1.623	259.680	400	Pass
2441MHz	2DH5	2.884	307.636	400	Pass
2441MHz	3DH1	0.340	108.800	400	Pass
2441MHz	3DH3	1.635	261.600	400	Pass
2441MHz	3DH5	2.888	308.063	400	Pass

Remarks:


The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$
Test channel: 2441MHz as blow
DH1 2DH1 3DH1 time slot= $\text{Burst Width(ms)} \times (1600 / (2 \times 79)) \times 31.6$
DH3 2DH3 3DH3 time slot= $\text{Burst Width(ms)} \times (1600 / (4 \times 79)) \times 31.6$
DH5 2DH5 3DH5 time slot= $\text{Burst Width(ms)} \times (1600 / (6 \times 79)) \times 31.6$

Test Plots


GFSK DH1 2441MHZ




GFSK DH3 2441MHZ




GFSK DH5 2441MHZ




$\pi/4$ -DQPSK 2DH1 2441MHZ




$\pi/4$ -DQPSK 2DH3 2441MHZ




$\pi/4$ -DQPSK 2DH5 2441MHZ




8-DPSK 3DH1 2441MHZ



8-DPSK 3DH3 2441MHZ



8-DPSK 3DH5 2441MHZ



12. Antenna Requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is FPC antenna, the best case gain of the antennas are 1.5dBi, reference to the below photo for details ANT for BT 	

13. Test Setup Photo






14. EUT Constructional Details



External photos







internal photos





***** END OF REPORT *****