



RF TEST REPORT

Applicant Amber-Link Network
Technology Co., Ltd.

FCC ID 2A6UH-UGW800PUC

Product uGW800 Pro

Brand uG

Model uGW800PUC

Report No. R2206A0476-R2V1

Issue Date June 10, 2022

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 15C**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Peng Tao

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Test Laboratory	5
1.1. Notes of the test report.....	5
1.2. Test facility	5
1.3. Testing Location.....	5
2. General Description of Equipment under Test.....	6
2.1. Applicant and Manufacturer Information.....	6
2.2. General information.....	6
3. Applied Standards	7
4. Test Configuration	8
5. Test Case Results	9
5.1. Maximum output power	9
5.2. 99% Bandwidth and 6dB Bandwidth	11
5.3. Band Edge	15
5.4. Power Spectral Density	18
5.5. Spurious RF Conducted Emissions.....	21
5.6. Unwanted Emission	24
5.7. Conducted Emission	41
6. Main Test Instruments	44
ANNEX A: The EUT Appearance	46
ANNEX B: Test Setup Photos	47



Version	Revision description	Issue Date
Rev.0	Initial issue of report.	June 6, 2022
Rev.1	Update description.	June 10, 2022

Note: This revised report (Report No. R2206A0476-R2V1) supersedes and replaces the previously issued report (Report No. R2206A0476-R2). Please discard or destroy the previously issued report and dispose of it accordingly.



Summary of measurement results

Number	Test Case	Clause in FCC rules	Verdict
1	Maximum output power	15.247(b)(3)	PASS
2	6 dB bandwidth	15.247(a)(2)	PASS
3	Power spectral density	15.247(e)	PASS
4	Band Edge	15.247(d)	PASS
5	Spurious RF Conducted Emissions	15.247(d)	PASS
6	Unwanted Emissions	15.247(d),15.205,15.209	PASS
7	Conducted Emissions	15.207	PASS

Date of Testing: April 18, 2022 ~ May 12, 2022 and May 27, 2022 and June 2, 2022

Date of Sample Received: March 8, 2022

Note: All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.



1. Test Laboratory

1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.

Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong

City: Shanghai

Post code: 201201

Country: P. R. China

Contact: Xu Kai

Telephone: +86-021-50791141/2/3

Fax: +86-021-50791141/2/3-8000

Website: <http://www.ta-shanghai.com>

E-mail: xukai@ta-shanghai.com



2. General Description of Equipment under Test

2.1. Applicant and Manufacturer Information

Applicant	Amber-Link Network Technology Co., Ltd.
Applicant address	Room 209, Building 1, Block 356, Guoshoujin Road, Pudong SH, China
Manufacturer	SHANGHAI FOJOAUTO COMPONENTS CO.,LTD
Manufacturer address	NO 767 XINGE ROAD SONGJIANG SHANGHAI CHINA

2.2. General information

EUT Description	
Model	uGW800PUC
SN	2909469160010339
Hardware Version	2022.7
Software Version	2022.12.3
Power Supply	AC adapter
Antenna Type	Dipole Antenna
Antenna Connector	A permanently attached antenna (meet with the standard FCC Part 15.203 requirement)
Antenna Gain	3 dBi
Operating Frequency Range(s)	US915: 923.3 ~ 927.5 MHz AS923: 919 ~ 925 MHz
Modulation Type	Chirp Spread Spectrum
Max. Conducted Power	US915: 26.91 dBm AS923: 12.97 dBm
EUT Description	
Adapter	Manufacturer: Huizhou Guoatong Technology Co Ltd Model: GA-1202000

Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR47 Part 15C Radio Frequency Devices

ANSI C63.10-2013

Reference standard:

KDB 558074 D01 15.247 Meas Guidance v05r02

4. Test Configuration

Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the loop antenna is vertical, the others are vertical and horizontal. and the worst case was recorded.

Channel List

Band	Channel	Frequency (MHz)
US915	00	923.3
	01	923.9
	02	924.5
	03	925.1
	04	925.7
	05	926.3
	06	926.9
	07	927.5
AS923	1	919
	2	921.8
	3	922
	4	923.2
	5	923.4
	6	923.6
	7	923.8
	8	924
	9	924.6
	10	925

5. Test Case Results

5.1. Maximum output power


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT was connected to Power meter with a known loss. The EUT is max power transmission with proper modulation.

Test Setup



Limits

Rule Part 15.247 (b) (3) specifies that " For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz: 1 Watt."

Average Output Power	$\leq 1W$ (30dBm)
----------------------	-------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.44$ dB.

**Test Results**

Test Mode	T _{on} (ms)	T _(on+off) (ms)	Duty cycle	Duty cycle correction Factor(dB)
US915	1.38	1.40	0.99	0
AS923	1.37	1.40	0.98	0

Note: when Duty cycle ≥ 0.98 , Duty cycle correction Factor not required.

Test Mode	Frequency (MHz)	Average Power Measured (dBm)	Average Power with duty factor (dBm)	Limit (dBm)	Conclusion
US915	923.3	26.58	26.58	30	PASS
	925.1	26.91	26.91	30	PASS
	927.5	26.58	26.58	30	PASS
AS923	919	12.97	12.97	30	PASS
	922	12.29	12.29	30	PASS
	925	12.45	12.45	30	PASS

Note: Average Power with duty factor = Average Power Measured +Duty cycle correction factor

5.2. 99% Bandwidth and 6dB Bandwidth

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable. RBW is set to 100 kHz; VBW is set to 300 kHz on spectrum analyzer. Dector=Peak, Trace mode=max hold.

The EUT was connected to the spectrum analyzer through a known loss cable. The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value.

Test Setup



Limits

Rule Part 15.247 (a) (2) specifies that "Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz."

minimum 6 dB bandwidth	≥ 500 kHz
------------------------	----------------

Measurement Uncertainty


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 936$ Hz.

**Test Results:**

Test Mode	Carrier frequency (MHz)	99% bandwidth (MHz)	Minimum 6 dB bandwidth (MHz)	Limit (kHz)	Conclusion
US915	923.3	0.520	0.619	500	PASS
	925.1	0.535	0.632	500	PASS
	927.5	0.540	0.618	500	PASS
AS923	919	0.531	0.628	500	PASS
	922	0.518	0.609	500	PASS
	925	0.519	0.614	500	PASS

US915


99% Bandwidth, Carrier frequency (MHz): 923.3



6dB Bandwidth, Carrier frequency (MHz): 923.3



99% Bandwidth, Carrier frequency (MHz): 925.1



6dB Bandwidth, Carrier frequency (MHz): 925.1



99% Bandwidth, Carrier frequency (MHz): 927.5




6dB Bandwidth, Carrier frequency (MHz): 927.5



AS923

99% Bandwidth, Carrier frequency (MHz): 919



6dB Bandwidth, Carrier frequency (MHz): 919




99% Bandwidth, Carrier frequency (MHz): 922



6dB Bandwidth, Carrier frequency (MHz): 922



99% Bandwidth, Carrier frequency (MHz): 925



6dB Bandwidth, Carrier frequency (MHz): 925



5.3. Band Edge


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable the band edge of the lowest and highest channels were measured. The peak detector is used and RBW is set to 100 kHz and VBW is set to 300 kHz on spectrum analyzer. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 15.247(d) specifies that “In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.” If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.”

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
2GHz-3GHz	1.407 dB




Test Results: PASS

US915


Carrier frequency (MHz): 923.3



Carrier frequency (MHz): 927.5



AS923



5.4. Power Spectral Density

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Method of Measurement

During the process of the testing, The EUT was connected to Spectrum Analyzer with a known loss. The EUT is max power transmission with proper modulation.

Method AVGPSD-1 was used for this test.

- a) Set instrument center frequency to DTS channel center frequency
- b) Set span to at least 1.5 times the OBW
- c) Set RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{kHz}$
- d) Set VBW $\geq [3 \times \text{RBW}]$
- e) Detector=power averaging (rms) or sample detector (when rms not available)
- f) Ensure that the number of measurement points in the sweep $2[2 \times \text{span}/\text{RBW}]$
- g) Sweep time auto couple
- h) Employ trace averaging (rms) mode over a minimum of 100 traces
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced)

Test setup



Limits

Rule Part 15.247(e) specifies that "For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission."

Limits	$\leq 8 \text{ dBm} / 3\text{kHz}$
--------	------------------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.75\text{dB}$.

**Test Results:**

Test Mode	Carrier frequency (MHz)	Read Value (dBm / 3kHz)	Power Spectral Density (dBm / 3kHz)	Limit (dBm / 3kHz)	Conclusion
US915	923.3	7.14	7.14	8	PASS
	925.1	7.32	7.32	8	PASS
	927.5	7.33	7.33	8	PASS
AS923	919	-6.72	-6.72	8	PASS
	922	-7.17	-7.17	8	PASS
	925	-7.05	-7.05	8	PASS

Note: Power Spectral Density =Read Value+Duty cycle correction factor



US915, Carrier frequency (MHz): 923.3



AS923, Carrier frequency (MHz): 919




US915, Carrier frequency (MHz): 925.1




AS923, Carrier frequency (MHz): 922



US915, Carrier frequency (MHz): 927.5



AS923, Carrier frequency (MHz): 925



5.5. Spurious RF Conducted Emissions

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to the spectrum analyzer with a known loss. The spectrum analyzer scans from 30MHz to the 10th harmonic of the carrier. The peak detector is used. Set RBW to 100 kHz and VBW to 300 kHz, Sweep is set to ATUO.

The test is in transmitting mode.

Test setup



Limits

Rule Part 15.247(d) pacifies that "In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. "

Test Mode	Carrier frequency (MHz)	Reference value (dBm)	Limit
US915	923.3	26.67	-3.33
	925.1	26.69	-3.31
	927.5	26.91	-3.09
AS923	919	13.28	-16.72
	922	12.26	-17.74
	925	12.69	-17.31

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.


Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-26GHz	1.407 dB

**Test Results:****The signal beyond the limit is carrier.****US915****923.3MHz, 30MHz to 26.5GHz****925.1MHz, 30MHz to 26.5GHz****927.5MHz, 30MHz to 26.5GHz**



AS923


919MHz, 30MHz to 26.5GHz



922MHz, 30MHz to 26.5GHz



925MHz, 30MHz to 26.5GHz



5.6. Unwanted Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	102.5kPa

Method of Measurement

The test set-up was made in accordance to the general provisions of ANSI C63.10.

The Equipment Under Test (EUT) was set up on a non-conductive table in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna.

The turntable shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. Sweep the Restricted Band and the emissions less than 20 dB below the permissible value are reported.

The radiated emissions measurements were made in a typical installation configuration.

Sweep the whole frequency band through the range from 9 kHz to the 10th harmonic of the carrier, and the emissions less than 20 dB below the permissible value are reported.

This method refer to ANSI C63.10.

The procedure for peak unwanted emissions measurements above 1000 MHz is as follows:

Set the spectrum analyzer in the following:

9kHz~150 kHz

RBW=200Hz, VBW=1kHz/ Sweep=AUTO

150 kHz~30MHz

RBW=9KHz, VBW=30KHz,/ Sweep=AUTO

Below 1GHz

RBW=100kHz / VBW=300kHz / Sweep=AUTO

a) Peak emission levels are measured by setting the instrument as follows:

Above 1GHz

PEAK: RBW=1MHz VBW=3MHz/ Sweep=AUTO

b) Average emission levels are measured by setting the instrument as follows:

Above 1GHz

AVERAGE: RBW=1MHz / VBW=3MHz / Sweep=AUTO

c) Detector: The measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)

e) Sweep time = auto.

f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission

is not continuous, then the number of traces shall be increased by a factor of $1 / D$, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)

g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is $[10 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.


2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.

3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.


The test is in transmitting mode.

Test setup


9KHz ~ 30MHz



30MHz ~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

Limits

Rule Part 15.247(d) specifies that “In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).”

Limit in restricted band

Frequency of emission (MHz)	Field strength(µV/m)	Field strength(dBuV/m)
0.009–0.490	2400/F(kHz)	/
0.490–1.705	24000/F(kHz)	/
1.705–30.0	30	/
30-88	100	40
88-216	150	43.5
216-960	200	46
Above960	500	54

§15.35(b)

There is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

Peak Limit=74 dBuV/m

Average Limit=54 dBuV/m




Spurious Radiated Emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
9KHz-30MHz	3.55 dB
30MHz-200MHz	4.17 dB
200MHz-1GHz	4.84 dB
1-18GHz	4.35 dB
18-26.5GHz	5.90 dB
26.5GHz~40GHz	5.92 dB


Test Results:**The signal beyond the limit is carrier.**A font ($\text{dB}_{\mu\text{V}/\text{m}}$) in the test plot = ($\text{dB}_{\mu\text{V}/\text{m}}$)

Result of RE**Test result**

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the Emissions in the frequency band 9kHz-30MHz and 18GHz-26.5GHz are more than 20dB below the limit are not reported.

The following graphs display the maximum values of horizontal and vertical by software.
For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.

A font (Level in dB μ V/m) in the test plot =(level in dB μ V/m)

US915**923.3 MHz**


Note: The signal beyond the limit is carrier.

Radiates Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dB μ V/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dB μ V/m)
43.05	19.68	111.0	V	290.00	14	20.32	40.00
77.42	31.85	175.0	V	239.00	8	8.15	40.00
150.00	38.37	100.0	V	320.00	9	5.13	43.50
250.03	40.56	125.0	H	69.00	14	5.44	46.00
326.57	27.07	100.0	H	49.00	16	18.93	46.00
815.17	29.07	105.0	H	331.00	24	16.93	46.00

Remark: 1. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)

2. Margin = Limit – Quasi-Peak




Radiates Emission from 1GHz to 18GHz

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1031.52	---	25.23	54.00	28.77	125.0	V	348.00	-20
1031.68	38.60	---	74.00	35.40	125.0	V	315.00	-20
1955.71	---	27.35	54.00	26.65	100.0	V	59.00	-15
1995.50	50.94	---	74.00	23.06	221.0	V	6.00	-15
2770.25	---	30.28	54.00	23.72	119.0	H	28.00	-14
2770.58	52.86	---	74.00	21.14	100.0	H	16.00	-14
4616.28	---	31.53	54.00	22.47	107.0	V	80.00	-9
4616.42	47.76	---	74.00	26.24	100.0	V	60.00	-9
5973.35	55.78	---	74.00	18.22	119.0	V	298.00	-6
6005.89	---	30.73	54.00	23.27	225.0	V	355.00	-5
8309.80	---	39.07	54.00	14.93	125.0	V	77.00	-3
8311.49	57.73	---	74.00	16.27	100.0	V	90.00	-3

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

925.1 MHz




Note: The signal beyond the limit is carrier.

Radiates Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
38.04	21.24	111.0	V	240.00	13	18.76	40.00
77.53	33.78	175.0	V	238.00	8	6.22	40.00
150.00	38.33	100.0	V	22.00	9	5.17	43.50
250.03	39.05	111.0	H	252.00	14	6.95	46.00
326.33	26.66	100.0	H	34.00	16	19.34	46.00
816.59	29.05	125.0	H	300.00	24	16.95	46.00

Remark: 1. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)

2. Margin = Limit – Quasi-Peak




Radiates Emission from 1GHz to 18GHz

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1033.65	33.72	---	74.00	40.28	100.0	H	249.00	-20
1033.79	---	49.60	54.00	4.40	108.0	V	332.00	-20
1991.63	48.28	---	74.00	25.72	196.0	V	339.00	-15
1994.37	---	24.17	54.00	29.83	100.0	V	50.00	-15
2774.95	53.82	---	74.00	20.18	107.0	H	14.00	-14
2775.82	---	30.78	54.00	23.22	125.0	H	25.00	-14
4625.37	---	26.87	54.00	27.13	107.0	H	46.00	-9
4625.97	40.39	---	74.00	33.61	100.0	V	266.00	-9
8327.06	---	43.90	54.00	10.10	108.0	V	279.00	-3
8327.57	46.66	---	74.00	27.34	107.0	V	268.00	-3
9674.77	48.14	---	74.00	25.86	125.0	V	178.00	-2
9706.12	---	35.39	54.00	18.61	119.0	H	14.00	-2

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

927.5 MHz




Note: The signal beyond the limit is carrier.

Radiates Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
41.36	24.17	105.0	V	285.00	14	15.83	40.00
78.09	34.31	125.0	V	220.00	8	5.69	40.00
150.00	39.39	100.0	V	4.00	9	4.11	43.50
249.99	38.54	100.0	H	254.00	14	7.46	46.00
350.02	32.89	100.0	H	184.00	16	13.11	46.00
818.29	29.52	111.0	H	298.00	24	16.48	46.00

Remark: 1. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)

2. Margin = Limit – Quasi-Peak




Radiates Emission from 1GHz to 18GHz

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1036.35	50.54	---	74.00	23.46	102.0	V	36.00	-20
1036.55	---	49.45	54.00	4.55	100.0	V	36.00	-20
1996.25	50.66	---	74.00	23.34	176.0	V	0.00	-15
1996.62	---	30.08	54.00	23.92	185.0	V	0.00	-15
2782.10	49.80	---	74.00	24.20	100.0	V	89.00	-14
2782.25	---	47.93	54.00	6.07	195.0	H	163.00	-14
4636.64	45.83	---	74.00	28.17	100.0	V	66.00	-9
4639.94	---	29.41	54.00	24.59	116.0	V	66.00	-9
5999.13	53.10	---	74.00	20.90	108.0	V	20.00	-5
8347.23	59.10	---	74.00	14.90	100.0	V	96.00	-3
8352.65	---	36.97	54.00	17.03	102.0	V	96.00	-3
9273.93	---	36.93	54.00	17.07	100.0	V	89.00	-2

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

AS923

919 MHz




Note: The signal beyond the limit is carrier.

Radiates Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dB _{uV} /m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dB _{uV} /m)
48.07	18.36	113.0	H	338.00	14	21.64	40.00
55.95	18.56	180.0	H	205.00	14	21.45	40.00
103.96	16.95	225.0	V	186.00	13	26.55	43.50
298.45	19.45	125.0	V	162.00	15	26.55	46.00
538.04	24.44	125.0	V	176.00	20	21.56	46.00
758.83	28.46	203.0	H	125.00	23	17.54	46.00

Remark: 1. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)

2. Margin = Limit – Quasi-Peak




Radiates Emission from 1GHz to 18GHz

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1197.47	---	28.26	54.00	21.64	100.0	H	196.00	-19
1204.61	36.83	---	74.00	21.45	107.0	H	226.00	-19
1329.02	46.60	---	74.00	26.55	196.0	V	1.00	-18
1329.85	---	26.12	54.00	26.55	196.0	V	1.00	-18
2750.60	---	36.09	54.00	21.56	100.0	V	310.00	-14
2757.44	46.24	---	74.00	17.54	125.0	V	290.00	-14
3675.71	44.44	---	74.00	21.64	119.0	V	291.00	-12
3675.82	---	35.12	54.00	21.45	125.0	V	276.00	-12
5982.26	51.17	---	74.00	26.55	119.0	V	298.00	-6
6438.38	---	30.97	54.00	26.55	221.0	V	331.00	-5
9339.90	---	34.57	54.00	21.56	211.0	H	56.00	-2
9665.45	47.25	---	74.00	17.54	107.0	H	182.00	-2

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

922 MHz




Note: The signal beyond the limit is carrier.

Radiates Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
49.04	18.64	180.0	V	3.00	14	21.36	40.00
57.65	18.94	100.0	V	124.00	14	21.06	40.00
103.84	19.53	125.0	H	206.00	13	23.97	43.50
214.66	22.09	125.0	H	112.00	12	21.41	43.50
488.45	25.16	196.0	H	218.00	19	20.84	46.00
783.21	28.71	125.0	H	22.00	23	17.29	46.00

Remark: 1. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)

2. Margin = Limit – Quasi-Peak




Radiates Emission from 1GHz to 18GHz

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1197.63	---	22.73	54.00	31.27	183.0	H	38.00	-19
1197.63	36.50	---	74.00	37.50	225.0	H	30.00	-19
2389.75	42.89	---	74.00	31.11	210.0	H	271.00	-14
2765.88	---	23.56	54.00	30.44	210.0	V	356.00	-14
3987.75	45.06	---	74.00	28.94	175.0	V	274.00	-11
4026.00	---	27.79	54.00	26.21	183.0	V	116.00	-11
5989.50	42.58	---	74.00	31.42	210.0	V	269.00	-5
6027.75	---	29.28	54.00	24.72	125.0	H	144.00	-6
7723.50	---	31.77	54.00	22.23	125.0	H	0.00	-3
8001.88	45.54	---	74.00	28.46	225.0	V	336.00	-2
9610.50	---	34.36	54.00	19.64	182.0	H	58.00	-2
9676.38	46.81	---	74.00	27.19	125.0	H	102.00	-2

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

925 MHz




Note: The signal beyond the limit is carrier.

Radiates Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
41.64	18.14	125.0	H	233.00	14	21.86	40.00
55.95	18.58	179.0	H	30.00	14	21.42	40.00
105.66	16.79	114.0	H	250.00	13	26.71	43.50
301.60	19.54	125.0	H	22.00	15	26.46	46.00
545.07	24.62	225.0	H	276.00	20	21.38	46.00
779.81	28.72	225.0	V	23.00	23	17.28	46.00

Remark: 1. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)

2. Margin = Limit – Quasi-Peak



Radiates Emission from 1GHz to 18GHz

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1327.25	44.13	---	74.00	29.87	100.0	V	241.00	-18
1329.38	---	24.00	54.00	30.01	196.0	H	14.00	-18
1847.88	42.49	---	74.00	31.51	182.0	V	228.00	-15
1850.00	---	33.82	54.00	20.18	225.0	V	339.00	-15
2774.38	---	24.27	54.00	29.73	225.0	V	6.00	-14
3193.00	37.42	---	74.00	36.58	221.0	V	206.00	-13
3996.25	---	28.26	54.00	25.74	119.0	V	269.00	-11
3998.38	44.51	---	74.00	29.49	196.0	V	203.00	-11
5993.75	50.93	---	74.00	23.07	125.0	V	198.00	-5
6474.00	---	31.74	54.00	22.26	119.0	V	99.00	-4
9440.50	---	33.02	54.00	20.98	100.0	H	323.00	-2
9623.25	48.22	---	74.00	25.78	125.0	H	262.00	-2

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

5.7. Conducted Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.10. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz.

The measurement result should include both L line and N line.

The test is in transmitting mode.

Test Setup



Note: AC Power source is used to change the voltage 110V/60Hz.

Limits

Frequency (MHz)	Conducted Limits(dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 [*]	56 to 46 [*]
0.5 - 5	56	46
5 - 30	60	50


^{*}: Decreases with the logarithm of the frequency.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 2.69$ dB.

Test Results:

Following plots, Blue trace uses the peak detection and Green trace uses the average detection. During the test, the Conducted Emission was performed in all modes (US915/AS923) with all channels, US915, 927.5 MHz are selected as the worst condition. The test data of the worst-case condition was recorded in this report.




Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.36	---	31.56	48.69	17.14	1000.00	9.000	L1	ON	21
0.36	41.50	---	58.69	17.20	1000.00	9.000	L1	ON	21
0.43	44.98	---	57.19	12.20	1000.00	9.000	L1	ON	20
0.44	---	35.81	47.06	11.25	1000.00	9.000	L1	ON	20
1.06	33.30	---	56.00	22.70	1000.00	9.000	L1	ON	20
1.30	---	23.44	46.00	22.56	1000.00	9.000	L1	ON	20
2.22	30.70	---	56.00	25.30	1000.00	9.000	L1	ON	20
2.24	---	20.19	46.00	25.81	1000.00	9.000	L1	ON	19
5.14	---	18.78	50.00	31.22	1000.00	9.000	L1	ON	19
5.18	25.88	---	60.00	34.12	1000.00	9.000	L1	ON	19
10.49	---	18.78	50.00	31.22	1000.00	9.000	L1	ON	20
10.51	23.91	---	60.00	36.09	1000.00	9.000	L1	ON	20

Remark: Correct factor=cable loss + LISN factor

L line

Conducted Emission from 150 KHz to 30 MHz



Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.36	---	33.16	48.69	15.54	1000.00	9.000	N	ON	21
0.36	46.19	---	58.69	12.51	1000.00	9.000	N	ON	21
0.44	51.34	---	57.14	5.80	1000.00	9.000	N	ON	20
0.44	---	38.05	47.06	9.00	1000.00	9.000	N	ON	20
0.88	41.64	---	56.00	14.36	1000.00	9.000	N	ON	20
0.88	---	26.44	46.00	19.56	1000.00	9.000	N	ON	20
2.27	---	22.51	46.00	23.49	1000.00	9.000	N	ON	20
2.35	34.54	---	56.00	21.46	1000.00	9.000	N	ON	20
5.19	30.62	---	60.00	29.38	1000.00	9.000	N	ON	19
10.36	---	21.29	50.00	28.71	1000.00	9.000	N	ON	20
13.70	26.30	---	60.00	33.70	1000.00	9.000	N	ON	20
13.77	---	18.27	50.00	31.73	1000.00	9.000	N	ON	20

Remark: Correct factor=cable loss + LISN factor

N line

Conducted Emission from 150 KHz to 30 MHz



6. Main Test Instruments

Date of Testing: April 18, 2022 ~ May 12, 2022

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Power Splitter	R&S	NRP18S	101954	2021-05-15	2022-05-14
Spectrum Analyzer	KEYSIGHT	N9020A	MY54420163	2021-12-12	2022-12-11
LISN	R&S	ENV216	102191	2020-12-13	2022-12-12
EMI Test Receiver	R&S	ESR	101667	2021-05-15	2022-05-14
Software	R&S	EMC32	10.35.10	/	/
EMI Test Receiver	R&S	ESCI7	100936	2021-12-12	2022-12-11
Signal Analyzer	R&S	FSV30	103591	2021-05-15	2022-05-14
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	391	2019-12-16	2022-12-15
Horn Antenna	Schwarzbeck	BBHA 9120D	430	2021-07-26	2024-07-25
Software	R&S	EMC32	9.26.01	/	/

Date of Testing: May 27, 2022

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Spectrum Analyzer	KEYSIGHT	N9020A	MY54420163	2021-12-12	2022-12-11



Date of Testing: June 2, 2022

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Power Splitter	R&S	OSP-B157W8	100924	2021/12/12	2022/12/11
Spectrum Analyzer	KEYSIGHT	N9020A	MY54420163	2021-12-12	2022-12-11
LISN	R&S	ENV216	102191	2020-12-13	2022-12-12
EMI Test Receiver	R&S	ESR	101667	2021-05-15	2022-05-14
EMI Test Receiver	R&S	ESCI7	100936	2021-12-12	2022-12-11
Software	R&S	EMC32	10.35.10	/	/
EMI Test Receiver	R&S	ESCI7	100936	2021-12-12	2022-12-11
Signal Analyzer	R&S	FSV30	103591	2021-05-15	2022-05-14
Signal Analyzer	R&S	FSV30	100815	2021-12-12	2022-12-11
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	391	2019-12-16	2022-12-15
Horn Antenna	Schwarzbeck	BBHA 9120D	430	2021-07-26	2024-07-25
Software	R&S	EMC32	9.26.01	/	/

*****END OF REPORT*****



ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.



ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.