

## MPE ESTIMATION

FCC ID: 2A6WF-G900PRO

### 1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm <sup>2</sup> )	Averaging time(minutes)
300MHz---1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

### 2, Estimation Result

	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )
2.4GWIFI	13.51	13±1(14)	25.12	3.84	2.42	0.01210
5.8GWIFI	8.34	8±1(9)	7.94	4.25	2.66	0.00421
$Pd = \frac{P_{out} * G}{4\pi r^2} ;$						
Note:						
Note: The estimation distance is 20cm						
The device could not transmit simultaneously in 2.4G and 5.8G						
Note: PK Output power= conducted power.						
Conducted power see the test report HK2406173152-1E/2E						

When the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01210 which is < 1.0, RF Exposure testing is not required.

-----The End-----