

RF EXPOSURE REPORT

FCC ID: 2A6WI-BLR10B

Report Reference No. : 22EFSS9077 09721

Date of issue : 2022-10-29

Applicant's name : Gunwerks, LLC.

Address : 201 Blackburn St. Cody, WY 82414

Manufacturer : Gunwerks, LLC.

Equipment : LASER RANGEFINDER

Trade Mark :  **REVIC**

Model : ACURA BLR10b

Ratings : Input: DC 3V for battery.
Output: --

Testing Laboratory : DongGuan ShuoXin Electronic Technology Co., Ltd.

Address : Zone A, 1F, No. 6, XinGang Road YuanGang Street,
XinAn District, ChangAn Town, DongGuan City,
GuangDong, China

According : KDB 447498 D01 General RF Exposure Guidance v06


Test Engineer:


Blue Qiu

Responsible Engineer :


Smile Wang

Authorized Signatory:


King Wang

MPE CALCULATION METHOD:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)	Note
1	Walsin Technology Corporation	RFANT5220110 AOT	Chip/Ceramic	SMT	2	

TEST RESULTS

Ant gain =2dBi

MAX output power : 0.198dBm@2440MHz

ERP=0.198+2-2.15=0.048dBm

WORSE CASE:

$10^{0.0198}=1.047\text{mW} < 2.715\text{mW}$

Then SAR evaluation is not required

END