

TEST REPORT

Product Name : Moving light
Model Number : Poseidon wash M
FCC ID : 2A6YG-WASHM

Prepared for : CLF LIGHTING B. V.
Address : De Kazematten 19, 6681 CS, Bommel

Prepared by : EMTEK (DONGGUAN) CO., LTD.
Address : -1&2/F., Building 2, Zone A, Zhongda Marine Biotechnology
Research and Development Base, No.9, Xincheng Avenue,
Songshanhu High-technology Industrial Development Zone,
Dongguan, Guangdong, China

TEL: +86-0769-22807078
FAX: +86-0769-22807079

Report Number : EDG2304130131E02202R
Date(s) of Tests : May 27, 2023 to September 19, 2023
Date of issue : September 19, 2023

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT:	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : CLF LIGHTING B. V.
Address : De Kazematten 19, 6681 CS, Bommel
Manufacturer : CLF LIGHTING B. V.
Address : De Kazematten 19, 6681 CS, Bommel
Factory : CLF LIGHTING B. V.
Address : De Kazematten 19, 6681 CS, Bommel
EUT : Moving light
Model Name : Poseidon wash M
Trademark : 


Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 1.1310: §1.1307(b)	PASS

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC 1.1310: §1.1307(b).

The test results of this report relate only to the tested sample identified in this report

Date of Test : May 27, 2023 to September 19, 2023

Prepared by : 
Xia Yang /Editor

Reviewer : 
Tim Dong/ Supervisor

Approve & Authorized Signer : 
Sam Lv / Manager

Modified History

Version	Report No.	Revision Date	Summary
	EDG2304130131E02202R	September 19, 2023	Original Report



2. EUT Specification

Characteristics	Description
Product:	Moving light
Model Number:	Poseidon wash M
Sample:	1#
Device Type:	SRD
Data Rate:	1 Mbps
Modulation:	GFSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	79 channels
Transmit Power Max:	9.80 dBm(0.009550 W)
Antenna Gain:	ANT1: -1.31dBi ANT2: 2.95dBi
Power supply:	AC 100-240V~50/60Hz
Evaluation applied:	☒ MPE Evaluation ☐ SAR Evaluation

3. Test Requirement:

RF EXPOSURE EVALUATION

According to KDB 447498: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

4. Measurement Result

ANT1 gain: -1.31dBi
ANT2 gain: 2.95dBi
Directional gain: 4.09dBi

ANT	Frequency (MHz)	Output Power (dBm)	E.I.R.P (dBm)	Target Power W/tolerance (dBm)	Max tune up power tolerance (dBm)	Max tune up power tolerance (mW)	Power Density at R=20cm (mW/cm2)	Limit (mW/cm2)	Verdict
ANT1	2402	7.54	6.23	7±1	8	6.31	0.000928	1	PASS
ANT2	2402	9.80	12.75	12±1	13	19.95	0.007829	1	PASS
TOTAL	2402	11.83	13.62	13±1	14	25.12	0.012812	1	PASS
ANT1	2441	6.41	5.10	6±1	7	5.01	0.000737	1	PASS
ANT2	2441	7.12	10.07	10±1	11	12.59	0.004940	1	PASS
TOTAL	2441	9.79	11.27	11±1	12	15.85	0.008084	1	PASS
ANT1	2480	5.77	4.46	5±1	6	3.98	0.000586	1	PASS
ANT2	2480	6.81	9.76	9±1	10	10.00	0.003924	1	PASS
TOTAL	2480	9.33	10.88	10±1	11	12.59	0.006421	1	PASS

*** End of Report ***