



# FCC TEST REPORT

**Test report  
On Behalf of  
Yuanfeng Technology Co., Ltd  
For  
VECS IHUB  
Model No.: VECS IHUB  
FCC ID: 2A6YK-VECSIHUB**

**Prepared For :** Yuanfeng Technology Co., Ltd  
No. 18, Industrial East Road, Songshan Lake Development Zone, Dongguan,  
Guangdong, China

**Prepared By :** Shenzhen HUAKE Testing Technology Co., Ltd.  
1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping,  
Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

**Date of Test:** May. 05, 2022 ~ May. 17, 2022

**Date of Report:** May. 17, 2022

**Report Number:** HK2205051851-3E

**TEST RESULT CERTIFICATION**

**Applicant's name** .....: Yuanfeng Technology Co., Ltd  
**Address** .....: No. 18, Industrial East Road, Songshan Lake Development Zone,  
Dongguan, Guangdong, China  
**Manufacture's Name**.....: Yuanfeng Technology Co., Ltd  
**Address** .....: No. 18, Industrial East Road, Songshan Lake Development Zone,  
Dongguan, Guangdong, China  
**Product description**  
**Trade Mark:** N/A  
**Product name**.....: VECS IHUB  
**Model and/or type reference** : VECS IHUB  
FCC Rules and Regulations Part 15 Subpart E Section 15.407  
**Standards** .....: ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Date of Test** .....:  
**Date (s) of performance of tests** .....: May. 05, 2022 ~ May. 17, 2022  
**Date of Issue**.....: May. 17, 2022  
**Test Result**.....: **Pass**

Prepared by:

Project Engineer

Reviewed by:

Project Supervisor

Approved by:

Technical Director



## TABLE OF CONTENTS

|                                                      |            |
|------------------------------------------------------|------------|
| <b>1. TEST RESULT SUMMARY .....</b>                  | <b>5</b>   |
| 1.1. TEST PROCEDURES AND RESULTS.....                | 5          |
| 1.2. INFORMATION OF THE TEST LABORATORY .....        | 5          |
| 1.3. MEASUREMENT UNCERTAINTY .....                   | 6          |
| <b>2. EUT DESCRIPTION .....</b>                      | <b>7</b>   |
| 2.1. GENERAL DESCRIPTION OF EUT .....                | 7          |
| 2.2. OPERATION FREQUENCY EACH OF CHANNEL .....       | 8          |
| 2.3. OPERATION OF EUT DURING TESTING.....            | 8          |
| 2.4. DESCRIPTION OF TEST SETUP .....                 | 9          |
| <b>3. GENERA INFORMATION .....</b>                   | <b>10</b>  |
| 3.1. TEST ENVIRONMENT AND MODE .....                 | 10         |
| 3.2. DESCRIPTION OF SUPPORT UNITS .....              | 11         |
| <b>4. TEST RESULTS AND MEASUREMENT DATA .....</b>    | <b>12</b>  |
| 4.1. CONDUCTED EMISSION .....                        | 12         |
| 4.2. MAXIMUM CONDUCTED OUTPUT POWER.....             | 15         |
| 4.3. 6DB EMISSION BANDWIDTH.....                     | 18         |
| 4.4. 26DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH ..... | 19         |
| 4.5. POWER SPECTRAL DENSITY .....                    | 36         |
| 4.6. BAND EDGE .....                                 | 58         |
| 4.7. SPURIOUS EMISSION .....                         | 113        |
| 4.8. FREQUENCY STABILITY MEASUREMENT .....           | 138        |
| 4.9. ANTENNA REQUIREMENT .....                       | 140        |
| <b>5. PHOTOGRAPHS OF TEST SETUP.....</b>             | <b>141</b> |
| <b>6. PHOTOS OF THE EUT .....</b>                    | <b>142</b> |

**\*\* Modified History \*\***

| Revision     | Description                 | Issued Data   | Remark     |
|--------------|-----------------------------|---------------|------------|
| Revision 1.0 | Initial Test Report Release | May. 17, 2022 | Jason Zhou |
|              |                             |               |            |
|              |                             |               |            |



## 1. TEST RESULT SUMMARY

### 1.1. TEST PROCEDURES AND RESULTS

| Requirement                                     | CFR 47 Section           | Result |
|-------------------------------------------------|--------------------------|--------|
| Antenna requirement                             | §15.203                  | PASS   |
| AC Power Line Conducted Emission                | §15.207                  | N/A    |
| Maximum Conducted Output Power                  | §15.407(a)               | PASS   |
| 6dB Emission Bandwidth                          | §15.407(e)               | N/A    |
| 26dB Emission Bandwidth& 99% Occupied Bandwidth | §15.407(a)               | PASS   |
| Power Spectral Density                          | §15.407(a)               | PASS   |
| Band edge                                       | §15.407(b)/15.209/15.205 | PASS   |
| Radiated Emission                               | §15.407(b)/15.209/15.205 | PASS   |
| Frequency Stability                             | §15.407(g)               | PASS   |

**Note:**

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

### 1.2. INFORMATION OF THE TEST LABORATORY

Shenzhen HUAK Testing Technology Co., Ltd.

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Testing Laboratory Authorization:

A2LA Accreditation Code is 4781.01.

FCC Designation Number is CN1229.

Canada IC CAB identifier is CN0045.

CNAS Registration Number is L9589.



### 1.3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

| No. | Item                          | MU                        |
|-----|-------------------------------|---------------------------|
| 1   | Conducted Emission            | $\pm 0.37\text{dB}$       |
| 2   | RF power, conducted           | $\pm 3.35\text{dB}$       |
| 3   | Spurious emissions, conducted | $\pm 2.20\text{dB}$       |
| 4   | All emissions, radiated(<1G)  | $\pm 3.90\text{dB}$       |
| 5   | All emissions, radiated(>1G)  | $\pm 4.28\text{dB}$       |
| 6   | Temperature                   | $\pm 0.1^{\circ}\text{C}$ |
| 7   | Humidity                      | $\pm 1.0\%$               |



## 2. EUT DESCRIPTION

### 2.1. GENERAL DESCRIPTION OF EUT

|                                                                                                                                                                                                                                                                                                     |                                                                                                                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Equipment:                                                                                                                                                                                                                                                                                          | VECS IHUB                                                                                                                     |
| Model Name:                                                                                                                                                                                                                                                                                         | VECS IHUB                                                                                                                     |
| Serial Model:                                                                                                                                                                                                                                                                                       | N/A                                                                                                                           |
| Model Difference:                                                                                                                                                                                                                                                                                   | N/A                                                                                                                           |
| Trade Mark:                                                                                                                                                                                                                                                                                         | N/A                                                                                                                           |
| FCC ID:                                                                                                                                                                                                                                                                                             | 2A6YK-VECSIHUB                                                                                                                |
| Operation Frequency:                                                                                                                                                                                                                                                                                | IEEE 802.11a/n/ac/ax(HT20) 5.180GHz-5.240GHz<br>IEEE 802.11n/ac/ax(HT40) 5.190GHz-5.230GHz<br>IEEE 802.11ac/ax(HT80) 5.210GHz |
| Modulation Technology:                                                                                                                                                                                                                                                                              | IEEE 802.11a/n/ac/ax                                                                                                          |
| Modulation Type:                                                                                                                                                                                                                                                                                    | OFDM, OFDMA                                                                                                                   |
| Antenna Type:                                                                                                                                                                                                                                                                                       | External Antenna                                                                                                              |
| Antenna Gain:                                                                                                                                                                                                                                                                                       | Antenna 1:1dBi<br>Antenna 2:1dBi<br>MIMO: 4.01dBi                                                                             |
| Power Source:                                                                                                                                                                                                                                                                                       | DC 12V                                                                                                                        |
| Power Supply:                                                                                                                                                                                                                                                                                       | DC 12V                                                                                                                        |
| Hardware Version                                                                                                                                                                                                                                                                                    | V2.1                                                                                                                          |
| Software Version:                                                                                                                                                                                                                                                                                   | V2.1                                                                                                                          |
| Note: The EUT incorporates a MIMO function. Physically, it provides two completed transmitters and receivers(2T2R), two transmit signals are completely correlated, then, Direction gain= GANT + Array Gain(Array Gain=10 log(2) dB for power spectral density; Array Gain=0 for power measurement) |                                                                                                                               |



## 2.2. OPERATION FREQUENCY EACH OF CHANNEL

| 802.11a/802.11n(HT20)<br>802.11ac(HT20)/<br>802.11ax(HT20) |           | 802.11n(HT40)/<br>802.11ac(HT40)/<br>802.11ax(HT40) |           | 802.11ac(HT80)/<br>802.11ax(HT80) |           |
|------------------------------------------------------------|-----------|-----------------------------------------------------|-----------|-----------------------------------|-----------|
| Channel                                                    | Frequency | Channel                                             | Frequency | Channel                           | Frequency |
| 36                                                         | 5180      | 38                                                  | 5190      | 42                                | 5210      |
| 40                                                         | 5200      | 46                                                  | 5230      |                                   |           |
| 44                                                         | 5220      |                                                     |           |                                   |           |
| 48                                                         | 5240      |                                                     |           |                                   |           |

**Note:**

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

## 2.3. OPERATION OF EUT DURING TESTING

For 802.11a/n (HT20)/ac(HT20)/ax(HT20)

| Band I (5150 - 5250 MHz) |         |                 |
|--------------------------|---------|-----------------|
| Channel Number           | Channel | Frequency (MHz) |
| 36                       | Low     | 5180            |
| 40                       | Mid     | 5200            |
| 48                       | High    | 5240            |

For 802.11n (HT40)/ ac(HT40)/ax(HT40)

| Band I (5150 - 5250 MHz) |         |                 |
|--------------------------|---------|-----------------|
| Channel Number           | Channel | Frequency (MHz) |
| 38                       | Low     | 5190            |
| 46                       | High    | 5230            |


For 802.11ac(HT80)/ax(HT80)

| Band I (5150 - 5250 MHz) |                 |
|--------------------------|-----------------|
| Channel Number           | Frequency (MHz) |
| 42                       | 5210            |



## 2.4. DESCRIPTION OF TEST SETUP

Operation of EUT during testing:



The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. The worst case is X position



### 3. GENERAL INFORMATION

#### 3.1. TEST ENVIRONMENT AND MODE

| Operating Environment:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| Temperature:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 25.0 °C                                                                                                    |
| Humidity:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 56 % RH                                                                                                    |
| Atmospheric Pressure:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1010 mbar                                                                                                  |
| Test Mode:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                            |
| Engineering mode:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 100%) |
| <p>The sample was placed 0.8m/1.5m for below/above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.</p> |                                                                                                            |

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

**Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.**

| Mode                             | Data rate                                               |
|----------------------------------|---------------------------------------------------------|
| 802.11a                          | 6 Mbps                                                  |
| 802.11n(HT20)                    | MCS0                                                    |
| 802.11n(HT40)                    | MCS0                                                    |
| 802.11ac(HT20)/ac(HT40)/ac(HT80) | MCS0                                                    |
| 802.11ax(HT20)/ax(HT40)/ax(HT80) | MCS0                                                    |
| Final Test Mode:                 |                                                         |
| Operation mode:                  | Keep the EUT in continuous transmitting with modulation |



### 3.2. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Equipment | Model No. | Serial No. | FCC ID | Trade Name |
|-----------|-----------|------------|--------|------------|
| /         | /         | /          | /      | /          |

**Note:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.



## 4. TEST RESULTS AND MEASUREMENT DATA

### 4.1. CONDUCTED EMISSION

#### 4.1.1. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |              |           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.207                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |              |           |
| <b>Test Method:</b>      | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |              |           |
| <b>Frequency Range:</b>  | 150 kHz to 30 MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |              |           |
| <b>Receiver setup:</b>   | RBW=9 kHz, VBW=30 kHz, Sweep time=auto                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |              |           |
| <b>Limits:</b>           | Frequency range (MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Limit (dBuV) |           |
|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Quasi-peak   | Average   |
|                          | 0.15-0.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 66 to 56*    | 56 to 46* |
|                          | 0.5-5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 56           | 46        |
|                          | 5-30                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 60           | 50        |
| <b>Test Setup:</b>       | <p>Remark:<br/>E.U.T: Equipment Under Test<br/>LISN: Line Impedance Stabilization Network<br/>Test table height=0.8m</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |              |           |
| <b>Test Mode:</b>        | Tx Mode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |              |           |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"><li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li><li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li><li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</li></ol> |              |           |
| <b>Test Result:</b>      | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |              |           |



#### 4.1.2. Test Instruments

| Conducted Emission Shielding Room Test Site (843) |              |                    |               |                  |                 |
|---------------------------------------------------|--------------|--------------------|---------------|------------------|-----------------|
| Equipment                                         | Manufacturer | Model              | Serial Number | Calibration Date | Calibration Due |
| Receiver                                          | R&S          | ESR-7              | HKE-010       | Feb. 18, 2022    | Feb. 17, 2023   |
| LISN                                              | R&S          | ENV216             | HKE-002       | Feb. 18, 2022    | Feb. 17, 2023   |
| Coax cable<br>(9KHz-30MHz)                        | Times        | 381806-00<br>2     | N/A           | Feb. 18, 2022    | Feb. 17, 2023   |
| Conducted test<br>software                        | Tonscend     | TS+ Rev<br>2.5.0.0 | HKE-081       | N/A              | N/A             |

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



#### 4.1.3. Test data


Not applicable.

Note: EUT power supply by DC Power, so this test item not applicable.



## 4.2. MAXIMUM CONDUCTED OUTPUT POWER

### 4.2.1. Test Specification

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|
| Test Requirement: | FCC Part15 E Section 15.407(a)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |       |
| Test Method:      | KDB789033 D02 General UNII Test Procedures New Rules v02.r01 Section E                                                                                                                                                                                                                                                                                                                                                                                                                                                          |       |
| Limit:            | Frequency Band (MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Limit |
|                   | 5150-5250                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 1W    |
| Test Setup:       |  <p>Power meter</p> <p>EUT</p>                                                                                                                                                                                                                                                                                                                                                                                                                |       |
| Test Mode:        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |       |
| Test Procedure:   | <ol style="list-style-type: none"><li>1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a.</li><li>2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li><li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li><li>4. Measure the conducted output power and record the results in the test report.</li></ol> |       |
| Test Result:      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |       |
| Remark:           | Conducted output power= measurement power<br>$+10\log(1/x)$ X is duty cycle=1, so $10\log(1/1)=0$<br>Conducted output power= measurement power                                                                                                                                                                                                                                                                                                                                                                                  |       |



#### 4.2.2. Test Instruments

| RF Test Room              |              |          |               |                  |                 |
|---------------------------|--------------|----------|---------------|------------------|-----------------|
| Equipment                 | Manufacturer | Model    | Serial Number | Calibration Date | Calibration Due |
| Spectrum analyzer         | Agilent      | N9020A   | HKE-048       | Feb. 18, 2022    | Feb. 17, 2023   |
| Power meter               | Agilent      | E4419B   | HKE-085       | Feb. 18, 2022    | Feb. 17, 2023   |
| Power Sensor              | Agilent      | E9300A   | HKE-086       | Feb. 18, 2022    | Feb. 17, 2023   |
| RF cable                  | Times        | 1-40G    | HKE-034       | Feb. 18, 2022    | Feb. 17, 2023   |
| RF automatic control unit | Tonscend     | JS0806-2 | HKE-060       | Feb. 18, 2022    | Feb. 17, 2023   |

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).




## 4.2.3. Test Data

| Configuration Band I (5150 - 5250 MHz ) |              |                                      |                |       |                 |        |
|-----------------------------------------|--------------|--------------------------------------|----------------|-------|-----------------|--------|
| Mode                                    | Test channel | Maximum Conducted Output Power (dBm) |                |       | FCC Limit (dBm) | Result |
|                                         |              | Antenna port 1                       | Antenna port 2 | MIMO  |                 |        |
| 11a                                     | CH36         | 9.96                                 | 10.86          | /     | 30              | PASS   |
| 11a                                     | CH40         | 10.20                                | 12.29          | /     | 30              | PASS   |
| 11a                                     | CH48         | 11.81                                | 11.35          | /     | 30              | PASS   |
| 11n(HT20)                               | CH36         | 9.76                                 | 9.59           | 12.69 | 30              | PASS   |
| 11n(HT20)                               | CH40         | 9.99                                 | 10.03          | 13.02 | 30              | PASS   |
| 11n(HT20)                               | CH48         | 9.62                                 | 10.06          | 12.86 | 30              | PASS   |
| 11n(HT40)                               | CH38         | 10.31                                | 10.31          | 13.32 | 30              | PASS   |
| 11n(HT40)                               | CH46         | 10.17                                | 10.82          | 13.52 | 30              | PASS   |
| 11ac(HT20)                              | CH36         | 9.75                                 | 9.45           | 12.61 | 30              | PASS   |
| 11ac(HT20)                              | CH40         | 9.99                                 | 9.84           | 12.93 | 30              | PASS   |
| 11ac(HT20)                              | CH48         | 9.61                                 | 9.84           | 12.74 | 30              | PASS   |
| 11ac(HT40)                              | CH38         | 10.30                                | 10.19          | 13.26 | 30              | PASS   |
| 11ac(HT40)                              | CH46         | 10.17                                | 10.72          | 13.46 | 30              | PASS   |
| 11ac(HT80)                              | CH42         | 10.18                                | 10.45          | 13.33 | 30              | PASS   |
| 11ax(HT20)                              | CH36         | 9.39                                 | 9.25           | 12.33 | 30              | PASS   |
| 11ax(HT20)                              | CH40         | 9.69                                 | 9.69           | 12.70 | 30              | PASS   |
| 11ax(HT20)                              | CH48         | 9.35                                 | 9.75           | 12.56 | 30              | PASS   |
| 11ax(HT40)                              | CH38         | 9.76                                 | 9.75           | 12.77 | 30              | PASS   |
| 11ax(HT40)                              | CH46         | 9.64                                 | 10.12          | 12.90 | 30              | PASS   |
| 11ax(HT80)                              | CH42         | 9.74                                 | 9.96           | 12.86 | 30              | PASS   |



### 4.3. 6DB EMISSION BANDWIDTH

#### 4.3.1. Test Specification

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC CFR47 Part 15 Section 15.407(e)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Test Method:      | KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Limit:            | >500kHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Test Setup:       |  <p>Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                                                                |
| Test Mode:        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Test Procedure:   | <ol style="list-style-type: none"><li>1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C.</li><li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li><li>3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.</li><li>4. Measure and record the results in the test report.</li></ol> |
| Test Result:      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

#### 4.3.2. Test Instruments

| RF Test Room              |              |          |               |                  |                 |
|---------------------------|--------------|----------|---------------|------------------|-----------------|
| Equipment                 | Manufacturer | Model    | Serial Number | Calibration Date | Calibration Due |
| Spectrum analyzer         | Agilent      | N9020A   | HKE-048       | Feb. 18, 2022    | Feb. 17, 2023   |
| RF cable                  | Times        | 1-40G    | HKE-034       | Feb. 18, 2022    | Feb. 17, 2023   |
| RF automatic control unit | Tonscend     | JS0806-2 | HKE-060       | Feb. 18, 2022    | Feb. 17, 2023   |

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).


#### 4.3.3. Test data

N/A



#### 4.4. 26DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

##### 4.4.1. Test Specification

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.407                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Test Method:      | KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C                                                                                                                                                                                                                                                                                                                                                                                                     |
| Limit:            | No restriction limits                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Test Setup:       |  <p>Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                      |
| Test Mode:        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Test Procedure:   | <ol style="list-style-type: none"><li>1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C.</li><li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li><li>3. Make the measurement with the spectrum analyzer's resolution bandwidth <math>RBW = 1\% \text{ EBW}</math>, <math>VBW \geq 3RBW</math>, In order to make an accurate measurement.</li><li>4. Measure and record the results in the test report.</li></ol> |
| Test Result:      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

##### 4.4.2. Test Instruments

| RF Test Room              |              |          |               |                  |                 |
|---------------------------|--------------|----------|---------------|------------------|-----------------|
| Equipment                 | Manufacturer | Model    | Serial Number | Calibration Date | Calibration Due |
| Spectrum analyzer         | Agilent      | N9020A   | HKE-048       | Feb. 18, 2022    | Feb. 17, 2023   |
| RF cable                  | Times        | 1-40G    | HKE-034       | Feb. 18, 2022    | Feb. 17, 2023   |
| RF automatic control unit | Tonscend     | JS0806-2 | HKE-060       | Feb. 18, 2022    | Feb. 17, 2023   |

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



#### 4.4.3. Test data

##### ANT 1

| Mode       | Test channel | Frequency (MHz) | 26 dB Bandwidth (MHz) | Verdict |
|------------|--------------|-----------------|-----------------------|---------|
| 11a        | CH36         | 5180            | 18.52                 | PASS    |
| 11a        | CH40         | 5200            | 18.52                 | PASS    |
| 11a        | CH48         | 5240            | 18.48                 | PASS    |
| 11n(HT20)  | CH36         | 5180            | 20.04                 | PASS    |
| 11n(HT20)  | CH40         | 5200            | 19.92                 | PASS    |
| 11n(HT20)  | CH48         | 5240            | 19.96                 | PASS    |
| 11n(HT40)  | CH38         | 5190            | 39.12                 | PASS    |
| 11n(HT40)  | CH46         | 5230            | 39.20                 | PASS    |
| 11ac(HT20) | CH36         | 5180            | 19.76                 | PASS    |
| 11ac(HT20) | CH40         | 5200            | 19.92                 | PASS    |
| 11ac(HT20) | CH48         | 5240            | 19.44                 | PASS    |
| 11ac(HT40) | CH38         | 5190            | 39.28                 | PASS    |
| 11ac(HT40) | CH46         | 5230            | 39.12                 | PASS    |
| 11ac(HT80) | CH42         | 5210            | 81.12                 | PASS    |
| 11ax(HT20) | CH36         | 5180            | 20.52                 | PASS    |
| 11ax(HT20) | CH40         | 5200            | 20.48                 | PASS    |
| 11ax(HT20) | CH48         | 5240            | 20.44                 | PASS    |
| 11ax(HT40) | CH38         | 5190            | 40.08                 | PASS    |
| 11ax(HT40) | CH46         | 5230            | 40.00                 | PASS    |
| 11ax(HT80) | CH42         | 5210            | 81.60                 | PASS    |

Test plots as follows:



## Band I (5150 – 5250 MHz)

802.11a



Low



Mid



High



## 802.11n(HT20)



Low



Mid



High





## 802.11ac(HT20)



Low




Mid



High



## 802.11ac(HT40)




Low



High

## 802.11ac(HT80)





## 802.11ax(HT20)



Low



Mid



High



## 802.11ax(HT40)



Low



High

## 802.11ax(HT80)





## ANT 2

| Mode       | Test channel | Frequency (MHz) | 26 dB Bandwidth (MHz) | Verdict |
|------------|--------------|-----------------|-----------------------|---------|
| 11a        | CH36         | 5180            | 18.44                 | PASS    |
| 11a        | CH40         | 5200            | 18.40                 | PASS    |
| 11a        | CH48         | 5240            | 18.40                 | PASS    |
| 11n(HT20)  | CH36         | 5180            | 19.60                 | PASS    |
| 11n(HT20)  | CH40         | 5200            | 19.72                 | PASS    |
| 11n(HT20)  | CH48         | 5240            | 19.76                 | PASS    |
| 11n(HT40)  | CH38         | 5190            | 39.28                 | PASS    |
| 11n(HT40)  | CH46         | 5230            | 39.44                 | PASS    |
| 11ac(HT20) | CH36         | 5180            | 19.52                 | PASS    |
| 11ac(HT20) | CH40         | 5200            | 19.60                 | PASS    |
| 11ac(HT20) | CH48         | 5240            | 19.68                 | PASS    |
| 11ac(HT40) | CH38         | 5190            | 38.96                 | PASS    |
| 11ac(HT40) | CH46         | 5230            | 39.12                 | PASS    |
| 11ac(HT80) | CH42         | 5210            | 81.92                 | PASS    |
| 11ax(HT20) | CH36         | 5180            | 20.36                 | PASS    |
| 11ax(HT20) | CH40         | 5200            | 20.40                 | PASS    |
| 11ax(HT20) | CH48         | 5240            | 20.64                 | PASS    |
| 11ax(HT40) | CH38         | 5190            | 40.24                 | PASS    |
| 11ax(HT40) | CH46         | 5230            | 40.00                 | PASS    |
| 11ax(HT80) | CH42         | 5210            | 81.28                 | PASS    |

Test plots as follows:



## Band I (5150 – 5250 MHz)

802.11a



Low



Mid



High



## 802.11n(HT20)



Low



Mid



High





## 802.11ac(HT20)



## Low



## Mid



## High

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



## 802.11ac(HT40)



Low



High

## 802.11ac(HT80)





## 802.11ax(HT20)



## Low



## Mid



## High



## 802.11ax(HT40)



Low



High

## 802.11ax(HT80)





## 4.5. POWER SPECTRAL DENSITY

### 4.5.1. Test Specification

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 E Section 15.407 (a)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Test Method:      | KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Limit:            | 17dBm/MHz for Band I 5150MHz-5250MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Test Setup:       |  <p>Spectrum Analyzer                      EMI</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Test Mode:        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Test Procedure:   | <ol style="list-style-type: none"> <li>1. Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth.</li> <li>2. Set RBW =1 MHz, VBW <math>\geq 3 \times</math> RBW, Sweep time = Auto, Detector = RMS.</li> <li>3. Allow the sweeps to continue until the trace stabilizes.</li> <li>4. Use the peak marker function to determine the maximum amplitude level.</li> <li>5. The E.I.R.P spectral density used radiated test method. At a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment.</li> </ol> |
| Test Result:      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

### 4.5.2. Test Instruments

| RF Test Room              |              |          |               |                  |                 |
|---------------------------|--------------|----------|---------------|------------------|-----------------|
| Equipment                 | Manufacturer | Model    | Serial Number | Calibration Date | Calibration Due |
| Spectrum analyzer         | Agilent      | N9020A   | HKE-048       | Feb. 18, 2022    | Feb. 17, 2023   |
| RF cable                  | Times        | 1-40G    | HKE-034       | Feb. 18, 2022    | Feb. 17, 2023   |
| RF automatic control unit | Tonscend     | JS0806-2 | HKE-060       | Feb. 18, 2022    | Feb. 17, 2023   |

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



## 4.5.3. Test data


ANT 1

| Configuration Band I (5150 - 5250 MHz ) |              |                 |                 |        |
|-----------------------------------------|--------------|-----------------|-----------------|--------|
| Mode                                    | Test channel | Level [dBm/MHz] | Limit (dBm/MHz) | Result |
| 11a                                     | CH36         | 5.05            | 17              | PASS   |
| 11a                                     | CH40         | 4.53            | 17              | PASS   |
| 11a                                     | CH48         | 4.72            | 17              | PASS   |
| 11n(HT20)                               | CH36         | 4.77            | 17              | PASS   |
| 11n(HT20)                               | CH40         | 4.99            | 17              | PASS   |
| 11n(HT20)                               | CH48         | 4.27            | 17              | PASS   |
| 11n(HT40)                               | CH38         | 1.67            | 17              | PASS   |
| 11n(HT40)                               | CH46         | 1.74            | 17              | PASS   |
| 11ac(HT20)                              | CH36         | 4.3             | 17              | PASS   |
| 11ac(HT20)                              | CH40         | 5.71            | 17              | PASS   |
| 11ac(HT20)                              | CH48         | 4.5             | 17              | PASS   |
| 11ac(HT40)                              | CH38         | 1.74            | 17              | PASS   |
| 11ac(HT40)                              | CH46         | 1.17            | 17              | PASS   |
| 11ac(HT80)                              | CH42         | -0.98           | 17              | PASS   |
| 11ax(HT20)                              | CH36         | 6.4             | 17              | PASS   |
| 11ax(HT20)                              | CH40         | 6.29            | 17              | PASS   |
| 11ax(HT20)                              | CH48         | 6.18            | 17              | PASS   |
| 11ax(HT40)                              | CH38         | 3.13            | 17              | PASS   |
| 11ax(HT40)                              | CH46         | 2.29            | 17              | PASS   |
| 11ax(HT80)                              | CH42         | -0.19           | 17              | PASS   |



Test plots as follows:


Band I (5150 – 5250 MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



802.11n(HT40)



Low



High



## 802.11ac(HT20)




Low




Mid



High







## 802.11ax(HT20)



Low



Mid



High




802.11ax(HT40)



Low



High





## ANT 2

| Configuration Band I (5150 - 5250 MHz ) |              |                 |                 |        |
|-----------------------------------------|--------------|-----------------|-----------------|--------|
| Mode                                    | Test channel | Level [dBm/MHz] | Limit (dBm/MHz) | Result |
| 11a                                     | CH36         | 5.39            | 17              | PASS   |
| 11a                                     | CH40         | 5.65            | 17              | PASS   |
| 11a                                     | CH48         | 6.16            | 17              | PASS   |
| 11n(HT20)                               | CH36         | 5.03            | 17              | PASS   |
| 11n(HT20)                               | CH40         | 5.11            | 17              | PASS   |
| 11n(HT20)                               | CH48         | 4.66            | 17              | PASS   |
| 11n(HT40)                               | CH38         | 1.45            | 17              | PASS   |
| 11n(HT40)                               | CH46         | 1.97            | 17              | PASS   |
| 11ac(HT20)                              | CH36         | 4.43            | 17              | PASS   |
| 11ac(HT20)                              | CH40         | 4.6             | 17              | PASS   |
| 11ac(HT20)                              | CH48         | 4.49            | 17              | PASS   |
| 11ac(HT40)                              | CH38         | 1.26            | 17              | PASS   |
| 11ac(HT40)                              | CH46         | 2.46            | 17              | PASS   |
| 11ac(HT80)                              | CH42         | -0.93           | 17              | PASS   |
| 11ax(HT20)                              | CH36         | 6.15            | 17              | PASS   |
| 11ax(HT20)                              | CH40         | 6.09            | 17              | PASS   |
| 11ax(HT20)                              | CH48         | 6.04            | 17              | PASS   |
| 11ax(HT40)                              | CH38         | 4.14            | 17              | PASS   |
| 11ax(HT40)                              | CH46         | 4.07            | 17              | PASS   |
| 11ax(HT80)                              | CH42         | -0.13           | 17              | PASS   |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : [service@cer-mark.com](mailto:service@cer-mark.com)

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China