

RF Exposure Evaluation Report

Product	:	Headlight
Trade mark	:	MORIMOTO
Model/Type reference	:	LF-777
Serial Number	:	N/A
Report Number	:	EED32R80913602
FCC ID	:	2A73A-LF777
Date of Issue	:	Aug. 13, 2025
Test Standards	:	47 CFR Part 1.1307 47 CFR Part 1.1310 47 CFR Part 2.1091 47 CFR Part 2.1093 KDB 447498 D04 Interim General RF Exposure Guidance v01
Test result	:	PASS

Prepared for:
Morimoto Lighting
2281 Defoor Hills Rd Atlanta GA 30318, United States

Prepared by:
Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Keven Tan

Reviewed by:

Frazer Li

Approved by:

Keven Tan

Frazer Li

Aaron Ma

Date:

Aug. 13, 2025

Report Seal

Check No.: 7930050625

1 Contents

	Page
1 CONTENTS	2
2 GENERAL INFORMATION	3
2.1 CLIENT INFORMATION	3
2.2 GENERAL DESCRIPTION OF EUT	3
2.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	3
2.4 TEST LOCATION	4
2.5 DEVIATION FROM STANDARDS	4
2.6 ABNORMALITIES FROM STANDARD CONDITIONS	4
2.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	4
3 SAR EVALUATION	5
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
3.1.1 <i>Limits</i>	5
3.1.2 <i>Test Procedure</i>	5
3.1.3 <i>EUT RF Exposure Evaluation</i>	6

Report No. : EED32R80913602

Page 3 of 7

2 General Information

2.1 Client Information

Applicant:	Morimoto Lighting
Address of Applicant:	2281 Defoor Hills Rd Atlanta GA 30318, United States
Manufacturer:	Zhejiang Hongguan Technology Co.,Ltd.
Address of Manufacturer:	No. 185, Fengdu 2nd Road, Tangxia Town, Rui'an City, Zhejiang Province 325200, China
Factory:	Zhejiang Hongguan Technology Co.,Ltd.
Address of Factory:	No. 185, Fengdu 2nd Road, Tangxia Town, Rui'an City, Zhejiang Province 325200, China

2.2 General Description of EUT

Product Name:	Headlight
Model No.:	LF-777
Trade mark:	MORIMOTO

2.3 Product Specification subjective to this standard

Frequency Range:	2402MHz~2480MHz
Modulation Type:	GFSK
Test Power Grade:	Default
Test Software of EUT:	Serial Port Utility
Antenna Type:	Ceramic Antenna
Antenna Gain:	2.8dBi
Power Supply:	DC 12V
Test Voltage:	DC 12V
Sample Received Date:	Jun. 24, 2025
Sample tested Date:	Jun. 24, 2025 to Jul. 08, 2025
Product nameplate:	<p>Headlight FCC ID:2A73A-LF777 Model:LF-777</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>

2.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd
Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China
Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

2.5 Deviation from Standards

None.

2.6 Abnormalities from Standard Conditions

None.

2.7 Other Information Requested by the Customer

None.

3 SAR Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20\text{cm}}$ is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.1.3 EUT RF Exposure Evaluation**For Stand alone:**

Frequency (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
@2.4GHz	20	-9.56	2.8	-8.91	0.1285	3060	0.00004	Pass

Note:

- ①EIRP=conducted power+antenna gain;
- ②ERP=EIRP-2.15;
- ③EIRP(dBm) = Field strength of the fundamental signal(dBuV/m@3m) – 95.23;
- ④ERP(mW) = $10^{(ERP\ (dBm)/10)}$;
- ⑤The estimation distance is 20cm;
- ⑥The test data please refer to the report of EED32R80913601 and only the worst case data was recorded in the report.

Statement

1. This report is considered invalid without approved signature, special seal and the seal on the perforation;
2. The Company Name shown on Report and Address, the sample(s) and sample information was/were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified;
3. The result(s) shown in this report refer(s) only to the sample(s) tested;
4. Unless otherwise stated, the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule stated in ILAC-G8:09/2019/CNAS-GL015:2022;
5. Without written approval of CTI, this report can't be reproduced except in full;

*** End of Report ***