

# RF EXPOSURE EVALUATION

# 1. PRODUCT INFORMATION

<u> </u>	
Product Description	Bluetooth headset
Model Name	TLL511451
Series Model	TLL511461, TLL511391
FCC ID	2A74I-TLL511451

#### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

## 3. CALCULATION

P<sub>t</sub>= -3.000dBm=0.50mW

The value of the Maximum output power P<sub>t</sub> is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation SAR= $(0.50 \text{mW} / 5 \text{mm}) \cdot [\sqrt{2.480 \text{GHz}}] = 0.16 < 3.0 \text{ for } 1-\text{g SAR} \text{ and } \leq 7.5 \text{ for } 10-\text{g extremity SAR}.$ 

### 4. CONCLUSION

The SAR evaluation is not required.