

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

RF Exposure evaluation**Report Reference No.....: GTS20241123006-1-03****FCC ID.: 2A762-CQ40**

Compiled by

(position+printed name+signature) .: File administrators Peter Xiao

Supervised by

(position+printed name+signature) .: Test Engineer Jenny Zeng

Approved by

(position+printed name+signature) .: Manager Jason Hu

Date of issue: Jan.08, 2025

Representative Laboratory Name.: Shenzhen Global Test Service Co.,Ltd.

Address: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name.....: Tianjian Group Co.,Ltd.

Address: 501, No.9, Nuclear Power Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen, China

Test specification**Standard.....: 47CFR §1.1310 Basis and purpose
47CFR §2.1091 Radiofrequency radiation exposure evaluation:
mobile devices
KDB447498 D01 General RF Exposure Guidance v06**

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: IP CAMERA

Trade Mark: N/A

Manufacturer: Tianjian Group Co.,Ltd.

Model/Type reference: CQ40

Listed Models: CQ10, CQ11, CQ12, CQ13, CQ14, CQ15, CQ16, CQ17, CQ18, CQ19, CQ20, CQ21, CQ22, CQ23, CQ24, CQ25, CQ26, CQ27, CQ28, CQ29, CQ30, CQ31, CQ32, CQ33, CQ34, CQ35, CQ36, CQ37, CQ38, CQ39, CQ41, CQ42, CQ43, CQ44, CQ45, CQ46, CQ47, CQ48, CQ49, CQ50, CQ51, CQ52, CQ53, CQ54, CQ55, CQ56, CQ57, CQ58, CQ59, CQ60, CQ61, CQ62, CQ63, CQ64, CQ65, CQ66, CQ67, CQ68, CQ69, CQ70, CQ71, CQ72, CQ73, CQ74, CQ75, CQ76, CQ77, CQ78, CQ79, CC20, T-CL6930LF-W4GAM, T-CL6930LF-W4GJM

Hardware Version: N/A

Software Version: N/A

Rating: DC 5.0V by Adapter

Result: **PASS**

TEST REPORT

Test Report No. :	GTS20241123006-1-03	Jan.08, 2025
		Date of issue

Equipment under Test : IP CAMERA

Model /Type : CQ40

Listed model : CQ10, CQ11, CQ12, CQ13, CQ14, CQ15, CQ16, CQ17, CQ18, CQ19, CQ20, CQ21, CQ22, CQ23, CQ24, CQ25, CQ26, CQ27, CQ28, CQ29, CQ30, CQ31, CQ32, CQ33, CQ34, CQ35, CQ36, CQ37, CQ38, CQ39, CQ41, CQ42, CQ43, CQ44, CQ45, CQ46, CQ47, CQ48, CQ49, CQ50, CQ51, CQ52, CQ53, CQ54, CQ55, CQ56, CQ57, CQ58, CQ59, CQ60, CQ61, CQ62, CQ63, CQ64, CQ65, CQ66, CQ67, CQ68, CQ69,CQ70, CQ71, CQ72, CQ73, CQ74, CQ75, CQ76, CQ77, CQ78, CQ79, CC20, T-CL6930LF-W4GAM, T-CL6930LF-W4GJM

Applicant : Tianjian Group Co.,Ltd.

Address : 501, No.9, Nuclear Power Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen, China

Manufacturer : Tianjian Group Co.,Ltd.

Address : 501, No.9, Nuclear Power Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen, China

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY 4

1.1 EUT CONFIGURATION..... 4

1.2 PRODUCT DESCRIPTION 4

2. TEST ENVIRONMENT 5

2.1 ADDRESS OF THE TEST LABORATORY 5

2.2 TEST FACILITY 5

2.3 ENVIRONMENTAL CONDITIONS 5

2.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY 5

3. METHOD OF MEASUREMENT 6

3.1 APPLICABLE STANDARD..... 6

3.2 REQUIREMENT 6

3.3 LIMIT 6

3.4 MPE CALCULATION METHOD 7

3.5 ANTENNA INFORMATION 7

4. CONDUCTED POWER RESULTS..... 8

5. MANUFACTURING TOLERANCE 9

6. MEASUREMENT RESULTS 10

6.1 STANDALONE MPE EVALUATION 10

7. CONCLUSION 11

1. SUMMARY

1.1 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

● /	Length (m) :	/
	Shield :	/
	Detachable :	/

1.2 Product Description

Product Name:	IP CAMERA
Trade Mark:	N/A
Model/Type reference:	CQ40
List Model:	CQ10, CQ11, CQ12, CQ13, CQ14, CQ15, CQ16, CQ17, CQ18, CQ19, CQ20, CQ21, CQ22, CQ23, CQ24, CQ25, CQ26, CQ27, CQ28, CQ29, CQ30, CQ31, CQ32, CQ33, CQ34, CQ35, CQ36, CQ37, CQ38, CQ39, CQ41, CQ42, CQ43, CQ44, CQ45, CQ46, CQ47, CQ48, CQ49, CQ50, CQ51, CQ52, CQ53, CQ54, CQ55, CQ56, CQ57, CQ58, CQ59, CQ60, CQ61, CQ62, CQ63, CQ64, CQ65, CQ66, CQ67, CQ68, CQ69, CQ70, CQ71, CQ72, CQ73, CQ74, CQ75, CQ76, CQ77, CQ78, CQ79, CC20, T-CL6930LF-W4GAM, T-CL6930LF-W4GJM
Model Declaration	PCB board, structure and internal of these model(s) are the same, Only the model name different , So no additional models were tested.
Power supply:	DC 5.0V by Adapter
Hardware Version	N/A
Software Version	N/A
Sample ID	GTS20241123006-1-S0001-1#& GTS20241123006-1-S0001-2#
LTE	
LTE Operation Frequency Band	E-UTRA Band 2(1850 MHz -1910MHz) E-UTRA Band 4(1710 MHz -1755MHz) E-UTRA Band 5(824 MHz -849MHz) E-UTRA Band 7(2500 MHz -2570MHz) E-UTRA Band 12(699 MHz -716MHz) E-UTRA Band 13(777 MHz -787MHz) E-UTRA Band 17(704 MHz -716MHz) E-UTRA Band 26(814 MHz -824MHz) E-UTRA Band 26(824 MHz -849MHz) E-UTRA Band 41(2496 MHz -2690MHz) E-UTRA Band 66(1710 MHz -1780MHz)
LTE Release Version	R10
Type Of Modulation	QPSK/16QAM
Antenna Description	External Antenna; 3.56dBi (max.) For LTE Band 2; 3.24dBi (max.) For LTE Band 4; 1.79dBi (max.) For LTE Band 5; 3.38dBi (max.) For LTE Band 7; 1.43dBi (max.) For LTE Band 12; 1.64dBi (max.) For LTE Band 13; 1.43dBi (max.) For LTE Band 17; 1.64dBi (max.) For LTE Band 26(814 MHz -824MHz) 1.64dBi (max.) For LTE Band 26(824 MHz -849MHz) 3.38dBi (max.) For LTE Band 41; 3.24dBi (max.) For LTE Band 66;

2. TEST ENVIRONMENT

2.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1234.

FCC Registered Test Site Number is165725.

2.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. METHOD OF MEASUREMENT

3.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2 Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498 D01 General RF Exposure Guidance v06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3.3 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.4 MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT transmits with the maximum source-based Duty Cycle of 100%-see the User manual, and the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, $r = 20\text{cm}$, and the power drift from Turn-up Procedure provide by manufacturer as following states, the RF power density can be obtained.

3.5 Antenna Information

CQ40 can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 1	LTE	External antenna	700 – 2700 MHz	3.56dBi (max.) For LTE Band 2; 3.24dBi (max.) For LTE Band 4; 1.79dBi (max.) For LTE Band 5; 3.38dBi (max.) For LTE Band 7; 1.43dBi (max.) For LTE Band 12; 1.64dBi (max.) For LTE Band 13; 1.43dBi (max.) For LTE Band 17; 1.64dBi (max.) For LTE Band 26(814 MHz - 824MHz); 1.64dBi (max.) For LTE Band 26(824 MHz - 849MHz); 3.38dBi (max.) For LTE Band 41; 3.24dBi (max.) For LTE Band 66;

4. Conducted Power Results

<LTE Max Conducted Power>				
Test Mode		Channel	Frequency (MHz)	Max Conducted Power (dBm)
LTE	Band 2	LCH	1850.70	22.74
		MCH	1880.00	23.01
		HCH	1909.30	23.14
	Band 4	LCH	1710.70	21.04
		MCH	1732.50	21.14
		HCH	1754.30	20.93
	Band 5	LCH	824.7	23.35
		MCH	836.5	23.21
		HCH	848.3	23.18
	Band 7	LCH	2502.5	20.68
		MCH	2535.0	20.7
		HCH	2567.5	20.75
	Band 12	LCH	699.7	22.94
		MCH	707.5	22.86
		HCH	715.3	22.96
	Band 13	LCH	779.5	23.22
		MCH	782.0	23.2
		HCH	784.5	23.33
	Band 17	LCH	706.50	22.86
		MCH	710.00	22.79
		HCH	713.50	22.9
	Band 26-1	LCH	814.7	23.18
		MCH	819.0	23.19
		HCH	823.3	23.19
	Band 26-2	LCH	824.7	23.44
		MCH	836.5	23.23
		HCH	848.3	23.22
	Band 41	LCH	2498.5	21.88
		MCH	2593.0	22.02
		HCH	2687.5	22.56
	Band 66	LCH	1710.7	21.37
		MCH	1745	21.18
		HCH	1779.3	21.53

5. Manufacturing Tolerance

LTE	
Mode	Target Power
LTE BAND 2	23±1.0 dBm
LTE BAND 4	21±1.0 dBm
LTE BAND 5	23±1.0 dBm
LTE BAND 7	20±1.0 dBm
LTE BAND 12	22±1.0 dBm
LTE BAND 13	23±1.0 dBm
LTE BAND 17	22±1.0 dBm
LTE BAND 26-1	23±1.0 dBm
LTE BAND 26-2	23±1.0 dBm
LTE BAND 41	22±1.0 dBm
LTE BAND 66	21±1.0 dBm

6. Measurement Results

6.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

LTE

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
LTE Band 2	24.00	251.1886	3.56	2.2699	0.1134	1.0000
LTE Band 4	22.00	158.4893	3.24	2.1086	0.0665	1.0000
LTE Band 5	24.00	251.1886	1.79	1.5101	0.0755	0.5493
LTE Band 7	21.00	125.8925	3.38	2.1777	0.0545	1.0000
LTE Band 12	23.00	199.5262	1.43	1.3900	0.0552	0.4660
LTE Band 13	24.00	251.1886	1.64	1.4588	0.0729	0.5180
LTE Band 17	23.00	199.5262	1.43	1.3900	0.0552	0.4693
LTE Band 26-1	24.00	251.1886	1.64	1.4588	0.0729	0.5427
LTE Band 26-2	24.00	251.1886	1.64	1.4588	0.0729	0.5427
LTE Band 41	23.00	199.5262	3.38	2.1777	0.0864	1.0000
LTE Band 66	22.00	158.4893	3.24	2.1086	0.0665	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06, No SAR is required.

.....End of Report.....