

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

RF Exposure evaluation**Report Reference No. : GTS20250509019-2-10****FCC ID. : 2A762-Y661**

Compiled by

(position+printed name+signature): File administrators Peter Xiao

Supervised by

(position+printed name+signature): Test Engineer Evan Ouyang

Approved by

(position+printed name+signature) : Manager Jason Hu

Date of issue : Jun.25, 2025

Representative Laboratory Name Shenzhen Global Test Service Co.,Ltd.

..... :

Address

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name..... : Tianjian Group Co.,Ltd

Address : 501, No. 9, Nuclear Power Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen, China.

Test specification

Standard..... : 47CFR §1.1310 Basis and purpose
47CFR §2.1091 Radiofrequency radiation exposure evaluation: mobile devices
TRF Originator : Shenzhen Global Test Service Co.,Ltd.
Master TRF : Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description : WIFI camera

Trade Mark : N/A

Manufacturer : Tianjian Group Co.,Ltd

Model/Type reference : Y661

Listed Models : CP10, CP11, CP12, CP13, CP14, CP15, CP16, CP17, CP18, CP19, CP30, CP31, CP32, CP33, CP34, CP35, CP36, CP37, CP38, CP39, CP40, CP41, CP42, CP43, CP44, CP45, CP16, CP47, CP48, CP49

Hardware Version : N/A

Software Version : N/A

Rating : DC 5.0V by Adapter

Result : **PASS**

TEST REPORT

Test Report No. :	GTS20250509019-2-10	Jun.25, 2025
		Date of issue

Equipment under Test : WIFI camera

Model /Type : Y661

Listed model : CP10, CP11, CP12, CP13, CP14, CP15, CP16, CP17, CP18, CP19, CP30, CP31, CP32, CP33, CP34, CP35, CP36, CP37, CP38, CP39, CP40, CP41, CP42, CP43, CP44, CP45, CP16, CP47, CP48, CP49

Applicant : Tianjian Group Co.,Ltd

Address : 501, No. 9, Nuclear Power Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen, China.

Manufacturer : Tianjian Group Co.,Ltd

Address : 501, No. 9, Nuclear Power Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen, China.

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY 4

1.1 EUT CONFIGURATION..... 4

1.2 PRODUCT DESCRIPTION 4

2. TEST ENVIRONMENT 5

2.1 ADDRESS OF THE TEST LABORATORY 5

2.2 TEST FACILITY 5

2.3 ENVIRONMENTAL CONDITIONS 5

2.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY 5

3. METHOD OF MEASUREMENT 6

3.1 APPLICABLE STANDARD..... 6

3.2 REQUIREMENT 6

3.3 LIMIT 6

3.4 MPE CALCULATION METHOD..... 7

3.5 ANTENNA INFORMATION 7

4. CONDUCTED POWER RESULTS..... 8

5. MANUFACTURING TOLERANCE 9

6. MEASUREMENT RESULTS 11

6.1 STANDALONE MPE EVALUATION..... 11

7. CONCLUSION 12

1. SUMMARY

1.1 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

●	N/A	M/N:	N/A
		Manufacturer:	N/A

1.2 Product Description

Product Name:	WIFI camera
Trade Mark:	N/A
Model/Type reference:	Y661
List Model:	CP10, CP11, CP12, CP13, CP14, CP15, CP16, CP17, CP18, CP19, CP30, CP31, CP32, CP33, CP34, CP35, CP36, CP37, CP38, CP39, CP40, CP41, CP42, CP43, CP44, CP45, CP16, CP47, CP48, CP49
Model Declaration	PCB board, structure and internal of these model(s) are the same, Only the model name different , So no additional models were tested.
Power supply:	DC 5.0V by Adapter
Hardware Version	N/A
Software Version	N/A
Sample ID	GTS20250509019-2-1#& GTS20250509019-2-2#
Bluetooth	
Frequency Range	2402MHz ~ 2480MHz
Channel Number	40 channels for Bluetooth (DTS)
Channel Spacing	2MHz for Bluetooth (DTS)
Modulation Type	GFSK for Bluetooth (DTS)
2.4GWLAN	
WLAN Operation frequency	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz IEEE 802.11ax HE20:2412-2462MHz
WLAN Modulation Type	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax HE20: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Channel number:	11 Channel for IEEE 802.11b/g/n/ax (HT20)
Channel separation:	5MHz
WIFI(5.2G/5.8G Band)	
WLAN Operation frequency	5180-5240MHz/ 5745MHz to 5825MHz
WLAN Modulation Type	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11ac VHT20: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax HE20: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Channel number:	4 Channels for 20MHz bandwidth(5180-5240MHz) 5 channels for 20MHz bandwidth(5745-5825MHz)
Antenna Description	Internal Antenna, 2.95dBi(Max.) for 2.4G Band and 4.16dBi(Max.) for 5G Band

2. TEST ENVIRONMENT

2.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1401.

FCC Registered Test Site Number is 684561.

2.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01" Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. METHOD OF MEASUREMENT

3.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2 Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498 D01 General RF Exposure Guidance v06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3.3 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.4 MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT transmits with the maximum source-based Duty Cycle of 100%-see the User manual, and the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna is 2.95&4.16dBi for BT&WLAN, and the power drift from Turn-up Procedure provide by manufacturer as following states, the RF power density can be obtained.

3.5 Antenna Information

Y661 can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 1	Bluetooth&WLAN	Internal Antenna	2.4 – 2.5 GHz 5.0 – 6.0 GHz	2.95 dBi(Max.) for 2.4G band 4.16 dBi(Max.) for 5G band

4. Conducted Power Results

Bluetooth

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK(BT LE)	0	2402	4.04
	19	2440	4.36
	39	2480	3.89

2.4GWLAN

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11b	01	2412	15.23
	06	2437	15.67
	11	2462	15.95
802.11g	01	2412	15.62
	06	2437	16.15
	11	2462	16.40
802.11n(HT20)	01	2412	15.47
	06	2437	16.02
	11	2462	16.16
802.11ax(HE20)	01	2412	18.44
	06	2437	21.12
	11	2462	19.41

5.2GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	36	5180	9.55
	40	5200	9.66
	48	5240	10.00
802.11n20	36	5180	9.28
	40	5200	9.71
	48	5240	9.48
802.11ac20	36	5180	9.27
	40	5200	9.45
	48	5240	9.21
802.11ax20	36	5180	9.58
	40	5200	9.83
	48	5240	10.10

5.8GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	149	5745	11.26
	157	5785	12.22
	165	5825	11.31
802.11n20	149	5745	10.97
	157	5785	11.84
	165	5825	11.45
802.11ac20	149	5745	10.93
	157	5785	11.52
	165	5825	11.22
802.11ax20	149	5745	10.93
	157	5785	11.18
	165	5825	11.84

5. Manufacturing Tolerance

Bluetooth

GFSK BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	4.00	4.00	3.00

2.4GWLAN

IEEE 802.11b (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	15.00	15.00	15.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	15.00	16.00	16.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	15.00	16.00	16.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ax HE20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	18.00	21.00	19.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.2GWLAN

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	9.00	9.00	10.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	9.00	9.00	9.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	9.00	9.00	9.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ax HE20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	9.00	9.00	10.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.8GWLAN

IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.00	12.00	11.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.00	11.00	11.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.00	11.00	11.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ax HE20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.00	11.00	11.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

6. Measurement Results

6.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

BT

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK (BT LE)	5.00	3.1623	2.95	1.9724	0.0012	1.0000

2.4GWLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11b	16.00	39.8107	2.95	1.9724	0.0156	1.0000
802.11g	17.00	50.1187	2.95	1.9724	0.0197	1.0000
802.11n(HT20)	17.00	50.1187	2.95	1.9724	0.0197	1.0000
802.11ax(HE20)	22.00	158.4893	2.95	1.9724	0.0622	1.0000

5.2GWLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11a	11.00	12.5893	4.16	2.6062	0.0065	1.0000
802.11n20	10.00	10.0000	4.16	2.6062	0.0052	1.0000
802.11ac20	10.00	10.0000	4.16	2.6062	0.0052	1.0000
802.11ax20	11.00	12.5893	4.16	2.6062	0.0065	1.0000

5.8GWLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11a	13.00	19.9526	4.16	2.6062	0.0103	1.0000
802.11n20	12.00	15.8489	4.16	2.6062	0.0082	1.0000
802.11ac20	12.00	15.8489	4.16	2.6062	0.0082	1.0000
802.11ax20	12.00	15.8489	4.16	2.6062	0.0082	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06, No SAR is required.

.....End of Report.....