





π/4-DQPSK_2441_30~1000



π/4-DQPSK_2441_1000~26500



 $\pi/4$ -DQPSK_2480_0~Reference


CTC Laboratories, Inc.

中国国家认证认可监督管理委员会






π/4-DQPSK_2480_30~1000



π/4-DQPSK_2480_1000~26500



8-DPSK_2402_0~Reference


CTC Laboratories, Inc.

中国国家认证认可监督管理委员会






8-DPSK_2402_30~1000



8-DPSK_2402_1000~26500




8-DPSK_2441_0~Reference








8-DPSK_2441_30~1000



8-DPSK_2441_1000~26500




8-DPSK_2480_0~Reference






8-DPSK_2480_30~1000



8-DPSK_2480_1000~26500






3.5. 20DB Bandwidth

Limit

N/A

Test Configuration



Test Procedure

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 6. OCB and 20dB Spectrum Setting:
 - (1) Set RBW = 1% ~ 5% occupied bandwidth.
 - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.

Note: The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.

Test Mode

Please refer to the clause 2.4.

Test Results

Test Mode	Frequency[MHz]	20db EBW[MHz] 20dB Bandwidth *2/3 (kHz)		Verdict
	2402	0.942	628	PASS
GFSK	2441	0.945	630	PASS
	2480	0.936	624	PASS
π/4-DQPSK	2402	1.290	860	PASS
	2441	1.290	860	PASS
	2480	1.314	876	PASS
	2402	1.302	868	PASS
8-DPSK	2441	1.302	868	PASS
	2480	1.302	868	PASS







GFSK_2441



GFSK_2480



CTC Laboratories, Inc.

中国国家认证认可监督管理委员会




π/4-DQPSK_2402



π/4-DQPSK 2441



π/4-DQPSK_2480



8-DPSK_2402

CTC Laboratories, Inc. 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China: yz.cnca.cn







8-DPSK_2441



8-DPSK_2480





3.6. Channel Separation

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1)/ RSS-247 5.1 b:

Test Item	Limit	Frequency Range(MHz)	
Channel Separation	>25KHz or >two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5	

Test Configuration



Test Procedure

- 7. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 8. Spectrum Setting:
 - (1) Set RBW = 100 kHz.
 - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.

Test Mode

Please refer to the clause 2.4.





Test Mode Frequency[MHz] Result[MHz] Limit[kHz] Verdict **GFSK PASS** Hop_2441 1.000 >630 **PASS** $\pi/4$ -DQPSK Hop_2441 1.008 >860 8-DPSK Hop_2441 1.000 >868 **PASS**








3.7. Number of Hopping Channel

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(iii)/ RSS-247 5.1 d:

Section	Test Item	Limit	
15.247 (a)(iii)/ RSS-247 5.1 d:	Number of Hopping Channel	>15	

Test Configuration



Test Procedure

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. Spectrum Setting:
 - (1) Peak Detector: RBW=100 kHz, VBW≥RBW, Sweep time= Auto.

Test Mode


Please refer to the clause 2.4.

Test Result


	Modulation type	Channel number	Limit	Result	
	GFSK	79			
π/4-DQPSK 79		79	≥15.00	Pass	
	8DPSK	79			








π/4-DQPSK



8-DPSK






3.8. Dwell Time

Limit

Section	Test Item	Limit	
15.247(a)(iii)/ RSS-247 5.1 d	Average Time of Occupancy	0.4 sec	

Test Configuration



Test Procedure

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. Spectrum Setting:
 - (1) Spectrum Setting: RBW=1MHz, VBW≥RBW.
 - (2) Use video trigger with the trigger level set to enable triggering only on full pulses.
 - (3) Sweep Time is more than once pulse time.
- (4) Set the center frequency on any frequency would be measure and set the frequency span to zero.
 - (5) Measure the maximum time duration of one single pulse.
 - (6) Set the EUT for packet transmitting.

Test Mode

Please refer to the clause 2.4.






Test Result

Modulation type	Channel	Frequency [MHz]	Pulse Time (ms)	Total of Dwell (ms)	Period Time (ms)	Limit (Second)	Result
	DH1	2441	0.38	121.60	31.60		
GFSK	DH3	2441	1.64	262.40	31.60	≤ 0.40	Pass
	DH5	2441	2.88	307.20	31.60		
π/4-DQPSK	2DH1	2441	0.38	121.60	31.60		
	2DH3	2441	1.64	262.40	31.60	≤ 0.40	Pass
	2DH5	2441	2.89	308.27	31.60		
	3DH1	2441	0.38	121.60	31.60		
8-DPSK	3DH3	2441	1.64	262.40	31.60	≤ 0.40	Pass
	3DH5	2441	2.89	308.27	31.60		


Note: 1DH1/2DH1/3DH1Total of Dwell= Pulse Time*(1600/2)*31.6/79 1DH3/2DH3/3DH3 Total of Dwell= Pulse Time*(1600/4)*31.6/79 1DH5/2DH5/3DH5 Total of Dwell= Pulse Time*(1600/6)*31.6/79








GFSK_2441



GFSK_2480




CTC Laboratories, Inc.


中国国家认证认可监督管理委员会




π/4-DQPSK_2402



π/4-DQPSK 2441



π/4-DQPSK_2480




8-DPSK_2402

CTC Laboratories, Inc. 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China


Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn








8-DPSK_2441



8-DPSK_2480






3.9. Peak Output Power

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1) / RSS-247 5.4 b:

Test Item	Limit	Frequency Range(MHz)	
Maximum Conducted Peak Output Power	Hopping Channels>75 Pow- er<1W(30dBm) Other <125mW(21dBm)	2400~2483.5	
E.I.R.P	4 Watt or 36dBm	2400~2483.5	

Test Configuration



Test Procedure

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- Spectrum Setting:
 - (1) Set RBW> 20DB Bandwidth.
 - (2) Set the video bandwidth (VBW) ≥ RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.

Test Mode


Please refer to the clause 2.4.

Test Result


Test Mode	Frequency[MHz]	Result[dBm]	Limit[dBm]	Verdict
	2402	9.86	<=30	PASS
GFSK	2441	10.33	<=30	PASS
	2480	9.66	<=30	PASS
	2402	9.60	<=30	PASS
π/4-DQPSK	2441	10.03	<=30	PASS
	2480	9.26	<=30	PASS
	2402	9.70	<=30	PASS
8-DPSK	2441	10.15	<=30	PASS
	2480	9.49	<=30	PASS








GFSK_2441



GFSK_2480







π/4-DQPSK_2402



π/4-DQPSK 2441




π/4-DQPSK_2480




8-DPSK_2402








8-DPSK_2441



8-DPSK_2480






3.10. Duty Cycle

Limit

None, for report purposes only.

Test Configuration



Test Procedure

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05r02.
- 3. Spectrum Setting:

Set analyzer center frequency to test channel center frequency.

Set the span to 0Hz Set the RBW to 10MHz Set the VBW to 10MHz

Detector: Peak Sweep time: Auto

Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

Test Mode


Please refer to the clause 2.4.

Test Result


Test Mode	Frequency [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
	2402	2.88	3.75	76.80	0.35	1
GFSK	2441	2.88	3.75	76.80	0.35	1
	2480	2.88	3.75	76.80	0.35	1
	2402	2.89	3.75	77.07	0.35	1
π/4-DQPSK	2441	2.88	3.74	77.01	0.35	1
	2480	2.88	3.75	76.80	0.35	1
	2402	2.89	3.75	77.07	0.35	1
8-DPSK	2441	2.88	3.75	76.80	0.35	1
	2480	2.89	3.75	77.07	0.35	1




GFSK_2402



GFSK_2441



GFSK_2480




CTC Laboratories, Inc.


中国国家认证认可监督管理委员会




π/4-DQPSK_2402



π/4-DQPSK 2441




π/4-DQPSK_2480




8-DPSK_2402






8-DPSK_2441



8-DPSK_2480



Page 89 of 89

Report No.: CTC20221749E02



3.11. Antenna requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result

The directional gain of the antenna less than 6dBi, please refer to the EUT internal photographs antenna photo.



