

# Testing Report

Customer Name: GUANGDONG KEGAO ELECTRONICS CO., LTD


Product Name: Humidifier

Sample Model: HU25-02H

Reference Standard: *GB/T 9410-2008; ANSI/IEEE Std 149-2021*

Issue Date: 2023.10.11

|                 |                  |
|-----------------|------------------|
| Engineer: Zkmis | Date: 2023.10.10 |
| Auditor: Eason  | Date: 2023.10.11 |
| Approver: Jaron | Date: 2023.10.11 |



## Version

| Version No. | Date       | Description                   | Formulate | Approval |
|-------------|------------|-------------------------------|-----------|----------|
| A0          | 2023.10.11 | For the first time, formulate | Zkris     | Eason    |
|             |            |                               |           |          |
|             |            |                               |           |          |

## Contents


|                                                       |   |
|-------------------------------------------------------|---|
| 1.General Information .....                           | 3 |
| 1.1 General information of testing institutions ..... | 3 |
| 1.2 Testing principle .....                           | 3 |
| 1.3 Test equipment .....                              | 4 |
| 1.4 Test environment .....                            | 4 |
| 1.5 Statement .....                                   | 4 |
| 2.Sample Information .....                            | 5 |
| 2.1 Client information .....                          | 5 |
| 2.2 Description of EUT(S) .....                       | 5 |
| 2.3 EUT appearance .....                              | 6 |
| 2.4 EUT setup photo of free space OTA tesing .....    | 6 |
| 3.Test Results .....                                  | 7 |
| 3.1 Test standard .....                               | 7 |
| 3.2 Test uncertainty .....                            | 7 |
| 3.3 Test data .....                                   | 7 |
| 3.3.1 Typical free space efficiency and gain .....    | 7 |
| 3.3.2 Typical free space radiation pattern .....      | 8 |
| (The following is blank) .....                        | 9 |

## 1. General Information

## 1.1 General information of testing institutions

|                  |                                                                                                                                                               |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Name</b>      | Shenzhen RFI-LAB Communication Technology Co., Ltd.                                                                                                           |
| <b>Address</b>   | 10/F A, Lingyun Bld, Liufang Rd, Baoan District, SZ                                                                                                           |
| <b>Tel</b>       | /                                                                                                                                                             |
| <b>E-mail</b>    | /                                                                                                                                                             |
| <b>Equipment</b> | All the equipment used in the report is fixed in Zone B, West Side of 1/F, Building 1, Tingwei Industrial Park, No.6 Liufang Road, Bao 'an District, Shenzhen |

## 1.2 Testing principle



### 1.3 Test equipment

| Equipment        | Model No.    | Serial No.     | Manufacturer | Calibration date | Next calibration date |
|------------------|--------------|----------------|--------------|------------------|-----------------------|
| OTA Test System  | RayZone-5000 | RFI-LAB-RF-D00 | GTS          | 2023.3.14        | 2025.3.13             |
| Network Analyzer | E5071C       | RFI-LAB-RF-D01 | KEYSIGHT     | 2023.5.11        | 2024.5.10             |
| Network Analyzer | E5071C       | RFI-LAB-RF-C02 | KEYSIGHT     | 2023.5.11        | 2024.5.10             |

### 1.4 Test environment

|             |           |
|-------------|-----------|
| Temperature | 23.6°C    |
| Humidity    | 57%RH     |
| Pressure    | 100.14kPa |

### 1.5 Statement

- (1) The test results in the report are only applicable to the tested samples and the tested samples work under the environment described in the report.
- (2) Only Shenzhen RFI-LAB Communication Technology Co., Ltd. have the right to modify the report, and the modification information shall be annotated in the revision form.
- (3) Any objection to this report shall be raised within 30 days after formal confirmation of the report.
- (4) This report is invalid if there is any evidence that the sample information provided is falsified.
- (5) The report is invalid without the signature of the auditor and approver.

## 2.Sample Information



### 2.1 Client information

|                     |                                                                                                                                         |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>Name</b>         | GUANGDONG KEGAO ELECTRONICS CO., LTD                                                                                                    |
| <b>Address</b>      | No.39 East Science & Technology Ave. Zone A Shishan Science &Technology Industrial Park, Nanhai District, Foshan, Guangdong, P.R.China. |
| <b>Contacts</b>     | /                                                                                                                                       |
| <b>Tel</b>          | /                                                                                                                                       |
| <b>E-mail</b>       | /                                                                                                                                       |
| <b>Manufacturer</b> | /                                                                                                                                       |

### 2.2 Description of EUT(S)


|                        |                                             |
|------------------------|---------------------------------------------|
| <b>Product Name</b>    | Humidifier                                  |
| <b>Sample Model</b>    | HU25-02H                                    |
| <b>Antenna Size</b>    | /                                           |
| <b>Serial No.</b>      | /                                           |
| <b>Antenna Type</b>    | PCB Antenna                                 |
| <b>Test Item</b>       | Antenna gain; Efficiency; Radiation pattern |
| <b>Frequency Range</b> | 2400-2500MHz                                |
| <b>Received Date</b>   | 2023.10.9                                   |
| <b>Test Date</b>       | 2023.10.10                                  |
| <b>Remark</b>          | /                                           |

## 2.3 EUT appearance




## 2.4 EUT setup photo of free space OTA testing

Planform



Front view



## 3. Test Results

### 3.1 Test standard

| Name                         | Parameter            | Method                                                               | Standard no.           |
|------------------------------|----------------------|----------------------------------------------------------------------|------------------------|
| Mobile communication antenna | Antenna gain         | Generic specification for antennas used in the mobile communications | GB/T 9410-2008         |
|                              | Radiation pattern    |                                                                      |                        |
| Antenna                      | Radiation efficiency | IEEE Standard Test Procedures for Antennas                           | ANSI/IEEE Std 149-2021 |
|                              | Gain and directivity |                                                                      |                        |

### 3.2 Test uncertainty

The uncertainty was calculated on the basis of the GUM published by ISO, using the inclusion factor of  $K=2$  and the 95% confidence level to express the extended uncertainty.

| Item                 | Uncertainty         |
|----------------------|---------------------|
| VSWR                 | $\pm 0.3$           |
| Antenna gain         | $\pm 0.72\text{dB}$ |
| Radiation efficiency | $\pm 0.72\text{dB}$ |


### 3.3 Test data

#### 3.3.1 Typical free space efficiency and gain


| Frequency/MHz | 2400  | 2410  | 2420  | 2430  | 2440  | 2450  | 2460  | 2470  | 2480  | 2490  | 2500  |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Peak Gain/dBi | 1.20  | 1.08  | 1.10  | 1.03  | 1.01  | 0.76  | 0.78  | 0.70  | 0.37  | 0.39  | 0.41  |
| Efficiency/%  | 34.77 | 34.16 | 34.04 | 34.11 | 33.60 | 32.00 | 32.67 | 32.42 | 29.74 | 29.25 | 29.00 |

### 3.3.2 Typical free space radiation pattern


(1) X-Z Plane(unit:dBi):




(2) Y-Z Plane(unit:dBi):



(3) X-Y Plane(unit:dBi):



(4) Typical Free Space 3D Radiation Pattern at 2.4GHz(unit:dBi):



End

(The following is blank)