

TEST REPORT

ACCORDING TO: FCC 47CFR part 15 subpart C §15.247 (DTS),
RSS-247 Issue 3:2023, RSS-Gen Issue 5

FOR:

ARAD TECHNOLOGIES

AT57-7

Models: AT57-7-21-5-P-1

FCC ID: 2A7AA-SON2LR30DB

IC: 28664-SON2LR30DB

This report is in conformity with ISO/ IEC 17025. The "A2LA Accredited" symbol endorsement applies only to the tests and calibrations that are listed in the scope of Hermon Laboratories accreditation. The test results relate only to the items tested.
This test report shall not be reproduced in any form except in full with the written approval of Hermon Laboratories Ltd.



Table of contents

1	Applicant information.....	3
2	Equipment under test attributes	3
3	Manufacturer information	3
4	Test details.....	3
5	Tests summary.....	4
6	EUT description.....	5
6.1	General information.....	5
6.2	Test configuration.....	5
6.3	Transmitter characteristics	6
7	Transmitter tests according to 47CFR part 15 subpart C and RSS-247 requirements.....	7
7.1	Minimum 6 dB and 99% bandwidth	7
7.2	Peak output power	10
7.3	Field strength of spurious emissions	15
7.4	Band edge radiated emissions	36
7.5	Peak spectral power density	41
7.6	Antenna requirements	46
8	APPENDIX A Test equipment and ancillaries used for tests.....	47
9	APPENDIX B Test equipment correction factors.....	48
10	APPENDIX C Measurement uncertainties	51
11	APPENDIX D Test laboratory description	52
12	APPENDIX E Specification references.....	53
13	APPENDIX F Abbreviations and acronyms.....	54



1 Applicant information

Client name: ARAD TECHNOLOGIES
Address: POB 537, HaMada 4, Yokneam Ind. Zone, Yokneam Ilit 20692, Israel
Telephone: 04-9935222, Ext: 271
Fax: 04-9935227
E-mail: viorel.negreanu@aradtec.com
Contact name: Mr. Vily Negreanu

2 Equipment under test attributes

Product name: AT57-7
Product type: Transceiver
Model(s): AT57-7-21-5-P-1
Serial number: 70B3D5A9F087F344
Hardware version: 0B
Software release: 57.1.2.4
Receipt date 22-Apr-25

3 Manufacturer information

Manufacturer name: ARAD TECHNOLOGIES
Address: POB 537, HaMada 4, Yokneam Ind. Zone, Yokneam Ilit 20692, Israel
Telephone: 04-9935222, Ext: 271
Fax: 04-9935227
E-Mail: viorel.negreanu@aradtec.com
Contact name: Mr. Vily Negreanu

4 Test details

Project ID: 56698
Location: Hermon Laboratories Ltd. 66 HaTachana str., P.O. Box 23, Binyamina 3055001, Israel
Test started: 22-Apr-25
Test completed: 14-May-25
Test specification(s): FCC 47CFR part 15 subpart C §15.247 (DTS),
RSS-247 Issue 3:2023, RSS-Gen Issue 5



5 Tests summary

Test	Status
Transmitter characteristics	
FCC Section 15.247(a)2 / RSS-247 section 5.2(1), 6 dB bandwidth	Pass
FCC Section 15.247(b)3/ RSS-247 section 5.4(4), Peak output power	Pass
FCC Section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions	Pass
FCC Section 15.247(d)/ RSS-247 section 5.5, Emissions at band edges	Pass
FCC Section 15.247(e) / RSS-247 section 5.2(2), Peak power density	Pass
FCC section 15.203 / RSS-Gen section 6.8, Antenna requirement	Pass

Testing was completed against all relevant requirements of the test standard. The results obtained indicate that the product under test complies in full with the requirements tested.

The test results relate only to the items tested. Pass/ fail decision was based on nominal values.

	Name and Title	Date	Signature
Tested by:	Mr. S. Sugatov, test engineer, EMC & Radio Mrs. N. Lenkina, test engineer, EMC & Radio	22-Apr-25 – 14-May-25	 
Reviewed by:	Mrs. S. Peysahov Sheynin, certification engineer, EMC & Radio	20-May-25	
Approved by:	Mr. M. Nikishin, group leader, EMC & Radio	28-May-25	



6 EUT description


Note: The following data in this clause is provided by the customer and represents his sole responsibility

6.1 General information

The AT57-7 LoRa water meter is a fully integrated radio and antenna solution. It is a battery-operated radio transceiver designed for automated water reading. The AT57-7 provides optional online data of all kinds (water consumption, temperature, Alerts, Tampering, back flow...) It uses LoRaWAN radio for relaying water consumption data to the utility.

AT57-7 Intergrate Bluetooth Low energy for field maintenance.

6.2 Test configuration





6.3 Transmitter characteristics

Type of equipment							
V	Stand-alone (Equipment with or without its own control provisions)						
	Combined equipment (Equipment where the radio part is fully integrated within another type of equipment)						
	Plug-in card (Equipment intended for a variety of host systems)						
Assigned frequency range		2400 -2483.5 MHz					
Operating frequencies		2402-2480 MHz					
Maximum rated output power		Peak output power 7.11 dBm					
Is transmitter output power variable?		V	No	continuous variable			
		Yes		stepped variable with stepsize			
				minimum RF power	dBm		
				maximum RF power	dBm		
Antenna connection							
unique coupling	standard connector		V	Integral	with temporary RF connector		
			V		without temporary RF connector		
Antenna/s technical characteristics							
Type	Manufacturer		Model number		Gain		
Internal	Inhouse design		N/A		0 dBi		
Transmitter aggregate data rate/s		1 Mbps					
Type of modulation		GFSK					
Modulating test signal (baseband)							
Transmitter power source							
V	Battery	Nominal rated voltage	3.6 VDC	Battery type	Lithium Inorganic battery		
	DC	Nominal rated voltage					
	AC mains	Nominal rated voltage		Frequency	Hz		



HERMON LABORATORIES

Test specification: Section 15.247(a)2 / RSS-247 section 5.2(1), 6 dB bandwidth			
Test procedure: ANSI C63.10 section 11.8.1			
Test mode: Compliance		Verdict: PASS	
Date(s): 24-Apr-25			
Temperature: 24 °C	Relative Humidity: 51 %	Air Pressure: 1006 hPa	Power: 3.6 VDC
Remarks:			

7 Transmitter tests according to 47CFR part 15 subpart C and RSS-247 requirements

7.1 Minimum 6 dB and 99% bandwidth

7.1.1 General

This test was performed to measure 6 dB bandwidth of the EUT carrier frequency. Specification test limits are given in Table 7.1.1.

Table 7.1.1 6 dB bandwidth limits


Assigned frequency, MHz	Modulation envelope reference points*, dBc	Minimum bandwidth, kHz
902.0 – 928.0		
2400.0 – 2483.5	6.0	500.0
5725.0 – 5850.0		

* - Modulation envelope reference points provided in terms of attenuation below the peak of modulated carrier.

7.1.2 Test procedure

- 7.1.2.1 The EUT was set up as shown in Figure 7.1.1, energized and its proper operation was checked.
- 7.1.2.2 The EUT was set to transmit modulated carrier.
- 7.1.2.3 The transmitter minimum 6 dB bandwidth was measured with spectrum analyzer as frequency delta between reference points on modulation envelope and provided in Table 7.1.2 and associated plot.

Figure 7.1.1 6 dB bandwidth test setup





HERMON LABORATORIES

Test specification: Section 15.247(a)2 / RSS-247 section 5.2(1), 6 dB bandwidth					
Test procedure: ANSI C63.10 section 11.8.1					
Test mode: Compliance					Verdict: PASS
Date(s): 24-Apr-25					
Temperature: 24 °C	Relative Humidity: 51 %	Air Pressure: 1006 hPa	Power: 3.6 VDC		
Remarks:					

Table 7.1.2 6 dB bandwidth test results


ASSIGNED FREQUENCY BAND: 2400.0 – 2483.5 MHz
 DETECTOR USED: Peak
 SWEEP TIME: Auto
 RESOLUTION BANDWIDTH: 100 kHz
 VIDEO BANDWIDTH: 300 kHz
 MODULATION: GFSK
 BIT RATE: 1 Mbps

Carrier frequency, MHz	99% bandwidth, kHz	6 dB bandwidth, kHz	Limit, kHz	Margin, kHz	Verdict
2402	1007	671.50	500	171.50	Pass
2440	1068	625.20	500	125.20	Pass
2480	1059	659.90	500	159.90	Pass

Reference numbers of test equipment used

HL 4355	HL 5601	HL 4135	HL 5637				
---------	---------	---------	---------	--	--	--	--


Full description is given in Appendix A.

Plot 7.1.1 6 dB bandwidth test result at low frequency




HERMON LABORATORIES

Test specification: Section 15.247(a)2 / RSS-247 section 5.2(1), 6 dB bandwidth			
Test procedure: ANSI C63.10 section 11.8.1			
Test mode: Compliance			Verdict: PASS
Date(s): 24-Apr-25			
Temperature: 24 °C	Relative Humidity: 51 %	Air Pressure: 1006 hPa	Power: 3.6 VDC
Remarks:			

Plot 7.1.2 6 dB bandwidth test result at mid frequency

Date: 24.APR.2025 15:55:20

Date: 24.APR.2025 15:56:50

Plot 7.1.3 6 dB bandwidth test result at high frequency

Date: 24.APR.2025 16:00:42

Date: 24.APR.2025 16:11:07



HERMON LABORATORIES

Report ID: ARARAD_FCC.56698_DTS.docx

Date of Issue: 28-May-25

Test specification: Section 15.247(b), RSS-247 section 5.4(1), Peak output power			
Test procedure: ANSI C63.10, section 7.8.5			
Test mode: Compliance		Verdict: PASS	
Date(s): 08-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

7.2 Peak output power

7.2.1 General

This test was performed to measure the maximum peak output power radiated by transmitter. Specification test limits are given in Table 7.2.1.

Table 7.2.1 Peak output power limits

Assigned frequency range, MHz	Maximum antenna gain, dBi	Peak output power*		Equivalent field strength limit @ 3m, dB(µV/m)**
		W	dBm	
902.0 – 928.0				
2400.0 – 2483.5	6.0	1.0	30.0	131.2
5725.0 – 5850.0				

*- The limit is provided in terms of conducted RF power at the antenna connector. If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power limit shall be reduced below the stated value as follows:

by 1 dB for every 3 dB that the directional gain of antenna exceeds 6 dBi for fixed point-to-point transmitters operate in 2400-2483.5 MHz band;

without any corresponding reduction for fixed point-to-point transmitters operate in 5725-5850 MHz band; by the amount in dB that the directional gain of antenna exceeds 6 dBi for the rest of transmitters.

**- Equivalent field strength limit was calculated from the peak output power as follows: $E = \sqrt{30 \times P \times G} / r$, where P is peak output power in Watts, r is antenna to EUT distance in meters and G is transmitter antenna gain in dBi.

7.2.2 Test procedure

7.2.2.1 The EUT was set up as shown in Figure 7.2.1, energized and its proper operation was checked.

7.2.2.2 The EUT was adjusted to produce maximum available to end user RF output power.

7.2.2.3 The resolution bandwidth of spectrum analyzer was set wider than 6 dB bandwidth of the EUT and the field strength of the EUT carrier frequency was measured with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360° and the measuring antenna height was swept in both vertical and horizontal polarizations.

7.2.2.4 The maximum field strength of the EUT carrier frequency was measured as provided in Table 7.2.2 and associated plots.

7.2.2.5 The maximum peak output power was calculated from the field strength of carrier as follows:

$$P = (E \times d)^2 / (30 \times G)$$

where P is the peak output power in W, E is the field strength in V/m, d is the test distance and G is the transmitter numeric antenna gain over an isotropic radiator.

The above equation was converted in logarithmic units for 3 m test distance:

$$\text{Peak output power in dBm} = \text{Field strength in dB}(\mu\text{V}/\text{m}) - \text{Transmitter antenna gain in dBi} - 95.2 \text{ dB}$$

7.2.2.6 The worst test results (the lowest margins) were recorded in Table 7.2.2.




HERMON LABORATORIES

Report ID: ARARAD_FCC.56698_DTS.docx

Date of Issue: 28-May-25

Test specification: Section 15.247(b), RSS-247 section 5.4(1), Peak output power			
Test procedure: ANSI C63.10, section 7.8.5			
Test mode: Compliance			Verdict: PASS
Date(s): 08-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Figure 7.2.1 Setup for carrier field strength measurements





HERMON LABORATORIES

Report ID: ARARAD_FCC.56698_DTS.docx

Date of Issue: 28-May-25

Test specification: Section 15.247(b), RSS-247 section 5.4(1), Peak output power	
Test procedure:	ANSI C63.10, section 7.8.5
Test mode:	Compliance
Date(s):	08-May-25
Temperature: 24 °C	Relative Humidity: 42 %
	Air Pressure: 1015 hPa
	Power: 3.7 VDC
Remarks:	

Table 7.2.2 Peak output power test results

ASSIGNED FREQUENCY: 2400 – 2483.5 MHz
 TEST DISTANCE: 3 m
 TEST SITE: Semi anechoic chamber
 EUT HEIGHT: 1.5 m
 DETECTOR USED: Peak
 TEST ANTENNA TYPE: Double ridged guide
 MODULATION: GFSK
 BIT RATE: 1 Mbps
 DETECTOR USED: Peak
 EUT 6 dB BANDWIDTH: 0.67 MHz
 RESOLUTION BANDWIDTH: 3 MHz
 VIDEO BANDWIDTH: 10 MHz

Frequency, MHz	Field strength, dB(µV/m)	Antenna polarization	Antenna height, m	Azimuth, degrees*	EUT antenna gain, dBi	Peak output power, dBm**	Limit, dBm	Margin, dB***	Verdict
2402	101.98	V	3.5	-40	0	6.78	30	-23.22	Pass
2440	102.31	V	3.7	-30	0	7.11	30	-22.89	Pass
2480	100.78	V	3.8	-10	0	5.58	30	-24.42	Pass

*- EUT front panel refer to 0 degrees position of turntable.

**- Peak output power was calculated from the field strength of carrier as follows: $P = (E \times d)^2 / (30 \times G)$, where P is the peak output power in W, E is the field strength in V/m, d is the test distance in meters and G is the transmitter numeric antenna gain over an isotropic radiator. The above equation was converted in logarithmic units for 3 m test distance: *Peak output power in dBm = Field strength in dB(µV/m) - Transmitter antenna gain in dBi - 95.2 dB*

***- Margin = Peak output power – specification limit.

Reference numbers of test equipment used

HL 4114	HL 5902	HL 7585	HL 3903				
---------	---------	---------	---------	--	--	--	--


Full description is given in Appendix A.




HERMON LABORATORIES

Test specification:	Section 15.247(b), RSS-247 section 5.4(1), Peak output power		
Test procedure:	ANSI C63.10, section 7.8.5		
Test mode:	Compliance	Verdict:	PASS
Date(s):	08-May-25		
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.2.1 Field strength of carrier at low frequency



Plot 7.2.2 Field strength of carrier at mid frequency






HERMON LABORATORIES

Test specification:	Section 15.247(b), RSS-247 section 5.4(1), Peak output power		
Test procedure:	ANSI C63.10, section 7.8.5		
Test mode:	Compliance	Verdict:	PASS
Date(s):	08-May-25		
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.2.3 Field strength of carrier at high frequency





HERMON LABORATORIES

Report ID: ARARAD_FCC.56698_DTS.docx

Date of Issue: 28-May-25

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance			
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

7.3 Field strength of spurious emissions

7.3.1 General

This test was performed to measure field strength of spurious emissions from the EUT. Specification test limits are given in Table 7.3.1.

Table 7.3.1 Radiated spurious emissions limits

Frequency, MHz	Field strength at 3 m within restricted bands, dB(µV/m)*			Attenuation of field strength of spurious versus carrier outside restricted bands, dBc***
	Peak	Quasi Peak	Average	
0.009 – 0.090	148.5 – 128.5	NA	128.5 – 108.5**	20.0
0.090 – 0.110	NA	108.5 – 106.8**	NA	
0.110 – 0.490	126.8 – 113.8	NA	106.8 – 93.8**	
0.490 – 1.705		73.8 – 63.0**		
1.705 – 30.0*		69.5		
30 – 88	NA	40.0	NA	
88 – 216		43.5		
216 – 960		46.0		
960 - 1000		54.0		
1000 – 10 th harmonic	74.0	NA	54.0	

*- The limit for 3 m test distance was calculated using the inverse square distance extrapolation factor as follows:

$$Lims_2 = Lims_1 + 40 \log (S_1/S_2)$$

where S_1 and S_2 – standard defined and test distance respectively in meters.

**- The limit decreases linearly with the logarithm of frequency.

*** - The field strength limits applied from the lowest radio frequency generated in the device, without going below 9 kHz up to the tenth harmonic of the highest fundamental frequency.

7.3.2 Test procedure for spurious emission field strength measurements in 9 kHz to 30 MHz band

7.3.2.1 The EUT was set up as shown in Figure 7.3.1, energized and the performance check was conducted.

7.3.2.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360° and the measuring antenna was rotated around its vertical axis.

7.3.2.3 The worst test results (the lowest margins) were recorded and shown in the associated plots.

7.3.3 Test procedure for spurious emission field strength measurements above 30 MHz

7.3.3.1 The EUT was set up as shown in Figure 7.3.2, Figure 1.1.3, energized and the performance check was conducted.

7.3.3.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360°, the measuring antenna height was changed from 1 to 4 m, its polarization was switched from vertical to horizontal.

7.3.3.3 The worst test results (the lowest margins) were recorded and shown in the associated plots.




HERMON LABORATORIES

Report ID: ARARAD_FCC.56698_DTS.docx

Date of Issue: 28-May-25

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance		Verdict: PASS	
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Figure 7.3.1 Setup for spurious emission field strength measurements below 30 MHz





HERMON LABORATORIES

Report ID: ARARAD_FCC.56698_DTS.docx

Date of Issue: 28-May-25

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance			Verdict: PASS
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Figure 7.3.2 Setup for spurious emission field strength measurements in 30 -1000 MHz





Figure 7.3.3 Setup for spurious emission field strength measurements above 1000 MHz





Test specification:	Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	ANSI C63.10, sections 6.5, 6.6		
Test mode:	Compliance	Verdict:	PASS
Date(s):	08-May-25 - 14-May-25		
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Table 7.3.2 Field strength of emissions outside restricted bands

ASSIGNED FREQUENCY:	2400 – 2483.5 MHz
INVESTIGATED FREQUENCY RANGE:	0.009 - 25000 MHz
TEST DISTANCE:	3 m
MODULATION:	GFSK
BIT RATE:	1 Mbps
TRANSMITTER OUTPUT POWER:	6.78 dBm at low carrier frequency 7.11 dBm at mid carrier frequency 5.58 dBm at high carrier frequency
DETECTOR USED:	Peak
RESOLUTION BANDWIDTH:	100 kHz
VIDEO BANDWIDTH:	300 kHz
TEST ANTENNA TYPE:	Active loop (9 kHz – 30 MHz) Biconilog (30 MHz – 1000 MHz) Double ridged guide (above 1000 MHz)

Basic ruggedized (above 1000 m.s.l.)										
Frequency, MHz	Field strength of spurious, dB(μ V/m)	Antenna polarization	Antenna height, m	Azimuth, degrees*	Field strength of carrier, dB(μ V/m)	Attenuation below carrier, dBc	Limit, dBc	Margin, dB**	Verdict	
Low carrier frequency 2402 MHz										
174.7	36.67	Horizontal	1.81	43	99.94	63.27	20.0	43.27	Pass	
178.7	36.46	Horizontal	1.60	-135		63.48		43.48		
16814.0	46.26	Vertical	2.8	0		53.68		33.68		
Mid carrier frequency 2440 MHz										
174.7	39.83	Horizontal	1.80	45	100.86	61.03	20.0	41.03	Pass	
17080.0	46.66	Vertical	1.02	-110		54.20		34.20		
High carrier frequency 2480 MHz										
178.7	39.40	Horizontal	1.75	43	100.48	61.08	20.0	41.08	Pass	
17360.0	48.57	Vertical	3.9	-145		51.91		31.91		

*- EUT front panel refers to 0 degrees position of turntable

**- Margin = Attenuation below carrier – specification limit



Test specification:	Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	ANSI C63.10, sections 6.5, 6.6		
Test mode:	Compliance		
Date(s):	08-May-25 - 14-May-25		
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Table 7.3.3 Field strength of spurious emissions above 1 GHz within restricted bands

ASSIGNED FREQUENCY:	2400 – 2483.5 MHz
INVESTIGATED FREQUENCY RANGE:	1000 - 25000 MHz
TEST DISTANCE:	3 m
MODULATION:	GFSK
BIT RATE:	1 Mbps
TRANSMITTER OUTPUT POWER:	6.78 dBm at low carrier frequency 7.11 dBm at mid carrier frequency 5.58 dBm at high carrier frequency
DETECTOR USED:	Peak
RESOLUTION BANDWIDTH:	1000 kHz
TEST ANTENNA TYPE:	Double ridged guide

Frequency, MHz	Antenna		Azimuth, degrees*	Peak field strength			Average field strength				Verdict
	Polarization	Height, m		Measured, dB(µV/m)	Limit, dB(µV/m)	Margin, dB**	Measured, dB(µV/m)	Calculated, dB(µV/m)	Limit, dB(µV/m)	Margin, dB***	
Low carrier frequency 2402 MHz											
4803.4	Vertical	2.72	-112	50.98	74.00	-23.02	50.98	37.01	54.00	-16.99	Pass
12008.9	Vertical	3.82	-85	60.24	74.00	-11.59	60.24	46.27	54.00	-7.73	
Mid carrier frequency 2440 MHz											
4879.9	Vertical	2.71	-112	50.13	74.00	-23.87	50.13	36.16	54.00	-17.84	Pass
7320.6	Vertical	3.57	-158	52.26	74.00	-21.74	52.26	38.29	54.00	-15.71	
12201.1	Vertical	1.02	-117	60.27	74.00	-19.27	60.27	46.30	54.00	-7.70	
High carrier frequency 2480 MHz											
4960.3	Vertical	1.44	-64	49.27	74.00	-24.73	49.27	35.97	54.00	-18.70	Pass
7440.1	Vertical	1.02	19	52.36	74.00	-21.64	52.36	38.39	54.00	-15.61	
12398.5	Horizontal	1.66	-89	54.06	74.00	-19.94	54.06	40.09	54.00	-13.91	

*- EUT front panel refers to 0 degrees position of turntable.

**- Margin = Measured field strength - specification limit.

***- Margin = Calculated field strength - specification limit.

where Calculated field strength = Measured field strength + average factor.

Table 7.3.4 Average factor calculation

Transmission pulse		Transmission burst		Transmission train duration, ms	Average factor, dB
Duration, ms	Period, ms	Duration, ms	Period, ms		
0.125	0.628	NA	NA	NA	-13.97

*- Average factor was calculated as follows

for pulse train shorter than 100 ms:

$$\therefore \text{Average factor} = 20 \times \log_{10} \left(\frac{\text{Pulse duration}}{\text{Pulse period}} \times \frac{\text{Burst duration}}{\text{Train duration}} \times \text{Number of bursts within pulse train} \right)$$

for pulse train longer than 100 ms:

$$Average\ factor = 20 \times \log_{10} \left(\frac{Pulse\ duration \times Burst\ duration}{Pulse\ period} \times \frac{100\ ms}{100\ ms} \times Number\ of\ bursts\ within\ 100\ ms \right)$$



HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance		Verdict: PASS	
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Table 7.3.5 Field strength of spurious emissions below 1 GHz within restricted bands

ASSIGNED FREQUENCY:	2400 – 2483.5 MHz
INVESTIGATED FREQUENCY RANGE:	0.009 – 1000 MHz
TEST DISTANCE:	3 m
MODULATION:	GFSK
BIT RATE:	1 Mbps
TRANSMITTER OUTPUT POWER:	6.78 dBm at low carrier frequency 7.11 dBm at mid carrier frequency 5.58 dBm at high carrier frequency
RESOLUTION BANDWIDTH:	0.2 kHz (9 kHz – 150 kHz) 9.0 kHz (150 kHz – 30 MHz) 120 kHz (30 MHz – 1000 MHz)
VIDEO BANDWIDTH:	> Resolution bandwidth
TEST ANTENNA TYPE:	Active loop (9 kHz – 30 MHz) Biconilog (30 MHz – 1000 MHz)

Frequency, MHz	Peak emission, dB(µV/m)	Quasi-peak			Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict
Low carrier frequency 2402 MHz		Measured emission, dB(µV/m)			Limit, dB(µV/m)	Margin, dB*		
		No emissions were detected					Pass	
Mid carrier frequency 2440 MHz		No emissions were detected					Pass	
High carrier frequency 2480 MHz		No emissions were detected					Pass	

*- Margin = Measured emission - specification limit.

**- EUT front panel refer to 0 degrees position of turntable.



HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions					
Test procedure: ANSI C63.10, sections 6.5, 6.6					
Test mode: Compliance				Verdict:	PASS
Date(s): 08-May-25 - 14-May-25					
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa		Power: 3.7 VDC	
Remarks:					

Table 7.3.6 Restricted bands according to FCC section 15.205

MHz	MHz	MHz	MHz	MHz	GHz
0.09 - 0.11	8.37625 - 8.38675	73 - 74.6	399.9 - 410	2690 - 2900	10.6 - 12.7
0.495 - 0.505	8.41425 - 8.41475	74.8 - 75.2	608 - 614	3260 - 3267	13.25 - 13.4
2.1735 - 2.1905	12.29 - 12.293	108 - 121.94	960 - 1240	3332 - 3339	14.47 - 14.5
4.125 - 4.128	12.51975 - 12.52025	123 - 138	1300 - 1427	3345.8 - 3358	15.35 - 16.2
4.17725 - 4.17775	12.57675 - 12.57725	149.9 - 150.05	1435 - 1626.5	3600 - 4400	17.7 - 21.4
4.20725 - 4.20775	13.36 - 13.41	156.52475 - 156.52525	1645.5 - 1646.5	4500 - 5150	22.01 - 23.12
6.215 - 6.218	16.42 - 16.423	156.7 - 156.9	1660 - 1710	5350 - 5460	23.6 - 24
6.26775 - 6.26825	16.69475 - 16.69525	162.0125 - 167.17	1718.8 - 1722.2	7250 - 7750	31.2 - 31.8
6.31175 - 6.31225	16.80425 - 16.80475	167.72 - 173.2	2200 - 2300	8025 - 8500	36.43 - 36.5
8.291 - 8.294	25.5 - 25.67	240 - 285	2310 - 2390	9000 - 9200	
8.362 - 8.366	37.5 - 38.25	322 - 335.4	2483.5 - 2500	9300 - 9500	Above 38.6

Table 7.3.7 Restricted bands according to RSS-Gen

MHz	MHz	MHz	MHz	MHz	GHz
0.09 - 0.11	8.291 - 8.294	16.80425 - 16.80475	399.9 - 410	3260 - 3267	10.6 - 12.7
2.1735 - 2.1905	8.362 - 8.366	25.5 - 25.67	608 - 614	3332 - 3339	13.25 - 13.4
3.020 - 3.026	8.37625 - 8.38675	37.5 - 38.25	960 - 1427	3345.8 - 3358	14.47 - 14.5
4.125 - 4.128	8.41425 - 8.41475	73 - 74.6	1435 - 1626.5	3500 - 4400	15.35 - 16.2
4.17725 - 4.17775	12.29 - 12.293	74.8 - 75.2	1645.5 - 1646.5	4500 - 5150	17.7 - 21.4
4.20725 - 4.20775	12.51975 - 12.52025	108 - 138	1660 - 1710	5350 - 5460	22.01 - 23.12
5.677 - 5.683	12.57675 - 12.57725	156.52475 - 156.52525	1718.8 - 1722.2	7250 - 7750	23.6 - 24
6.215 - 6.218	13.36 - 13.41	156.7 - 156.9	2200 - 2300	8025 - 8500	31.2 - 31.8
6.26775 - 6.26825	16.42 - 16.423	240 - 285	2310 - 2390	9000 - 9200	36.43 - 36.5
6.31175 - 6.31225	16.69475 - 16.69525	322 - 335.4	2655 - 2900	9300 - 9500	Above 38.6

Reference numbers of test equipment used

HL 3903	HL 4114	HL 4338	HL 4933	HL 4956	HL 5112	HL 5288	HL 5902
HL 7585							

Full description is given in Appendix A.




HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure:	ANSI C63.10, sections 6.5, 6.6		
Test mode:	Compliance		
Date(s):	08-May-25 - 14-May-25		
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			


Plot 7.3.1 Radiated emission measurements at the low carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.3.2 Radiated emission measurements at the mid carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal






HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance			
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.3.3 Radiated emission measurements at the high carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal





HERMON LABORATORIES


Report ID: ARARAD_FCC.56698_DTS.docx

Date of Issue: 28-May-25

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance			
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			


Plot 7.3.4 Radiated emission measurements from 9 kHz to 30 MHz at the low carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical



Plot 7.3.5 Radiated emission measurements from 9 kHz to 30 MHz at the mid carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical





HERMON LABORATORIES


Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure:	ANSI C63.10, sections 6.5, 6.6		
Test mode:	Compliance		
Date(s):	08-May-25 - 14-May-25		
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.3.6 Radiated emission measurements from 9 kHz to 30 MHz at the high carrier frequency

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m

ANTENNA POLARIZATION: Vertical






HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance			
Date(s): 08-May-25 - 14-May-25			Verdict: PASS
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			


Plot 7.3.7 Radiated emission measurements from 30 to 1000 MHz at the low carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.3.8 Radiated emission measurements from 30 to 1000 MHz at the mid carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal






HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance			Verdict: PASS
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.3.9 Radiated emission measurements from 30 to 1000 MHz at the high carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal






HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance			Verdict: PASS
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			


Plot 7.3.10 Radiated emission measurements from 1000 to 18000 MHz at the low carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.3.11 Radiated emission measurements from 1000 to 18000 MHz at the mid carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal






HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance			Verdict: PASS
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.3.12 Radiated emission measurements from 1000 to 18000 MHz at the high carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal



NOTE: Frequency band 2.1 – 3 GHz was suppressed by the filter HL4338.




HERMON LABORATORIES


Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance			
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.3.13 Radiated emission measurements from 2100 to 3000 MHz at the low carrier frequency

TEST SITE: Semi anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical and Horizontal

**Plot 7.3.14 Radiated emission measurements from 2100 to 3000 MHz at the mid carrier frequency**

TEST SITE: Semi anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical and Horizontal






HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure:	ANSI C63.10, sections 6.5, 6.6		
Test mode:	Compliance		
Date(s):	08-May-25 - 14-May-25		
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.3.15 Radiated emission measurements from 2100 to 3000 MHz at the high carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal






HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance			
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			


Plot 7.3.16 Radiated emission measurements from 18000 to 25000 MHz at the low carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.3.17 Radiated emission measurements from 18000 to 25000 MHz at the mid carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal






HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance			Verdict: PASS
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.3.18 Radiated emission measurements from 18000 to 25000 MHz at the high carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal





HERMON LABORATORIES


Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance		Verdict: PASS	
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.3.19 Radiated emission measurements at the seventh harmonic of low carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m

**Plot 7.3.20 Radiated emission measurements at the seventh harmonic of mid carrier frequency**



TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m





HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions			
Test procedure: ANSI C63.10, sections 6.5, 6.6			
Test mode: Compliance			Verdict: PASS
Date(s): 08-May-25 - 14-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.3.21 Radiated emission measurements at the seventh harmonic of high carrier frequencyTEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m**Plot 7.3.22 Transmission pulse duration and transmission pulse period**



HERMON LABORATORIES

Report ID: ARARAD_FCC.56698_DTS.docx

Date of Issue: 28-May-25

Test specification: Section 15.247(d), RSS-247 section 5.5, Emissions at band edges			
Test procedure:	ANSI C63.10, section 7.8.6		
Test mode:	Compliance		
Date(s):	08-May-25		
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

7.4 Band edge radiated emissions

7.4.1 General

This test was performed to measure emissions, radiated from the EUT at the assigned frequency band edges. Specification test limits are given in Table 7.4.1.

Table 7.4.1 Band edge emission limits

Output power	Assigned frequency, MHz	Attenuation below carrier*, dBc	Field strength at 3 m within restricted bands, dB(µV/m)	
			Peak	Average
Peak	902.0 – 928.0	20.0	74.0	54.0
	2400.0 – 2483.5			
	5725.0 – 5850.0			

* - Band edge emission limit is provided in terms of attenuation below the peak of modulated carrier measured with the same resolution bandwidth.

7.4.2 Test procedure


- 7.4.2.1 The EUT was set up as shown in Figure 7.4.1, energized normally modulated at the maximum data rate and its proper operation was checked.
- 7.4.2.2 The EUT was adjusted to produce maximum available to end user RF output power at the lowest carrier frequency.
- 7.4.2.3 The spectrum analyzer span was set to capture the carrier frequency and associated modulation products. The resolution bandwidth was set wider than 1 % of the frequency span.
- 7.4.2.4 The spectrum analyzer was set in max hold mode and allowed trace to stabilize. The highest emission level within the authorized band was measured.
- 7.4.2.5 The maximum band edge emission and modulation product outside of the band were measured as provided in Table 7.4.2 and associated plots and referenced to the highest emission level measured within the authorized band.
- 7.4.2.6 The above procedure was repeated with the EUT adjusted to produce maximum RF output power at the highest carrier frequency.
- 7.4.2.7 The above procedure was repeated with the frequency hopping function enabled.



HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Emissions at band edges			
Test procedure: ANSI C63.10, section 7.8.6			
Test mode: Compliance			Verdict: PASS
Date(s): 08-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Figure 7.4.1 Band edge emission test setup





HERMON LABORATORIES

Report ID: ARARAD_FCC.56698_DTS.docx

Date of Issue: 28-May-25

Test specification: Section 15.247(d), RSS-247 section 5.5, Emissions at band edges	
Test procedure: ANSI C63.10, section 7.8.6	
Test mode: Compliance	Verdict: PASS
Date(s): 08-May-25	
Temperature: 24 °C	Air Pressure: 1015 hPa
Relative Humidity: 42 %	Power: 3.7 VDC
Remarks:	

Table 7.4.2 Band edge emission test results outside restricted band

ASSIGNED FREQUENCY RANGE: 2400 – 2483.5 MHz
 DETECTOR USED: Peak
 MODULATION: GFSK
 BIT RATE: 1 Mbps
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum
 TRANSMITTER OUTPUT POWER: 6.78 dBm at low carrier frequency
 5.58 dBm at high carrier frequency
 RESOLUTION BANDWIDTH: 100 kHz / 1 MHz
 VIDEO BANDWIDTH: 300 kHz / 3 MHz

Frequency, MHz	Band edge emission, dB _u V/m	Emission at carrier, dB _u V/m	Attenuation below carrier, dBc	Limit, dBc	Margin, dB	Verdict
2400.0	63.00	101.13	38.13	20.0	18.13	Pass

Table 7.4.3 Band edge emission within restricted band test results

Frequency, MHz	Peak field strength			Average field strength			Verdict
	Measured, dB(μV/m)	Limit, dB(μV/m)	Margin, dB*	Measured Peak, dB(μV/m)	Limit, dB(μV/m)	Margin, dB*	
2390.0	48.22	74	-25.78	48.22	54	-5.78	Pass
2483.5	53.59	74	-20.41	53.59	54	-0.31	Pass

*- Margin = Measured field strength - specification limit.

Reference numbers of test equipment used



HL 4114	HL 5902	HL 7585					
---------	---------	---------	--	--	--	--	--

Full description is given in Appendix A.



HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Emissions at band edges			
Test procedure: ANSI C63.10, section 7.8.6			
Test mode: Compliance			Verdict: PASS
Date(s): 08-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			


Plot 7.4.1 The highest emission level within the assigned band at low carrier frequency**Plot 7.4.2 The highest emission level within the assigned band at high carrier frequency**



HERMON LABORATORIES

Test specification: Section 15.247(d), RSS-247 section 5.5, Emissions at band edges			
Test procedure: ANSI C63.10, section 7.8.6			
Test mode: Compliance		Verdict: PASS	
Date(s): 08-May-25			
Temperature: 24 °C	Relative Humidity: 42 %	Air Pressure: 1015 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.4.3 The highest band edge emission at low carrier frequency





HERMON LABORATORIES

Report ID: ARARAD_FCC.56698_DTS.docx

Date of Issue: 28-May-25

Test specification:	Section 15.247(e) / RSS-247 section 5.2(2), Maximum power spectral density		
Test procedure:	ANSI C63.10 section 11.10.2		
Test mode:	Compliance		
Date(s):	22-Apr-25 - 13-May-25		
Temperature: 24 °C	Relative Humidity: 51 %	Air Pressure: 1003 hPa	Power: 3.7 VDC
Remarks:			

7.5 Peak spectral power density

7.5.1 General

This test was performed to measure the peak spectral power density radiated by the transmitter RF antenna. Specification test limits are given in Table 7.5.1

Table 7.5.1 Peak spectral power density limits

Assigned frequency range, MHz	Measurement bandwidth, kHz	Peak spectral power density, dBm	Equivalent field strength limit @ 3m, dB(µV/m)*
902.0 – 928.0			
2400.0 – 2483.5	3.0	8.0	103.2
5725.0 – 5850.0			

* - Equivalent field strength limit was calculated from the peak spectral power density as follows: $E = \sqrt{30 \times P} / r$, where P is peak spectral power density and r is antenna to EUT distance in meters.

7.5.2 Test procedure for field strength measurements


- 7.5.2.1 The EUT was set up as shown in Figure 7.5.1, energized and its proper operation was checked.
- 7.5.2.2 The EUT was adjusted to produce maximum available to end user RF output power.
- 7.5.2.3 The field strength of the EUT carrier frequency was measured with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360° and the measuring antenna height was swept in both vertical and horizontal polarizations.
- 7.5.2.4 The frequency span of spectrum analyzer was set to capture the entire 6 dB band of the transmitter, in peak hold mode with resolution bandwidth set to 3.0 kHz, video bandwidth wider than resolution bandwidth, auto sweep time and sufficient number of sweeps was allowed for trace stabilization. The spectrum lines spacing was verified to be wider than 3 kHz. Otherwise the resolution bandwidth was reduced until individual spectrum lines were resolved and the power of individual spectrum lines was integrated over 3 kHz band.
- 7.5.2.5 The peak of emission was zoomed with span set just wide enough to capture the emission peak area and sweep time was set equal to span width divided by resolution bandwidth. Spectrum analyzer was set in peak hold mode, sufficient number of sweeps was allowed for trace stabilization and peak spectral power density was measured as provided in Table 7.5.2 and associated plots.



HERMON LABORATORIES

Test specification: Section 15.247(e) / RSS-247 section 5.2(2), Maximum power spectral density			
Test procedure: ANSI C63.10 section 11.10.2			
Test mode: Compliance			Verdict: PASS
Date(s): 22-Apr-25 - 13-May-25			
Temperature: 24 °C	Relative Humidity: 51 %	Air Pressure: 1003 hPa	Power: 3.7 VDC
Remarks:			

Figure 7.5.1 Setup for carrier field strength measurements





HERMON LABORATORIES

Report ID: ARARAD_FCC.56698_DTS.docx

Date of Issue: 28-May-25

Test specification:		Section 15.247(e) / RSS-247 section 5.2(2), Maximum power spectral density		
Test procedure:		ANSI C63.10 section 11.10.2		
Test mode:		Compliance		
Date(s):		22-Apr-25 - 13-May-25		
Temperature: 24 °C	Relative Humidity: 51 %	Air Pressure: 1003 hPa	Power: 3.7 VDC	
Remarks:				

Table 7.5.2 Field strength measurement of peak spectral power density

ASSIGNED FREQUENCY:

2400 – 2483.5 MHz

TEST DISTANCE:

3 m

TEST SITE:

Semi anechoic chamber

EUT HEIGHT:

0.8 m

DETECTOR USED:

Peak

RESOLUTION BANDWIDTH:

3 kHz

VIDEO BANDWIDTH:

10 kHz

TEST ANTENNA TYPE:

Double ridged guide

MODULATION:

GFSK

Frequency, MHz	Field strength, dB(µV/m)	EUT antenna gain, dBi	Limit, dB(µV/m)	Margin, dB*	Antenna polarization	Antenna height, m	Turn-table position**, degrees
2402	85.31	0	103.2	-17.89	V	3.7	-40
2440	86.19	0	103.2	-17.01	V	3.5	-40
2480	85.06	0	103.2	-18.14	V	3.4	-35

*- Margin = Field strength - EUT antenna gain - calculated field strength limit.

**- EUT front panel refer to 0 degrees position of turntable.

Reference numbers of test equipment used

HL 7585	HL 4114	HL 3903	HL 5902				
---------	---------	---------	---------	--	--	--	--

Full description is given in Appendix A.



HERMON LABORATORIES

Test specification: Section 15.247(e) / RSS-247 section 5.2(2), Maximum power spectral density			
Test procedure: ANSI C63.10 section 11.10.2			
Test mode: Compliance		Verdict: PASS	
Date(s): 22-Apr-25 - 13-May-25			
Temperature: 24 °C	Relative Humidity: 51 %	Air Pressure: 1003 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.5.1 Peak spectral power density at low frequency



Plot 7.5.2 Peak spectral power density at mid frequency






HERMON LABORATORIES

Test specification: Section 15.247(e) / RSS-247 section 5.2(2), Maximum power spectral density			
Test procedure: ANSI C63.10 section 11.10.2			
Test mode: Compliance		Verdict: PASS	
Date(s): 22-Apr-25 - 13-May-25			
Temperature: 24 °C	Relative Humidity: 51 %	Air Pressure: 1003 hPa	Power: 3.7 VDC
Remarks:			

Plot 7.5.3 Peak spectral power density at high frequency





HERMON LABORATORIES

Test specification:	FCC Section 15.203/ RSS-Gen, Section 7.1.4, Antenna requirement		
Test procedure:	Visual inspection / supplier declaration		
Test mode:	Compliance	Verdict:	PASS
Date(s):	22-Apr-25 - 13-May-25		
Temperature: 24 °C	Relative Humidity: 51 %	Air Pressure: 1003 hPa	Power: 3.7 VDC
Remarks:			

7.6 Antenna requirements

The EUT was verified for compliance with antenna requirements. A transmitter shall be designed to ensure that no antenna other than that furnished by the responsible party will be used with the device. It may be either permanently attached or employs a unique antenna connector for every antenna proposed for use with the EUT. This requirement does not apply to professionally installed transmitters.

The rationale for compliance with the above requirements was either visual inspection results or supplier declaration. The summary of results is provided in Table 7.6.1.

Table 7.6.1 Antenna requirements

Requirement	Rationale	Verdict
The transmitter antenna is permanently attached	Visual inspection	Comply
The transmitter employs a unique antenna connector	NA	
The transmitter requires professional installation	NA	



HERMON LABORATORIES

8 APPENDIX A Test equipment and ancillaries used for tests

HL No	Description	Manufacturer	Model	Ser. No.	Last Cal./Check	Due Cal./Check
0604	Antenna BiconiLog Log-Periodic/T Bow-TIE, 26 - 2000 MHz	EMCO	3141	9611-1011	23-Aug-23	23-Aug-26
3903	Microwave Cable Assembly, 40.0 GHz, 1.5 m, SMA/SMA	Huber-Suhner	SUCOFL EX 102A	1226/2A	06-May-24	06-Jun-25
4114	Antenna, Double-Ridged Waveguide Horn, 1 to 18 GHz	ETS Lindgren	3117	00123515	27-Oct-24	27-Oct-25
4135	Shield Box	TESCOM CO., LTD	TC-5916A	5916A000 136	20-May-24	20-May-25
4338	Reject Band Filter, 50 Ohm, 0 to 2170 and 3000 to 18000 MHz, SMA-FM / SMA-M	Micro-Tronics	BRM 50702-02	023	10-Jul-24	10-Jul-26
4355	Signal and Spectrum Analyzer, 9 kHz to 7 GHz	Rohde & Schwarz	FSV 7	101630	19-Jun-24	19-Jun-25
4933	Active Horn Antenna, 1 GHz to 18 GHz	COM-POWER CORPORATION	AHA-118	701046	19-Feb-25	19-Feb-26
4956	Active horn antenna, 18 to 40 GHz	COM-POWER CORPORATION	AHA-840	105004	25-Mar-25	25-Mar-26
5112	RF cable, 40 GHz, 5.5 m, K-type	Huber-Suhner	SF102EA/ 11SK/11S K/5500M M	502494/2E A	02-Jun-24	02-Jun-25
5288	Trilog Antenna, 25 MHz - 8 GHz, 100W	Frankonia	ALX- 8000E	00809	08-Apr-25	08-Apr-27
5601	Precision Fixed Attenuator, 50 Ohm, 5 W, 10 dB, DC to 18000 MHz	Mini Circuits	BW- N10W5+	NA	14-Aug-24	14-Aug-25
5611	Precision Fixed Attenuator, 50 Ohm, 5 W, 10 dB, DC to 18 GHz	Mini Circuits	BW- S10W5+	NA	06-Feb-25	06-Feb-26
5637	Cable, 50 Ohm, DC to 18 GHz, 1.8 m, SMA/SMA	Mini Circuits	CBL-6FT- SMSM+	NA	21-Apr-25	21-Apr-26
5902	RF cable, 18 GHz, 6.0m, N-type	Huber-Suhner	SF126EA/ 11N/11N/ 6000	NA	24-Apr-25	24-Apr-26
5903	RF cable, 18 GHz, 6.0m, N-type	Huber-Suhner	SF126EA/ 11N/11N/ 6000		06-Aug-24	06-Aug-25
7585	EMI Test Receiver, 1 Hz to 44 GHz	Rohde & Schwarz	ESW44	103130	24-Sep-24	24-Sep-25



HERMON LABORATORIES

9 APPENDIX B Test equipment correction factors

**HL 5288: Trilog Antenna
Frankonia, model: ALX-8000E, s/n: 00809
30-1000 MHz**

Frequency, MHz	Antenna factor, dB/m
30	14.96
35	15.33
40	16.37
45	17.56
50	17.95
60	16.87
70	13.22
80	10.56
90	13.61
100	15.46
120	14.03
140	12.23

Frequency, MHz	Antenna factor, dB/m
160	12.67
180	13.34
200	15.40
250	16.42
300	17.28
400	19.98
500	21.11
600	22.90
700	24.13
800	25.25
900	26.35
1000	27.18

The antenna factor shall be added to receiver reading in dB μ V to obtain field strength in dB μ V/m.
above 1000 MHz

Frequency, MHz	Antenna factor, dB/m
1000	26.9
1100	28.1
1200	28.4
1300	29.6
1400	29.1
1500	30.4
1600	30.7
1700	31.5
1800	32.3
1900	32.6
2000	32.5
2100	32.9
2200	33.5
2300	33.2
2400	33.7
2500	34.6
2600	34.7
2700	34.6
2800	35.0
2900	35.5
3000	36.2
3100	36.8
3200	36.8
3300	37.0
3400	37.5
3500	38.2

Frequency, MHz	Antenna factor, dB/m
3600	38.9
3700	39.4
3800	39.4
3900	39.6
4000	39.7
4100	39.8
4200	40.5
4300	40.9
4400	41.1
4500	41.4
4600	41.3
4700	41.6
4800	41.9
4900	42.3
5000	42.7
5100	43.0
5200	42.9
5300	43.5
5400	43.6
5500	44.3
5600	44.7
5700	45.0
5800	45.0
5900	45.3
6000	45.9

The antenna factor shall be added to receiver reading in dB μ V to obtain field strength in dB μ V/m.



HERMON LABORATORIES

**HL 0446: Active Loop Antenna
EMCO, model: 6502, s/n 2857**

Frequency,	Measured antenna factor, dBs/m	Measurement uncertainty, dB
10	-33.4	±1.0
20	-37.8	±1.0
50	-40.5	±1.0
75	-41.0	±1.0
100	-41.2	±1.0
150	-41.2	±1.0
250	-41.1	±1.0
500	-41.2	±1.0
750	-41.3	±1.0
1000	-41.3	±1.0

Frequency,	Measured antenna factor, dBs/m	Measurement uncertainty, dB
2000	-41.4	±1.0
3000	-41.4	±1.0
4000	-41.5	±1.0
5000	-41.5	±1.0
10000	-41.7	±1.0
15000	-42.1	±1.0
20000	-42.7	±1.0
25000	-44.2	±1.0
30000	-45.8	±1.0

The antenna factor shall be added to receiver reading in dB μ V to obtain field strength in dB μ A/m.



HERMON LABORATORIES

HL 4933: Active Horn Antenna
COM-POWER CORPORATION, model: AHA-118, s/n 701046

Frequency, MHz	Measured antenna factor (with preamplifier), dB/m
1000	-16.1
1500	-15.1
2000	-10.9
2500	-11.9
3000	-11.1
3500	-10.6
4000	-8.6
4500	-8.3
5000	-5.9
5500	-5.7
6000	-3.3
6500	-4.0
7000	-2.2
7500	-1.7
8000	1.1
8500	-0.8
9000	-1.5
9500	-0.2

Frequency, MHz	Measured antenna factor (with preamplifier), dB/m
10000	1.8
10500	1.0
11000	0.3
11500	-0.5
12000	3.1
12500	1.4
13000	-0.3
13500	-0.4
14000	2.5
14500	2.2
15000	1.9
15500	0.5
16000	2.1
16500	1.2
17000	0.6
17500	3.1
18000	4.2

The antenna factor shall be added to receiver reading in dB μ V to obtain field strength in dB μ V/m.



HERMON LABORATORIES

10 APPENDIX C Measurement uncertainties

Expanded uncertainty at 95% confidence in Hermon Labs EMC measurements

Test description	Expanded uncertainty
Conducted carrier power at RF antenna connector	Below 12.4 GHz: ± 1.7 dB 12.4 GHz to 40 GHz: ± 2.3 dB
Conducted emissions at RF antenna connector	9 kHz to 2.9 GHz: ± 2.6 dB 2.9 GHz to 6.46 GHz: ± 3.5 dB 6.46 GHz to 13.2 GHz: ± 4.3 dB 13.2 GHz to 22.0 GHz: ± 5.0 dB 22.0 GHz to 26.8 GHz: ± 5.5 dB 26.8 GHz to 40.0 GHz: ± 4.8 dB
Occupied bandwidth	± 8.0 %
Duty cycle, timing (Tx ON / OFF) and average factor measurements	± 1.0 %
Conducted emissions with LISN	9 kHz to 150 kHz: ± 3.9 dB 150 kHz to 30 MHz: ± 3.8 dB
Radiated emissions at 3 m measuring distance Horizontal polarization	Biconilog antenna: ± 5.3 dB Biconical antenna: ± 5.0 dB Log periodic antenna: ± 5.3 dB Double ridged horn antenna: ± 5.3 dB Biconilog antenna: ± 6.0 dB Biconical antenna: ± 5.7 dB Log periodic antenna: ± 6.0 dB Double ridged horn antenna: ± 6.0 dB
Vertical polarization	

Hermon Laboratories is accredited by A2LA for calibration according to present requirements of ISO/IEC 17025 and NCSL Z540-1. The accreditation is granted to perform calibration of parameters that are listed in the Scope of Hermon Laboratories Accreditation.

Hermon Laboratories calibrates its reference and transfer standards by calibration laboratories accredited to ISO/IEC 17025 by a mutually recognized Accreditation Body or by a recognized national metrology institute. All reference and transfer standards used in the calibration system are traceable to national or international standards.

In-house calibration of all test and measurement equipment is performed on a regular basis according to Hermon Laboratories calibration procedures, manufacturer calibration/verification procedures or procedures defined in the relevant standards. The Hermon Laboratories test and measurement equipment is calibrated within the tolerances specified by the manufacturers and/or by the relevant standards.



HERMON LABORATORIES

11 APPENDIX D Test laboratory description

Tests were performed at Hermon Laboratories Ltd., which is a fully independent, private, EMC, Radio, Safety, Environmental and Telecommunication testing facility.

Hermon Laboratories is recognized and accredited by the Federal Communications Commission (USA) for relevant parts of Code of Federal Regulations 47 (CFR 47), Test Firm Registration Number is 927748, Designation Number is IL1001; Recognized by Innovation, Science and Economic Development Canada for wireless and terminal testing (ISED), ISED #2186A, CAB identifier is IL1001; Certified by VCCI, Japan (the registration numbers are R-10808 for OATS, R-1082 for anechoic chamber, G-10869 for RE measurements above 1 GHz, C-10845 for conducted emissions site and T-11606 for conducted emissions at telecommunication ports).

The laboratory is accredited by American Association for Laboratory Accreditation (USA) according to ISO/IEC 17025 for electromagnetic compatibility, product safety, telecommunications testing, environmental simulation and calibration (for exact scope please refer to Certificate No. 839.01, 839.03 and 839.04).

Address: P.O. Box 23, Binyamina 3055001, Israel.
Telephone: +972 4628 8001
Fax: +972 4628 8277
e-mail: mail@hermonlabs.com
website: www.hermonlabs.com

Person for contact: Mr. Michael Nikishin, EMC&Radio group manager



HERMON LABORATORIES

12 APPENDIX E

Specification references

FCC 47CFR part 15: 2022	Radio Frequency Devices
ANSI C63.10: 2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
RSS-247 Issue 3: 2023	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence- Exempt Local Area Network (LE-LAN) Devices
RSS-Gen Issue 5 with_amendment_1_2: 2021	General Requirements and Information for the Certification of Radiocommunication Equipment



HERMON LABORATORIES

13 APPENDIX F Abbreviations and acronyms

A	ampere
AC	alternating current
A/m	ampere per meter
AM	amplitude modulation
AVRG	average (detector)
cm	centimeter
dB	decibel
dBm	decibel referred to one milliwatt
dB(µV)	decibel referred to one microvolt
dB(µV/m)	decibel referred to one microvolt per meter
dB(µA)	decibel referred to one microampere
DC	direct current
EIRP	equivalent isotropically radiated power
ERP	effective radiated power
EUT	equipment under test
F	frequency
GHz	gigahertz
GND	ground
H	height
HL	Hermon laboratories
Hz	hertz
k	kilo
kHz	kilohertz
LO	local oscillator
m	meter
MHz	megahertz
min	minute
mm	millimeter
ms	millisecond
µs	microsecond
NA	not applicable
NB	narrow band
OATS	open area test site
Ω	Ohm
PM	pulse modulation
PS	power supply
ppm	part per million (10^{-6})
QP	quasi-peak
RE	radiated emission
RF	radio frequency
rms	root mean square
Rx	receive
s	second
T	temperature
Tx	transmit
V	volt
WB	wideband

END OF DOCUMENT