

尺寸: 67\*47mm  
数量: 12000张  
正反面印刷



### MagSafe mobile power supply manual

#### Product parameters

Product name: Magnetic Wireless Power Bank  
Model: CD-08  
Type-C Output: 5V= 3A 9V= 2A 12V=1.5A(QC3.0 18W)  
USB Output: 5V= 3A 9V= 2A 12V= 1.5A(QC3.0 18W 22.5W)  
Battery Capacity: 10000mAh / 37Wh  
Wireless Charger Output: 7.5W/10W/15W  
Type-C Input: 5V- 3A 9V- 2A 12V- 1.5A(PD3.0 20W)  
wireless power out: 5V-2.1A 5V-3A 15W  
Product material: ABS + PC  
Usage: magnetic suction  
Battery type : polymer lithium ion battery  
Packaging standard configuration: MagSafe mobile power supply \* 1  
manual\* 1

#### Instructions

1. When charging the mobile power supply, first connect the power cord With the mobile power supply lightning, and then connect the other End with the charger Connect the charging head and insert the Charging head into the power supply.
2. Orange light means less than 80% power, and a green light means more Than 80% power
3. Aim the mobile power supply at the wireless charging receiving Position of the mobile phone and pull it on the mobile phone to Charge the mobile phone

4. When the mobile phone is fully charged or does not need to be Charged, remove the mobile power supply.
5. When the mobile power supply is low, the orange light flashes to Prompt charging. Please connect the power cord for charging.
6. If the Qi wireless receiving equipment is far away from the center of The module, the module will not enter the charging state, at this time The Qi wireless receiving device needs to be moved to the center of The transmitting module coil, and the module will enter automatically State of charge.
7. If the module detects that the Qi wireless receiver is abnormal, the Foreign matter at the receiver shall be transmitted from the transmitter Remove it from the module and put the receiving end equipment on The transmitting module again to enter the charging state.

#### Attention

1. It has overcurrent protection (OCP), short circuit protection (short), Overvoltage and undervoltage protection (UVP),foreign object Detection (FOD), no-load protection and other functions
2. Short circuit protection when the output port is short circuited or Exceeds the software protection current value, the power supply will Be automatically turned off. The load must be removed and the Machine must be started again. If the load is seriously short circuited, It may cause hardware short circuit After the protective circuit action Power supply is turned off, the load must be removed and the power Supply can be used normally only after charging is activated.
3. Avoid direct sunlight, high temperature and other environments, and Stay away from fire and heat sources.
4. Store in a dry environment and avoid contact with corrosive Substances.
5. The power supply shall be kept at 50% of the rated capacity for more Than 3 months.
6. When children use the power supply, they should be guided by their Parents and operate according to the contents of the manual to Ensure that it is correct Use power.
7. Do not disassemble or put into the fire without permission to avoid Explosion

#### FCC Warning

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

NOTE 1: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

NOTE 2: Any changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.