



FCC ID: 2A7CZ-JB01

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



FCC ID: 2A7CZ-JB01

Test Result of RF Exposure Evaluation

Antenna gain=2dBi

For BLE

Mode	Output power (dBm)	Output power (mW)	Numeric antenna gain	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
GFSK	2.33	1.71	1.58	0.0005	1.0	PASS

For 2.4G WIFI

Mode	Output power (dBm)	Output power (mW)	Numeric antenna gain	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11b	11.83	15.24	1.58	0.0048	1.0	PASS
802.11g	15.19	33.04	1.58	0.0104	1.0	PASS
802.11n(HT20)	15.08	32.21	1.58	0.0101	1.0	PASS
802.11n(HT40)	13.58	22.80	1.58	0.0072	1.0	PASS

For 5.2G WIFI

Mode	Output power (dBm)	Output power (mW)	Numeric antenna gain	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11a	10.91	12.33	1.58	0.0039	1.0	PASS
802.11n(HT20)	11.37	13.71	1.58	0.0043	1.0	PASS
802.11n(HT40)	11.34	13.61	1.58	0.0043	1.0	PASS
802.11ac(HT20)	11.41	13.84	1.58	0.0044	1.0	PASS
802.11ac(HT40)	11.42	13.87	1.58	0.0044	1.0	PASS
802.11ac(HT80)	11.00	12.59	1.58	0.0040	1.0	PASS

For 5.8G WIFI

Mode	Output power (dBm)	Output power (mW)	Numeric antenna gain	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11a	10.08	10.19	1.58	0.0032	1.0	PASS
802.11n(HT20)	10.21	10.50	1.58	0.0033	1.0	PASS
802.11n(HT40)	9.94	9.86	1.58	0.0031	1.0	PASS
802.11ac(HT20)	10.13	10.30	1.58	0.0032	1.0	PASS
802.11ac(HT40)	9.81	9.57	1.58	0.0030	1.0	PASS
802.11ac(HT80)	9.57	9.06	1.58	0.0029	1.0	PASS

If BLE and 2.4G WIFI operate simultaneously, Total power density=0.0005/1+0.0104/1=0.0109<1.0

If BLE and 5.2G WIFI operate simultaneously, Total power density=0.0005/1+0.0044/1=0.0049<1.0

If BLE and 5.8G WIFI operate simultaneously, Total power density=0.0005/1+0.0033/1=0.0038<1.0

Then SAR evaluation is not require .