



# FCC RADIO TEST REPORT

**FCC ID** : 2A7DJ-2346766867652  
**Equipment** : Smart Radio LTE with Walkie-Talkie  
**Brand Name** : weavix  
**Model Name** : walt  
**Applicant** : PK Solutions LLC  
10811 E Harry St. Wichita, KS 67207, USA  
**Manufacturer** : Arima Communications (Jiangsu) Co., Ltd  
No.168, Jiaotong Notrh Road, Economic  
and Technological Development Zone,  
Wujiang District Suzhou City, Jiangsu  
Province, P.R.China  
**Standard** : FCC Part 15 Subpart C §15.247

The product was received on Jun. 17, 2022 and testing was performed from Jul. 12, 2022 to Aug. 16, 2022. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

**Sportun International Inc. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



## Table of Contents

<b>History of this test report.....</b>	<b>3</b>
<b>Summary of Test Result.....</b>	<b>4</b>
<b>1 General Description.....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT .....	5
1.3 Testing Location .....	6
1.4 Applicable Standards.....	6
<b>2 Test Configuration of Equipment Under Test.....</b>	<b>7</b>
2.1 Carrier Frequency Channel .....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system .....	9
2.5 EUT Operation Test Setup .....	10
2.6 Measurement Results Explanation Example.....	10
<b>3 Test Result.....</b>	<b>11</b>
3.1 Number of Channel Measurement .....	11
3.2 Hopping Channel Separation Measurement .....	13
3.3 Dwell Time Measurement .....	17
3.4 20dB and 99% Bandwidth Measurement .....	19
3.5 Output Power Measurement.....	26
3.6 Conducted Band Edges Measurement.....	27
3.7 Conducted Spurious Emission Measurement .....	32
3.8 Radiated Band Edges and Spurious Emission Measurement .....	39
3.9 AC Conducted Emission Measurement.....	43
3.10 Antenna Requirements .....	45
<b>4 List of Measuring Equipment .....</b>	<b>46</b>
<b>5 Uncertainty of Evaluation.....</b>	<b>48</b>
<b>Appendix A. Conducted Test Results</b>	
<b>Appendix B. AC Conducted Emission Test Result</b>	
<b>Appendix C. Radiated Spurious Emission</b>	
<b>Appendix D. Radiated Spurious Emission Plots</b>	
<b>Appendix E. Duty Cycle Plots</b>	
<b>Appendix F. Setup Photographs</b>	



## History of this test report



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	Pass	-
3.4	2.1049	99% Occupied Bandwidth	Reporting only	-
3.5	15.247(b)(1)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	8.97 dB under the limit at 30.000 MHz
3.9	15.207	AC Conducted Emission	Pass	8.79 dB under the limit at 0.542 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	Pass	-

**Declaration of Conformity:**

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.  
It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
2. The measurement uncertainty please refer to report "Uncertainty of Evaluation".

**Comments and Explanations:**

The product specifications of the EUT presented in the report are declared by the manufacturer who shall take full responsibility for the authenticity.

**Reviewed by: Avis Chuang****Report Producer: Cindy Liu**



## 1 General Description

### 1.1 Product Feature of Equipment Under Test

LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ac, Wi-Fi 5GHz 802.11a/n/ac, NFC, and GNSS.

Product Feature	
<b>HW Version</b>	0910MB-003
<b>SW Version</b>	2.A.0025
<b>Antenna Type</b>	WWAN: PIFA Antenna WLAN: Loop Antenna Bluetooth: Loop Antenna GPS / Glonass / BDS / Galileo: PIFA Antenna NFC: Loop Antenna
Antenna information	
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi) 0.8

**Remark:** The EUT's information above is declared by manufacturer. Please refer to Comments and Explanations in report summary.

### 1.2 Modification of EUT

No modifications made to the EUT during the testing.



### 1.3 Testing Location

<b>Test Site</b>	Sportun International Inc. EMC & Wireless Communications Laboratory
<b>Test Site Location</b>	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
<b>Test Site No.</b>	<b>Sportun Site No.</b> CO05-HY, 03CH07-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

<b>Test Site</b>	Sportun International Inc. Wensan Laboratory
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
<b>Test Site No.</b>	<b>Sportun Site No.</b> TH05-HY (TAF Code: 3786)
<b>Remark</b>	The Conducted test item subcontracted to Sporton International Inc. Wensan Laboratory

FCC designation No.: TW1190 and TW3786

### 1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

**Remark:**

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-




## 2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
  
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	Data Rate / Modulation		
Conducted Test Cases	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
	Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :WLAN (2.4GHz) Link + Bluetooth Link + USB Cable (Charging from AC Adapter) + Earphone		
<b>Remark:</b> For Radiated Test Cases, the worst mode data rate 1Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission.			

## 2.3 Connection Diagram of Test System



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	Dell	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A



## 2.5 EUT Operation Test Setup

The RF test items, utility “QRCT 4.0.00158.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

*Offset(dB) = RF cable loss(dB) + attenuator factor(dB).*

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

##### 3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300 kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.


##### 3.1.4 Test Setup





### 3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.



## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


### 3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

### 3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300 kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup




### 3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.




&lt;1Mbps&gt;






&lt;2Mbps&gt;





&lt;3Mbps&gt;



### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

#### 3.3.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

**Remark:**

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

### 3.4 20dB and 99% Bandwidth Measurement

#### 3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


#### 3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

#### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Use the following spectrum analyzer settings for 20 dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.  
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;  
RBW  $\geq$  1-5% of the 99% bandwidth; VBW  $\geq$  3 \* RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
6. Measure and record the results in the test report.

#### 3.4.4 Test Setup




#### 3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.




&lt;1Mbps&gt;






&lt;2Mbps&gt;





&lt;3Mbps&gt;






### 3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


<1Mbps>



**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




&lt;2Mbps&gt;



**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



&lt;3Mbps&gt;



**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.5 Output Power Measurement

### 3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band:

1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.


### 3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

### 3.5.4 Test Setup



### 3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

### 3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

### 3.6.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set the maximum power setting and enable the EUT to transmit continuously.
3. Set RBW = 100 kHz, VBW = 300 kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2 and 3.
5. Measure and record the results in the test report.

### 3.6.4 Test Setup




### 3.6.5 Test Result of Conducted Band Edges

<1Mbps>




<2Mbps>






&lt;3Mbps&gt;




### 3.6.6 Test Result of Conducted Hopping Mode Band Edges

<1Mbps>




<2Mbps>





&lt;3Mbps&gt;





## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.7.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

### 3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, scan up through 10th harmonic. All harmonics / spurious must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


### 3.7.4 Test Setup






### 3.7.5 Test Result of Conducted Spurious Emission

<1Mbps>









&lt;2Mbps&gt;


## CSE Plot on CH 00 between 30 MHz ~ 3 GHz




## CSE Plot on CH 00 between 2 GHz ~ 25 GHz




## CSE Plot on CH 39 between 30 MHz ~ 3 GHz



## CSE Plot on CH 39 between 2 GHz ~ 25 GHz









&lt;3Mbps&gt;

## CSE Plot on CH 00 between 30 MHz ~ 3 GHz




Date: 22.JUL.2022 17:31:26

## CSE Plot on CH 00 between 2 GHz ~ 25 GHz




Date: 22.JUL.2022 17:32:02

## CSE Plot on CH 39 between 30 MHz ~ 3 GHz




Date: 25.JUL.2022 09:06:55

## CSE Plot on CH 39 between 2 GHz ~ 25 GHz



Date: 25.JUL.2022 09:07:26





## 3.8 Radiated Band Edges and Spurious Emission Measurement

### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics / spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### 3.8.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.




### 3.8.3 Test Procedures

1. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
2. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT is arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW = 100 kHz for  $f < 1$  GHz, RBW = 1 MHz for  $f > 1$  GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 \cdot \log_{10}$  (Duty cycle)
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
8. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.


Note: The average levels are calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from  $20 \log_{10} (\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup


For radiated emissions test below 30MHz




For radiated emissions test from 30MHz to 1GHz



For radiated emissions test from 1GHz to 18GHz



For radiated emissions test above 18GHz



### 3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

### 3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

### 3.8.7 Duty Cycle

Please refer to Appendix E.

### 3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

Please refer to Appendix C and D.



## 3.9 AC Conducted Emission Measurement

### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


### 3.9.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

### 3.9.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.9.4 Test Setup



### 3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	35419 & 03	30MHz~1GHz	Apr. 24, 2022	Jul. 19, 2022~ Aug. 16, 2022	Apr. 23, 2023	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Dec. 03, 2021	Jul. 19, 2022~ Aug. 16, 2022	Dec. 02, 2022	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	1GHz~18GHz	Apr. 21, 2022	Jul. 19, 2022~ Aug. 16, 2022	Apr. 20, 2023	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	Oct. 04, 2021	Jul. 19, 2022~ Aug. 16, 2022	Oct. 03, 2022	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~26.5GHz	Oct. 04, 2021	Jul. 19, 2022~ Aug. 16, 2022	Oct. 03, 2022	Radiation (03CH07-HY)
Preamplifier	EMEC	EM18G40G	060715	18-40GHz	Dec. 24, 2021	Jul. 19, 2022~ Jul. 27, 2022	Dec. 23, 2022	Radiation (03CH07-HY)
Preamplifier	EMEC	EM18G40G	0600789	18-40GHz	Jul. 21, 2022	Jul. 21, 2022~ Aug. 16, 2022	Jul. 20, 2023	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9038A(MXE)	MY53290053	20Hz~26.5GHz	May 27, 2022	Jul. 19, 2022~ Jul. 27, 2022	May 26, 2023	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9030A	MY52350276	3Hz~44GHz	Jul. 22, 2022	Jul. 28, 2022~ Aug. 16, 2022	Jul. 21, 2023	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY15682/4	30MHz to 18GHz	Feb. 23, 2022	Jul. 19, 2022~ Aug. 16, 2022	Feb. 22, 2023	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/4	9kHz to 18GHz	Feb. 23, 2022	Jul. 19, 2022~ Aug. 16, 2022	Feb. 22, 2023	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4	9kHz to 18GHz	Feb. 23, 2022	Jul. 19, 2022~ Aug. 16, 2022	Feb. 22, 2023	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126	532078/126E	30MHz~18GHz	Sep. 17, 2021	Jul. 19, 2022~ Aug. 16, 2022	Sep. 16, 2022	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2858/2	18GHz~40GHz	Feb. 23, 2022	Jul. 19, 2022~ Aug. 16, 2022	Feb. 22, 2023	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	801606/2	9KHz ~ 40GHz	Apr. 14, 2022	Jul. 19, 2022~ Aug. 16, 2022	Apr. 13, 2023	Radiation (03CH07-HY)
Controller	EMEC	EM1000	N/A	Control Ant Mast	N/A	Jul. 19, 2022~ Aug. 16, 2022	N/A	Radiation (03CH07-HY)
Controller	MF	MF-7802	N/A	Control Turn table	N/A	Jul. 19, 2022~ Aug. 16, 2022	N/A	Radiation (03CH07-HY)
Antenna Mast	EMEC	AM-BS-4500E	N/A	Boresight mast 1M~4M	N/A	Jul. 19, 2022~ Aug. 16, 2022	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Jul. 19, 2022~ Aug. 16, 2022	N/A	Radiation (03CH07-HY)
Software	Audix	E3	N/A	N/A	N/A	Jul. 19, 2022~ Aug. 16, 2022	N/A	Radiation (03CH07-HY)
USB Data Logger	TECPHEL	TR-32	HE17XB2495	N/A	Mar. 07, 2022	Jul. 19, 2022~ Aug. 16, 2022	Mar. 06, 2023	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	18GHz~40GHz	Nov. 30, 2021	Jul. 19, 2022~ Aug. 16, 2022	Nov. 29, 2022	Radiation (03CH07-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 16, 2021	Jul. 15, 2022~ Jul. 25, 2022	Nov. 15, 2022	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GHz	Aug. 01, 2021	Jul. 15, 2022~ Jul. 25, 2022	Jul. 31, 2022	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 30, 2021	Jul. 15, 2022~ Jul. 25, 2022	Aug. 29, 2022	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 12, 2022	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Dec. 01, 2021	Jul. 12, 2022	Nov. 30, 2022	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 17, 2021	Jul. 12, 2022	Nov. 16, 2022	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 03, 2021	Jul. 12, 2022	Dec. 02, 2022	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Jul. 12, 2022	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	00691	N/A	Jul. 28, 2021	Jul. 12, 2022	Jul. 27, 2022	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 30, 2021	Jul. 12, 2022	Dec. 29, 2022	Conduction (CO05-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	3.1 dB
---	--------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	5.1 dB
---	--------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	5.8 dB
---	--------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	4.0 dB
---	--------

## Appendix A. Test Result of Conducted Test Items

Test Engineer:	Mina Liu	Temperature:	21~25	°C
Test Date:	2022/7/15~2022/7/25	Relative Humidity:	51~54	%

<b><u>TEST RESULTS DATA</u></b>									
<b><u>20dB and 99% Occupied Bandwidth and Hopping Channel Separation</u></b>									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.874	0.816	0.999	0.5827	Pass
DH	1Mbps	1	39	2441	0.874	0.816	0.999	0.5827	Pass
DH	1Mbps	1	78	2480	0.871	0.816	0.695	0.5808	Pass
2DH	2Mbps	1	0	2402	1.263	1.164	1.029	0.8423	Pass
2DH	2Mbps	1	39	2441	1.263	1.161	1.003	0.8423	Pass
2DH	2Mbps	1	78	2480	1.263	1.164	1.003	0.8423	Pass
3DH	3Mbps	1	0	2402	1.224	1.146	1.003	0.8162	Pass
3DH	3Mbps	1	39	2441	1.289	1.169	1.003	0.8596	Pass
3DH	3Mbps	1	78	2480	1.289	1.166	1.003	0.8596	Pass

<b><u>TEST RESULTS DATA</u></b>						
<b><u>Dwell Time</u></b>						
Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.88	0.31	0.4	Pass
AFH	20	53.33	2.88	0.15	0.4	Pass

<b><u>TEST RESULTS DATA</u></b>					
<b><u>Peak Power Table</u></b>					
DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	5.54	20.97	Pass
	39	1	5.51	20.97	Pass
	78	1	6.89	20.97	Pass
2DH1	0	1	5.20	20.97	Pass
	39	1	5.10	20.97	Pass
	78	1	6.50	20.97	Pass
3DH1	0	1	5.49	20.97	Pass
	39	1	5.47	20.97	Pass
	78	1	6.82	20.97	Pass

<b><u>TEST RESULTS DATA</u></b>				
<b><u>Average Power Table</u></b>				
<b><u>(Reporting Only)</u></b>				
DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	5.35	5.15
	39	1	5.22	5.15
	78	1	6.55	5.15
2DH1	0	1	2.93	5.08
	39	1	2.41	5.08
	78	1	3.88	5.08
3DH1	0	1	2.51	5.11
	39	1	2.31	5.11
	78	1	3.66	5.11

<b><u>TEST RESULTS DATA</u></b>			
<b><u>Number of Hopping Frequency</u></b>			
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass




## **Appendix B. AC Conducted Emission Test Results**

<b>Test Engineer :</b>	Tom Lee	<b>Temperature :</b>	23~26°C
		<b>Relative Humidity :</b>	45~55%

## EUT Information

Report NO : 261611  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum



## Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154500	---	31.83	55.75	23.92	L1	OFF	19.6
0.154500	45.56	---	65.75	20.19	L1	OFF	19.6
0.165750	---	34.36	55.17	20.81	L1	OFF	19.6
0.165750	48.13	---	65.17	17.04	L1	OFF	19.6
0.172500	---	39.36	54.84	15.48	L1	OFF	19.6
0.172500	54.17	---	64.84	10.67	L1	OFF	19.6
0.177000	---	32.35	54.63	22.28	L1	OFF	19.6
0.177000	46.03	---	64.63	18.60	L1	OFF	19.6
0.190500	---	29.78	54.02	24.24	L1	OFF	19.6
0.190500	44.37	---	64.02	19.65	L1	OFF	19.6
0.206250	---	35.53	53.36	17.83	L1	OFF	19.6
0.206250	50.22	---	63.36	13.14	L1	OFF	19.6
0.213000	---	28.30	53.09	24.79	L1	OFF	19.6
0.213000	39.50	---	63.09	23.59	L1	OFF	19.6
0.226500	---	29.48	52.58	23.10	L1	OFF	19.6
0.226500	43.31	---	62.58	19.27	L1	OFF	19.6
0.235500	---	33.02	52.25	19.23	L1	OFF	19.6
0.235500	44.54	---	62.25	17.71	L1	OFF	19.6
0.242250	---	33.73	52.02	18.29	L1	OFF	19.6
0.242250	45.37	---	62.02	16.65	L1	OFF	19.6
0.246750	---	28.72	51.87	23.15	L1	OFF	19.6

0.246750	38.55	---	61.87	23.32	L1	OFF	19.6
0.260250	---	31.49	51.42	19.93	L1	OFF	19.6
0.260250	43.65	---	61.42	17.77	L1	OFF	19.6
0.276000	---	34.26	50.94	16.68	L1	OFF	19.6
0.276000	44.43	---	60.94	16.51	L1	OFF	19.6
0.294000	---	31.70	50.41	18.71	L1	OFF	19.6
0.294000	43.45	---	60.41	16.96	L1	OFF	19.6
0.312000	---	30.72	49.92	19.20	L1	OFF	19.6
0.312000	39.68	---	59.92	20.24	L1	OFF	19.6
0.339000	---	34.65	49.23	14.58	L1	OFF	19.6
0.339000	43.91	---	59.23	15.32	L1	OFF	19.6
0.363750	---	32.14	48.64	16.50	L1	OFF	19.6
0.363750	43.93	---	58.64	14.71	L1	OFF	19.6
0.399750	---	30.13	47.86	17.73	L1	OFF	19.6
0.399750	43.01	---	57.86	14.85	L1	OFF	19.6
0.433500	---	32.24	47.19	14.95	L1	OFF	19.6
0.433500	43.75	---	57.19	13.44	L1	OFF	19.6
0.467250	---	34.59	46.56	11.97	L1	OFF	19.6
0.467250	45.11	---	56.56	11.45	L1	OFF	19.6
0.503250	---	32.88	46.00	13.12	L1	OFF	19.6
0.503250	43.67	---	56.00	12.33	L1	OFF	19.6
0.541500	---	37.06	46.00	8.94	L1	OFF	19.6
0.541500	47.21	---	56.00	8.79	L1	OFF	19.6
0.570750	---	33.83	46.00	12.17	L1	OFF	19.6
0.570750	41.12	---	56.00	14.88	L1	OFF	19.6
0.609000	---	36.24	46.00	9.76	L1	OFF	19.6
0.609000	46.07	---	56.00	9.93	L1	OFF	19.6
0.640500	---	31.26	46.00	14.74	L1	OFF	19.6
0.640500	42.52	---	56.00	13.48	L1	OFF	19.6
0.674250	---	32.91	46.00	13.09	L1	OFF	19.6
0.674250	42.89	---	56.00	13.11	L1	OFF	19.6
0.710250	---	33.70	46.00	12.30	L1	OFF	19.6
0.710250	43.86	---	56.00	12.14	L1	OFF	19.6
0.744000	---	32.85	46.00	13.15	L1	OFF	19.6
0.744000	42.86	---	56.00	13.14	L1	OFF	19.6
0.786750	---	29.31	46.00	16.69	L1	OFF	19.6
0.786750	37.54	---	56.00	18.46	L1	OFF	19.6
0.822750	---	28.12	46.00	17.88	L1	OFF	19.6
0.822750	36.24	---	56.00	19.76	L1	OFF	19.6
0.856500	---	29.36	46.00	16.64	L1	OFF	19.6
0.856500	37.50	---	56.00	18.50	L1	OFF	19.6
0.890250	---	30.82	46.00	15.18	L1	OFF	19.6
0.890250	38.50	---	56.00	17.50	L1	OFF	19.6
0.924000	---	30.62	46.00	15.38	L1	OFF	19.6
0.924000	38.08	---	56.00	17.92	L1	OFF	19.6
0.957750	---	30.56	46.00	15.44	L1	OFF	19.6
0.957750	38.18	---	56.00	17.82	L1	OFF	19.6
0.993750	---	29.94	46.00	16.06	L1	OFF	19.6
0.993750	38.86	---	56.00	17.14	L1	OFF	19.6
1.043250	---	29.01	46.00	16.99	L1	OFF	19.7
1.043250	38.42	---	56.00	17.58	L1	OFF	19.7
1.077000	---	28.81	46.00	17.19	L1	OFF	19.7
1.077000	39.21	---	56.00	16.79	L1	OFF	19.7
1.117500	---	29.36	46.00	16.64	L1	OFF	19.7
1.117500	40.25	---	56.00	15.75	L1	OFF	19.7
2.312250	---	25.89	46.00	20.11	L1	OFF	19.7
2.312250	32.83	---	56.00	23.17	L1	OFF	19.7
14.655750	---	28.16	50.00	21.84	L1	OFF	20.3
14.655750	35.10	---	60.00	24.90	L1	OFF	20.3

## EUT Information

Report NO : 261611  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.170250	---	35.75	54.95	19.20	N	OFF	19.6
0.170250	50.35	---	64.95	14.60	N	OFF	19.6
0.204000	---	32.96	53.45	20.49	N	OFF	19.6
0.204000	46.90	---	63.45	16.55	N	OFF	19.6
0.399750	---	30.48	47.86	17.38	N	OFF	19.6
0.399750	41.69	---	57.86	16.17	N	OFF	19.6
0.429000	---	28.51	47.27	18.76	N	OFF	19.6
0.429000	39.91	---	57.27	17.36	N	OFF	19.6
0.467250	---	31.48	46.56	15.08	N	OFF	19.6
0.467250	40.29	---	56.56	16.27	N	OFF	19.6
0.496500	---	29.74	46.06	16.32	N	OFF	19.6
0.496500	40.87	---	56.06	15.19	N	OFF	19.6
0.532500	---	35.43	46.00	10.57	N	OFF	19.6
0.532500	40.95	---	56.00	15.05	N	OFF	19.6
0.570750	---	36.88	46.00	9.12	N	OFF	19.6
0.570750	45.25	---	56.00	10.75	N	OFF	19.6
0.600000	---	34.78	46.00	11.22	N	OFF	19.6
0.600000	40.71	---	56.00	15.29	N	OFF	19.6
0.638250	---	31.27	46.00	14.73	N	OFF	19.6
0.638250	42.06	---	56.00	13.94	N	OFF	19.6
0.674250	---	31.38	46.00	14.62	N	OFF	19.6

0.674250	41.83	---	56.00	14.17	N	OFF	19.6
0.712500	---	28.74	46.00	17.26	N	OFF	19.6
0.712500	39.21	---	56.00	16.79	N	OFF	19.6
0.744000	---	30.38	46.00	15.62	N	OFF	19.6
0.744000	41.02	---	56.00	14.98	N	OFF	19.6
0.771000	---	31.47	46.00	14.53	N	OFF	19.6
0.771000	40.75	---	56.00	15.25	N	OFF	19.6
0.811500	---	30.43	46.00	15.57	N	OFF	19.6
0.811500	41.35	---	56.00	14.65	N	OFF	19.6
0.847500	---	30.11	46.00	15.89	N	OFF	19.6
0.847500	41.06	---	56.00	14.94	N	OFF	19.6
0.881250	---	30.01	46.00	15.99	N	OFF	19.6
0.881250	40.74	---	56.00	15.26	N	OFF	19.6
0.915000	---	29.30	46.00	16.70	N	OFF	19.6
0.915000	39.41	---	56.00	16.59	N	OFF	19.6
0.948750	---	29.29	46.00	16.71	N	OFF	19.6
0.948750	39.21	---	56.00	16.79	N	OFF	19.6
0.978000	---	30.60	46.00	15.40	N	OFF	19.6
0.978000	40.87	---	56.00	15.13	N	OFF	19.6
1.014000	---	29.87	46.00	16.13	N	OFF	19.6
1.014000	41.72	---	56.00	14.28	N	OFF	19.6
1.050000	---	28.76	46.00	17.24	N	OFF	19.6
1.050000	40.69	---	56.00	15.31	N	OFF	19.6
1.083750	---	28.66	46.00	17.34	N	OFF	19.6
1.083750	40.69	---	56.00	15.31	N	OFF	19.6
1.131000	---	28.67	46.00	17.33	N	OFF	19.6
1.131000	40.28	---	56.00	15.72	N	OFF	19.6
1.173750	---	28.22	46.00	17.78	N	OFF	19.6
1.173750	40.82	---	56.00	15.18	N	OFF	19.6
1.214250	---	29.78	46.00	16.22	N	OFF	19.6
1.214250	41.33	---	56.00	14.67	N	OFF	19.6
1.254750	---	27.93	46.00	18.07	N	OFF	19.6
1.254750	37.95	---	56.00	18.05	N	OFF	19.6
1.286250	---	29.09	46.00	16.91	N	OFF	19.7
1.286250	41.00	---	56.00	15.00	N	OFF	19.7
2.370750	---	27.16	46.00	18.84	N	OFF	19.7
2.370750	36.42	---	56.00	19.58	N	OFF	19.7
14.601750	---	28.03	50.00	21.97	N	OFF	20.3
14.601750	38.20	---	60.00	21.80	N	OFF	20.3



## Appendix C. Radiated Spurious Emission

Test Engineer :	Jesse Wang, Stan Hsieh, Ken Wu and Howard Huang	Temperature :		22~28.1°C	
		Relative Humidity :		53.3~67.5%	

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dB $\mu$ V/m )	( dB )	( dB $\mu$ V/m )	( dB $\mu$ V )	( dB/m )	( dB )	( dB )	( cm )	Pos	Pos	Avg.
BT CH00 2402MHz		2380.14	44.88	-29.12	74	40.53	31.4	8.36	35.41	349	243	P	H
		2380.14	20.09	-33.91	54	-	-	-	-	-	-	A	H
	*	2402	95.15	-	-	90.74	31.42	8.41	35.42	349	243	P	H
	*	2402	70.36	-	-	-	-	-	-	-	-	A	H
													H
													H
		2342.55	44.91	-29.09	74	40.61	31.43	8.27	35.4	100	299	P	V
		2342.55	20.12	-33.88	54	-	-	-	-	-	-	A	V
	*	2402	92.51	-	-	88.1	31.42	8.41	35.42	100	299	P	V
	*	2402	67.72	-	-	-	-	-	-	-	-	A	V
BT CH 39 2441MHz													V
		2380.42	44.96	-29.04	74	40.61	31.4	8.36	35.41	375	247	P	H
		2380.42	20.17	-33.83	54	-	-	-	-	-	-	A	H
	*	2441	96.65	-	-	91.86	31.73	8.5	35.44	375	247	P	H
	*	2441	71.86	-	-	-	-	-	-	-	-	A	H
		2493.35	44.67	-29.33	74	39.36	32.15	8.62	35.46	375	247	P	H
		2493.35	19.88	-34.12	54	-	-	-	-	-	-	A	H
		2359.84	44.18	-29.82	74	39.86	31.4	8.32	35.4	100	322	P	V
		2359.84	19.39	-34.61	54	-	-	-	-	-	-	A	V
	*	2441	96.27	-	-	91.48	31.73	8.5	35.44	100	322	P	V
	*	2441	71.48	-	-	-	-	-	-	-	-	A	V
		2485.02	46.02	-27.98	74	40.79	32.08	8.6	35.45	100	322	P	V
		2485.02	21.23	-32.77	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	98.99	-	-	93.81	32.04	8.59	35.45	400	260	P	H
	*	2480	74.2	-	-	-	-	-	-	-	-	A	H
		2483.56	45.93	-28.07	74	40.72	32.07	8.59	35.45	400	260	P	H
		2483.56	21.14	-32.86	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	98.06	-	-	92.88	32.04	8.59	35.45	100	275	P	V
	*	2480	73.27	-	-	-	-	-	-	-	-	A	V
		2493.24	45.19	-28.81	74	39.88	32.15	8.62	35.46	100	275	P	V
		2493.24	20.4	-33.6	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 2.4GHz 2400~2483.5MHz

## BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dB $\mu$ V/m )	Margin ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	43.17	-30.83	74	55.46	34.01	12.7	59	-	-	P	H
		4804	18.38	-35.62	54	-	-	-	-	-	-	A	H
		14475	50.18	-23.82	74	46.51	39.55	21.65	57.53	-	-	P	H
		14475	25.39	-28.61	54	-	-	-	-	-	-	A	H
		16125	51.82	-22.18	74	44.02	41.2	22.67	56.07	-	-	P	H
		16125	27.03	-26.97	54	-	-	-	-	-	-	A	H
		17925	53.75	-20.25	74	43.73	41.43	23.67	55.08	-	-	P	H
		17925	28.96	-25.04	54	-	-	-	-	-	-	A	H
													H
													H
													H
													H
													H
													V
		4804	43.21	-30.79	74	55.5	34.01	12.7	59	-	-	P	V
		4804	18.42	-35.58	54	-	-	-	-	-	-	A	V
		14475	49.82	-24.18	74	46.15	39.55	21.65	57.53	-	-	P	V
		14475	25.03	-28.97	54	-	-	-	-	-	-	A	V
		16125	51.8	-22.2	74	44	41.2	22.67	56.07	-	-	P	V
		16125	27.01	-26.99	54	-	-	-	-	-	-	A	V
		17715	53.29	-20.71	74	43.41	41.51	23.55	55.18	-	-	P	V
		17715	28.5	-25.5	54	-	-	-	-			A	V
													V
													V
													V



BT	Note	Frequency ( MHz )	Level ( dB $\mu$ V/m )	Margin ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
BT CH 39 2441MHz		4882	43.94	-30.06	74	55.99	34.04	12.76	58.85	-	-	P	H
		4882	19.15	-34.85	54	-	-	-	-	-	-	A	H
		7323	43.95	-30.05	74	50.74	35.69	15.03	57.51	-	-	P	H
		7323	19.16	-34.84	54	-	-	-	-	-	-	A	H
		14499	49.39	-24.61	74	45.65	39.6	21.66	57.52	-	-	P	H
		14499	24.6	-29.4	54	-	-	-	-	-	-	A	H
		16020	51.78	-22.22	74	44.12	41.04	22.62	56	-	-	P	H
		16020	26.99	-27.01	54	-	-	-	-	-	-	A	H
		17910	52.99	-21.01	74	43.01	41.41	23.66	55.09	-	-	P	H
		17910	28.2	-25.8	54	-	-	-	-			A	H
													H
													H
		4882	43.89	-30.11	74	55.94	34.04	12.76	58.85	-	-	P	V
		4882	19.1	-34.9	54	-	-	-	-	-	-	A	V
		7323	44.89	-29.11	74	51.68	35.69	15.03	57.51	-	-	P	V
		7323	20.1	-33.9	54	-	-	-	-	-	-	A	V
		14499	50.17	-23.83	74	46.43	39.6	21.66	57.52	-	-	P	V
		14499	25.38	-28.62	54	-	-	-	-	-	-	A	V
		15930	51.34	-22.66	74	43.94	40.93	22.57	56.1	-	-	P	V
		15930	26.55	-27.45	54	-	-	-	-	-	-	A	V
		17985	53.24	-20.76	74	43.11	41.49	23.7	55.06	-	-	P	V
		17985	28.45	-25.55	54	-	-	-	-	-	-	A	V
													V
													V



BT	Note	Frequency ( MHz )	Level ( dB $\mu$ V/m )	Margin ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
BT CH 78 2480MHz		4960	46.01	-27.99	74	57.8	34.1	12.82	58.71	-	-	P	H
		4960	21.22	-32.78	54	-	-	-	-	-	-	A	H
		7440	44.55	-29.45	74	51.29	35.82	15.03	57.59	-	-	P	H
		7440	19.76	-34.24	54	-	-	-	-	-	-	A	H
		14499	50.79	-23.21	74	47.05	39.6	21.66	57.52	-	-	P	H
		14499	26	-28	54	-	-	-	-	-	-	A	H
		16035	51.78	-22.22	74	44.1	41.07	22.62	56.01	-	-	P	H
		16035	26.99	-27.01	54	-	-	-	-	-	-	A	H
		17865	53.02	-20.98	74	43.02	41.47	23.64	55.11	-	-	P	H
		17865	28.23	-25.77	54	-	-	-	-	-	-	A	H
													H
													H
		4960	47.62	-26.38	74	59.41	34.1	12.82	58.71	-	-	P	V
		4960	22.83	-31.17	54	-	-	-	-	-	-	A	V
		7440	44.92	-29.08	74	51.66	35.82	15.03	57.59	-	-	P	V
		7440	20.13	-33.87	54	-	-	-	-	-	-	A	V
		14499	49.92	-24.08	74	46.18	39.6	21.66	57.52	-	-	P	V
		14499	25.13	-28.87	54	-	-	-	-	-	-	A	V
		16020	51.89	-22.11	74	44.23	41.04	22.62	56	-	-	P	V
		16020	27.1	-26.9	54	-	-	-	-	-	-	A	V
		17865	53.07	-20.93	74	43.07	41.47	23.64	55.11	-	-	P	V
		17865	28.28	-25.72	54	-	-	-	-	-	-	A	V
													V
													V
Remark		1. No other spurious found. 2. All results are PASS against Peak and Average limit line. 3. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only. 4. The emission level close to 18GHz is checked that the average emission level is noise floor only.											



## Emission above 18GHz

## 2.4GHz BT (SHF)

BT	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.									
												Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.			
												( MHz )	( dB $\mu$ V/m )	( dB )	( dB $\mu$ V/m )	( dB $\mu$ V )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )
2.4GHz BT SHF		22998	38.51	-35.49	74	50.86	38.4	17.89	59.1	-	-	P	H									
	Remark	1. No other spurious found. 2. All results are PASS against limit line. 3. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.																				



## Emission below 1GHz

## 2.4GHz BT (LF)

**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak or Average</b>
H/V	<b>Horizontal or Vertical</b>



**A calculation example for radiated spurious emission is shown as below:**

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
			Limit	Line	Level	Factor	Loss	Factor	Pos	Pos		Avg.	
		( MHz )	( dB $\mu$ V/m )	( dB )	( dB $\mu$ V/m )	( dB $\mu$ V )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
<b>BT</b> <b>CH 00</b> <b>2402MHz</b>		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dB $\mu$ V/m) =  
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB $\mu$ V) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dB $\mu$ V/m) - Limit Line(dB $\mu$ V/m)

**For Peak Limit @ 2390MHz:**

1. Level(dB $\mu$ V/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB $\mu$ V) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dB $\mu$ V) - 35.86 (dB)  
= 55.45 (dB $\mu$ V/m)
2. Over Limit(dB)  
= Level(dB $\mu$ V/m) - Limit Line(dB $\mu$ V/m)  
= 55.45(dB $\mu$ V/m) - 74(dB $\mu$ V/m)  
= -18.55(dB)

**Peak measured complies with the limit line, so test result is "PASS".**





## Appendix D. Radiated Spurious Emission Plots


<b>Test Engineer :</b>	Jesse Wang, Stan Hsieh, Ken Wu and Howard Huang	<b>Temperature :</b>	22~28.1°C
		<b>Relative Humidity :</b>	53.3~67.5%


### 2.4GHz 2400~2483.5MHz


#### BT (Band Edge @ 3m)



















## 2.4GHz 2400~2483.5MHz

## BT (Harmonic @ 3m)










## Emission above 18GHz


## 2.4GHz BT (SHF @ 1m)






## Emission below 1GHz

## 2.4GHz BT (LF)





## Appendix E. Duty Cycle Plots



### Note:

1. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. **DH5** has the highest duty cycle worst case and is reported.

### Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the on time period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100 \text{ ms} / 57.6 \text{ ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100 \text{ ms}) = -24.79 \text{ dB}$$