

DOKE COMMUNICATION (HK) LIMITED

TEST REPORT

SCOPE OF WORK

FCC Testing – BV6200 Plus

REPORT NUMBER

250219088SZN-005

ISSUE DATE

21 April 2025

PAGES

53

DOCUMENT CONTROL NUMBER

FCC ID 22/24/27/90_a

© 2017 INTERTEK



FCC

RF Test Report

For

DOKE COMMUNICATION (HK) LIMITED

Smart phone

Model: BV6200 Plus

Brand Name: Blackview

FCC ID: 2A7DX-BV6200PLUS

Sample ID: Z250219088-001

Report No: 250219088SZN-005

Tested and Prepared by:



Tony Tang
Engineer

Approved by:



Johnny Wang
Project Engineer
Date: 21 April 2025

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Service Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen.

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

Table of Contents

1. Summary of Test Result	3
1.1 Band 2 PCS Band (1850-1910MHz paired with 1930-1990MHz)	4
1.2 AWS Band (1710-1755MHz paired with 2110-2155MHz)	4
1.3 Band 5 Cellular Band (824-849MHz paired with 869-894MHz)	5
1.4 BRS&EBS Band (2500-2570 MHz paired with 2620-2655 MHz)	6
1.5 Band 12 (699-716MHz paired with 729-746 MHz)	7
1.6 Band 17 (704-716MHz paired with 734-746 MHz)	7
1.7 Band 41 (2496-2690 MHz paired with 2496-2690 MHz)	8
1.8 Band 66 (1710-1780MHz paired with 2110-2180MHz)	9
2. General Description	10
2.1 Product Description	10
2.2 Test Facility	10
2.3 Test Environment Condition	10
2.4 Sub-Assembly	10
2.5 Technical Specification	11
3. General Test Conditions/Configuration	14
3.1 Test Modes	14
3.2 Test Environment	14
3.3 Test Frequency	14
4. DESCRIPTION OF TESTS	17
4.1 Radiated Power and Radiated Spurious Emissions	17
4.2 Peak-to-Average Ratio	18
4.3 Occupied Bandwidth	19
4.4 Band Edge Compliance	19
4.5 Spurious and Harmonic Emissions at Antenna Terminal	20
4.6 Frequency Stability / Temperature Variation	21
5. Test Setups	22
5.1 Test Setup 1	22
5.2 Test Setup 2	22
5.3 Test Setup 3	23
5.4 Test Conditions	24
6. Test Results	26
6.1 Field Strength of Spurious	26
7. Main Test Instruments	52
8. Measurement Uncertainty	53
9. Appendixes	53

1. Summary of Test Result

Applicant:	DOKE COMMUNICATION (HK) LIMITED
Address:	19H MAXGRAND PLAZA NO 3 TAI YAU STREET SAN PO KONG KL
Product name:	Smart phone
Model Number:	BV6200 Plus
FCC ID:	2A7DX-BV6200PLUS
Report number:	250219088SZN-005
Date of Test	19 February 2025 to 17 March 2025

The above equipment was tested by Intertek Testing Services Shenzhen Ltd. Longhua Branch. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI 63.26:2015, FCC KDB 971168 D01, FCC KDB 971168 D02 and FCC KDB 412172 D01. This device is in compliance with FCC rules as follows:

47 CFR FCC Part 02:2023

47 CFR FCC Part 22:2023

47 CFR FCC Part 24:2023

47 CFR FCC Part 27:2023

47 CFR FCC Part 90:2023

The test results of this report relate only to the tested sample identified in this report.

1.1 Band 2 PCS Band (1850-1910MHz paired with 1930-1990MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	§2.1046, §24.232	EIRP ≤ 2 W	Appendix A	Pass
Peak-to-Average Ratio	§2.1046, §24.232	Limit ≤ 13 dB	Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Appendix C	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Appendix D	Pass
Band Edges Compliance	§2.1051, §24.238	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Appendix E	Pass
Spurious Emission at Antenna Terminals	§2.1051, §24.238	≤ -13 dBm/1 MHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	Appendix F	Pass
Field Strength of Spurious Radiation	§2.1053, §24.238	≤ -13 dBm/1 MHz.	Chapter 6	Pass
Frequency Stability	§2.1055, §24.235	$\leq \pm 2.5$ ppm.	Appendix H	Pass
Note1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".				




1.2 AWS Band (1710-1755MHz paired with 2110-2155MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(d)	EIRP ≤ 1 W	Appendix A	Pass
Peak-to-Average Ratio	§2.1046, §27.50(d)	Limit ≤ 13 dB	Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Appendix C	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Appendix D	Pass
Band Edges Compliance	§2.1051, §27.53(h)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Appendix E	Pass
Spurious Emission at Antenna Terminals	§2.1051, §27.53(h)	≤ -13 dBm/1 MHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	Appendix F	Pass
Field Strength of Spurious Radiation	§2.1053, §27.53(h)	≤ -13 dBm/1 MHz.	Chapter 6	Pass
Frequency Stability	§2.1055, §27.54	$\leq \pm 2.5$ ppm.	Appendix G	Pass
Note1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".				

1.3 Band 5 Cellular Band (824-849MHz paired with 869-894MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	§ 2.1046, § 22.913	FCC: ERP $\leq$ 7 W.	Appendix A	Pass
Peak-to-Average Ratio	--	--	Appendix B	Pass
Modulation Characteristics	§ 2.1047	Digital modulation	Appendix C	Pass
Bandwidth	§ 2.1049	OBW: No limit. EBW: No limit.	Appendix D	Pass
Band Edges Compliance	§ 2.1051, § 22.917	$\leq$ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Appendix E	Pass
Spurious Emission at Antenna Terminals	§ 2.1051, § 22.917	FCC: $\leq$ -13 dBm/100 kHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	Appendix F	Pass
Field Strength of Spurious Radiation	§ 2.1053, § 22.917	FCC: $\leq$ -13 dBm/100 kHz.	Chapter 6	Pass
Frequency Stability	§ 2.1055, § 22.355	$\leq \pm 2.5$ ppm.	Appendix G	Pass
Note1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".				

1.4 BRS&EBS Band (2500-2570 MHz paired with 2620-2655 MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(h)	$EIRP \leq 2W$	Appendix A	Pass
Peak-to-Average Ratio	--	--	Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Appendix C	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Appendix D	Pass
Band Edges Compliance	§2.1051, §27.53(m4)	FCC/IC: 	Appendix E	Pass
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)		Appendix F	Pass
Field Strength of Spurious Radiation	§2.1053, §27.53(m)		Chapter 6	Pass
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	Appendix G	Pass

Note1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".




1.5 Band 12 (699-716MHz paired with 729-746 MHz)

Test Item	FCC Rule No	Requirements	Test Result	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(c)	FCC: ERP ≤ 3 W.	Appendix A	Pass
Peak-to-Average Ratio	--	--	Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Appendix C	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Appendix D	Pass
Band Edges Compliance	§2.1051	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Appendix E	Pass
Spurious Emission at Antenna Terminals	§2.1051, §27.53(g)	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges.	Appendix F	Pass
Field Strength of Spurious Radiation	§2.1053, §27.53(g)	FCC: ≤ -13 dBm/100 kHz.	Chapter 6	Pass
Frequency Stability	§2.1055, §27.54	≤ ±2.5ppm.	Appendix G	Pass
Note1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".				

1.6 Band 17 (704-716MHz paired with 734-746 MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(c)	FCC: ERP ≤ 3 W.	Appendix A	Pass
Peak-to-Average Ratio	--	--	Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Appendix C	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Appendix D	Pass
Band Edges Compliance	§2.1051, §27.53(g)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Appendix E	Pass
Spurious Emission at Antenna Terminals	§2.1051, §27.53(g)	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges.	Appendix F	Pass
Field Strength of Spurious Radiation	§2.1053, §27.53(g)	FCC: ≤ -13 dBm/100 kHz.	Chapter 6	Pass
Frequency Stability	§2.1055, §27.54	≤ ±2.5ppm.	Appendix G	Pass
Note1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".				

1.7 Band 41 (2496-2690 MHz paired with 2496-2690 MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(h)	EIRP ≤ 2W	Appendix A	Pass
Peak-to-Average Ratio	--	--	Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Appendix C	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Appendix D	Pass
Band Edges Compliance	§2.1051, §27.53(m4)	FCC/IC: 	Appendix E	Pass
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)		Appendix F	Pass
Field Strength of Spurious Radiation	§2.1053, §27.53(m)		Chapter 6	Pass
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	Appendix G	Pass

Note1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".

1.8 Band 66 (1710-1780MHz paired with 2110-2180MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(d)	$EIRP \leq 1\text{ W}$	Appendix A	Pass
Peak-to-Average Ratio	§2.1046, §27.50(d)	Limit $\leq 13\text{ dB}$	Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Appendix C	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Appendix D	Pass
Band Edges Compliance	§2.1051, §27.53(h)	$\leq -13\text{ dBm}/1\%*EBW$, in 1 MHz bands immediately outside and adjacent to the frequency block.	Appendix E	Pass
Spurious Emission at Antenna Terminals	§2.1051, §27.53(h)	$\leq -13\text{ dBm}/1\text{ MHz}$, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	Appendix F	Pass
Field Strength of Spurious Radiation	§2.1053, §27.53(h)	$\leq -13\text{ dBm}/1\text{ MHz}$.	Chapter 6	Pass
Frequency Stability	§2.1055, §27.54	$\leq \pm 2.5\text{ ppm}$.	Appendix G	Pass
Note1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".				

2. General Description

2.1 Product Description

BV6200 Plus is subscriber equipment in the GSM/UMTS/LTE system. The GSM frequency band includes GSM850 and PCS1900. The UMTS frequency band is Band 2/4/5. The LTE frequency band is Band2/4/5/7/12/17/41/66. The device implements such functions as RF signal receiving/transmitting, LTE/UMTS and GSM/GPRS/EDGE protocol processing. Externally it provides USIM card interface. The EUT is powered by DC 3.85V from battery. For more detailed features description, please refer to the user's manual.

2.2 Test Facility

Company Name:	Intertek Testing Service Shenzhen Ltd. Longhua Branch
Address:	101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen, P.R. China.
FCC Registration Number:	CN1188

2.3 Test Environment Condition

Ambient Temperature:	19.5 to 25 °C
Ambient Relative Humidity:	40 to 55 %
Atmospheric Pressure:	Not applicable

2.4 Sub-Assembly

Description	Manufacturer	Model No.
Adaptor (Provided by applicant)	N/A	Model: QZ-0180AAA00 Input: 100-240V~, 50/60Hz, 0.5A Output: 5.0V=3.0A, 9.0V=2.0A, 12.0V=1.5A
USB Cable (Provided by applicant)	N/A	Shielded, Length: 100cm

2.5 Technical Specification

Characteristics	Description	
Radio System Type	GSM/UMTS/LTE	
Supported Frequency Range	GSM850/ WCDMA850	Transmission (TX): 824 to 849 MHz
		Receiving (RX): 869 to 894 MHz
	GSM1900/ WCDMA1900	Transmission (TX): 1850 to 1910 MHz
		Receiving (RX): 1930 to 1990 MHz
	WCDMA1700	Transmission (TX): 1710 to 1755 MHz
		Receiving (RX): 2110 to 2155 MHz
	LTE BAND2	Transmission (TX): 1850 to 1910 MHz
		Receiving (RX): 1930 to 1990 MHz
	LTE BAND4	Transmission (TX): 1710 to 1755 MHz
		Receiving (RX): 2110 to 2155 MHz
	LTE BAND5	Transmission (TX): 824 to 849 MHz
		Receiving (RX): 869 to 894 MHz
	LTE BAND7	Transmission (TX): 2500 to 2570 MHz
		Receiving (RX): 2620 to 2655 MHz
	LTE BAND12	Transmission (TX): 699 to 716 MHz
		Receiving (RX): 729 to 746 MHz
TX and RX Antenna Ports	TX & RX port:	1
	TX-only port:	0
	RX-only port:	1
Target TX Output Power	GSM850: 32.5dBm GSM1900: 29.5dBm UMTS850: 24dBm UMTS1700: 23dBm UMTS1900: 23dBm LTE BAND2: 23dBm LTE BAND4: 23dBm LTE BAND5: 24dBm LTE BAND7: 22dBm LTE BAND12: 24.5dBm LTE BAND17: 24.5dBm LTE BAND41: 22.5dBm LTE BAND66: 23dBm	
Antenna Gain:	GSM850: -4.23dBi PCS1900: 1.24dBi UMTS850: -3.88dBi UMTS1700: 1.28dBi UMTS1900: 1.45dBi LTE BAND2: 1.47dBi LTE BAND4: 1.19dBi LTE BAND5: -3.73dBi LTE BAND7: 1.45dBi LTE BAND12: -5.47dBi LTE BAND17: -5.86dBi LTE BAND41: 1.58dBi LTE BAND66: 1.28dBi	
Supported Channel Bandwidth	GSM system:	200 kHz
	UMTS system:	5 MHz
	LTE band 2	1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz

Characteristics	Description	
	LTE band 4	1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz
	LTE band 5	1.4 MHz, 3 MHz, 5 MHz, 10 MHz
	LTE band 7	5MHz, 10MHz, 15MHz, 20MHz
	LTE band 12	1.4 MHz, 3 MHz, 5 MHz, 10 MHz
	LTE band 17	5 MHz, 10 MHz
	LTE band 41	5MHz, 10MHz, 15MHz, 20MHz
	LTE band 66	1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz
Designation of Emissions (Note: the necessary bandwidth of which is the worst value from the measured occupied bandwidths for each type of channel bandwidth configuration.)	GSM850:	246KGXW, 242KG7W
	GSM1900:	246KGXW, 243KG7W
	UMTS850:	4M22F9W
	UMTS1700:	4M20F9W
	UMTS1900:	4M21F9W
	LTE BAND2:	1M09G7D (1.4 MHz QPSK modulation), 1M09W7D (1.4 MHz 16QAM modulation) 2M71G7D (3 MHz QPSK modulation), 2M70W7D (3 MHz 16QAM modulation) 4M50G7D (5 MHz QPSK modulation), 4M51W7D (5 MHz 16QAM modulation) 8M99G7D (10 MHz QPSK modulation), 8M99W7D (10 MHz 16QAM modulation) 13M5G7D (15 MHz QPSK modulation), 13M5W7D (15 MHz 16QAM modulation) 18M0G7D (20 MHz QPSK modulation), 18M0W7D (20 MHz 16QAM modulation)
	LTE BAND4:	1M09G7D (1.4 MHz QPSK modulation), 1M09W7D (1.4 MHz 16QAM modulation) 2M71G7D (3 MHz QPSK modulation), 2M70W7D (3 MHz 16QAM modulation) 4M50G7D (5 MHz QPSK modulation), 4M51W7D (5 MHz 16QAM modulation) 8M99G7D (10 MHz QPSK modulation), 8M99W7D (10 MHz 16QAM modulation) 13M5G7D (15 MHz QPSK modulation), 13M5W7D (15 MHz 16QAM modulation) 18M0G7D (20 MHz QPSK modulation), 18M1W7D (20 MHz 16QAM modulation)
	LTE BAND5:	1M09G7D (1.4 MHz QPSK modulation), 1M09W7D (1.4 MHz 16QAM modulation) 2M70G7D (3 MHz QPSK modulation), 2M70W7D (3 MHz 16QAM modulation) 4M50G7D (5 MHz QPSK modulation), 4M50W7D (5 MHz 16QAM modulation) 9M02G7D (10 MHz QPSK modulation), 8M99W7D (10 MHz 16QAM modulation)
	LTE BAND7:	4M51G7D (5 MHz QPSK modulation), 4M51W7D (5 MHz 16QAM modulation) 9M02G7D (10 MHz QPSK modulation), 8M99W7D (10 MHz 16QAM modulation) 13M5G7D (15 MHz QPSK modulation), 13M5W7D (15 MHz 16QAM modulation) 18M0G7D (20 MHz QPSK modulation), 18M0W7D (20 MHz 16QAM modulation)
	LTE BAND12:	1M09G7D (1.4 MHz QPSK modulation), 1M09W7D (1.4 MHz 16QAM modulation) 2M71G7D (3 MHz QPSK modulation), 2M70W7D (3 MHz 16QAM modulation) 4M50G7D (5 MHz QPSK modulation),

Characteristics	Description	
		4M51W7D (5 MHz 16QAM modulation) 8M99G7D (10 MHz QPSK modulation), 8M99W7D (10 MHz 16QAM modulation)
	LTE BAND17:	4M51G7D (5 MHz QPSK modulation), 4M50W7D (5 MHz 16QAM modulation) 8M95G7D (10 MHz QPSK modulation), 8M95W7D (10 MHz 16QAM modulation)
	LTE BAND41:	4M50G7D (5 MHz QPSK modulation), 4M50W7D (5 MHz 16QAM modulation) 8M99G7D (10 MHz QPSK modulation), 8M99W7D (10 MHz 16QAM modulation) 13M5G7D (15 MHz QPSK modulation), 13M5W7D (15 MHz 16QAM modulation) 18M0G7D (20 MHz QPSK modulation), 18M0W7D (20 MHz 16QAM modulation)
	LTE BAND66:	1M09G7D (1.4 MHz QPSK modulation), 1M09W7D (1.4 MHz 16QAM modulation) 2M71G7D (3 MHz QPSK modulation), 2M70W7D (3 MHz 16QAM modulation) 4M50G7D (5 MHz QPSK modulation), 4M51W7D (5 MHz 16QAM modulation) 8M99G7D (10 MHz QPSK modulation), 8M99W7D (10 MHz 16QAM modulation) 13M5G7D (15 MHz QPSK modulation), 13M5W7D (15 MHz 16QAM modulation) 18M0G7D (20 MHz QPSK modulation), 18M1W7D (20 MHz 16QAM modulation)

3. General Test Conditions/Configuration

3.1 Test Modes

Test Mode	Test Modes Description
GSM/TM1	GSM system, GPRS, GMSK modulation
GSM/TM2	GSM system, EDGE, 8PSK modulation
UMTS/TM1	WCDMA system, QPSK modulation
UMTS/TM2	HSDPA system, QPSK modulation
UMTS/TM3	HSUPA system, QPSK modulation
LTE/TM1	LTE system, QPSK modulation
LTE/TM2	LTE system, 16QAM modulation

3.2 Test Environment

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Temperature	TN	Ambient
Voltage	VL	3.6V
	VN	3.85V
	VH	4.4V

NOTE: VL= lower extreme test voltage, VN= nominal voltage, VH= upper extreme test voltage
TN= normal temperature

3.3 Test Frequency

Test Mode	TX / RX	RF Channel		
		Low (L)	Middle (M)	High (H)
GSM850	TX	Channel 128	Channel 190	Channel 251
		824.2MHz	836.6MHz	848.8MHz
GSM1900	TX	Channel 512	Channel 661	Channel 810
		1850.2MHz	1880.0MHz	1909.8MHz

Test Mode	TX / RX	RF Channel		
		Low (L)	Middle (M)	High (H)
WCDMA850	TX	Channel 4132	Channel 4182	Channel 4233
		826.4MHz	836.4MHz	846.6MHz
WCDMA1900	TX	Channel 9262	Channel 9400	Channel 9538
		1852.4MHz	1880.0MHz	1907.6MHz
WCDMA1700	TX	Channel1312	Channel1413	Channel1513
		1712.4MHz	1732.6MHz	1752.6MHz

Test Mode	TX / RX	RF Channel		
		Low (B)	Middle (M)	High (T)
LTE Band 2	TX(1.4M)	Channel 18607	Channel 18900	Channel 19193
		1850.7 MHz	1880 MHz	1909.3 MHz
	TX(3M)	Channel 18615	Channel 18900	Channel 19185
		1851.5 MHz	1880 MHz	1908.5 MHz
	TX(5M)	Channel 18625	Channel 18900	Channel 19175
		1852.5 MHz	1880 MHz	1907.5 MHz
	TX(10M)	Channel 18650	Channel 18900	Channel 19150
		1855 MHz	1880 MHz	1905 MHz
	TX(15M)	Channel 18675	Channel 18900	Channel 19125
		1857.5 MHz	1880 MHz	1902.5 MHz
	TX(20M)	Channel 18700	Channel 18900	Channel 19100
		1860 MHz	1880 MHz	1900 MHz
LTE Band 4	TX(1.4M)	Channel 19957	Channel 20175	Channel 20393
		1710.7 MHz	1732.5 MHz	1754.3 MHz
	TX(3M)	Channel 19965	Channel 20175	Channel 20385
		1711.5 MHz	1732.5 MHz	1753.5 MHz
	TX(5M)	Channel 19975	Channel 20175	Channel 20375
		1712.5 MHz	1732.5 MHz	1752.5 MHz
	TX(10M)	Channel 20000	Channel 20175	Channel 20350
		1715 MHz	1732.5 MHz	1750 MHz
	TX(15M)	Channel 20025	Channel 20175	Channel 20325
		1717.5 MHz	1732.5 MHz	1747.5 MHz
	TX(20M)	Channel 20050	Channel 20175	Channel 20300
		1720 MHz	1732.5 MHz	1745 MHz
LTE Band 5	TX(1.4M)	Channel 20407	Channel 20525	Channel 20643
		824.7 MHz	836.5 MHz	848.3 MHz
	TX(3M)	Channel 20415	Channel 20525	Channel 20635
		825.5 MHz	836.5 MHz	847.5 MHz
	TX(5M)	Channel 20425	Channel 20525	Channel 20625
		826.5 MHz	836.5 MHz	846.5 MHz
	TX(10M)	Channel 20450	Channel 20525	Channel 20600
		829 MHz	836.5 MHz	844 MHz
LTE Band 7	TX (5M)	Channel 20775	Channel 21100	Channel 21425
		2502.5 MHz	2535 MHz	2567.5 MHz
	TX (10M)	Channel 20800	Channel 21100	Channel 21400
		2505 MHz	2535 MHz	2565 MHz
	TX (15M)	Channel 20825	Channel 21100	Channel 21375
		2507.5 MHz	2535 MHz	2562.5 MHz
	TX (20M)	Channel 20850	Channel 21100	Channel 21350
		2510 MHz	2535 MHz	2560 MHz
LTE Band 12	TX(1.4M)	Channel 23017	Channel 23095	Channel 23173
		699.7 MHz	707.5 MHz	715.3 MHz
	TX(3M)	Channel 23025	Channel 23095	Channel 23165
		700.5 MHz	707.5 MHz	714.5 MHz

	TX(5M)	Channel 23035	Channel 23095	Channel 23155
		701.5 MHz	707.5 MHz	713.5 MHz
	TX(10M)	Channel 23060	Channel 23095	Channel 23130
		704 MHz	707.5 MHz	711 MHz
LTE Band 17	TX (5M)	Channel 23755	Channel 23790	Channel 23825
		706.5 MHz	710 MHz	713.5 MHz
	TX (10M)	Channel 23780	Channel 23790	Channel 23800
		709 MHz	710 MHz	711 MHz
LTE Band 41	TX/RX (5M)	Channel 39675	Channel 40620	Channel 41565
		2498.5 MHz	2593 MHz	2687.5 MHz
	TX/RX (10M)	Channel 39700	Channel 40620	Channel 41540
		2501 MHz	2593 MHz	2685 MHz
	TX/RX (15M)	Channel 39725	Channel 40620	Channel 41515
		2503.5 MHz	2593 MHz	2682.5 MHz
	TX/RX (20M)	Channel 39750	Channel 40620	Channel 41490
		2506 MHz	2593 MHz	2680 MHz
LTE Band 66	TX(1.4M)	Channel 131979	Channel 132322	Channel 132665
		1710.7 MHz	1745.0 MHz	1779.3 MHz
	TX(3M)	Channel 131987	Channel 132322	Channel 132657
		1711.5 MHz	1745.0 MHz	1778.5 MHz
	TX(5M)	Channel 131997	Channel 132322	Channel 132647
		1712.5 MHz	1745.0 MHz	1777.5 MHz
	TX(10M)	Channel 132022	Channel 132322	Channel 132622
		1715 MHz	1745.0 MHz	1775.0 MHz
	TX(15M)	Channel 132047	Channel 132322	Channel 132597
		1717.5 MHz	1745.0 MHz	1772.5 MHz
	TX(20M)	Channel 132072	Channel 132322	Channel 132572
		1720 MHz	1745.0 MHz	1770.0 MHz

4. DESCRIPTION OF TESTS

4.1 Radiated Power and Radiated Spurious Emissions

Radiated spurious emissions are investigated indoors in a semi-anechoic chamber to determine the frequencies producing the worst case emissions. Final measurements for radiated power and radiated spurious emissions are performed on the 3 meter OATS per the guidelines of ANSI C63.26-2015. The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Emissions are also investigated with the receive antenna horizontally and vertically polarized.

A portable or small unlicensed wireless device shall be placed on a non-metallic test fixture or other non-metallic support during testing. The supporting fixture shall permit orientation of the EUT in each of three orthogonal (x, y, z) axis positions such that emissions from the EUT are maximized. Measure the EUT maximum RF power and record the result.

A half-wave dipole is then substituted in place of the EUT. For emissions above 3GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT.

The power of the emission is calculated using the following formula:

$$P_d [\text{dBm}] = P_g [\text{dBm}] - \text{cable loss} [\text{dB}] + \text{antenna gain} [\text{dBd/dBi}]$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g [\text{dBm}] - \text{cable loss} [\text{dB}]$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power} [\text{Watts}])$.

Test Procedures Used

971168 D01 v03r01 -Section 5.2 / 971168 D01 v03r01 -Section 5.8

ANSI C63.26 §5.2 / ANSI C63.26 §5.5/ ANSI C63.26 §6.4

Note: Reference test setup 3

4.2 Peak-to-Average Ratio

A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. The traces are generated with the spectrum analyzer set to zero span mode.

Test Procedures Used

971168 D01 v03r01 -Section 5.7

ANSI C63.26 §5.2

Test Settings

1. The signal analyzer's CCDF measurement profile enabled
2. Frequency = carrier center frequency
3. Measurement BW > EBW of signal
4. for continuous transmissions, set to 1ms
5. Record the maximum PAPR level associated with a probability of 0.1%. Note: Reference test setup 1

4.3 Occupied Bandwidth

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

Test Procedures Used

971168 D01 v03r01 -Section 4.3

ANSI C63.26 §5.4

Test Settings

1. SET RBW=1-5% of OBW
2. SET VBW $\geq 3 \times$ RBW
3. Detector: Peak
4. Trace mode= max hold.
5. Sweep= auto couple
6. Steps 1-5 were repeated after it is stable

Note: Reference test setup 1.

4.4 Band Edge Compliance

the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission power must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log_{10} P$ dB.

Test Procedures Used

971168 D01 v03r01 -Section 6

ANSI C63.26 §5.7/ ANSI C63.26 §6.4

Test Settings

1. SET RBW $\geq 1\%$ of Emission BW.
2. SET VBW about three times of RBW
3. Detector: RMS
4. Trace mode= max hold.
5. Span= 2MHz

Note: Reference test setup 1.

4.5 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least

$43 + 10 \log(P)$ dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission is attenuated at least 26 dB below the transmitter power.

Test Procedures Used

KDB 971168 v03r01-Section 6.0

Test Settings

1. 9kHz~150kHz, RBW = 1KHz, VBW $\geq 3 \times$ RBW,
150kHz~30MHz, RBW = 10KHz, VBW $\geq 3 \times$ RBW,
30MHz~1GHz, RBW = 100 kHz, VBW = 300 kHz.
Above 1GHz, RBW = 1 MHz, VBW = 3 MHz.
2. Detector: Peak
3. Trace mode= max hold.

Note: Reference test setup 1.

4.6 Frequency Stability / Temperature Variation

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +60°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +60°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Procedures Used

971168 D01 v03r01 -Section 9


ANSI C63.26 §5.6

Note: Reference test setup 2.


There is no transmission when the EUT operates at the test temperature condition: -30°C.

5. Test Setups

5.1 Test Setup 1




5.2 Test Setup 2




5.3 Test Setup 3

NOTE: Effective radiated power (ERP) and Equivalent Isotropic Radiated Power (EIRP) refers to the radiation power output of the EUT, assuming all emissions are radiated from half-wave dipole antennas.

5.3.1 Step 1: Pre-test



5.3.2 Step 2: Substitution method to verify the maximum ERP/EIRP



5.4 Test Conditions

Test Case		Test Conditions	
Transmit Output Power Data	Average Power, Total	Test Env.	Ambient Climate & Rated Voltage
		Test Setup	Test Setup 1
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)
		Test Mode	GSM/TM1, GSM/TM2, UMTS/TM1, LTE/TM1, LTE/TM2
	Average Power, Spectral Density (if required)	Test Env.	Ambient Climate & Rated Voltage
		Test Setup	Test Setup 1
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)
		Test Mode	GSM/TM1,GSM/TM2,UMTS/TM1,LTE/TM1,LTE/TM2
Peak-to-Average Ratio (if required)		Test Env.	Ambient Climate & Rated Voltage
		Test Setup	Test Setup 1
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)
		Test Mode	GSM/TM1, GSM/TM2, UMTS/TM1, LTE/TM1, LTE/TM2
Modulation Characteristics		Test Env.	Ambient Climate & Rated Voltage
		Test Setup	Test Setup 1
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)
		Test Mode	GSM/TM1, GSM/TM2, UMTS/TM1, LTE/TM1, LTE/TM2
Bandwidth	Occupied Bandwidth	Test Env.	Ambient Climate & Rated Voltage
		Test Setup	Test Setup 1
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)
		Test Mode	GSM/TM1, GSM/TM2, UMTS/TM1, LTE/TM1, LTE/TM2
	Emission Bandwidth (if required)	Test Env.	Ambient Climate & Rated Voltage
		Test Setup	Test Setup 1
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)
		Test Mode	GSM/TM1, GSM/TM2, UMTS/TM1, LTE/TM1, LTE/TM2
Band Edges Compliance		Test Env.	Ambient Climate & Rated Voltage
		Test Setup	Test Setup 1
		RF Channels (TX)	L, H (L= low channel, M= middle channel, H= high channel)
		Test Mode	GSM/TM1, GSM/TM2, UMTS/TM1, LTE/TM1, LTE/TM2
Spurious Emission at Antenna Terminals		Test Env.	Ambient Climate & Rated Voltage
		Test Setup	Test Setup 1
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)
		Test Mode	GSM/TM1, GSM/TM2, UMTS/TM1, LTE/TM1, LTE/TM2

Test Case	Test Conditions	
Field Strength of Spurious Radiation	Test Env.	Ambient Climate & Rated Voltage
	Test Setup	Test Setup 3
	Test Mode	GSM/TM1/TM2, UMTS/TM1/TM2/TM3, LTE/TM1/TM2 NOTE: If applicable, the EUT conf. that has maximum power density (based on the equivalent power level) is selected.
	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)
Frequency Stability	Test Env.	(1) -30 °C to +60 °C with step 10 °C at Rated Voltage; (2) VL, VN and VH of Rated Voltage at Ambient Climate.
	Test Setup	Test Setup 2
	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)
	Test Mode	GSM/TM1, GSM/TM2, UMTS/TM1, LTE/TM1, LTE/TM2

6. Test Results

6.1 Field Strength of Spurious


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (GSM/TM1 GSM850)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency range 30 MHz ~ 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (GSM/TM1 GSM850)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency above 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (GSM/TM1 GSM1900)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency range 30 MHz ~ 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (GSM/TM1 GSM1900)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency above 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (UMTS/TM1 WCDMA1900)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency range 30 MHz ~ 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (UMTS/TM1 WCDMA1900)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency above 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (UMTS/TM1 WCDMA850)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency range 30 MHz ~ 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (UMTS/TM1 WCDMA850)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency above 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (UMTS/TM1 WCDMA1700)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency range 30 MHz ~ 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (UMTS/TM1 WCDMA1700)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency above 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 2, 20MHz)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency range 30 MHz ~ 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 2, 20MHz)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency above 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 4, 20MHz)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency range 30 MHz ~ 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 4, 20MHz)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency above 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 5, 10MHz)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency range 30 MHz ~ 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 5, 10MHz)

Worst-case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency above 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 7, 10MHz)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency range 30 MHz ~ 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 7, 10MHz)

Worst-case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency above 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 12, 10MHz)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency range 30 MHz ~ 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 12, 10MHz)

Worst-case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency above 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 17, 10MHz)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency range 30 MHz ~ 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 17, 10MHz)

Worst-case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency above 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 41, 10MHz)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency range 30 MHz ~ 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 41, 10MHz)

Worst-case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency above 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 66, 20MHz)

Worst Case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency range 30 MHz ~ 1 GHz.


Applicant: DOKE COMMUNICATION (HK) LIMITED

Model: BV6200 Plus

Date of Test: 05 March 2025

Worst Case Operating Mode: Transmitting (LTE/TM1 Band 66, 20MHz)

Worst-case ANT Polarity: Horizontal



Remark: The emissions were very low against the limit in the frequency above 1 GHz.

7. Main Test Instruments

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ006-27	DC Power Supply	Keysight	E3648A	MY56096119	2024-12-03	2025-12-03
SZ047-35	Digital Temperature-Humidity Recorder	Yijie	RS210	0045340A15	2024-08-08	2025-08-08
SZ065-08	Wideband Radio Communication Tester	R&S	CMW500	144665	2024-09-29	2025-09-29
SZ056-07	Signal Analyzer	R&S	FSV 40	101214	2024-12-05	2025-12-05
SZ061-13	BiConiLog Antenna	ETS	3142E	00217919	2022-07-13	2025-07-13
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	2024-05-05	2027-05-05
SZ185-03	EMI Receiver	R&S	ESR7	101975	2024-04-23	2025-04-23
SZ061-08	Double - Ridged Waveguide Horn Antenna	ETS	3115	00092346	2024-09-13	2027-09-13
SZ056-06	Signal Analyzer	R&S	FSV 40	101101	2024-12-06	2025-12-06
SZ181-08	Microwave System Amplifier	keysight	83017A	MY57280108	2024-07-29	2025-07-29
SZ188-05	Anechoic Chamber	ETS	FACT 3-2.0	CT001880-Q13914102	2021-05-25	2026-05-25
SZ062-02	RF Cable	RADIAL	RG 213U	--	2024-11-01	2025-05-01
SZ062-05	RF Cable	RADIAL	0.04-26.5GHz	0833254	2024-11-01	2025-05-01
SZ062-12	RF Cable	RADIAL	0.04-26.5GHz	083387	2024-11-01	2025-05-01
SZ016-12	Programmable Temperature & Humidity Chamber	Taili	MHK-120NK	AB0105	2024-12-04	2025-12-04

Software Information			
Test Item	Software Name	Manufacturer	Version
RSE	EMC32	R&S	V8.40.0
Conducted RF	JS1120 RF Test System	Shenzhen JS tonscond co., Ltd	2.6.9.0518

8. Measurement Uncertainty

For a 95% confidence level ($k = 2$), the measurement expanded uncertainties for defined systems, in accordance with

the recommendations of ISO 17025 as following:

Test Item		Extended Uncertainty
Transmit Output Power Data	Power [dBm]	U = 0.42 dB
Bandwidth	Magnitude [%]	U = 0.2%
Band Edge Compliance	Disturbance Power [dBm]	U = 1.24 dB
Spurious Emissions, Conducted	Disturbance Power [dBm]	U = 1.62 dB
Field Strength of Spurious Radiation	ERP [dBm]	For 3 m Chamber: U = 4.9 dB (30 MHz to 26.5GHz)
Frequency Stability	Frequency Accuracy [ppm]	U = 0.017 ppm

9. Appendixes

Appendix No.	Description
250219088SZN-005-Appendix A	Appendix for GSM
250219088SZN-005-Appendix B	Appendix for WCDMA
250219088SZN-005-Appendix C	Appendix for LTE

***** End of Report *****