

RF Exposure evaluation

Product Name : Mini PC
Brand Name : Blackview
Model : MP30
Series Model : N/A
FCCID : 2A7DX-MP30
Applicant : **DOKE COMMUNICATION (HK) LIMITED**
Address : 19H MAXGRAND PLAZA NO 3 TAI YAU STREET SAN PO KONG
KL
Manufacturer : **Shenzhen DOKE Electronic Co., Ltd**
Address : 801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road,
Guangming District, Shenzhen, China.
Standard(s) : 47CFR §1.1310, 47CFR §2.1091
KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt : July 18, 2025
Date of Test : July 18, 2025~Aug. 26, 2025
Issued Date : Aug. 27, 2025

Issued By: **Dongguan Yaxu (AiT) Technology Limited**
No.22, Jinqianling 3rd Street, Jitigang, Huangjiang, Dongguan, Guangdong, China
Tel.: +86-769-8202 0499 Fax.: +86-769-8202 0495

Reviewed by: Emiya Lin
Emiya Lin

Approved by: Simba Huang
Simba Huang

Note: This device has been tested and found to comply with the standard(s) listed, this test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory. This report shall not be reproduced except in full, without the written approval of Dongguan Yaxu (AiT) Technology Limited. If there is a need to alter or revise this document, the right belongs to Dongguan Yaxu (AiT) Technology Limited, and it should give a prior written notice of the revision document. This test report must not be used by the client to claim product endorsement.



Report Revise Record

Report Version	Issued Date	Notes
V1.0	Aug. 27, 2025	Initial Release

Contents

1	GENERAL INFORMATION	4
1.1	ENVIRONMENTAL CONDITIONS	4
1.2	GENERAL DESCRIPTION OF EUT	4
1.3	TEST FACILITY	6
1.4	MEASUREMENT UNCERTAINTY	7
2	METHOD OF MEASUREMENT	8
2.1	APPLICABLE STANDARD	8
2.2	LIMIT	8
2.3	MPE CALCULATION METHOD	9
2.4	MANUFACTURING TOLERANCE	9
2.5	STANDALONE MPE RESULT	13
2.6	CONCLUSION	13

1 GENERAL INFORMATION

1.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

1.2 General Description of EUT

Product Name:	Mini PC
Model/Type reference:	MP30
Serial Model:	N/A
Power Supply:	DC 12.0V from adapter
Adapter:	MODEL: AS3603A-1203000US INPUT: 100-240V~ 50/60Hz 1.0A MAX OUTPUT: 12.0V=3.0A
Configuration:	Configuration 1:RAM 16GB, ROM:512GB Configuration 2:RAM 8GB, ROM:256GB
Hardware version.:	AN15_MB_R20
Software version.:	E.AN15_R20_8.E1.041.202507011613
Test sample(s) ID:	AiTDG-250718003-1 AiTDG-250718003-2

BT:				
Operation frequency:	2402MHz-2480MHz			
Channel Number:	BR/EDR:79 Channels BLE:40 Channels			
Channel separation:	BR/EDR:1MHz BLE:2MHz			
Modulation Technology:	GFSK, $\pi/4$ -DQPSK, 8-DPSK			
Antenna Type:	FPC Antenna			
Antenna gain:	ANT1(AUX):2.80dBi			
2.4G WIFI:				
Operation frequency:	802.11b/802.11g/802.11n(HT20)/ax(HE20): 2412MHz~2462MHz 802.11n(HT40)/ax(HE40): 2422MHz~2452MHz			
Channel Number:	802.11b/802.11g/802.11n(HT20)/ax(HT20): 11 802.11n(HT40)/ax(HE40):7			
Channel separation:	5MHz			
Modulation Technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(HT20)/ax(HE20)/802.11n(HT40)/ax(HT40): Orthogonal Frequency Division Multiplexing (OFDM/OFDMA)			
Antenna Type:	FPC Antenna			
Antenna gain:	ANT1(AUX):2.80dBi ANT2(MAIN):3.44dBi Directional Gain:6.14dBi			
5G WIFI:				
Modulation:	IEEE 802.11a/n/ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDMA(1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)			
Operation frequency:	Band	Mode	Frequency Range(MHz)	Number of channels
	U-NII Band I	IEEE 802.11a	5180-5240	4
		IEEE 802.11n/ac/ax 20MHz	5180-5240	4
		IEEE 802.11n/ac/ax 40MHz	5190-5230	2
		IEEE 802.11ac/ax 80MHz	5210	1
	U-NII Band III	IEEE 802.11a	5745-5825	5
		IEEE 802.11n/ac/ax 20MHz	5745-5825	5
		IEEE 802.11n/ac/ax 40MHz	5755-5795	2
IEEE 802.11ac/ax 80MHz		5775	1	
Antenna type:	FPC Antenna			
Antenna gain:	ANT1(AUX): 3.33dBi for 5150-5250MHz 3.0dBi for 5725-5875MHz ANT2(MAIN): 3.72dBi for 5150-5250MHz 2.99dBi for 5725-5875MHz Directional Gain: 6.54dBi for 5150-5250MHz 6.01dBi for 5725-5875MHz			
Remark: The above DUT's information was declared by manufacturer. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.				

1.3 Test Facility

Test Laboratory:

Dongguan Yaxu (AiT) Technology Limited

No.22, Jinqianling 3rd Street, Jitigang, Huangjiang, Dongguan, Guangdong, China

The test facility is recognized, certified or accredited by the following organizations:

CNAS- Registration No: L6177

Dongguan Yaxu (AiT) technology Limited is accredited to ISO/IEC 17025:2017 general Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the competence of testing and calibration laboratories) on April 18, 2022

FCC-Registration No.: 703111 Designation Number: CN1313

Dongguan Yaxu (AiT) Technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC —Registration No.: 6819A CAB identifier: CN0122

The 3m Semi-anechoic chamber of Dongguan Yaxu (AiT) Technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 6819A

A2LA-Lab Cert. No.: 6317.01

Dongguan Yaxu (AiT) Technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

1.4 Measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Dongguan Yaxu (AiT) Technology Limited's quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Yaxu (AiT) laboratory is reported:

Test	Measurement Uncertainty	Notes
Power Line Conducted Emission	150KHz~30MHz $\pm 1.20\text{dB}$	(1)
Radiated Emission	9KHz~30Hz $\pm 3.10\text{dB}$	(1)
Radiated Emission	9KHz~1GHz $\pm 3.75\text{dB}$	(1)
Radiated Emission	1GHz~18GHz $\pm 3.88\text{dB}$	(1)
Radiated Emission	18GHz~40GHz $\pm 3.88\text{dB}$	(1)

The report uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty Multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

2 Method of measurement

2.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

FCC KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures

2.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

2.3 MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

2.4 Manufacturing Tolerance

BR_EDR (Conducted)

Frequency (MHz)	BR_EDR_GFSK		
	2402	2441	2480
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
Frequency (MHz)	BR_EDR $\pi/4$ -DQPSK		
	2402	2441	2480
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
Frequency (MHz)	BR_EDR 8-DPSK		
	2402	2441	2480
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

BLE (Conducted)

Frequency (MHz)	GFSK 1Mbps		
	2402	2440	2480
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
Frequency (MHz)	GFSK 2Mbps		
	2402	2440	2480
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

2.4GWIFI (Conducted)

Frequency (MHz)	ANT1_11b(Peak)			ANT2_11b(Peak)		
	2412	2437	2462	2412	2437	2462
Target (dBm)	16	16	16	16	16	16
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
Frequency (MHz)	ANT1_11g(Peak)			ANT2_11g(Peak)		
	2412	2437	2462	2412	2437	2462
Target (dBm)	15	15	15	15	15	15
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
Frequency (MHz)	ANT1_11n(HT20) (Peak)			ANT2_11n(HT20)(Peak)		
	2412	2437	2462	2412	2437	2462
Target (dBm)	11	11	11	11	11	11
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
Frequency (MHz)	ANT1_11n(HT40) (Peak)			ANT2_11n(HT40)(Peak)		
	2422	2437	2452	2422	2437	2452
Target (dBm)	11	11	11	11	11	11
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
Frequency (MHz)	ANT1_11ax(HT20) (Peak)			ANT2_11ax(HT20)(Peak)		
	2412	2437	2412	2437	2412	2437
Target (dBm)	11	11	11	11	11	11
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
Frequency (MHz)	ANT1_11ax(HT40) (Peak)			ANT2_11ax(HT40)(Peak)		
	2422	2437	2452	2422	2437	2452
Target (dBm)	11	11	11	11	11	11
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0

5.2G WIFI (Conducted)

Frequency (MHz)	ANT 1 _IEEE 802.11a(AV)			ANT 2 _IEEE 802.11a(AV)		
	5180	5200	5240	5180	5200	5240
Target (dBm)	15	15	15	15	15	15
Tolerance ± (dB)	1.0	1.0	1.0	1.0	1.0	1.0
Frequency (MHz)	ANT 1 _IEEE 802.11n20(AV)			ANT 2 _IEEE 802.11n20(AV)		
	5180	5200	5240	5180	5200	5240
Target (dBm)	11	11	11	11	11	11
Tolerance ± (dB)	1.0	1.0	1.0	1.0	1.0	1.0
Frequency (MHz)	ANT 1 _IEEE 802.11n40(AV)			ANT 2 _IEEE 802.11n40(AV)		
	5190		5230	5190		5230
Target (dBm)	11		11	11		11
Tolerance ± (dB)	1.0		1.0	1.0		1.0
Frequency (MHz)	ANT 1 _IEEE 802.11ac20(AV)			ANT 2 _IEEE 802.11ac20(AV)		
	5180	5200	5240	5180	5200	5240
Target (dBm)	11	11	11	11	11	11
Tolerance ± (dB)	1.0	1.0	1.0	1.0	1.0	1.0
Frequency (MHz)	ANT 1 _IEEE 802.11ac40(AV)			ANT 2 _IEEE 802.11ac40(AV)		
	5190		5230	5190		5230
Target (dBm)	11		11	11		11
Tolerance ± (dB)	1.0		1.0	1.0		1.0
Frequency (MHz)	ANT 1 _IEEE 802.11ac80(AV)			ANT 2 _IEEE 802.11ac80(AV)		
	5210			5210		
Target (dBm)	11			11		
Tolerance ± (dB)	1.0			1.0		
Frequency (MHz)	ANT 1 _IEEE 802.11ax20(AV)			ANT 2 _IEEE 802.11ax20(AV)		
	5180	5200	5240	5180	5200	5240
Target (dBm)	11	11	11	11	11	11
Tolerance ± (dB)	1.0	1.0	1.0	1.0	1.0	1.0
Frequency (MHz)	ANT 1 _IEEE 802.11ax40(AV)			ANT 2 _IEEE 802.11ax40(AV)		
	5190		5230	5190		5230
Target (dBm)	11		11	11		11
Tolerance ± (dB)	1.0		1.0	1.0		1.0
Frequency (MHz)	ANT 1 _IEEE 802.11ax80(AV)			ANT 2 _IEEE 802.11ax80(AV)		
	5210			5210		
Target (dBm)	11			11		
Tolerance ± (dB)	1.0			1.0		

5.8G WIFI (Conducted)

Frequency (MHz)	ANT 1 _IEEE 802.11a(AV)			ANT 2 _IEEE 802.11a(AV)		
	5745	5785	5825	5745	5785	5825
Target (dBm)	15	15	14	15	15	15
Tolerance ± (dB)	1.0	1.0	1.0	1.0	1.0	1.0
Frequency (MHz)	ANT 1 _IEEE 802.11n20(AV)			ANT 2 _IEEE 802.11n20(AV)		
	5745	5785	5825	5745	5785	5825
Target (dBm)	11	11	10	11	11	10
Tolerance ± (dB)	1.0	1.0	1.0	1.0	1.0	1.0
Frequency (MHz)	ANT 1 _IEEE 802.11n40(AV)			ANT 2 _IEEE 802.11n40(AV)		
	5755		5795	5755		5795
Target (dBm)	11		11	11		11
Tolerance ± (dB)	1.0		1.0	1.0		1.0
Frequency (MHz)	ANT 1 _IEEE 802.11ac20(AV)			ANT 2 _IEEE 802.11ac20(AV)		
	5745	5785	5825	5745	5785	5825
Target (dBm)	11	11	10	11	11	10
Tolerance ± (dB)	1.0	1.0	1.0	1.0	1.0	1.0
Frequency (MHz)	ANT 1 _IEEE 802.11ac40(AV)			ANT 2 _IEEE 802.11ac40(AV)		
	5755		5795	5755		5795
Target (dBm)	11		11	11		11
Tolerance ± (dB)	1.0		1.0	1.0		1.0
Frequency (MHz)	ANT 1 _IEEE 802.11ac80(AV)			ANT 2 _IEEE 802.11ac80(AV)		
	5775			5775		
Target (dBm)	11			11		
Tolerance ± (dB)	1.0			1.0		
Frequency (MHz)	ANT 1 _IEEE 802.11ax20(AV)			ANT 2 _IEEE 802.11ax20(AV)		
	5745	5785	5825	5745	5785	5825
Target (dBm)	11	11	10	11	11	10
Tolerance ± (dB)	1.0	1.0	1.0	1.0	1.0	1.0
Frequency (MHz)	ANT 1 _IEEE 802.11ax40(AV)			ANT 2 _IEEE 802.11ax40(AV)		
	5755		5795	5755		5795
Target (dBm)	11		11	11		11
Tolerance ± (dB)	1.0		1.0	1.0		1.0
Frequency (MHz)	ANT 1 _IEEE 802.11ax80(AV)			ANT 2 _IEEE 802.11ax80(AV)		
	5775			5775		
Target (dBm)	11			11		
Tolerance ± (dB)	1.0			1.0		

2.5 Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna is refer to section 4, the RF power density can be obtained.

ANT1(AUX):

Modulation Type	Output power with tune_up		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
BR_EDR	7	5.012	2.80	1.905	0.00190	1.0000
BLE	7	5.012	2.80	1.905	0.00190	1.0000
2.4G WIFI	17	50.119	2.80	1.905	0.01900	1.0000
5.2G WIFI	16	39.811	3.33	2.153	0.01705	1.0000
5.8G WIFI	16	39.811	3.0	1.995	0.01580	1.0000

ANT2(MAIN):

Modulation Type	Output power with tune_up		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
2.4G WIFI	17	50.119	3.44	2.208	0.02202	1.0000
5.2G WIFI	16	39.811	3.72	2.355	0.01865	1.0000
5.8G WIFI	16	39.811	2.99	1.991	0.01577	1.0000

Remark:

1. Output power (Peak) including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

Max. Simultaneous MPE Result

	ANT1 MPE (Ratio)	ANT2 MPE (Ratio)	simultaneous MPE (Ratio)	MPE Limits (Ratio)
WIFI+WIFI	0.01989	0.02202	0.04191	1.0000
BT+WIFI	0.0019	0.02202	0.02392	1.0000

2.6 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

*****End of Report*****