

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: HUIZHOU MTN WEIYE TECHNOLOGY DEVELOPMENT CO.,LTD
Address of applicant: NO.2 Huitai Road,Huinan High-tech Industrial Park,Huiao Avenue,
Huizhou City,Guangdong Province,China

Manufacturer: HUIZHOU MTN WEIYE TECHNOLOGY DEVELOPMENT CO.,LTD
Address of manufacturer: NO.2 Huitai Road,Huinan High-tech Industrial Park,Huiao Avenue,
Huizhou City,Guangdong Province,China

General Description of EUT:

Product Name: WiFi 6 Range Extender
Trade Name: MTN
Model No.: EAX1805
Adding Model(s): /
Rated Voltage: AC120V/60Hz
Power Adapter Model: /
FCC ID: 2A7EI-EAX1805

Technical Characteristics of EUT:	
Wi-Fi (2.4G)	
Support Standards:	802.11b, 802.11g, 802.11n, 802.11ax
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2412-2462MHz for 802.11ax(HE20) 2422-2452MHz for 802.11n(HT40) 2422-2452MHz for 802.11ax(HE40)
RF Output Power:	Antenna 1: 18.36dBm (Conducted) Antenna 2: 18.65dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM, 256QAM, 1024QAM
Quantity of Channels:	11 for 802.11b/g/n(HT20);11 for 802.11ax(HE20); 7 for 802.11n(HT40); 7 for 802.11ax(HE40);
Channel Separation:	5MHz
Type of Antenna:	External Antenna
Antenna Gain:	3dBi
Support Standards:	802.11b, 802.11g, 802.11n, 802.11ax
Wi-Fi (5G)	
Support Standards:	802.11a, 802.11n(HT20), 802.11n-HT40, 802.11ax-HE20, 802.11ax-HE40, 802.11ac-VHT80, 802.11ax-HE80
Frequency Range:	5150-5250MHz, 5725-5850MHz

RF Output Power:	5150-5250MHz: Antenna 1: 17.69dBm (Conducted) Antenna 2: 17.57dBm (Conducted) 5725-5850MHz: Antenna 1: 17.09dBm (Conducted) Antenna 2: 17.54dBm (Conducted)
Type of Modulation:	QPSK, 16QAM, 64QAM, 256QAM, 1024QAM
Type of Antenna:	External Antenna
Antenna Gain:	3dBi
Support Standards:	802.11a, 802.11n(HT20), 802.11n-HT40, 802.11ax-HE20, 802.11ax-HE40, 802.11ac-VHT80, 802.11ax-HE80

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz; * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30*P*G) / (377*R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

For Wi-Fi (2.4G):

Maximum Tune-Up output power: 19.0(dBm)

Maximum peak output power at antenna input terminal: 79.43 (mW)

Prediction distance: >20(cm)

Prediction frequency: 2412 (MHz)

Antenna gain: 3.0(dBi)

Directional gain (numeric gain): 2.00

The worst case is power density at prediction frequency at 20cm: 0.0315(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

For Wi-Fi (5G):

Maximum Tune-Up output power: 19.5(dBm)

Maximum peak output power at antenna input terminal: 89.13(mW)

Prediction distance: >20(cm)

Prediction frequency: 5180 (MHz)

Antenna gain: 3.0(dBi)

Directional gain (numeric gain): 2.00

The worst case is power density at prediction frequency at 20cm: 0.0354 (mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Mode for Simultaneous Multi-band Transmission

Wi-Fi (2.4G) + Wi-Fi (5G)

The worst case is power density at prediction frequency at 20cm: $0.0315+0.0354 = 0.0669(\text{mw/cm}^2)$

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass