



12.Radiated Emission

12.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2025/09/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ- 1.5M	DDT-ZC02762	2025/03/31
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31
RF cable	Yuhu Technology	JCTB810-NJ-NJ- 9M	DDT-ZC02538	2025/03/31
RF cable	Yuhu Technology	ZT26S-SMAJ- SMAJ-1M	DDT-ZC02037	2025/03/31
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2025/08/25
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2025/07/11

12.2. Block diagram of test setup





12.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

(2) FCC 15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		mV/m	dB(mV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dB(mV)/m (Peak) 54.0 dB(mV)/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V}/\text{m}) + 40\text{Log}(30\text{m}/3\text{m})$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits.

12.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

12.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilob Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 40 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) 30 MHz ~ 40 GHz: (Scan with all mode, the worst case is record and report)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with the worst mode.

12.6. Test result

PASS. (See below detailed test result)

12.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-03-13

Tested By:

Lin Guoyuan

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

5G WIFI mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.5°C;Humi:50.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q25030309-2E\FCC Below 1G\20250313-033426_H

Memo:

Sample Number:S25030309-001 (Adapter: MN012S-L120100-10)



Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	217.916	31.89	10.87	4.84	16.36	46.00	29.64	QP	Horizontal
2	239.888	48.41	11.79	4.94	33.86	46.00	12.14	QP	Horizontal
3	374.959	40.02	15.40	5.52	29.50	46.00	16.50	QP	Horizontal
4	439.960	35.1	16.10	5.77	25.50	46.00	20.50	QP	Horizontal
5	559.972	35.39	18.09	6.22	28.20	46.00	17.80	QP	Horizontal
6	640.219	31.19	18.53	6.50	24.72	46.00	21.28	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-03-13

Tested By:

Lin Guoyuan

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

5G WIFI mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.5°C;Humi:50.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q25030309-2E\FCC Below 1G\20250313-033446_V

Memo:

Sample Number:S25030309-001 (Adapter: MN012S-L120100-10)



Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	34.759	40.19	11.59	3.79	24.47	40.00	15.53	QP	Vertical
2	37.494	39.48	11.55	3.80	23.73	40.00	16.27	QP	Vertical
3	44.677	35.25	13.14	3.85	21.14	40.00	18.86	QP	Vertical
4	250.020	35.88	11.70	4.99	21.27	46.00	24.73	QP	Vertical
5	374.959	36.59	15.40	5.52	26.07	46.00	19.93	QP	Vertical
6	499.844	34.71	17.08	6.00	26.29	46.00	19.71	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-03-13

Tested By:

Lin Guoyuan

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

5G WIFI mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.5°C;Humi:50.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q25030309-2E\FCC Below 1G\20250313-033647_H

Memo:

Sample Number:S25030309-001 (Adapter: TEKA-AB1B120100US)



Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	111.865	29.27	11.73	4.28	14.17	43.50	29.33	QP	Horizontal
2	159.955	33.34	8.89	4.54	15.61	43.50	27.89	QP	Horizontal
3	250.020	36.42	11.70	4.99	21.81	46.00	24.19	QP	Horizontal
4	350.059	35.78	14.51	5.42	24.28	46.00	21.72	QP	Horizontal
5	374.959	40.69	15.40	5.52	30.17	46.00	15.83	QP	Horizontal
6	549.856	34.96	17.10	6.18	26.74	46.00	19.26	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-03-13

Tested By:

Lin Guoyuan

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

5G WIFI mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.5°C;Humi:50.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q25030309-2E\FCC Below 1G\20250313-033731_V

Memo:

Sample Number:S25030309-001 (Adapter: TEKA-AB1B120100US)



Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	42.957	39.18	12.81	3.84	24.73	40.00	15.27	QP	Vertical
2	73.707	38.49	8.99	4.05	20.43	40.00	19.57	QP	Vertical
3	239.888	46.04	11.79	4.94	31.49	46.00	14.51	QP	Vertical
4	374.959	43.74	15.40	5.52	33.22	46.00	12.78	QP	Vertical
5	599.803	37.57	19.18	6.37	31.62	46.00	14.38	QP	Vertical
6	640.219	40.44	18.53	6.50	33.97	46.00	12.03	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-28

Tested By:

Genliu

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

5G WIFI mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q25030309-1E\FCC BELOW 1G\20240628-024909_H

Memo:

Sample Number:S24051516-001(Adapter: MN012E-L120100)



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	33.351	32.21	11.13	3.78	-30.95	16.17	40.00	23.83	QP	Horizontal
2	47.788	31	12.29	3.87	-30.73	16.43	40.00	23.57	QP	Horizontal
3	124.971	39.73	8.91	4.35	-30.83	22.16	43.50	21.34	QP	Horizontal
4	166.594	46.83	8.76	4.58	-30.70	29.47	43.50	14.03	QP	Horizontal
5	250.020	38.42	11.70	4.99	-30.45	24.66	46.00	21.34	QP	Horizontal
6	374.959	39.74	15.40	5.52	-30.15	30.51	46.00	15.49	QP	Horizontal

Note:

- Result Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-28

Tested By:

Genliu

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

5G WIFI mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q25030309-1E\FCC BELOW 1G\20240628-024950_V

Memo:

Sample Number:S24051516-001 (Adapter: MN012E-L120100)



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	32.179	46.57	10.24	3.77	-30.97	29.61	40.00	10.39	QP	Vertical
2	43.199	41.1	12.84	3.84	-30.80	26.98	40.00	13.02	QP	Vertical
3	72.223	38	9.51	4.04	-30.55	21.00	40.00	19.00	QP	Vertical
4	124.971	33.71	8.91	4.35	-30.83	16.14	43.50	27.36	QP	Vertical
5	166.594	45.14	8.76	4.58	-30.70	27.78	43.50	15.72	QP	Vertical
6	374.959	41.06	15.40	5.52	-30.15	31.83	46.00	14.17	QP	Vertical

Note:

- Result Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5180MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\23

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3905.300	45.55	31.19	5.28	-40.39	41.63	74.00	32.37	PK	Horizontal
2	7599.400	44.42	36.50	7.61	-42.20	46.33	74.00	27.67	PK	Horizontal
3	9069.900	41.67	38.44	8.13	-38.79	49.45	74.00	24.55	PK	Horizontal
4	10809.000	41.71	39.39	8.36	-39.02	50.44	74.00	23.56	PK	Horizontal
5	11392.100	41.92	39.29	8.66	-39.27	50.60	74.00	23.40	PK	Horizontal
6	15824.000	39.15	38.25	10.16	-39.25	48.31	74.00	25.69	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5180MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\26

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3908.700	46.32	31.18	5.28	-40.39	42.39	74.00	31.61	PK	Vertical
2	4780.800	45.30	32.42	6.24	-40.16	43.80	74.00	30.20	PK	Vertical
3	7509.300	43.28	36.48	7.56	-41.97	45.35	74.00	28.65	PK	Vertical
4	11381.900	41.78	39.28	8.65	-39.27	50.44	74.00	23.56	PK	Vertical
5	11881.700	41.99	38.90	8.95	-39.50	50.34	74.00	23.66	PK	Vertical
6	15963.400	39.49	38.04	10.22	-39.34	48.41	74.00	25.59	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5200MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\27

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3895.100	46.13	31.17	5.28	-40.39	42.19	74.00	31.81	PK	Horizontal
2	4903.200	44.90	33.01	6.38	-40.12	44.17	74.00	29.83	PK	Horizontal
3	7441.300	43.65	36.62	7.51	-41.80	45.98	74.00	28.02	PK	Horizontal
4	9204.200	42.23	38.60	8.12	-38.78	50.17	68.20	18.03	PK	Horizontal
5	11286.700	42.98	39.20	8.59	-39.22	51.55	74.00	22.45	PK	Horizontal
6	12306.700	42.11	39.30	9.16	-39.68	50.89	74.00	23.11	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5200MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\28

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3799.900	46.83	30.70	5.25	-40.33	42.45	74.00	31.55	PK	Vertical
2	4767.200	46.21	32.37	6.22	-40.17	44.63	74.00	29.37	PK	Vertical
3	7497.400	44.00	36.51	7.55	-41.94	46.12	74.00	27.88	PK	Vertical
4	9462.600	42.57	38.70	8.12	-38.76	50.63	74.00	23.37	PK	Vertical
5	11298.600	41.78	39.20	8.60	-39.23	50.35	74.00	23.65	PK	Vertical
6	15601.300	41.29	38.60	10.06	-39.12	50.83	74.00	23.17	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5240MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\29

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3903.600	45.60	31.19	5.28	-40.39	41.68	74.00	32.32	PK	Horizontal
2	4772.300	46.11	32.39	6.23	-40.16	44.57	74.00	29.43	PK	Horizontal
3	7470.200	43.36	36.56	7.53	-41.88	45.57	74.00	28.43	PK	Horizontal
4	9025.700	42.06	38.35	8.13	-38.79	49.75	74.00	24.25	PK	Horizontal
5	11905.500	42.37	38.92	8.96	-39.52	50.73	74.00	23.27	PK	Horizontal
6	15815.500	39.38	38.27	10.16	-39.25	48.56	74.00	25.44	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5240MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\30

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3939.300	46.12	31.12	5.29	-40.41	42.12	74.00	31.88	PK	Vertical
2	4774.000	45.51	32.40	6.23	-40.16	43.98	74.00	30.02	PK	Vertical
3	7516.100	43.67	36.47	7.56	-41.99	45.71	74.00	28.29	PK	Vertical
4	9477.900	41.60	38.70	8.12	-38.76	49.66	74.00	24.34	PK	Vertical
5	11473.700	41.52	39.23	8.70	-39.31	50.14	74.00	23.86	PK	Vertical
6	15713.500	42.22	38.47	10.11	-39.19	51.61	74.00	22.39	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5260MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\31

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4088.900	46.09	31.08	5.42	-40.42	42.17	74.00	31.83	PK	Horizontal
2	7368.200	42.80	36.76	7.47	-41.62	45.41	74.00	28.59	PK	Horizontal
3	9387.800	41.89	38.70	8.12	-38.76	49.95	74.00	24.05	PK	Horizontal
4	11138.800	40.86	39.26	8.50	-39.16	49.46	74.00	24.54	PK	Horizontal
5	12293.100	41.16	39.30	9.15	-39.67	49.94	74.00	24.06	PK	Horizontal
6	15693.100	38.85	38.51	10.10	-39.18	48.28	74.00	25.72	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5260MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\32

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4879.400	43.95	33.33	6.36	-40.12	43.52	74.00	30.48	PK	Vertical
2	7492.300	43.62	36.52	7.55	-41.93	45.76	74.00	28.24	PK	Vertical
3	9160.000	41.71	38.52	8.13	-38.78	49.58	74.00	24.42	PK	Vertical
4	11184.700	40.84	39.22	8.53	-39.18	49.41	74.00	24.59	PK	Vertical
5	11793.300	41.78	38.91	8.90	-39.46	50.13	74.00	23.87	PK	Vertical
6	16118.100	39.73	37.88	10.33	-39.46	48.48	74.00	25.52	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5280MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\35

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO .	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3777.800	46.71	30.61	5.24	-40.31	42.25	74.00	31.75	PK	Horizontal
2	7242.400	44.13	36.80	7.39	-41.31	47.01	68.20	21.19	PK	Horizontal
3	9411.600	41.80	38.70	8.12	-38.76	49.86	74.00	24.14	PK	Horizontal
4	11281.600	41.55	39.20	8.59	-39.22	50.12	74.00	23.88	PK	Horizontal
5	12072.100	41.14	39.27	9.05	-39.59	49.87	74.00	24.13	PK	Horizontal
6	16155.500	40.07	37.84	10.36	-39.49	48.78	74.00	25.22	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5280MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\36

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4073.600	47.01	31.05	5.40	-40.42	43.04	74.00	30.96	PK	Vertical
2	7349.500	43.60	36.80	7.45	-41.57	46.28	74.00	27.72	PK	Vertical
3	9044.400	42.97	38.39	8.13	-38.79	50.70	74.00	23.30	PK	Vertical
4	11137.100	42.07	39.26	8.50	-39.15	50.68	74.00	23.32	PK	Vertical
5	11718.500	41.76	38.98	8.85	-39.43	50.16	74.00	23.84	PK	Vertical
6	16073.900	40.09	37.93	10.30	-39.42	48.90	74.00	25.10	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5320MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\33

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3867.900	46.33	31.01	5.27	-40.37	42.24	74.00	31.76	PK	Horizontal
2	7495.700	43.68	36.51	7.55	-41.94	45.80	74.00	28.20	PK	Horizontal
3	8423.900	42.21	37.50	7.98	-41.33	46.36	74.00	27.64	PK	Horizontal
4	9149.800	42.01	38.50	8.13	-38.78	49.86	74.00	24.14	PK	Horizontal
5	11279.900	42.20	39.20	8.59	-39.22	50.77	74.00	23.23	PK	Horizontal
6	15569.000	39.42	38.66	10.05	-39.10	49.03	74.00	24.97	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5320MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\34

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4022.600	46.29	30.95	5.34	-40.44	42.14	74.00	31.86	PK	Vertical
2	7460.000	43.25	36.58	7.52	-41.85	45.50	74.00	28.50	PK	Vertical
3	9365.700	41.64	38.70	8.12	-38.76	49.70	74.00	24.30	PK	Vertical
4	10637.300	43.78	39.27	8.30	-38.96	52.39	74.00	21.61	PK	Vertical
5	11914.000	42.39	38.94	8.97	-39.52	50.78	74.00	23.22	PK	Vertical
6	15963.400	42.21	38.04	10.22	-39.34	51.13	74.00	22.87	PK	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5500MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\37

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3784.600	46.75	30.64	5.24	-40.32	42.31	74.00	31.69	PK	Horizontal
2	7436.200	43.64	36.63	7.51	-41.79	45.99	74.00	28.01	PK	Horizontal
3	9007.000	42.02	38.31	8.13	-38.79	49.67	74.00	24.33	PK	Horizontal
4	11138.800	41.61	39.26	8.50	-39.16	50.21	74.00	23.79	PK	Horizontal
5	11810.300	41.74	38.90	8.91	-39.47	50.08	74.00	23.92	PK	Horizontal
6	15706.700	39.01	38.49	10.11	-39.18	48.43	74.00	25.57	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5500MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\38

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO .	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4316.700	45.59	31.60	5.69	-40.33	42.55	74.00	31.45	PK	Vertical
2	7332.500	46.72	36.84	7.44	-41.53	49.47	74.00	24.53	PK	Vertical
3	9146.400	41.95	38.50	8.13	-38.78	49.80	74.00	24.20	PK	Vertical
4	10994.300	44.33	39.30	8.42	-39.09	52.96	74.00	21.04	PK	Vertical
5	11880.000	41.62	38.90	8.95	-39.50	49.97	74.00	24.03	PK	Vertical
6	15567.300	38.81	38.67	10.05	-39.10	48.43	74.00	25.57	PK	Vertical

Data List										
NO .	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	10997.780	37.17	39.30	8.42	-39.09	45.80	54.0	8.20	AV	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5580MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\39

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4207.900	46.60	31.23	5.56	-40.37	43.02	74.00	30.98	PK	Horizontal
2	7439.600	45.07	36.62	7.51	-41.80	47.40	74.00	26.60	PK	Horizontal
3	9112.400	41.85	38.50	8.13	-38.78	49.70	74.00	24.30	PK	Horizontal
4	11171.100	42.54	39.23	8.52	-39.17	51.12	74.00	22.88	PK	Horizontal
5	12298.200	41.43	39.30	9.16	-39.68	50.21	74.00	23.79	PK	Horizontal
6	15657.400	39.59	38.54	10.09	-39.15	49.07	74.00	24.93	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5580MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\40

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3907.000	46.17	31.19	5.28	-40.39	42.25	74.00	31.75	PK	Vertical
2	7439.600	46.22	36.62	7.51	-41.80	48.55	74.00	25.45	PK	Vertical
3	9071.600	41.56	38.44	8.13	-38.78	49.35	74.00	24.65	PK	Vertical
4	11162.600	46.05	39.24	8.52	-39.17	54.64	74.00	19.36	PK	Vertical
5	12294.800	41.84	39.30	9.16	-39.67	50.63	74.00	23.37	PK	Vertical
6	15757.700	38.98	38.38	10.13	-39.21	48.28	74.00	25.72	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11162.600	40.14	39.24	8.52	-39.17	48.73	54.0	5.27	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5700MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\41

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO .	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3675.800	45.90	30.30	5.21	-40.25	41.16	74.00	32.84	PK	Horizontal
2	4070.200	46.29	31.04	5.39	-40.42	42.30	74.00	31.70	PK	Horizontal
3	9129.400	41.41	38.50	8.13	-38.78	49.26	74.00	24.74	PK	Horizontal
4	11285.000	41.80	39.20	8.59	-39.22	50.37	74.00	23.63	PK	Horizontal
5	11966.700	41.32	39.10	9.00	-39.54	49.88	74.00	24.12	PK	Horizontal
6	15817.200	39.23	38.27	10.16	-39.25	48.41	74.00	25.59	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-18

Tested By:

Junchang Du

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

11AX20 TX 5700MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5G\42

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3803.300	45.99	30.71	5.25	-40.33	41.62	74.00	32.38	PK	Vertical
2	4044.700	45.02	30.99	5.36	-40.43	40.94	74.00	33.06	PK	Vertical
3	7599.400	45.89	36.50	7.61	-42.20	47.80	74.00	26.20	PK	Vertical
4	11400.600	45.46	39.30	8.66	-39.28	54.14	74.00	19.86	PK	Vertical
5	12029.600	41.60	39.23	9.03	-39.57	50.29	74.00	23.71	PK	Vertical
6	15752.600	39.05	38.39	10.13	-39.21	48.36	74.00	25.64	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11400.600	40.12	39.30	8.66	-39.28	48.80	54.0	5.20	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-28

Tested By:

Genliu

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

AX20 TX 5720MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G KUAYUE17

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3779.500	46.57	30.62	5.24	-40.32	42.11	74.00	31.89	PK	Horizontal
2	3854.300	47.38	30.93	5.26	-40.36	43.21	74.00	30.79	PK	Horizontal
3	7334.200	42.74	36.83	7.44	-41.54	45.47	74.00	28.53	PK	Horizontal
4	11138.800	41.63	39.26	8.50	-39.16	50.23	74.00	23.77	PK	Horizontal
5	11441.400	41.44	39.26	8.68	-39.30	50.08	74.00	23.92	PK	Horizontal
6	15715.200	39.25	38.47	10.11	-39.19	48.64	74.00	25.36	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-28

Tested By:

Genliu

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

AX20 TX 5720MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G KUAYUE\8

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3896.800	46.84	31.18	5.28	-40.39	42.91	74.00	31.09	PK	Vertical
2	4309.900	45.17	31.60	5.68	-40.34	42.11	74.00	31.89	PK	Vertical
3	4894.700	44.18	33.08	6.37	-40.12	43.51	74.00	30.49	PK	Vertical
4	7626.600	46.59	36.55	7.63	-42.27	48.50	74.00	25.50	PK	Vertical
5	11434.600	44.45	39.27	8.68	-39.29	53.11	74.00	20.89	PK	Vertical
6	11885.100	41.42	38.90	8.95	-39.51	49.76	74.00	24.24	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11434.600	40.6	39.27	8.68	-39.29	49.26	54.0	4.74	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-28

Tested By:

Genliu

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

AX20 TX 5745MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5.8G\7

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3867.900	45.23	31.01	5.27	-40.37	41.14	74.00	32.86	PK	Horizontal
2	5006.900	44.78	33.21	6.50	-40.08	44.41	74.00	29.59	PK	Horizontal
3	7392.000	42.73	36.72	7.48	-41.68	45.25	74.00	28.75	PK	Horizontal
4	9007.000	41.56	38.31	8.13	-38.79	49.21	74.00	24.79	PK	Horizontal
5	11482.200	42.71	39.22	8.71	-39.32	51.32	74.00	22.68	PK	Horizontal
6	12043.200	40.50	39.24	9.04	-39.58	49.20	74.00	24.80	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-28

Tested By:

Genliu

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

AX20 TX 5745MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5.8G\8

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	7449.800	42.36	36.60	7.52	-41.82	44.66	74.00	29.34	PK	Vertical
2	7660.600	45.28	36.62	7.65	-42.35	47.20	74.00	26.80	PK	Vertical
3	9051.200	41.80	38.40	8.13	-38.79	49.54	74.00	24.46	PK	Vertical
4	9528.900	41.47	38.64	8.11	-38.75	49.47	68.20	18.73	PK	Vertical
5	11485.600	45.94	39.21	8.71	-39.32	54.54	74.00	19.46	PK	Vertical
6	12046.600	41.18	39.25	9.04	-39.58	49.89	74.00	24.11	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11484.720	38.14	39.21	8.71	-39.32	46.74	54.0	7.26	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-28

Tested By:

Genliu

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

AX20 TX 5785MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5.8G\9

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO .	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4874.300	45.25	33.41	6.35	-40.13	44.88	74.00	29.12	PK	Horizontal
2	7352.900	43.72	36.79	7.46	-41.58	46.39	74.00	27.61	PK	Horizontal
3	9005.300	41.53	38.31	8.13	-38.79	49.18	74.00	24.82	PK	Horizontal
4	10752.900	41.30	39.40	8.34	-39.00	50.04	74.00	23.96	PK	Horizontal
5	11560.400	42.33	39.08	8.76	-39.35	50.82	74.00	23.18	PK	Horizontal
6	12259.100	41.26	39.30	9.14	-39.66	50.04	74.00	23.96	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-28

Tested By:

Genliu

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

AX20 TX 5785MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5.8G\10

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4785.900	44.70	32.44	6.25	-40.16	43.23	74.00	30.77	PK	Vertical
2	5003.500	43.67	33.21	6.50	-40.08	43.30	74.00	30.70	PK	Vertical
3	7393.700	42.60	36.71	7.48	-41.68	45.11	74.00	28.89	PK	Vertical
4	7713.300	44.08	36.73	7.69	-42.48	46.02	74.00	27.98	PK	Vertical
5	9112.400	41.71	38.50	8.13	-38.78	49.56	74.00	24.44	PK	Vertical
6	11572.300	46.11	39.06	8.76	-39.36	54.57	74.00	19.43	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11569.845	40.22	39.06	8.76	-39.36	48.68	54.0	5.32	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-28

Tested By:

Genliu

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

AX20 TX 5825MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5.8G\11

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO .	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4194.300	45.22	31.20	5.54	-40.38	41.58	74.00	32.42	PK	Horizontal
2	4882.800	44.38	33.28	6.36	-40.12	43.90	74.00	30.10	PK	Horizontal
3	7453.200	42.29	36.59	7.52	-41.83	44.57	74.00	29.43	PK	Horizontal
4	11266.300	41.84	39.20	8.58	-39.22	50.40	74.00	23.60	PK	Horizontal
5	12274.400	40.11	39.30	9.15	-39.67	48.89	74.00	25.11	PK	Horizontal
6	15773.000	39.82	38.35	10.14	-39.22	49.09	74.00	24.91	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-28

Tested By:

Genliu

EUT:

Dual-band WiFi6 AX1500 Router

Model Number:

Flow AX1501

Test Mode:

AX20 TX 5825MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:21.9°C;Humi:60.0%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q25030309-1E\FCC ABOVE 1G 5.8G\12

Memo:

Sample Number:S24051516-001 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4774.000	45.45	32.40	6.23	-40.16	43.92	74.00	30.08	PK	Vertical
2	7587.500	42.28	36.48	7.61	-42.17	44.20	74.00	29.80	PK	Vertical
3	7766.000	43.72	36.80	7.72	-42.62	45.62	68.20	22.58	PK	Vertical
4	9505.100	41.95	38.69	8.11	-38.75	50.00	68.20	18.20	PK	Vertical
5	11648.800	42.49	39.00	8.81	-39.39	50.91	74.00	23.09	PK	Vertical
6	12753.800	41.39	39.71	9.37	-39.85	50.62	68.20	17.58	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.