

FCC REPORT

(ZIGBEE)

Applicant: OMO Systems Ltd.

Address of Applicant: Griva Digeni, 80, SWEPCO COURT 6, 2nd floor, 31016 Limassol, Cyprus

Equipment Under Test (EUT)

Product Name: OMO HUB

Model No.: PRO NEO V1.0

FCC ID: 2A7ER-PRONEO-V1

Applicable Standards: FCC CFR Title 47 Part 15C (§15.247)

Date of Sample Receipt: 21 Jun., 2022

Date of Test: 22 Jun., to 02 Aug., 2022

Date of Report Issued: 03 Aug., 2022

Test Result: PASS

Tested by: Mike Ou

Date: 03 Aug., 2022

Test Engineer

Reviewed by: Wenren Zhou

Date: 03 Aug., 2022

Project Engineer

Approved by: Mike Zhou

Date: 03 Aug., 2022

Manager

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	03 Aug., 2022	<i>Original</i>

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF E.U.T.....	4
4.3 TEST ENVIRONMENT AND MODE	5
4.4 DESCRIPTION OF SUPPORT UNITS.....	5
4.5 MEASUREMENT UNCERTAINTY.....	5
4.6 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD.....	5
4.7 LABORATORY FACILITY.....	6
4.8 LABORATORY LOCATION	6
4.9 TEST INSTRUMENTS LIST.....	7
5 MEASUREMENT SETUP AND PROCEDURE.....	8
5.1 TEST CHANNEL.....	8
5.2 TEST SETUP	8
5.3 TEST PROCEDURE.....	10
6 TEST RESULTS.....	11
6.1 SUMMARY	11
6.1.1 Clause and Data Summary.....	11
6.1.2 Test Limit.....	12
6.2 ANTENNA REQUIREMENT	13
6.3 AC POWER LINE CONDUCTED EMISSION	14
6.4 EMISSIONS IN RESTRICTED FREQUENCY BANDS	16
6.5 EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	20

4 General Information

4.1 Client Information

Applicant:	OMO Systems Ltd.
Address:	Griva Digeni, 80, SWEPCO COURT 6, 2nd floor, 31016 Limassol, Cyprus
Manufacturer:	OMO Systems Ltd.
Address:	Griva Digeni, 80, SWEPCO COURT 6, 2nd floor, 31016 Limassol, Cyprus
Factory:	Hangzhou Roombanker Technology Co., Ltd.
Address:	A#801 Wantong center, Hangzhou, China

4.2 General Description of E.U.T.

Product Name:	OMO HUB
Model No.:	PRO NEO V1.0
Operation Frequency:	2405MHz~2480MHz (IEEE 802.15.4)
Channel numbers:	16 for (IEEE 802.15.4)
Channel separation:	5 MHz
Modulation technology: (IEEE 802.15.4)	OQPSK
Data speed(IEEE 802.15.4):	250kbps
Antenna Type:	External glue stick Antenna
Antenna gain:	1.25 dBi (declare by applicant)
Power supply:	Rechargeable Li-ion Battery DC3.7V, 5200mAh*2
AC Adapter:	Model: KA2401A-1202000US Input: AC100-240V, 50/60Hz, 0.65A Max Output: DC 12.0V, 2000mA
Test Sample Condition:	The applicant provided engineering samples for staying in continuously transmitting for testing.

4.3 Test environment and mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1008 mbar
Test mode:	
Transmitting mode	Keep the EUT in continuous transmitting with modulation
<p>The sample was placed 0.8m (below 1GHz)/1.5m (above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. Duty cycle setting during the transmission is 100% with maximum power setting for all modulations.</p>	

4.4 Description of Support Units

The EUT has been tested as an independent unit.

4.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Conducted Emission for LISN (9kHz ~ 150kHz)	±3.11 dB
Conducted Emission for LISN (150kHz ~ 30MHz)	±2.62 dB
Radiated Emission (1GHz ~ 18GHz) (3m SAC)	±5.34 dB
Radiated Emission (18GHz ~ 40GHz) (3m SAC)	±5.34 dB

Note: All the measurement uncertainty value were shown with a coverage k=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

4.6 Additions to, deviations, or exclusions from the method

No

4.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

4.8 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

4.9 Test Instruments list

Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	04-14-2021	04-13-2024
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	03-08-2022	03-07-2023
Biconical Antenna	Schwarzbeck	VUBA9117	WXJ002-1	07-02-2021	07-01-2024
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-2	03-08-2022	03-07-2023
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-3	04-07-2022	04-06-2023
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-5	04-07-2022	04-06-2023
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-6	04-07-2022	04-06-2023
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXJ001-2	01-20-2022	01-19-2023
Pre-amplifier (1GHz ~ 18GHz)	SKET	LNPA_0118G-50	WXJ001-3	01-20-2022	01-19-2023
Pre-amplifier (18GHz ~ 40GHz)	RF System	TRLA-180400G45B	WXJ002-7	03-30-2022	03-29-2023
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	03-05-2022	03-04-2023
Spectrum Analyzer	KEYSIGHT	N9010B	WXJ004-2	01-20-2022	01-19-2023
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	10-27-2021	10-26-2022
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG001-5	01-20-2022	01-19-2023
Coaxial Cable (18GHz ~ 40GHz)	JYTSZ	JYT3M-40G-SS-8M	WXG001-7	01-20-2022	01-19-2023
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Test Software	Tonscend	TS+	Version: 3.0.0.1		

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESR3	WXJ003-2	10-21-2021	10-20-2022
RF Switch	TOP PRECISION	RSU0301	WXG003	N/A	
LISN	Schwarzbeck	NSLK 8127	QCJ001-13	02-24-2022	02-23-2023
LISN	Rohde & Schwarz	ESH3-Z5	WXJ005-1	03-30-2022	03-29-2023
LISN Coaxial Cable (9kHz ~ 30MHz)	JYTSZ	JYTCE-1G-NN-2M	WXG003-1	02-24-2022	02-23-2023
Test Software	AUDIX	E3	Version: 6.110919b		

Conducted Method:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
Spectrum Analyzer	Keysight	N9010B	WXJ004-3	10-27-2021	10-26-2022
Power Detector Box	MWRFTEST	MW100-PSB	WXJ007-4	11-19-2021	11-18-2022
RF Control Unit	MWRFTEST	MW100-RFCB	WXG006	N/A	
Test Software	MWRFTEST	MTS 8310	Version: 2.0.0.0		

5 Measurement Setup and Procedure


5.1 Test Channel

According to ANSI C63.10-2013 chapter 5.6.1 Table 4 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:

Lowest channel		Middle channel		Highest channel	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2405	8	2440	16	2480

5.2 Test Setup


1) Conducted emission measurement:




Note: The 0.8 m distance specified between EUT/AE/PSU and AMN/AAN, is applicable only to the EUT being measured. If the device is AE then it shall be >0.8 m.

2) Radiated emission measurement:

Below 1GHz (3m SAC)





5.3 Test Procedure

Test method	Test step
Conducted emission	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
Radiated emission	<p>For below 1GHz:</p> <ol style="list-style-type: none"> 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data. <p>For above 1GHz:</p> <ol style="list-style-type: none"> 1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.
Conducted test method	<ol style="list-style-type: none"> 1. The BLE antenna port of EUT was connected to the test port of the test system through an RF cable. 2. The EUT is keeping in continuous transmission mode and tested in all modulation modes. 3. Open the test software, prepare a test plan, and control the system through the software. After the test is completed, the test report is exported through the test software.

6 Test Results

6.1 Summary

6.1.1 Clause and Data Summary

Test items	Standard clause	Test data	Result
Antenna Requirement	15.203 15.247 (b)(4)	See Section 6.2	Pass
AC Power Line Conducted Emission	15.207	See Section 6.3	Pass
Duty Cycle	ANSI C63.10-2013	Appendix A - Zigbee	N/A
Conducted Output Power	15.247 (b)(3)	Appendix A - Zigbee	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Appendix A - Zigbee	Pass
Power Spectral Density	15.247 (e)	Appendix A - Zigbee	Pass
Band-edge Emission Conduction Spurious Emission	15.247 (d)	Appendix A - Zigbee	Pass
Emissions in Restricted Frequency Bands	15.205 15.247 (d)	See Section 6.4	Pass
Emissions in Non-restricted Frequency Bands	15.209 15.247(d)	See Section 6.5	Pass
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (provided by the customer).			
Test Method:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02		

6.1.2 Test Limit


Test items	Limit																																
AC Power Line Conducted Emission	Frequency (MHz)	Limit (dB μ V)																															
		Quasi-Peak	Average																														
	0.15 – 0.5	66 to 56 Note 1	56 to 46 Note 1																														
	0.5 – 5	56	46																														
	5 – 30	60	50																														
Note 1: The limit level in dB μ V decreases linearly with the logarithm of frequency. Note 2: The more stringent limit applies at transition frequencies.																																	
Conducted Output Power	For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.																																
6dB Emission Bandwidth	The minimum 6 dB bandwidth shall be at least 500 kHz.																																
99% Occupied Bandwidth	N/A																																
Power Spectral Density	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.																																
Band-edge Emission	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).																																
Conduction Spurious Emission																																	
Emissions in Restricted Frequency Bands	<table border="1"> <thead> <tr> <th rowspan="2">Frequency (MHz)</th> <th colspan="2">Limit (dBμV/m)</th> <th rowspan="2">Detector</th> </tr> <tr> <th>@ 3m</th> <th>@ 10m</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>40.0</td> <td>30.0</td> <td>Quasi-peak</td> </tr> <tr> <td>88 – 216</td> <td>43.5</td> <td>33.5</td> <td>Quasi-peak</td> </tr> <tr> <td>216 – 960</td> <td>46.0</td> <td>36.0</td> <td>Quasi-peak</td> </tr> <tr> <td>960 – 1000</td> <td>54.0</td> <td>44.0</td> <td>Quasi-peak</td> </tr> </tbody> </table> <p>Note: The more stringent limit applies at transition frequencies.</p> <table border="1"> <thead> <tr> <th rowspan="2">Frequency</th> <th colspan="2">Limit (dBμV/m) @ 3m</th> </tr> <tr> <th>Average</th> <th>Peake</th> </tr> </thead> <tbody> <tr> <td>Above 1 GHz</td> <td>54.0</td> <td>74.0</td> </tr> </tbody> </table> <p>Note: The measurement bandwidth shall be 1 MHz or greater.</p>	Frequency (MHz)	Limit (dB μ V/m)		Detector	@ 3m	@ 10m	30 – 88	40.0	30.0	Quasi-peak	88 – 216	43.5	33.5	Quasi-peak	216 – 960	46.0	36.0	Quasi-peak	960 – 1000	54.0	44.0	Quasi-peak	Frequency	Limit (dB μ V/m) @ 3m		Average	Peake	Above 1 GHz	54.0	74.0		
Frequency (MHz)	Limit (dB μ V/m)		Detector																														
	@ 3m	@ 10m																															
30 – 88	40.0	30.0	Quasi-peak																														
88 – 216	43.5	33.5	Quasi-peak																														
216 – 960	46.0	36.0	Quasi-peak																														
960 – 1000	54.0	44.0	Quasi-peak																														
Frequency	Limit (dB μ V/m) @ 3m																																
	Average	Peake																															
Above 1 GHz	54.0	74.0																															
Emissions in Non-restricted Frequency Bands																																	

6.2 Antenna requirement

Standard requirement:	FCC Part 15 C Section 15.203 /247(b)(4)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
E.U.T Antenna: The Zigbee antenna is an external glue stick Antenna which cannot replace by end-user, the best case gain of the antenna is 1.25 dBi. See product internal photos for details.	

6.3 AC Power Line Conducted Emission

Product name:	OMO HUB	Product model:	PRO NEO V1.0
Test by:	Mike	Test mode:	Transmitting mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%




Freq	Read	LISN	Cable	Limit	Over	Remark
	Level	Factor	Loss			
MHz	dBuV	dB	dB	dBuV	dBuV	dB
1	0.158	45.94	0.04	0.01	45.99	55.56 -9.57 Average
2	0.158	57.09	0.04	0.01	57.14	65.56 -8.42 Peak
3	0.194	50.91	0.05	0.03	50.99	63.84 -12.85 Peak
4	0.299	43.49	0.06	0.03	43.58	50.28 -6.70 Average
5	0.373	48.58	0.06	0.03	48.67	58.43 -9.76 Peak
6	0.381	44.29	0.06	0.03	44.38	48.25 -3.87 Average
7	1.021	36.19	0.07	0.05	36.31	46.00 -9.69 Average
8	1.094	43.83	0.07	0.07	43.97	56.00 -12.03 Peak
9	9.156	41.86	0.21	0.11	42.18	60.00 -17.82 Peak
10	9.705	32.82	0.22	0.12	33.16	50.00 -16.84 Average
11	19.326	40.09	0.33	0.15	40.57	50.00 -9.43 Average
12	19.428	47.57	0.33	0.15	48.05	60.00 -11.95 Peak

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level = Receiver Read level + LISN Factor + Cable Loss.

Product name:	OMO HUB	Product model:	PRO NEO V1.0
Test by:	Mike	Test mode:	Transmitting mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%




Freq MHz	Read Level dBuV	LISN Factor	Cable Loss dB	Level dBuV	Limit Line dBuV	Over Limit dB	Over Limit Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.174	54.42	0.05	0.01	54.48	64.77	-10.29 QP
2	0.198	50.49	0.05	0.04	50.58	63.71	-13.13 QP
3	0.299	43.05	0.05	0.03	43.13	50.28	-7.15 Average
4	0.354	43.98	0.05	0.02	44.05	48.87	-4.82 Average
5	0.354	50.74	0.05	0.02	50.81	58.87	-8.06 QP
6	0.471	38.73	0.04	0.03	38.80	46.49	-7.69 Average
7	0.541	43.31	0.04	0.03	43.38	56.00	-12.62 QP
8	0.683	42.60	0.06	0.03	42.69	56.00	-13.31 QP
9	0.857	35.35	0.06	0.04	35.45	46.00	-10.55 Average
10	6.153	32.66	0.14	0.09	32.89	50.00	-17.11 Average
11	18.524	48.69	0.31	0.15	49.15	60.00	-10.85 QP
12	18.721	41.64	0.32	0.15	42.11	50.00	-7.89 Average

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level =Receiver Read level + LISN Factor + Cable Loss.

6.4 Emissions in Restricted Frequency Bands

Product Name:	OMO HUB	Product model:	PRO NEO V1.0
Test By:	Mike	Test mode:	Transmitting mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120V/60HZ	Environment:	Temp: 24°C Huni: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dB μ V/m]	Level [dB μ V/m]	Factor [dB]	Limit [dB μ V/m]	Margin [dB]	Trace	Polarity
1	2326.62	23.37	58.49	35.12	74.00	15.51	PK	Vertical
2	2326.62	12.66	47.78	35.12	54.00	6.22	AV	Vertical
3	2354.88	24.03	59.36	35.33	74.00	14.64	PK	Vertical
4	2354.88	12.69	48.02	35.33	54.00	5.98	AV	Vertical
5	2390.00	22.63	58.23	35.60	74.00	15.77	PK	Vertical
6	2390.00	12.44	48.04	35.60	54.00	5.96	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	OMO HUB	Product model:	PRO NEO V1.0
Test By:	Mike	Test mode:	Transmitting mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120V/60HZ	Environment:	Temp: 24°C Huni: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dB μ V/m]	Level [dB μ V/m]	Factor [dB]	Limit [dB μ V/m]	Margin [dB]	Trace	Polarity
1	2327.2380	23.34	58.46	35.12	74.00	15.54	PK	Horizontal
2	2327.2380	12.78	47.90	35.12	54.00	6.10	AV	Horizontal
3	2356.6140	22.98	58.32	35.34	74.00	15.68	PK	Horizontal
4	2356.6140	12.57	47.91	35.34	54.00	6.09	AV	Horizontal
5	2390.0000	22.21	57.81	35.60	74.00	16.19	PK	Horizontal
6	2390.0000	12.33	47.93	35.60	54.00	6.07	AV	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	OMO HUB	Product model:	PRO NEO V1.0
Test By:	Mike	Test mode:	Transmitting mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120V/60HZ	Environment:	Temp: 24°C Huni: 57%




Suspected Data List

NO.	Freq. [MHz]	Reading [dB μ V/m]	Level [dB μ V/m]	Factor [dB]	Limit [dB μ V/m]	Margin [dB]	Trace	Polarity
1	2483.50	26.03	61.54	35.51	74.00	12.46	PK	Vertical
2	2483.50	15.96	51.47	35.51	54.00	2.53	AV	Vertical
3	2489.07	12.81	48.31	35.50	54.00	5.69	AV	Vertical
4	2489.07	22.96	58.46	35.50	74.00	15.54	PK	Vertical
5	2494.05	23.00	58.49	35.49	74.00	15.51	PK	Vertical
6	2494.05	12.42	47.91	35.49	54.00	6.09	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	OMO HUB	Product model:	PRO NEO V1.0
Test By:	Mike	Test mode:	Transmitting mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120V/60HZ	Environment:	Temp: 24°C Huni: 57%



Suspected Data List								
NO.	Freq. [MHz]	Reading [dB μ V/m]	Level [dB μ V/m]	Factor [dB]	Limit [dB μ V/m]	Margin [dB]	Trace	Polarity
1	2483.5000	23.17	58.68	35.51	74.00	15.32	PK	Horizontal
2	2483.5000	13.59	49.10	35.51	54.00	4.90	AV	Horizontal
3	2489.1000	12.60	48.10	35.50	54.00	5.90	AV	Horizontal
4	2489.1000	23.15	58.65	35.50	74.00	15.35	PK	Horizontal
5	2495.0000	23.35	58.84	35.49	74.00	15.16	PK	Horizontal
6	2495.0000	12.34	47.83	35.49	54.00	6.17	AV	Horizontal


Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

6.5 Emissions in Non-restricted Frequency Bands

Below 1GHz:

Product Name:	OMO HUB	Product model:	PRO NEO V1.0
Test By:	Mike	Test mode:	Transmitting mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120V/60HZ	Environment:	Temp: 24°C Huni: 57%




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	53.0883	41.94	28.91	-13.03	40.00	11.09	PK	Vertical
2	61.9162	47.95	33.42	-14.53	40.00	6.58	PK	Vertical
3	131.181	45.01	27.04	-17.97	43.50	16.46	PK	Vertical
4	191.812	35.27	19.52	-15.75	43.50	23.98	PK	Vertical
5	549.681	27.82	19.77	-8.05	46.00	26.23	PK	Vertical
6	890.670	26.95	24.19	-2.76	46.00	21.81	PK	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	OMO HUB	Product model:	PRO NEO V1.0
Test By:	Mike	Test mode:	Transmitting mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60HZ	Environment:	Temp: 24°C Huni: 57%



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	53.2823	28.95	15.90	-13.05	40.00	24.10	PK	Horizontal
2	64.2444	34.70	20.00	-14.70	40.00	20.00	PK	Horizontal
3	125.360	40.66	23.09	-17.57	43.50	20.41	PK	Horizontal
4	221.303	36.28	21.54	-14.74	46.00	24.46	PK	Horizontal
5	339.558	33.81	22.11	-11.70	46.00	23.89	PK	Horizontal
6	756.020	28.65	24.37	-4.28	46.00	21.63	PK	Horizontal

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Above 1GHz

Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4810.00	57.62	-9.60	48.02	74.00	25.98	Vertical
4810.00	57.97	-9.60	48.37	74.00	25.63	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4810.00	53.76	-9.60	44.16	54.00	9.84	Vertical
4810.00	51.75	-9.60	42.15	54.00	11.85	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4880.00	57.75	-9.04	48.71	74.00	25.29	Vertical
4880.00	58.01	-9.04	48.97	74.00	25.03	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4880.00	53.80	-9.04	44.76	54.00	9.24	Vertical
4880.00	51.71	-9.04	42.67	54.00	11.33	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4960.00	57.40	-8.45	48.95	74.00	25.05	Vertical
4960.00	57.57	-8.45	49.12	74.00	24.88	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4960.00	53.31	-8.45	44.86	54.00	9.14	Vertical
4960.00	51.50	-8.45	43.05	54.00	10.95	Horizontal

Remark:

1. Final Level = Receiver Read level + Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

-----End of report-----