



# TEST Report

**Applicant:** Shenzhen TwoTrees Technology Co., Ltd.

**Address of Applicant:** Room 402, Building 11, No.9 Qilin Road, Nankeng Community Bantian Street, Longgang District, Shenzhen, Guangdong, China, 518000

**Manufacturer :** Shenzhen TwoTrees Technology Co., Ltd.

**Address of Manufacturer :** Room 402, Building 11, No.9 Qilin Road, Nankeng Community Bantian Street, Longgang District, Shenzhen, Guangdong, China, 518000

**Equipment Under Test (EUT)**

Product Name: LASER ENGRAVER

Model No.: TTS-55 Pro

Series model: TTS-25 Pro, TTS-10 Pro, TTS-20 Pro, TTS 25 Pro, TTS 55 Pro, TTS 10 Pro, TTS 20 Pro, TTS-25, TTS-55, TTS-10, TTS 25, TTS 55, TTS 10

Trade Mark: N/A

FCC ID: 2A7F8-TTS-55PRO

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.247

**Date of sample receipt:** Nov. 24, 2023

**Date of Test:** Nov. 24, 2023~Nov. 30, 2023

**Date of report issued:** Nov. 30, 2023

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.



### 1. Version

Version No.	Date	Description
00	Nov. 30, 2023	Original

**Tested/ Prepared By** Heber He **Date:** Nov. 30, 2023  
**Project Engineer**

**Check By:** Bruce Zhu **Date:** Nov. 30, 2023  
**Reviewer**

**Approved By :** Kevin Yang **Date:** Nov. 30, 2023  
**Authorized Signature**





## 2. Contents

Page

<b>1. VERSION</b> .....	<b>2</b>
<b>2. CONTENTS</b> .....	<b>3</b>
<b>3. TEST SUMMARY</b> .....	<b>4</b>
<b>4. GENERAL INFORMATION</b> .....	<b>5</b>
4.1. GENERAL DESCRIPTION OF EUT .....	5
4.2. TEST MODE .....	7
4.3. DESCRIPTION OF SUPPORT UNITS .....	7
4.4. DEVIATION FROM STANDARDS .....	7
4.5. ABNORMALITIES FROM STANDARD CONDITIONS.....	7
4.6. TEST FACILITY.....	7
4.7. TEST LOCATION.....	7
4.8. ADDITIONAL INSTRUCTIONS .....	7
<b>5. TEST INSTRUMENTS LIST</b> .....	<b>8</b>
<b>6. TEST RESULTS AND MEASUREMENT DATA</b> .....	<b>9</b>
6.1. CONDUCTED EMISSIONS .....	9
6.2. CONDUCTED PEAK OUTPUT POWER.....	12
6.3. CHANNEL BANDWIDTH .....	13
6.4. POWER SPECTRAL DENSITY.....	16
6.5. BAND EDGE.....	19
6.5.1. <i>Conducted Emission Method</i> .....	19
6.5.2. <i>Radiated Emission Method</i> .....	22
6.6. SPURIOUS EMISSION.....	24
6.6.1. <i>Conducted Emission Method</i> .....	24
6.6.2. <i>Radiated Emission Method</i> .....	29
6.7. ANTENNA REQUIREMENT.....	36
<b>7. TEST SETUP PHOTO</b> .....	<b>37</b>
<b>8. EUT CONSTRUCTIONAL DETAILS</b> .....	<b>37</b>



### 3. Test Summary

Test Item	Section	Result
Antenna requirement	FCC part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	FCC part 15.207	Pass
Conducted Peak Output Power	FCC part 15.247 (b)(3)	Pass
6dB Bandwidth	FCC part 15.247 (a)(2)	Pass
Power Spectral Density	FCC part 15.247 (e)	Pass
Band Edge	FCC part 15.247(d)	Pass
Spurious Emission	FCC part 15.205/15.209	Pass

*Remark: Test according to ANSI C63.10:2013 and RSS-Gen*

*Pass: The EUT complies with the essential requirements in the standard.*

#### Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	3.45 dB	(1)
Radiated Emission	1~6GHz	3.54 dB	(1)
Radiated Emission	6~40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.66 dB	(1)

Note (1): The measurement uncertainty is for coverage factor of  $k=2$  and a level of confidence of 95%.



## 4. General Information

### 4.1. General Description of EUT

Product Name:	LASER ENGRAVER
Model No.:	TTS-55 Pro
Series model:	TTS-25 Pro, TTS-10 Pro, TTS-20 Pro, TTS 25 Pro, TTS 55 Pro, TTS 10 Pro, TTS 20 Pro, TTS-25, TTS-55, TTS-10, TTS 25, TTS 55, TTS 10
Test sample(s) ID:	HTT202311547-1(Engineer sample) HTT202311547-2(Normal sample)
Channel numbers:	802.11b/802.11g /802.11n(HT20): 11 802.11n(HT40):7
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(H20)/802.11n(HT40): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	FPC antenna
Antenna gain:	3.00 dBi
Power supply:	DC 12V
Adapter Information:	Mode: FY0471204000 Input: AC100-240V, 50/60Hz, 1.5A Output: DC 12.0V, 4.0A



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	X	

**Note:**

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/802.11g/802.11n(HT20)	802.11n(HT40)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz



## 4.2. Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: During the test, the duty cycle &gt;98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:				
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.				
Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	13Mbps

## 4.3. Description of Support Units

None.
-------

## 4.4. Deviation from Standards

None.
-------

## 4.5. Abnormalities from Standard Conditions

None.
-------

## 4.6. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:  <b>FCC-Registration No.: 779513 Designation Number: CN1319</b> Shenzhen HTT Technology Co.,Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. <b>A2LA-Lab Cert. No.: 6435.01</b> Shenzhen HTT Technology Co.,Ltd. has been accredited by American Association for Laboratory Accreditation to perform electromagnetic emission measurement. The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.
--

## 4.7. Test Location

All tests were performed at:
Shenzhen HTT Technology Co.,Ltd. 1F, Building B, Huafeng International Robotics Industrial Park, Hangcheng Road,Nanchang Community, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China Tel: 0755-23595200 Fax: 0755-23595201

## 4.8. Additional Instructions

Test Software	Special AT test command provided by manufacturer to Keep the EUT in continuously transmitting mode and hopping mode
Power level setup	Default




## 5. Test Instruments list

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	Shenzhen C.R.T technology co., LTD	9*6*6	HTT-E028	Aug. 10 2021	Aug. 09 2024
2	Control Room	Shenzhen C.R.T technology co., LTD	4.8*3.5*3.0	HTT-E030	Aug. 10 2021	Aug. 09 2024
3	EMI Test Receiver	Rohde&Schwar	ESCI7	HTT-E022	Apr. 26 2023	Apr. 25 2024
4	Spectrum Analyzer	Rohde&Schwar	FSP	HTT-E037	Apr. 26 2023	Apr. 25 2024
5	Coaxial Cable	ZDecl	ZT26-NJ-NJ-0.6M	HTT-E018	Apr. 26 2023	Apr. 25 2024
6	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-2M	HTT-E019	Apr. 26 2023	Apr. 25 2024
7	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-0.6M	HTT-E020	Apr. 26 2023	Apr. 25 2024
8	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-8.5M	HTT-E021	Apr. 26 2023	Apr. 25 2024
9	Composite logarithmic antenna	Schwarzbeck	VULB 9168	HTT-E017	May. 21 2023	May. 20 2024
10	Horn Antenna	Schwarzbeck	BBHA9120D	HTT-E016	May. 20 2023	May. 19 2024
11	Loop Antenna	Zhinan	ZN30900C	HTT-E039	Apr. 26 2023	Apr. 25 2024
12	Horn Antenna	Beijing Hangwei Dayang	OBH100400	HTT-E040	Apr. 26 2023	Apr. 25 2024
13	low frequency Amplifier	Sonoma Instrument	310	HTT-E015	Apr. 26 2023	Apr. 25 2024
14	high-frequency Amplifier	HP	8449B	HTT-E014	Apr. 26 2023	Apr. 25 2024
15	Variable frequency power supply	Shenzhen Anbiao Instrument Co., Ltd	ANB-10VA	HTT-082	Apr. 26 2023	Apr. 25 2024
16	EMI Test Receiver	Rohde & Schwarz	ESCS30	HTT-E004	Apr. 26 2023	Apr. 25 2024
17	Artificial Mains	Rohde & Schwarz	ESH3-Z5	HTT-E006	May. 23 2023	May. 22 2024
18	Artificial Mains	Rohde & Schwarz	ENV-216	HTT-E038	May. 23 2023	May. 22 2024
19	Cable Line	Robinson	Z302S-NJ-BNCJ-1.5M	HTT-E001	Apr. 26 2023	Apr. 25 2024
20	Attenuator	Robinson	6810.17A	HTT-E007	Apr. 26 2023	Apr. 25 2024
21	Variable frequency power supply	Shenzhen Yanghong Electric Co., Ltd	YF-650 (5KVA)	HTT-E032	Apr. 26 2023	Apr. 25 2024
22	Control Room	Shenzhen C.R.T technology co., LTD	8*4*3.5	HTT-E029	Aug. 10 2021	Aug. 09 2024
23	DC power supply	Agilent	E3632A	HTT-E023	Apr. 26 2023	Apr. 25 2024
24	EMI Test Receiver	Agilent	N9020A	HTT-E024	Apr. 26 2023	Apr. 25 2024
25	Analog signal generator	Agilent	N5181A	HTT-E025	Apr. 26 2023	Apr. 25 2024
26	Vector signal generator	Agilent	N5182A	HTT-E026	Apr. 26 2023	Apr. 25 2024
27	Power sensor	Keysight	U2021XA	HTT-E027	Apr. 26 2023	Apr. 25 2024
28	Temperature and humidity meter	Shenzhen Anbiao Instrument Co., Ltd	TH10R	HTT-074	Apr. 28 2023	Apr. 27 2024
29	Radiated Emission Test Software	Farad	EZ-EMC	N/A	N/A	N/A
30	Conducted Emission Test Software	Farad	EZ-EMC	N/A	N/A	N/A
31	RF Test Software	panshanrf	TST	N/A	N/A	N/A



## 6. Test results and Measurement Data

### 6.1. Conducted Emissions


Test Requirement:	FCC Part15 C Section 15.207					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak	Average		
	0.15-0.5		66 to 56*	56 to 46*		
	0.5-5		56	46		
	5-30		60	50		
* Decreases with the logarithm of the frequency.						
Test setup:	 <p>Remark:                      E.U.T: Equipment Under Test                      LISN: Line Impedance Stabilization Network                      Test table height=0.8m</p>					
Test procedure:	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.</li> </ol>					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	PASS					

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.



Measurement data:


Line:



No.	Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1505	30.44	10.16	40.60	65.97	-25.37	QP
2		0.1505	11.40	10.16	21.56	55.97	-34.41	AVG
3		0.2010	22.85	10.21	33.06	63.57	-30.51	QP
4		0.2010	11.71	10.21	21.92	53.57	-31.65	AVG
5		0.6303	19.31	10.32	29.63	56.00	-26.37	QP
6	*	0.6303	13.24	10.32	23.56	46.00	-22.44	AVG
7		2.5442	14.82	10.46	25.28	56.00	-30.72	QP
8		2.5442	7.65	10.46	18.11	46.00	-27.89	AVG
9		4.8016	15.50	10.61	26.11	56.00	-29.89	QP
10		4.8016	7.73	10.61	18.34	46.00	-27.66	AVG
11		20.5859	15.92	11.29	27.21	60.00	-32.79	QP
12		20.5859	8.87	11.29	20.16	50.00	-29.84	AVG



Neutral:




No.	Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1635	28.50	10.18	38.68	65.28	-26.60	QP
2		0.1635	9.66	10.18	19.84	55.28	-35.44	AVG
3		0.6316	22.52	10.35	32.87	56.00	-23.13	QP
4	*	0.6316	14.77	10.35	25.12	46.00	-20.88	AVG
5		1.0907	17.81	10.33	28.14	56.00	-27.86	QP
6		1.0907	10.45	10.33	20.78	46.00	-25.22	AVG
7		4.6082	12.27	10.53	22.80	56.00	-33.20	QP
8		4.6082	3.04	10.53	13.57	46.00	-32.43	AVG
9		9.1087	12.82	10.83	23.65	60.00	-36.35	QP
10		9.1087	5.09	10.83	15.92	50.00	-34.08	AVG
11		23.9679	19.27	11.36	30.63	60.00	-29.37	QP
12		23.9679	11.99	11.36	23.35	50.00	-26.65	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Los


## 6.2. Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)					
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02					
Limit:	30dBm					
Test setup:	<p>Power sensor and Spectrum analyzer</p>  <p>Non-Conducted Table</p> <p>Ground Reference Plane</p>					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar

### Measurement Data

Test CH	Peak Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	9.44	10.84	10.79	9.35	30.00	Pass
Middle	9.05	10.33	10.61	8.62		
Highest	7.78	8.99	9.09	7.55		

### 6.3. Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)					
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02					
Limit:	>500KHz					
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an Equipment Under Test (E.U.T.). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar



### Measurement Data

Test CH	Channel Bandwidth (MHz)				Limit(KHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	11.105	17.257	18.297	35.157	>500	Pass
Middle	11.556	17.240	18.308	35.121		
Highest	11.139	17.274	18.319	35.167		





Test plot as follows:



802.11b	802.11g
---------	---------



Lowest channel





Middle channel





Highest channel





802.11n(HT20)	802.11n(HT40)
---------------	---------------



Lowest channel




Middle channel



Highest channel

### 6.4. Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)					
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02					
Limit:	8dBm/3kHz					
Test setup:						
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar

### Measurement Data

Test CH	Power Spectral Density (dBm/3kHz)				Limit (dBm/3kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	-18.17	-23.06	-22.14	-25.38	8.00	Pass
Middle	-17.34	-23.09	-22.11	-27.67		
Highest	-19.11	-23.35	-23.28	-29.20		



Remark: We have tested all mode at high, middle and low channel, and recorded worst case at middle







Test plot as follows:



802.11b	802.11g
---------	---------



Lowest channel





Middle channel





Highest channel





802.11n(HT20)	802.11n(HT40)
---------------	---------------



Lowest channel




Middle channel



Highest channel

## 6.5. Band Edge


### 6.5.1. Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)					
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02					
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar




Test plot as follows:

Test mode:	802.11b
------------	---------




Lowest channel




Highest channel

Test mode:	802.11g
------------	---------




Lowest channel




Highest channel



Test mode: 802.11n(HT20)




Lowest channel




Highest channel

Test mode: 802.11n(HT40)




Lowest channel



Highest channel

**6.5.2. Radiated Emission Method**

Test Requirement:	FCC Part15 C Section 15.209 and 15.205					
Test Method:	ANSI C63.10: 2013					
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.					
Test site:	Measurement Distance: 3m					
Receiver setup:	Frequency	Detector	RBW	VBW	Remark	
	Above 1GHz	Peak	1MHz	3MHz	Peak Value	
		Peak	1MHz	10Hz	Average Value	
Limit:	Frequency		Limit (dBuV/m @3m)		Remark	
	Above 1GHz		54.00		Average Value	
			74.00		Peak Value	
Test setup:						
Test Procedure:	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar




**Measurement Data**

Remark: During the test, pre-scan the 802.11b/802.11g/802.11n (H20)/802.11n (H40) modulation, and found the 802.11b modulation which it is worse case.

Frequency(MHz):			2412		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	62.49	PK	74	11.51	63.88	27.2	4.31	32.9	-1.39
2390.00	44.71	AV	54	9.29	46.10	27.2	4.31	32.9	-1.39
Frequency(MHz):			2412		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	59.71	PK	74	14.29	61.10	27.2	4.31	32.9	-1.39
2390.00	46.30	AV	54	7.70	47.69	27.2	4.31	32.9	-1.39
Frequency(MHz):			2462		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	56.80	PK	74	17.20	57.73	27.4	4.47	32.8	-0.93
2483.50	43.54	AV	54	10.46	44.47	27.4	4.47	32.8	-0.93
Frequency(MHz):			2462		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	55.65	PK	74	18.35	56.58	27.4	4.47	32.8	-0.93
2483.50	43.53	AV	54	10.47	44.46	27.4	4.47	32.8	-0.93

## 6.6. Spurious Emission


### 6.6.1. Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)				
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02				
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.				
Test setup:					
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				
Test results:	Pass				
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.: 1012mbar





Measurement Data:







**802.11n(HT40)**



802.11b



802.11g

Lowest channel





30MHz~25GHz

Middle channel



30MHz~25GHz

Highest channel





30MHz~25GHz



802.11n(HT20)



802.11n(HT40)

Lowest channel





30MHz~25GHz

Middle channel




30MHz~25GHz



Highest channel



30MHz~25GHz

**6.6.2. Radiated Emission Method**

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit:	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	QP	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	30m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
		5000	Peak		
Test setup:	<p>For radiated emissions from 9kHz to 30MHz</p>  <p>The diagram illustrates the test setup for radiated emissions. An Equipment Under Test (EUT) is placed on a turn table with a diameter of less than 80cm. The EUT is positioned at a distance of less than 3m from a Test Antenna. The Test Antenna is connected to a Receiver. The distance between the Test Antenna and the Receiver is 1m. The ground plane is indicated by a ground symbol.</p>				

	<p>For radiated emissions from 30MHz to 1GHz</p>  <p>For radiated emissions above 1GHz</p> 
<p>Test Procedure:</p>	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>
<p>Test Instruments:</p>	<p>Refer to section 6.0 for details</p>
<p>Test mode:</p>	<p>Refer to section 5.2 for details</p>



Report No.: HTT202311547F01

Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

*Remarks:*

- 1.Only the worst case Main Antenna test data.*
- 2.Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.*

**Measurement data:**


■ **9kHz~30MHz**

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.




■ Below 1GHz

Pre-scan all test modes, found worst case at 802.11b 2437MHz, and so only show the test result of 802.11b 2437MHz









■ Above 1-25GHz

Note: During the test, pre-scan the 802.11b/802.11g/802.11n (H20)/802.11n (H40) modulation, and found the 802.11b modulation which it is worse case.

802.11b:

Frequency(MHz):			2412		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	59.38	PK	74	14.62	53.56	31.05	6.52	31.75	5.82
4824.00	43.85	AV	54	10.15	38.03	31.05	6.52	31.75	5.82
7236.00	57.21	PK	74	16.79	44.40	36.08	8.18	31.45	12.81
7236.00	47.13	AV	54	6.87	34.32	36.08	8.18	31.45	12.81

Frequency(MHz):			2412		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	59.33	PK	74	14.67	53.51	31.05	6.52	31.75	5.82
4824.00	44.00	AV	54	10.00	38.18	31.05	6.52	31.75	5.82
7236.00	56.97	PK	74	17.03	44.16	36.08	8.18	31.45	12.81
7236.00	47.34	AV	54	6.66	34.53	36.08	8.18	31.45	12.81

Frequency(MHz):			2437		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4874.00	61.05	PK	74	12.95	54.61	31.25	6.7	31.51	6.44
4874.00	45.15	AV	54	8.85	38.71	31.25	6.7	31.51	6.44
7311.00	55.64	PK	74	18.36	42.50	36.25	8.31	31.42	13.14
7311.00	46.23	AV	54	7.77	33.09	36.25	8.31	31.42	13.14



Frequency(MHz):			2437		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4874.00	60.94	PK	74	13.06	54.50	31.25	6.7	31.51	6.44
4874.00	46.02	AV	54	7.98	39.58	31.25	6.7	31.51	6.44
7311.00	57.64	PK	74	16.36	44.50	36.25	8.31	31.42	13.14
7311.00	46.54	AV	54	7.46	33.40	36.25	8.31	31.42	13.14

Frequency(MHz):			2462		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4924.00	60.05	PK	74	13.95	53.18	31.52	6.8	31.45	6.87
4924.00	45.67	AV	54	8.33	38.80	31.52	6.8	31.45	6.87
7386.00	56.58	PK	74	17.42	43.02	36.51	8.4	31.35	13.56
7386.00	45.87	AV	54	8.13	32.31	36.51	8.4	31.35	13.56

Frequency(MHz):			2462		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4924.00	61.64	PK	74	12.36	54.77	31.52	6.8	31.45	6.87
4924.00	45.15	AV	54	8.85	38.28	31.52	6.8	31.45	6.87
7386.00	55.62	PK	74	18.38	42.06	36.51	8.4	31.35	13.56
7386.00	47.03	AV	54	6.97	33.47	36.51	8.4	31.35	13.56

Remark:  
 (1) Data of measurement within this frequency range shown “--- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.  
 (2) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed.



## 6.7. Antenna Requirement

### Standard Applicable

#### **For intentional device, according to FCC 47 CFR Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):**

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

### Antenna Connected Construction

The maximum gain of antenna was 3.0 dBi.

Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Shenzhen HTT Technology Co., Ltd. does not assume any responsibility.



## 7. Test Setup Photo

Reference to the **appendix I** for details.

## 8. EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----