






## TX CH06




## TX CH11








## TX CH06




## TX CH11






|               |           |                     |       |
|---------------|-----------|---------------------|-------|
| Temperature : | 26℃       | Relative Humidity : | 54%   |
| Pressure :    | 101kPa    | Test Voltage :      | DC 5V |
| Test Mode :   | TX g Mode |                     |       |

| Frequency | Power Spectral Density (dBm/3kHz) ANT1 | Power Spectral Density (dBm/3kHz) ANT2 | Limit (dBm/3kHz) | Result |
|-----------|----------------------------------------|----------------------------------------|------------------|--------|
| 2412 MHz  | -14.349                                | -13.030                                | 8                | PASS   |
| 2437 MHz  | -11.130                                | -10.233                                | 8                | PASS   |
| 2462 MHz  | -14.779                                | -14.409                                | 8                | PASS   |







## TX CH06




## TX CH11








## TX CH06




## TX CH11






|               |                |                     |       |
|---------------|----------------|---------------------|-------|
| Temperature : | 26°C           | Relative Humidity : | 54%   |
| Pressure :    | 101kPa         | Test Voltage :      | DC 5V |
| Test Mode :   | TX n Mode(20M) |                     |       |

| Frequency | Power Spectral Density (dBm/3kHz) Ant1 | Power Spectral Density (dBm/3kHz) Ant2 | Power Spectral Density (dBm/3kHz) Total | Limit (dBm/3kHz) | Result |
|-----------|----------------------------------------|----------------------------------------|-----------------------------------------|------------------|--------|
| 2412 MHz  | -12.772                                | -13.148                                | -9.95                                   | 8                | PASS   |
| 2437 MHz  | -11.918                                | -9.434                                 | -7.49                                   | 8                | PASS   |
| 2462 MHz  | -14.514                                | -13.478                                | -10.95                                  | 8                | PASS   |







## TX CH06




## TX CH11








## TX CH06



## TX CH11






|               |                |                     |       |
|---------------|----------------|---------------------|-------|
| Temperature : | 26℃            | Relative Humidity : | 54%   |
| Pressure :    | 101kPa         | Test Voltage :      | DC 5V |
| Test Mode :   | TX n Mode(40M) |                     |       |


| Frequency | Power Spectral Density (dBm/3kHz) Ant1 | Power Spectral Density (dBm/3kHz) Ant2 | Power Spectral Density (dBm/3kHz) Total | Limit (dBm/3kHz) | Result |
|-----------|----------------------------------------|----------------------------------------|-----------------------------------------|------------------|--------|
| 2422 MHz  | -16.339                                | -15.899                                | -13.10                                  | 8                | PASS   |
| 2437 MHz  | -13.666                                | -12.871                                | -10.24                                  | 8                | PASS   |
| 2452 MHz  | -17.589                                | -17.012                                | -14.28                                  | 8                | PASS   |

#### TX CH03 ANT1






### TX CH06




### TX CH09






## TX CH03 ANT2




## TX CH06





## TX CH09





## 7. CHANNEL BANDWIDTH& 99% OCCUPY BANDWIDTH

|                   |                                                           |
|-------------------|-----------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(2)                        |
| Test Method:      | ANSI C63.10:2013 and KDB558074 D01DTS Meas Guidancev05r02 |

### 7.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C |           |                                         |                       |        |
|---------------------------------|-----------|-----------------------------------------|-----------------------|--------|
| Section                         | Test Item | Limit                                   | Frequency Range (MHz) | Result |
| 15.247(a)(2)                    | Bandwidth | $\geq 500\text{KHz}$<br>(6dB bandwidth) | 2400-2483.5           | PASS   |

### 7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3 \times \text{RBW}$ .
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 7.3 DEVIATION FROM STANDARD

No deviation.

### 7.4 TEST SETUP



### 7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



## 7.6 TEST RESULT

|               |           |                     |       |
|---------------|-----------|---------------------|-------|
| Temperature : | 26℃       | Relative Humidity : | 54%   |
| Pressure :    | 101kPa    | Test Voltage :      | DC 5V |
| Test Mode :   | TX b Mode |                     |       |

| Test CH | -6dB Occupy Bandwidth (MHz)<br>ANT1 |         |               |               |            |        |
|---------|-------------------------------------|---------|---------------|---------------|------------|--------|
|         | 802.11b                             | 802.11g | 802.11n(HT20) | 802.11n(HT40) | Limit(KHz) | Result |
| Lowest  | 9.551                               | 15.052  | 17.543        | 35.106        | >500       | Pass   |
| Middle  | 9.113                               | 15.014  | 15.023        | 33.206        |            |        |
| Highest | 9.542                               | 15.042  | 15.086        | 33.824        |            |        |

The test plot shows only the worst case ANT1.

| Test CH | -6dB Occupy Bandwidth (MHz)<br>ANT2 |         |               |               |            |        |
|---------|-------------------------------------|---------|---------------|---------------|------------|--------|
|         | 802.11b                             | 802.11g | 802.11n(HT20) | 802.11n(HT40) | Limit(KHz) | Result |
| Lowest  | 9.115                               | 13.902  | 13.885        | 31.337        | >500       | Pass   |
| Middle  | 9.092                               | 13.899  | 15.349        | 35.062        |            |        |
| Highest | 9.111                               | 15.744  | 15.095        | 35.094        |            |        |





Test plot as follows:


802.11b

802.11g


Lowest channel



Middle channel



Highest channel








802.11n20

802.11n40

## Lowest channel



## Middle channel



## Highest channel





## 8. PEAK OUTPUT POWER TEST

|                   |                                                           |
|-------------------|-----------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3)                        |
| Test Method:      | ANSI C63.10:2013 and KDB558074 D01DTS Meas Guidancev05r02 |

### 8.1 APPLIED PROCEDURES/LIMIT

| FCC Part15 (15.247) , Subpart C |                   |                 |                       |        |
|---------------------------------|-------------------|-----------------|-----------------------|--------|
| Section                         | Test Item         | Limit           | Frequency Range (MHz) | Result |
| 15.247(b)(3)                    | Peak Output Power | 1 watt or 30dBm | 2400-2483.5           | PASS   |

### 8.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

### 8.3 DEVIATION FROM STANDARD

No deviation.

### 8.4 TEST SETUP



### 8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



## 8.6 TEST RESULT

|               |        |                     |              |
|---------------|--------|---------------------|--------------|
| Temperature : | 26℃    | Relative Humidity : | 54%          |
| Pressure :    | 101kPa | Test Voltage :      | AC 120V/60Hz |

| Test CH | Peak Output Power (dBm) |                 |                 |                 | Limit(dBm) | Result |
|---------|-------------------------|-----------------|-----------------|-----------------|------------|--------|
|         | 802.11b<br>Ant1         | 802.11b<br>Ant2 | 802.11g<br>Ant1 | 802.11g<br>Ant2 |            |        |
| Lowest  | 12.317                  | 12.327          | 10.952          | 10.903          | 30.00      | Pass   |
| Middle  | 12.983                  | 13.073          | 12.515          | 13.561          |            |        |
| Highest | 12.847                  | 12.912          | 9.269           | 9.947           |            |        |

| Test CH | Peak Output Power (dBm) |                       |                        | Limit(dBm) | Result |
|---------|-------------------------|-----------------------|------------------------|------------|--------|
|         | 802.11n(HT20)<br>Ant1   | 802.11n(HT20)<br>Ant2 | 802.11n(HT20)<br>Total |            |        |
| Lowest  | 10.573                  | 10.363                | 13.480                 | 30.00      | Pass   |
| Middle  | 13.094                  | 13.157                | 16.140                 |            |        |
| Highest | 9.728                   | 9.763                 | 12.760                 |            |        |

| Test CH | Peak Output Power (dBm) |                       |                        | Limit(dBm) | Result |
|---------|-------------------------|-----------------------|------------------------|------------|--------|
|         | 802.11n(HT40)<br>Ant1   | 802.11n(HT40)<br>Ant2 | 802.11n(HT40)<br>Total |            |        |
| Lowest  | 9.951                   | 10.268                | 13.120                 | 30.00      | Pass   |
| Middle  | 12.933                  | 12.961                | 15.960                 |            |        |
| Highest | 9.112                   | 9.260                 | 12.200                 |            |        |



## 9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

|                   |                                                           |
|-------------------|-----------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (d)                           |
| Test Method:      | ANSI C63.10:2013 and KDB558074 D01DTS Meas Guidancev05r02 |

### 9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

### 9.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

### 9.3 DEVIATION FROM STANDARD

No deviation.

### 9.4 TEST SETUP



### 9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


### 9.6 TEST RESULTS



Test plot as follows:

Test mode:

802.11b




Lowest channel



Highest channel

Test mode:

802.11g



Lowest channel




Highest channel



Test mode:

802.11n(HT20)




Lowest channel




Highest channel

Test mode:

802.11n(HT40)



Lowest channel



Highest channel


The test plot shows only the worst case ANT1.




Test plot as follows:

802.11b


Lowest channel



Middle channel




Highest channel






802.11g


Lowest channel



Middle channel




Highest channel







## 802.11n(HT20) Lowest channel



## Middle channel




## Highest channel







802.11n(HT40)  
Lowest channel



Middle channel



Highest channel



The test plot shows only the worst case ANT1.



## 10. ANTENNA REQUIREMENT

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| Standard requirement:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | FCC Part15 C Section 15.203 /247(c) |
| <p>15.203 requirement:<br/>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement:<br/>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.<br/>A transmitter can only be sold or operated with antennas with which it was approved.</p> |                                     |
| EUT Antenna:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                     |
| The antenna is External Antenna, the best case gain of the antenna is 2dBi, reference to the appendix II for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                     |



## 11. TEST SETUP PHOTO

Reference to the appendix I for details.

## 12. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

\*\*\*\*\* END OF REPORT \*\*\*\*\*