

## FCC 22H 24E 27L, §2.1091 – RF Exposure

FCC ID: 2A7GC-AR350

### Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

#### Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: *f* is frequency in MHz

\* = Power density limit is applicable at frequencies greater than 100 MHz

#### Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: *f* = frequency in MHz

\* = Plane-wave equivalent power density

## MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

## Test Result of RF Exposure Evaluation

	Tune up Produce power	Maximum peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numerical)	Power Density (S) (mW/cm <sup>2</sup> )	Limit (mW / cm <sup>2</sup> )	Result
2.4G WIFI	10±1	11	12.589	1.259 (1.0dBi)	0.00315	1	Pass
WCDMA Band 2	23±1	24	251.189	1.585 (2.0dBi)	0.07924	1	Pass
WCDMA Band 5	23±1	24	251.189	1.122 (0.5dBi)	0.05610	0.549	Pass
LTE BADN 2	23±1	24	251.189	1.585 (2.0dBi)	0.07924	1	Pass
LTE BADN 4	23±1	24	251.189	1.585 (2.0dBi)	0.07924	1	Pass
LTE BADN 5	24±1	25	316.228	1.122 (0.5dBi)	0.07062	0.549	Pass
LTE BADN 12	24±1	25	316.228	1.585 (2.0dBi)	0.09976	0.466	Pass
LTE BADN 13	24±1	25	316.228	1.122 (0.5dBi)	0.07062	0.519	Pass
LTE BADN 17	24±1	25	316.228	1.122 (0.5dBi)	0.07062	0.471	Pass
LTE BADN 66	23±1	24	251.189	1.585 (2.0dBi)	0.07924	1	Pass

$$S=0.09976/0.466+0.00315/1=0.21723 < 1 \text{ Pass}$$