



FCC Part 15E Test Report

FCC ID: 2A7IF-THTX6

Applicant: Top High Technology Co.,Ltd

Address: 101B, 102B Building C6, Hengfeng Industrail park, Hezhou, Xixiang, Bao'an district, Shenzhen

Manufacturer: Top High Technology Co.,Ltd

Address: 101B, 102B Building C6, Hengfeng Industrail park, Hezhou, Xixiang, Bao'an district, Shenzhen

Product: Wireless Selfie Monitor Screen

Trade Mark: N/A

Model No.: THT-X6
THT-X6-1, THT-X6-2, THT-X6-3, THT-X6-4, THT-X6-5, THT-X6-6, THT-X6-7, THT-X6-8, THT-X6-9

Date of Receipt: Apr. 28, 2025

Test Date: Apr. 28, 2025 - May. 26, 2025

Date of Report: May. 26, 2025

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1 Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China

Applicable Standards: FCC PART 15 E 15.407
ANSI C63.10:2013

Test Result: Pass

Report Number: DLE-250428028R

Prepared (Test Engineer): Alisa Song

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents	Page
1. . SUMMARY OF TEST RESULTS	5
1.1. MEASUREMENT UNCERTAINTY	5
2. . GENERAL INFORMATION	6
2.1. GENERAL DESCRIPTION OF EUT	6
2.2. DESCRIPTION OF TEST MODES	7
2.3. BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
2.4. DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	8
2.5. TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	8
2.6. EQUIPMENTS LIST FOR ALL TEST ITEMS	9
3. . EMC EMISSION TEST	10
3.1. CONDUCTED EMISSION MEASUREMENT	10
3.1.1. POWER LINE CONDUCTED EMISSION LIMITS	10
3.1.2. TEST PROCEDURE	10
3.1.3. DEVIATION FROM TEST STANDARD	10
3.1.4. TEST SETUP	11
3.1.5. EUT OPERATING CONDITIONS	11
3.1.6. TEST RESULTS	11
3.2. RADIATED EMISSION MEASUREMENT	14
3.2.1. RADIATED EMISSION LIMITS	14
3.2.2. TEST PROCEDURE	15
3.2.3. DEVIATION FROM TEST STANDARD	15
3.2.4. TEST SETUP	16
3.2.5. EUT OPERATING CONDITIONS	17
3.2.6. TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	18
3.2.7. TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	19
3.2.8. TEST RESULTS (1GHZ~40GHZ)	21
3.3 RADIATED BAND EMISSION MEASUREMENT	26
3.3.1 TEST REQUIREMENT:	26
3.3.2 TEST PROCEDURE	27
3.3.3 DEVIATION FROM TEST STANDARD	27
3.3.4 TEST SETUP	27
3.3.5 EUT OPERATING CONDITIONS	27
4. . AVERAGE OUTPUT POWER	34
4.1. APPLIED PROCEDURES / LIMIT	34
4.1.1. TEST PROCEDURE	34
4.1.2. DEVIATION FROM STANDARD	34



Table of Contents	Page
4.1.3. TEST SETUP	34
4.1.4. EUT OPERATION CONDITIONS	34
4.1.5. TEST RESULTS	35
5. . POWER SPECTRAL DENSITY TEST	39
5.1. APPLIED PROCEDURES / LIMIT	39
5.1.1. TEST PROCEDURE	39
5.1.2. DEVIATION FROM STANDARD	40
5.1.3. TEST SETUP	40
5.1.4. EUT OPERATION CONDITIONS	40
5.1.5. TEST RESULTS	40
6. . 26DB&99% BANDWIDTH TEST	44
6.1. APPLIED PROCEDURES / LIMIT	44
6.1.1. TEST PROCEDURE	44
6.1.2. DEVIATION FROM STANDARD	44
6.1.3. TEST SETUP	44
6.1.4. EUT OPERATION CONDITIONS	44
6.1.5. TEST RESULTS	45
7. . DUTY CYCLE TEST SIGNAL	52
7.1. APPLIED PROCEDURES / LIMIT	52
7.1.1. TEST PROCEDURE	52
7.1.2. DEVIATION FROM STANDARD	52
7.1.3. TEST SETUP	52
7.1.4. EUT OPERATION CONDITIONS	52
7.1.5. TEST RESULTS	53
8. . FREQUENCY STABILITY	57
8.1. APPLIED PROCEDURES / LIMIT	57
8.1.1. TEST PROCEDURE	57
8.1.2. DEVIATION FROM STANDARD	57
8.1.3. TEST SETUP	57
8.1.4. EUT OPERATION CONDITIONS	57
8.1.5. TEST RESULTS	58
9. . TRANSMISSION IN THE ABSENCE OF DATA	60
9.1. STANDARD REQUIREMENT	60
9.2. TEST RESULT	60
10. . ANTENNA REQUIREMENT	60
10.1. STANDARD REQUIREMENT	60
10.2. EUT ANTENNA	60



Table of Contents	Page
11. . TEST SEUUP PHOTO	60
12. . EUT PHOTO	60



1.. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.407(b), 15.209 15.205	Radiated Spurious Emission	PASS	
15.407 (b)	Band Edge Emission	PASS	
15.407 (a)	Average Output Power	PASS	
15.407 (a)	Power Spectral Density	PASS	
15.403(i) 15.407(e)	26dB bandwidth and 99%dB Bandwidth	PASS	
15.407(g)	Frequency Stability	PASS	
15.407(c)	Transmission in case of Absence of Information	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

Test lab: Shenzhen DL Testing Technology Co., Ltd.

101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1

Address: Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB ID.: CN0118

1.1. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.56\text{dB}$
2	RF power,conducted	$\pm 0.42\text{dB}$
3	Spurious emissions,conducted	$\pm 2.76\text{dB}$
4	All emissions,radiated(<1G)	$\pm 3.65\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$
8	Bandwidth	$\pm 0.2\text{MHz}$
9	Power Spectral Density	$\pm 2.45\text{dBm}$
10	Frequency Stability	$\pm 0.3\text{MHz}$
11	DUTY CYCLE	$\pm 0.53\text{dB}$



2.. GENERAL INFORMATION

2.1. GENERAL DESCRIPTION OF EUT

Product Name:	Wireless Selfie Monitor Screen
Trademark	N/A
Model No.:	THT-X6 THT-X6-1, THT-X6-2, THT-X6-3, THT-X6-4, THT-X6-5, THT-X6-6, THT-X6-7, THT-X6-8, THT-X6-9
Model Difference	All models are same as the samples except model name, they have the same structure and circuit.
Operation Frequency:	5180-5240MHz(802.11a/n/ac(HT20)) 5190-5230MHz(802.11n/ac(HT40)) 5210MHzMHz (802.11ac(HT80))
Channel numbers:	See channel list
Channel separation:	5MHz
Modulation technology:	64QAM, 16QAM, QPSK, BPSK for OFDM
Rate of Transmitter	802.11a: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps,54Mbps 802.11n: Up to 500Mbps 802.11ac: up to 867Mbps
Antenna Type:	Internal Antenna
Antenna gain:	2.7dBi
Power supply:	DC 3.7V from battery DC 5V from adapter

Note:

- 1.For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.The EUT's all information provided by client.



2. Channel List

Channel List for 802.11a/n(HT20)/ac(HT20)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
40	5200	48	5240

Channel List for 802.11n(HT40)/ac(HT40)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	46	5230

Channel List for 802.11ac(HT80)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	/	/

2.2. DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Description		
Pretest Mode	Channel	Band 1
Mode 1	802.11a/n/acHT20	CH36, CH44, CH48
Mode 2	802.11n/acHT40	CH38, CH46
Mode 3	802.11acHT80	CH42


For Radiated Emission		
Pretest Mode	Channel	Band 1
Mode 1	802.11a/n/acHT20	CH36, CH44, CH48
Mode 2	802.11n/acHT40	CH38, CH46
Mode 3	802.11acHT80	CH42

Note: 1. The measurements are performed at the highest, middle, lowest available channels.
2. During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.




2.3. BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Power line conducted emission Test



2.4. DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	Wireless Selfie Monitor Screen	THT-X6	N/A	EUT
E-2	Adapter	HW-0501000E	N/A	Adapter (Provide by test lab): Manufacturer: HAIWEI Model: HW-0501000E I/P: AC 100-240V 50/60Hz O/P: DC 5V 1A

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5. TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Max output power Setting				
Test software Version	Test program: rtwpriv_tool			
Mode	802.11a	802.11n HT20	802.11n HT40	802.11ac HT20/HT40/HT80
Data Rate	6Mbps	MSC0	MSC0	MSC0
Power Setting of Software	60	60	66	66



2.6. EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 01, 2024	Oct. 31, 2025
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 01, 2024	Oct. 31, 2025
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 01, 2024	Oct. 31, 2025
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 01, 2024	Oct. 31, 2025
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 01, 2024	Oct. 31, 2025
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 01, 2024	Oct. 31, 2025
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 01, 2024	Oct. 31, 2025
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 01, 2024	Oct. 31, 2025
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 01, 2024	Oct. 31, 2025
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 01, 2024	Oct. 31, 2025
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 01, 2024	Oct. 31, 2025
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 01, 2024	Oct. 31, 2025
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 01, 2024	Oct. 31, 2025
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 01, 2024	Oct. 31, 2025
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 01, 2024	Oct. 31, 2025
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 01, 2024	Oct. 31, 2025

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Nov. 05, 2023	Nov. 04, 2026
2	EMI Receiver	R&S	ESR	101421	Nov. 01, 2024	Oct. 31, 2025
3	LISN	R&S	ENV216	102417	Nov. 01, 2024	Oct. 31, 2025
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 01, 2024	Oct. 31, 2025

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMCC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMCC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



3.. EMC EMISSION TEST

3.1. CONDUCTED EMISSION MEASUREMENT

3.1.1. POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.5 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2. TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3. DEVIATION FROM TEST STANDARD

No deviation

3.1.4. TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5. EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

3.1.6. TEST RESULTS



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 3




Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2220	21.21	10.12	31.33	62.74	-31.41	QP	P	
2	0.2220	9.81	10.12	19.93	52.74	-32.81	AVG	P	
3 *	0.6134	22.03	10.13	32.16	56.00	-23.84	QP	P	
4	0.6134	9.81	10.13	19.94	46.00	-26.06	AVG	P	
5	1.6395	10.56	10.06	20.62	56.00	-35.38	QP	P	
6	1.6395	0.17	10.06	10.23	46.00	-35.77	AVG	P	
7	6.9855	12.53	10.78	23.31	60.00	-36.69	QP	P	
8	6.9855	-1.30	10.78	9.48	50.00	-40.52	AVG	P	
9	14.3295	13.25	11.61	24.86	60.00	-35.14	QP	P	
10	14.3295	1.42	11.61	13.03	50.00	-36.97	AVG	P	
11	27.4425	9.85	13.04	22.89	60.00	-37.11	QP	P	
12	27.4425	-3.29	13.04	9.75	50.00	-40.25	AVG	P	



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 3



Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2220	21.44	10.18	31.62	62.74	-31.12	QP	P	
2	0.2220	7.93	10.18	18.11	52.74	-34.63	AVG	P	
3 *	0.6134	19.57	10.16	29.73	56.00	-26.27	QP	P	
4	0.6134	8.04	10.16	18.20	46.00	-27.80	AVG	P	
5	1.4415	12.96	10.08	23.04	56.00	-32.96	QP	P	
6	1.4415	0.23	10.08	10.31	46.00	-35.69	AVG	P	
7	4.9785	11.72	10.32	22.04	56.00	-33.96	QP	P	
8	4.9785	0.05	10.32	10.37	46.00	-35.63	AVG	P	
9	12.6870	16.10	11.41	27.51	60.00	-32.49	QP	P	
10	12.6870	4.13	11.41	15.54	50.00	-34.46	AVG	P	
11	25.2825	11.19	12.58	23.77	60.00	-36.23	QP	P	
12	25.2825	-3.97	12.58	8.61	50.00	-41.39	AVG	P	

**3.2. RADIATED EMISSION MEASUREMENT****3.2.1. RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)**

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

The provisions of §15.205 apply to intentional radiators operating under this section, 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) Measurement was performed at an antenna to the closed point of EUT distance of meters.
- (5) Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of 15.205, and the emissions located in restricted bands also comply with 15.209 limit.



Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2. TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change from table 0.8 metre to 1.5 metre.
- Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


3.2.3. DEVIATION FROM TEST STANDARD

No deviation




3.2.4. TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5. EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6. TEST RESULTS (Between 9KHz – 30 MHz)**

Temperature:	20℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 3	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

**3.2.7. TEST RESULTS (Between 30MHz – 1GHz)**

Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz		
Test Mode :	Mode 3		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1	*	958.7943	33.17	-0.12	33.05	46.00	-12.95	QP
2		595.1329	36.95	-5.44	31.51	46.00	-14.49	QP
3		404.6665	41.45	-9.44	32.01	46.00	-13.99	QP
4		297.2241	38.95	-11.87	27.08	46.00	-18.92	QP
5		189.0743	42.64	-15.44	27.20	43.50	-16.30	QP
6		101.2885	27.91	-14.80	13.11	43.50	-30.39	QP


Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;



Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
test voltage :	AC 120V/60Hz		
Test Mode :	Mode 3		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	622.8900	38.13	-5.01	33.12	46.00	-12.88	QP
2		459.1144	36.36	-8.19	28.17	46.00	-17.83	QP
3		334.8589	31.93	-11.20	20.73	46.00	-25.27	QP
4		189.0743	43.12	-15.44	27.68	43.50	-15.82	QP
5		135.0319	37.04	-18.13	18.91	43.50	-24.59	QP
6		49.3594	28.11	-12.89	15.22	40.00	-24.78	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;

**3.2.8. TEST RESULTS (1ghz~40ghZ)**

802.11a band 1

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5180									
V	10360	56.68	49.05	15.3	37.39	60.32	68.2	-7.88	PK
V	10360	41.82	49.05	15.3	37.39	45.46	54	-8.54	AV
V	15540	52.18	49.16	15.27	40.45	58.74	74	-15.26	PK
V	15540	39.63	49.16	15.27	40.45	46.19	54	-7.81	AV
H	10360	56.14	49.05	15.3	37.39	59.78	68.2	-8.42	PK
H	10360	40.96	49.05	15.3	37.39	44.6	54	-9.40	AV
H	15540	51.42	49.16	15.27	40.45	57.98	74	-16.02	PK
H	15540	38.85	49.16	15.27	40.45	45.41	54	-8.59	AV
operation frequency:5200									
V	10400	57.63	49.09	15.34	37.42	61.3	68.2	-6.90	PK
V	10400	39.21	49.09	15.34	37.42	42.88	54	-11.12	AV
V	15600	52.88	49.18	15.29	40.47	59.46	74	-14.54	PK
V	15600	38.61	49.18	15.29	40.47	45.19	54	-8.81	AV
H	10400	56.56	49.09	15.34	37.42	60.23	68.2	-7.97	PK
H	10400	39.85	49.09	15.34	37.42	43.52	54	-10.48	AV
H	15600	53.12	49.18	15.29	40.47	59.7	74	-14.30	PK
H	15600	38.79	49.18	15.29	40.47	45.37	54	-8.63	AV
operation frequency:5240									
V	10480	58.21	49.11	15.37	37.46	61.93	68.2	-6.27	PK
V	10480	39.66	49.11	15.37	37.46	43.38	54	-10.62	AV
V	15720	53.52	49.21	15.34	40.51	60.16	74	-13.84	PK
V	15720	38.37	49.21	15.34	40.51	45.01	54	-8.99	AV
H	10480	57.56	49.11	15.37	31.31	55.13	68.2	-13.07	PK
H	10480	45.65	49.11	15.37	31.31	43.22	54	-10.78	AV
H	15720	54.86	49.21	15.34	40.51	61.5	74	-12.50	PK
H	15720	37.21	49.21	15.34	40.51	43.85	54	-10.15	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	10360	56.63	49.05	15.3	37.39	60.27	68.2	-7.93	PK
V	10360	38.14	49.05	15.3	37.39	41.78	54	-12.22	AV
V	15540	52.56	49.16	15.27	40.45	59.12	74	-14.88	PK
V	15540	38.58	49.16	15.27	40.45	45.14	54	-8.86	AV
H	10360	56.69	49.05	15.3	37.39	60.33	68.2	-7.87	PK
H	10360	39.92	49.05	15.3	37.39	43.56	54	-10.44	AV
H	15540	51.38	49.16	15.27	40.45	57.94	74	-16.06	PK
H	15540	38.23	49.16	15.27	40.45	44.79	54	-9.21	AV
operation frequency:5200									
V	10400	56.24	49.09	15.34	37.42	59.91	68.2	-8.29	PK
V	10400	39.63	49.09	15.34	37.42	43.3	54	-10.70	AV
V	15600	52.88	49.18	15.29	40.47	59.46	74	-14.54	PK
V	15600	38.94	49.18	15.29	40.47	45.52	54	-8.48	AV
H	10400	55.33	49.09	15.34	37.42	59	68.2	-9.20	PK
H	10400	40.54	49.09	15.34	37.42	44.21	54	-9.79	AV
H	15600	53.46	49.18	15.29	40.47	60.04	74	-13.96	PK
H	15600	39.88	49.18	15.29	40.47	46.46	54	-7.54	AV
operation frequency:5240									
V	10480	57.21	49.11	15.37	37.46	60.93	68.2	-7.27	PK
V	10480	40.63	49.11	15.37	37.46	44.35	54	-9.65	AV
V	15720	52.87	49.21	15.34	40.51	59.51	74	-14.49	PK
V	15720	38.25	49.21	15.34	40.51	44.89	54	-9.11	AV
H	10480	57.58	49.11	15.37	31.31	55.15	68.2	-13.05	PK
H	10480	44.86	49.11	15.37	31.31	42.43	54	-11.57	AV
H	15720	51.94	49.21	15.34	40.51	58.58	74	-15.42	PK
H	15720	39.58	49.21	15.34	40.51	46.22	54	-7.78	AV
Remark:									
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit									
2. If peak below the average limit, the average emission was no test.									
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5190									
V	10380	56.52	49.07	15.33	37.41	60.19	68.2	-8.01	PK
V	10380	39.66	49.07	15.33	37.41	43.33	54	-10.67	AV
V	15570	52.85	49.17	15.28	40.46	59.42	74	-14.58	PK
V	15570	38.32	49.17	15.28	40.46	44.89	54	-9.11	AV
H	10380	56.24	49.07	15.33	37.41	59.91	68.2	-8.29	PK
H	10380	40.86	49.07	15.33	37.41	44.53	54	-9.47	AV
H	15570	52.85	49.17	15.28	40.46	59.42	74	-14.58	PK
H	15570	38.55	49.17	15.28	40.46	45.12	54	-8.88	AV
operation frequency:5230									
V	10460	57.16	49.11	15.37	37.46	60.88	68.2	-7.32	PK
V	10460	39.68	49.11	15.37	37.46	43.4	54	-10.60	AV
V	15690	52.25	49.21	15.34	40.51	58.89	74	-15.11	PK
V	15690	38.64	49.21	15.34	40.51	45.28	54	-8.72	AV
H	10460	57.38	49.11	15.37	31.31	54.95	68.2	-13.25	PK
H	10460	44.53	49.11	15.37	31.31	42.1	54	-11.90	AV
H	15690	52.64	49.21	15.34	40.51	59.28	74	-14.72	PK
H	15690	39.29	49.21	15.34	40.51	45.93	54	-8.07	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11ac HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5180									
V	10360	56.64	49.05	15.3	37.39	60.28	68.2	-7.92	PK
V	10360	39.25	49.05	15.3	37.39	42.89	54	-11.11	AV
V	15540	51.36	49.16	15.27	40.45	57.92	74	-16.08	PK
V	15540	38.21	49.16	15.27	40.45	44.77	54	-9.23	AV
H	10360	56.85	49.05	15.3	37.39	60.49	68.2	-7.71	PK
H	10360	38.16	49.05	15.3	37.39	41.8	54	-12.20	AV
H	15540	52.14	49.16	15.27	40.45	58.7	74	-15.30	PK
H	15540	39.83	49.16	15.27	40.45	46.39	54	-7.61	AV
operation frequency:5200									
V	10400	56.68	49.09	15.34	37.42	60.35	68.2	-7.85	PK
V	10400	41.41	49.09	15.34	37.42	45.08	54	-8.92	AV
V	15600	52.26	49.18	15.29	40.47	58.84	74	-15.16	PK
V	15600	40.52	49.18	15.29	40.47	47.1	54	-6.90	AV
H	10400	55.76	49.09	15.34	37.42	59.43	68.2	-8.77	PK
H	10400	40.21	49.09	15.34	37.42	43.88	54	-10.12	AV
H	15600	53.66	49.18	15.29	40.47	60.24	74	-13.76	PK
H	15600	41.57	49.18	15.29	40.47	48.15	54	-5.85	AV
operation frequency:5240									
V	10480	57.21	49.11	15.37	37.46	60.93	68.2	-7.27	PK
V	10480	40.63	49.11	15.37	37.46	44.35	54	-9.65	AV
V	15720	51.47	49.21	15.34	40.51	58.11	74	-15.89	PK
V	15720	39.52	49.21	15.34	40.51	46.16	54	-7.84	AV
H	10480	57.23	49.11	15.37	31.31	54.8	68.2	-13.40	PK
H	10480	44.34	49.11	15.37	31.31	41.91	54	-12.09	AV
H	15720	52.45	49.21	15.34	40.51	59.09	74	-14.91	PK
H	15720	40.21	49.21	15.34	40.51	46.85	54	-7.15	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11ac 40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5190									
V	10380	56.26	49.07	15.33	37.41	59.93	68.2	-8.27	PK
V	10380	40.27	49.07	15.33	37.41	43.94	54	-10.06	AV
V	15570	52.75	49.17	15.28	40.46	59.32	74	-14.68	PK
V	15570	39.43	49.17	15.28	40.46	46	54	-8.00	AV
H	10380	56.24	49.07	15.33	37.41	59.91	68.2	-8.29	PK
H	10380	40.52	49.07	15.33	37.41	44.19	54	-9.81	AV
H	15570	51.31	49.17	15.28	40.46	57.88	74	-16.12	PK
H	15570	39.62	49.17	15.28	40.46	46.19	54	-7.81	AV
operation frequency:5230									
V	10460	57.52	49.11	15.37	37.46	61.24	68.2	-6.96	PK
V	10460	41.58	49.11	15.37	37.46	45.3	54	-8.70	AV
V	15690	52.21	49.21	15.34	40.51	58.85	74	-15.15	PK
V	15690	39.83	49.21	15.34	40.51	46.47	54	-7.53	AV
H	10460	57.98	49.11	15.37	31.31	55.55	68.2	-12.65	PK
H	10460	44.75	49.11	15.37	31.31	42.32	54	-11.68	AV
H	15690	52.14	49.21	15.34	40.51	58.78	74	-15.22	PK
H	15690	40.73	49.21	15.34	40.51	47.37	54	-6.63	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ac HT80

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5210									
V	10420	56.21	49.07	15.33	37.41	59.88	68.2	-8.32	PK
V	10420	41.63	49.07	15.33	37.41	45.3	54	-8.70	AV
V	15630	51.52	49.17	15.28	40.46	58.09	74	-15.91	PK
V	15630	39.68	49.17	15.28	40.46	46.25	54	-7.75	AV
H	10420	56.14	49.07	15.33	37.41	59.81	68.2	-8.39	PK
H	10420	41.63	49.07	15.33	37.41	45.3	54	-8.70	AV
H	15630	52.85	49.17	15.28	40.46	59.42	74	-14.58	PK
H	15630	40.77	49.17	15.28	40.46	47.34	54	-6.66	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

**3.3 RADIATED BAND EMISSION MEASUREMENT****3.3.1 TEST REQUIREMENT:**

15.407 (b)

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

The provisions of §15.205 apply to intentional radiators operating under this section, 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	5000MHz
Stop Frequency	5420MHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average



3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.3.6 TEST RESULT**

802.11a

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	5150	53.68	49.12	15.6	37.34	57.5	74	-16.5	PK
V	5150	39.41	49.12	15.6	37.34	43.23	54	-10.77	AV
V	5145	54.36	49.19	15.24	40.43	60.84	74	-13.16	PK
V	5145	36.14	49.19	15.24	40.43	42.62	54	-11.38	AV
H	5150	52.53	49.12	15.6	37.34	56.35	74	-17.65	PK
H	5150	37.58	49.12	15.6	37.34	41.4	54	-12.6	AV
H	5145	54.52	49.19	15.24	40.43	61	74	-13	PK
H	5145	33.61	49.19	15.24	40.43	40.09	54	-13.91	AV
operation frequency:5240									
V	5350	53.36	49.13	15.32	37.46	57.01	74	-16.99	PK
V	5350	35.48	49.13	15.32	37.46	39.13	54	-14.87	AV
V	5370	53.52	49.24	15.36	40.51	60.15	74	-13.85	PK
V	5370	32.84	49.24	15.36	40.51	39.47	54	-14.53	AV
H	5350	52.21	49.13	15.32	31.31	49.71	74	-24.29	PK
H	5350	40.36	49.13	15.32	31.31	37.86	54	-16.14	AV
H	5370	52.28	49.24	15.36	40.51	58.91	74	-15.09	PK
H	5370	32.35	49.24	15.36	40.51	38.98	54	-15.02	AV
Remark:									
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit									
2. If peak below the average limit, the average emission was no test.									
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	5150	51.41	49.12	15.6	37.34	55.23	74	-18.77	PK
V	5150	33.23	49.12	15.6	37.34	37.05	54	-16.95	AV
V	5145	51.58	49.19	15.24	40.43	58.06	74	-15.94	PK
V	5145	33.21	49.19	15.24	40.43	39.69	54	-14.31	AV
H	5150	51.89	49.12	15.6	37.34	55.71	74	-18.29	PK
H	5150	33.52	49.12	15.6	37.34	37.34	54	-16.66	AV
H	5145	50.51	49.19	15.24	40.43	56.99	74	-17.01	PK
H	5145	32.63	49.19	15.24	40.43	39.11	54	-14.89	AV
operation frequency:5240									
V	5350	53.52	49.13	15.32	37.46	57.17	74	-16.83	PK
V	5350	34.31	49.13	15.32	37.46	37.96	54	-16.04	AV
V	5370	50.88	49.24	15.36	40.51	57.51	74	-16.49	PK
V	5370	33.63	49.24	15.36	40.51	40.26	54	-13.74	AV
H	5350	54.52	49.13	15.32	31.31	52.02	74	-21.98	PK
H	5350	36.21	49.13	15.32	31.31	33.71	54	-20.29	AV
H	5370	51.66	49.24	15.36	40.51	58.29	74	-15.71	PK
H	5370	33.85	49.24	15.36	40.51	40.48	54	-13.52	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11ac HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5180									
V	5150	52.21	49.12	15.33	37.41	55.83	74	-18.17	PK
V	5150	34.63	49.12	15.33	37.41	38.25	54	-15.75	AV
V	5145	51.84	49.19	15.28	40.46	58.39	74	-15.61	PK
V	5145	33.21	49.19	15.28	40.46	39.76	54	-14.24	AV
H	5150	52.85	49.12	15.33	37.41	56.47	74	-17.53	PK
H	5150	34.63	49.12	15.33	37.41	38.25	54	-15.75	AV
H	5145	50.52	49.19	15.28	40.46	57.07	74	-16.93	PK
H	5145	33.41	49.19	15.28	40.46	39.96	54	-14.04	AV
operation frequency:5240									
V	5350	53.21	49.13	15.32	37.46	56.86	74	-17.14	PK
V	5350	36.16	49.13	15.32	37.46	39.81	54	-14.19	AV
V	5370	50.85	49.24	15.36	40.51	57.48	74	-16.52	PK
V	5370	33.65	49.24	15.36	40.51	40.28	54	-13.72	AV
H	5350	53.82	49.13	15.32	31.31	51.32	74	-22.68	PK
H	5350	40.58	49.13	15.32	31.31	38.08	54	-15.92	AV
H	5370	51.36	49.24	15.36	40.51	57.99	74	-16.01	PK
H	5370	35.57	49.24	15.36	40.51	42.2	54	-11.8	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5190									
V	5150	52.63	49.12	15.6	37.39	56.5	74	-17.5	PK
V	5150	35.52	49.12	15.6	37.39	39.39	54	-14.61	AV
V	5145	51.48	49.19	15.24	40.45	57.98	74	-16.02	PK
V	5145	34.54	49.19	15.24	40.45	41.04	54	-12.96	AV
H	5150	52.85	49.12	15.6	37.39	56.72	74	-17.28	PK
H	5150	34.83	49.12	15.6	37.39	38.7	54	-15.3	AV
H	5145	50.52	49.19	15.24	40.45	57.02	74	-16.98	PK
H	5145	35.21	49.19	15.24	40.45	41.71	54	-12.29	AV
operation frequency:5230									
V	5350	53.63	49.13	15.34	37.46	57.3	74	-16.7	PK
V	5350	37.38	49.13	15.34	37.46	41.05	54	-12.95	AV
V	5370	50.24	49.24	15.35	40.51	56.86	74	-17.14	PK
V	5370	36.63	49.24	15.35	40.51	43.25	54	-10.75	AV
H	5350	54.18	49.13	15.34	31.31	51.7	74	-22.3	PK
H	5350	41.51	49.13	15.34	31.31	39.03	54	-14.97	AV
H	5370	52.21	49.24	15.35	40.51	58.83	74	-15.17	PK
H	5370	36.28	49.24	15.35	40.51	42.9	54	-11.1	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11ac HT40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5190									
V	5150	52.36	49.12	15.32	37.41	55.97	74	-18.03	PK
V	5150	37.41	49.12	15.32	37.41	41.02	54	-12.98	AV
V	5145	52.25	49.19	15.36	40.46	58.88	74	-15.12	PK
V	5145	36.33	49.19	15.36	40.46	42.96	54	-11.04	AV
H	5150	52.81	49.12	15.32	37.41	56.42	74	-17.58	PK
H	5150	37.85	49.12	15.32	37.41	41.46	54	-12.54	AV
H	5145	51.63	49.19	15.36	40.46	58.26	74	-15.74	PK
H	5145	36.34	49.19	15.36	40.46	42.97	54	-11.03	AV
operation frequency:5230									
V	5350	54.61	49.13	15.34	37.34	58.16	74	-15.84	PK
V	5350	36.29	49.13	15.34	37.34	39.84	54	-14.16	AV
V	5370	51.52	49.24	15.35	40.43	58.06	74	-15.94	PK
V	5370	36.71	49.24	15.35	40.43	43.25	54	-10.75	AV
H	5350	54.59	49.13	15.34	37.34	58.14	74	-15.86	PK
H	5350	41.45	49.13	15.34	37.34	45	54	-9	AV
H	5370	50.66	49.24	15.35	40.43	57.2	74	-16.8	PK
H	5370	35.21	49.24	15.35	40.43	41.75	54	-12.25	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11ac HT80

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5210									
V	5150	52.69	49.13	15.32	37.48	56.36	74	-17.64	PK
V	5150	35.61	49.13	15.32	37.48	39.28	54	-14.72	AV
V	5145	51.63	49.24	15.36	40.42	58.17	74	-15.83	PK
V	5145	35.85	49.24	15.36	40.42	42.39	54	-11.61	AV
H	5150	52.64	49.13	15.32	37.48	56.31	74	-17.69	PK
H	5150	36.68	49.13	15.32	37.48	40.35	54	-13.65	AV
H	5145	50.36	49.24	15.36	40.42	56.9	74	-17.1	PK
H	5145	35.21	49.24	15.36	40.42	41.75	54	-12.25	AV
V	5350	52.25	49.13	15.32	37.48	55.92	74	-18.08	PK
V	5350	35.99	49.13	15.32	37.48	39.66	54	-14.34	AV
V	5370	51.21	49.24	15.36	40.42	57.75	74	-16.25	PK
V	5370	35.83	49.24	15.36	40.42	42.37	54	-11.63	AV
H	5350	52.85	49.13	15.32	37.48	56.52	74	-17.48	PK
H	5350	36.14	49.13	15.32	37.48	39.81	54	-14.19	AV
H	5370	50.33	49.24	15.36	40.42	56.87	74	-17.13	PK
H	5370	35.85	49.24	15.36	40.42	42.39	54	-11.61	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



4.. AVERAGE OUTPUT POWER

4.1. APPLIED PROCEDURES / LIMIT

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.

4.1.1. TEST PROCEDURE

Method SA-2 uses trace averaging across ON and OFF times of the EUT transmissions, followed by duty cycle correction. The procedure for this method is as follows:

- a) Measure the duty cycle D of the transmitter output signal as described in 12.2.
- b) Set span to encompass the entire 26 dB EBW or 99% OBW of the signal.
- c) Set RBW=1 MHz.
- d) Set VBW $\geq$ 3 MHz.
- e) Number of points in sweep $\geq$ $[2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq$ RBW / 2, so that narrowband signals are not lost between frequency bins.)
- f) Sweep time = auto.
- g) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- h) Do not use sweep triggering. Allow the sweep to "free run."
- i) Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.
- j) Compute power by integrating the spectrum across the 26 dB EBW or 99% OBW of the signal using the instrument's band power measurement function with band limits set equal to the EBW or OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at 1MHz intervals extending across the 26 dB EBW or 99% OBW of the spectrum.
- k) Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and off times of the transmission). For example, add $[10 \log (1 / 0.25)] = 6 \text{ dB}$ if the duty cycle is 25%.

4.1.2. DEVIATION FROM STANDARD

No deviation.

4.1.3. TEST SETUP



4.1.4. EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


**4.1.5. TEST RESULTS**

Temperature:	25 °C	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	AC 120V/60Hz


Band	Mode	Test Channel	Average Output Power (dBm)	Duty factor (dB)	Total Output Power(dB)	LIMIT (dBm)
Band 1	802.11a	Low	4.686	1.06	5.746	23.98
		Middle	4.232	1.12	5.352	23.98
		High	5.129	0.87	5.999	23.98
	802.11ac HT20	Low	3.35	0.16	3.51	23.98
		Middle	2.872	0.13	3.002	23.98
		High	3.885	0.13	4.015	23.98
	802.11ac HT40	Low	4.073	0.26	4.333	23.98
		High	3.899	0.26	4.159	23.98
	802.11ac HT80	/	4.214	0.5	4.714	23.98
	802.11n HT20	Low	4.837	0.13	4.967	23.98
		Middle	3.946	0.16	4.106	23.98
		High	2.887	0.13	3.017	23.98
	802.11n HT40	Low	4.018	0.26	4.278	23.98
		High	3.882	0.26	4.142	23.98




802.11a




802.11ac HT20




5180MHz




5180MHz



5200MHz



5200MHz




5240MHz


5240MHz




802.11ac HT40




802.11n HT20




5190MHz



5180MHz



5230MHz




5200MHz


5240MHz




802.11n HT40



802.11ac HT80



5190MHz



5210MHz

5230MHz



5.. POWER SPECTRAL DENSITY TEST

5.1. APPLIED PROCEDURES / LIMIT

In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW $\geq$ 1MHz for band 1 RBW $\geq$ 510KHz for band 4
VB	VBW $\geq$ 3RBW
Detector	RMS (i.e., power averaging).
Trace	Max Hold
Sweep Time	Auto

5.1.1. TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. The testing follows FCC KDB 789033 D02.
3. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to Spectrum.
4. For U-NII1, U-NII-2A, U-NII-2C Band:
Set RBW=1MHz, VBW=3MHz, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
For U-NII-3 Band:
Set RBW=510 kHz, VBW=3*RBW, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
5. Use the cursor on spectrum to peak search the highest level of trace
6. Record the max. reading and add $10 \log(1/\text{duty cycle})$.
we test all antennas, the antenna 1 was worst mode and the data recording in the report.
7. Duty factor Reference is made to the test results in Section 7.1.5.

Method SA-2 uses trace averaging across ON and OFF times of the EUT transmissions, followed by duty cycle correction. The procedure for this method is as follows:

- a) Measure the duty cycle D of the transmitter output signal as described in 12.2.
- b) Set span to encompass the entire 26 dB EBW or 99% OBW of the signal.
- c) Set RBW=1 MHz.
- d) Set VBW $\geq$ 3 MHz.
- e) Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- f) Sweep time = auto.
- g) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- h) Do not use sweep triggering. Allow the sweep to "free run."
- i) Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.
- j. Use the peak search function on the instrument to find the peak of the spectrum.
- k. Make the following adjustments to the peak value of the spectrum, if applicable:
 - 1) If method SA-2 or SA-2A was used, then add $[10 \log (1 / D)]$, where D is the duty cycle, to the peak of the spectrum.
 - 2) If method SA-3A was used and the linear mode was used in step h) of 12.3.2.7, add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
- l. The result is the PPSD.



5.1.2. DEVIATION FROM STANDARD

No deviation.

5.1.3. TEST SETUP



5.1.4. EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5. TEST RESULTS

	Mode	Test Channel	Reading Level (dBm)	Duty factor (dB)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
Band1	802.11a	Low	-4.578	1.06	-3.518	11.00	PASS
		Middle	-5.351	1.12	-4.231	11.00	PASS
		High	-4.016	0.87	-3.146	11.00	PASS
	802.11ac20	Low	-6.667	0.16	-6.507	11.00	PASS
		Middle	-7.255	0.13	-7.125	11.00	PASS
		High	-5.716	0.13	-5.586	11.00	PASS
	802.11ac40	Low	-8.156	0.26	-7.896	11.00	PASS
		High	-8.687	0.26	-8.427	11.00	PASS
	802.11ac80	/	-11.466	0.5	-10.966	11.00	PASS
	802.11n20	Low	-5.136	0.13	-5.006	11.00	PASS
		Middle	-6.011	0.16	-5.851	11.00	PASS
		High	-6.575	0.13	-6.445	11.00	PASS
	802.11n40	Low	-8.145	0.26	-7.885	11.00	PASS
		High	-8.683	0.26	-8.423	11.00	PASS