



[TestMode: TX]; [Polarity: Vertical]


Test Result: Pass

Above 1GHz:

[TestMode: TX low channel]; [Polarity: Horizontal]




Site	Polarization: Horizontal	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: Sound amplifier		
M/N: diacovsky CR430S B+		
Mode: BLE TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over				
							dBuV	dB	dBuV/m	dB	Detector
1		4804.000	39.72	4.51	44.23	74.00	-29.77		peak		
2		7206.000	38.73	7.41	46.14	74.00	-27.86		peak		
3		9608.000	38.10	11.59	49.69	74.00	-24.31		peak		
4	*	11328.25	39.00	13.39	52.39	74.00	-21.61		peak		
5		7862.000	40.74	8.70	49.44	74.00	-24.56		peak		
6		5864.500	39.77	6.62	46.39	74.00	-27.61		peak		

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]




Site: Polarization: **Vertical** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Sound amplifier
M/N: diacovsky CR430S B+
Mode: BLE TX-L
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over					
							MHz	dBuV	dB	dBuV/m	dB	Detector
1		4804.000	38.90	4.51	43.41	74.00	-30.59			peak		
2		5899.750	39.76	6.75	46.51	74.00	-27.49			peak		
3		7206.000	38.24	7.41	45.65	74.00	-28.35			peak		
4		8226.250	40.43	8.56	48.99	74.00	-25.01			peak		
5		9608.000	37.50	11.59	49.09	74.00	-24.91			peak		
6	*	10717.25	39.06	13.32	52.38	74.00	-21.62			peak		

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Horizontal]



Site

Polarization: **Horizontal**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Sound amplifier

M/N: diacovery CR430S B+


Mode: BLE TX-M

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dB			
1	4884.000	39.99	4.62	44.61	74.00	-29.39	peak		
2	5852.750	40.19	6.58	46.77	74.00	-27.23	peak		
3	7326.000	38.27	7.82	46.09	74.00	-27.91	peak		
4	8038.250	40.52	8.62	49.14	74.00	-24.86	peak		
5	9768.000	36.79	11.77	48.56	74.00	-25.44	peak		
6 *	11328.25	39.15	13.39	52.54	74.00	-21.46	peak		

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Vertical]




Site	Polarization: Vertical	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: Sound amplifier		
M/N: diacovsky CR430S B+		
Mode: BLE TX-M		
Note:		

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment		Detector	Comment
1		4884.000	39.33	4.62	43.95	74.00	-30.05	peak
2		5911.500	39.40	6.75	46.15	74.00	-27.85	peak
3		7326.000	38.13	7.82	45.95	74.00	-28.05	peak
4		8672.750	39.97	9.81	49.78	74.00	-24.22	peak
5		9768.000	37.58	11.77	49.35	74.00	-24.65	peak
6	*	11387.00	38.77	13.41	52.18	74.00	-21.82	peak

Test Result: Pass

[TestMode: TX High channel]; [Polarity: Horizontal]




Site: Limit: FCC Part15 (PK) Polarization: **Horizontal** Temperature: (C)
EUT: Sound amplifier Power: Humidity: %RH
M/N: diacovsky CR430S B+
Mode: BLE TX-H
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over							
							MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	38.64	5.47	44.11	74.00	-29.89			peak				
2		5899.750	39.27	6.75	46.02	74.00	-27.98			peak				
3		7440.000	38.35	8.24	46.59	74.00	-27.41			peak				
4		8696.250	40.01	9.87	49.88	74.00	-24.12			peak				
5		9920.000	36.21	11.96	48.17	74.00	-25.83			peak				
6	*	11375.25	39.20	13.40	52.60	74.00	-21.40			peak				

Test Result: Pass

[TestMode: TX High channel]; [Polarity: Vertical]



Site: Limit: FCC Part15 (PK) EUT: Sound amplifier M/N: diacovsky CR430S B+ Mode: BLE TX-H Note: Polarization: **Vertical** Power: Temperature: (C) Humidity: %RH

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment		Detector	Comment
1		4960.000	38.96	5.47	44.43	74.00	-29.57	peak
2		5899.750	39.65	6.75	46.40	74.00	-27.60	peak
3		7440.000	39.53	8.24	47.77	74.00	-26.23	peak
4		8719.750	39.97	9.91	49.88	74.00	-24.12	peak
5		9920.000	36.23	11.96	48.19	74.00	-25.81	peak
6	*	11375.25	39.05	13.40	52.45	74.00	-21.55	peak

Test Result: Pass

13 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


13.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.7dBi.



14 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Charlie
Temperature	25 °C
Humidity	60%

14.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

14.2 BLOCK DIAGRAM OF TEST SETUP



14.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

14.4 TEST DATA

[TestMode: TX low channel]; [Polarity: Horizontal]


Radiated Emission Measurement

Project No.: RE

Data #:11

2023/6/26

107.0 dBuV/m



Site

Polarization: **Horizontal**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Sound amplifier

M/N: diacovery CR430S B+

Mode: BLE TX-L

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2310.000	42.69	-4.40	38.29	74.00	-35.71	peak	
2	*	2390.000	43.14	-4.31	38.83	74.00	-35.17	peak	

Test Result: Pass

[TestMode:TX low channel]; [Polarity: Vertical]


Radiated Emission Measurement

Project No.: RE

Data :#12

2023/6/26

107.0 dBuV/m



Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Sound amplifier

M/N: diacovery CR430S B+

Mode: BLE TX-L

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	2310.000	42.89	-4.40	38.49	74.00	-35.51	peak	
2		2390.000	42.65	-4.31	38.34	74.00	-35.66	peak	

Test Result: Pass


[TestMode: TX High channel]; [Polarity: Horizontal]

Radiated Emission Measurement

Project No.: RE
103.0 dBuV/m

Data :#13

2023/6/26



Site Polarization: **Horizontal** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: Sound amplifier

M/N: discovery CR430S B+

Mode: BLE TX-H

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over				
							dBuV	dB	dBuV/m	dB	Detector
1		2483.500	43.34	-4.64	38.70	74.00	-35.30		peak		
2	*	2500.000	43.84	-4.75	39.09	74.00	-34.91		peak		

Test Result: Pass


[TestMethod:TX High channel]; [Polarity: Vertical]

Radiated Emission Measurement

Project No.: RE
107.0 dBuV/m

Data :#14

2023/6/26



Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Sound amplifier

M/N: diacovery CR430S B+

Mode: BLE TX-H

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dB			
1		2483.500	43.02	-4.64	38.38	74.00	-35.62	peak	
2	*	2500.000	43.36	-4.75	38.61	74.00	-35.39	peak	

Test Result: Pass


15 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Charlie
Temperature	25 °C
Humidity	60%

15.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

15.2 BLOCK DIAGRAM OF TEST SETUP



15.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


16 POWER SPECTRUM DENSITY

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.10.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Charlie
Temperature	25 °C
Humidity	60%

16.1 LIMITS

Limit: $\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission

16.2 BLOCK DIAGRAM OF TEST SETUP



16.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details


17 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Charlie
Temperature	25 °C
Humidity	60%

17.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

17.2 BLOCK DIAGRAM OF TEST SETUP



17.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia