

You must use a Min QC 3.0 18W charger when using this product.

The USB-A charging function requires the use of a PD 30W charger.

Please do not put the metal or magnetic goods. (such as coin, bank card, key etc..) on the charging are.

When using the product, use it away from water or other liquid. (This product is not waterproof)

It generates heat during operation, so use it in a cool place.

Do not disassemble charger without authorization.

- Name of the product : Magnetic wireless charger
- MODEL NO: SMC-300
- Material: PC, ABS, silicon
- INPUT: QC 3.0 or PD30W Charger
- OUTPUT: Max 15W Wireless charger, Max 10W USB-A
- Size: 253 x 120 x 127 mm
- Weight: 500g
- Manufacture : Dongguan LUNE Technology Co., Ltd














5 - in - 1 Magnetic wireless charger & Mood Lamp



**USER'S MANUAL** 

## FCC Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1)This device may not cause harmful interference.(2)This device must accept any interference received, including interference that may cause undesired operation.

2. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide

reasonable protection against harmful interference in a residential installation.

This equipment generates uses and can radiate radio frequence energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation if this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Reorient or relocate the receiving antenna.

Increase the separation between the equipment and receiver.

- Connect the equipment into an autlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. This equipment should be installed and operated with a minumum distance of 20 cm between the radiator and your body.