



FCC TEST REPORT

FCC Part 18

FCC ID:2A7L6-R-300

Report Number.....: ZKT-220628L4387E

Date of Test..... Jun. 21, 2022 to Jul. 05, 2022

Date of issue.....: Jul. 05, 2022

Total number of pages..... 19

Test Result: PASS

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.

Address: 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name: Xiamen Irun Power Co.,Ltd

Address: Sixth of 5th Floor, Comprehensive Building, No. 326, Tongji South Road, Jimei District, Xiamen,China

Manufacturer's name: Xiamen Irun Power Co.,Ltd

Address: 5th floor of the comprehensive building,NO.326,Tongji South Road,Jimei District, Xiamen,China

Test specification:

Standard.....: FCC Part 18

Test procedure.....: /

Non-standard test method: N/A

Test Report Form No......: TRF-EL-117_V0

Test Report Form(s) Originator.... : ZKT Testing

Master TRF: Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name.....: CAR REFRIGERATOR POWER

Trademark: iRun

Model/Type reference.....: R-300

Capacity:20000mAh Voltage:14.4V

DC IN: 5V-30V/4A (Max 80W)

Type-C IN: PD3.0 5V-20V/4A (Preference for use)

USB Output: QC3.0 5V/3A 9V/2A 12V/1.5A

DC OUT: 12-16.8V/10A (Max 150W)

Wireless: QI 15W (Max 15W)

Type-C Output: PD3.0 5V-20V/4A (Max 80W)



Testing procedure and testing location:

Testing Laboratory.....: **Shenzhen ZKT Technology Co., Ltd.**

Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature).....: Alen He

Reviewer (name + signature).....: Joe Liu



Approved (name + signature).....: Lake Xie

**TABLE OF CONTENT**

	Page
1.VERSION	4
2.GENERAL INFORMATION	5
2.1 Description of Device (EUT)	5
2.2 Tested System Details	5
2.3 Test Facility	5
2.4 MEASUREMENT UNCERTAINTY	6
2.5 Test Instrument Used	7
3.CONDUCTED EMISSION AT THE MAINS TERMINALS TEST	8
3.1 Block Diagram Of Test Setup	8
3.2 Test Standard	8
3.3 Power Line Conducted Emission Limit	8
3.4 EUT Configuration on Test	8
3.5 Operating Condition of EUT	8
3.6 Test Procedure	8
3.7 Test Result	8
4.RADIATION EMISSION TEST	11
4.1 Block Diagram of Test Setup	11
4.2 Test Standard	11
4.3 Radiation Limit	11
4.4 EUT Configuration on Test	12
4.5 Operating Condition of EUT	12
4.6 Test Procedure	12
4.7 Test Result	13
5.EUT PHOTOGRAPHS	17
6.EUT TEST PHOTOGRAPHS	18



1.VERSION

Report No.	Version	Description	Approved
ZKT-220628L4387E	Rev.01	Initial issue of report	Jul. 05, 2022



2.GENERAL INFORMATION

2.1 Description of Device (EUT)

EUT	CAR REFRIGERATOR POWER
Trademark	N/A
Model Number	R-300
Model Difference	N/A
Power Supply	DC 20V/4A From PD adapter input AC 120V/60Hz for charging and DC 3.7V From Battery for Discharging.

2.2 Tested System Details

None.

2.3 Description Of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E1	CAR REFRIGERATOR POWER	N/A	R-300	N/A	EUT
E2	Mobile Phone	N/A	OPPO A96	N/A	Auxiliary
E3	PD Adapter	N/A	PD-014	N/A	Auxiliary

2.4 Test mode

Test Modes:		
Mode 1	PD Adapter + EUT + Mobile Phone	Record
Mode 2	PD Adapter+ EUT + Output	Pre-tested
Mode 3	EUT + Mobile Phone	Pre-tested
Mode 4	DC IN+ EUT+ Mobile Phone	Pre-tested
Mode 5	DC IN+ EUT+ Output	Pre-tested
Note: All test modes were pre-tested, but we only recorded the worst case in this report.		



2.5 Test Facility

Site Description

Name of Firm : Shenzhen ZKT Technology Co., Ltd.

Site Location : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225

Designation Number: CN1299

IC Registered No.: 27033

2.6 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Value (dB)
Conducted Emission (150K-30MHZ)	3.20
Radiated disturbance30MHz-1000MHz	4.80



2.7 Test Instrument Used

Conducted emissions Test

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	N/A	Sep. 22, 2021	Sep. 21, 2022
2	LISN	CYBERTEK	EM5040A	N/A	Sep. 22, 2021	Sep. 21, 2022
3	Test Cable	N/A	C01	N/A	Sep. 22, 2021	Sep. 21, 2022
4	Test Cable	N/A	C02	N/A	Sep. 22, 2021	Sep. 21, 2022
5	EMI Test Receiver	R&S	ESCI3	101421	Sep. 22, 2021	Sep. 21, 2022
6	Triple-Loop Antenna	LAPLACE	RF300	9194	Sep. 22, 2021	Sep. 21, 2022
7	Absorbing Clamp	DZ	ZN23201	N/A	Sep. 22, 2021	Sep. 21, 2022


Radiated emissions Test (966 chamber)

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Bilog Antenna	Schwarzbeck	VULB9168	N/A	Sep. 22, 2021	Sep. 21, 2022
2	Loop Antenna	SCHWARZBECK	FMZB1519B	014	Sep. 22, 2021	Sep. 21, 2022
3	Test Cable	N/A	R-01	N/A	Sep. 22, 2021	Sep. 21, 2022
4	Test Cable	N/A	R-02	N/A	Sep. 22, 2021	Sep. 21, 2022
5	EMI Test Receiver	R&S	ESCI7	101154	Sep. 22, 2021	Sep. 21, 2022
6	Antenna Mast	EM	SC100_1	N/A	N/A	
7	Turn Table	EM	SC100	N/A	N/A	
8	Spectrum Analyzer	KEYSIGHT	9020A		Sep. 22, 2021	Sep. 21, 2022
9	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	1541	Sep. 22, 2021	Sep. 21, 2022
10	Horn Antenna (18GHz-40GHz)	Schwarzbeck	BBHA9170	822	Sep. 22, 2021	Sep. 21, 2022
11	Amplifier (20-3000MHz)	EM Electronics	EZQ-LG302 1 Amplifier	N/A	Sep. 22, 2021	Sep. 21, 2022
12	Amplifier (0.5GHz-18GHz)	SCHWARZBECK	8449B	9718-309	Sep. 22, 2021	Sep. 21, 2022
13	Amplifier (18GHz-40GHz)	MITEQ	ZLNA-18-40 G-21	2034381	Sep. 22, 2021	Sep. 21, 2022



3.CONDUCTED EMISSION AT THE MAINS TERMINALS TEST

3.1 Block Diagram Of Test Setup



3.2 Test Standard

FCC PART 18

3.3 Power Line Conducted Emission Limit

Frequency		Limits dB(μ V)	
MHz		Quasi-peak Level	Average Level
0.15	~ 0.50	66 ~ 56*	56 ~ 46*
0.50	~ 5.00	56	46
5.00	~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

3.4 EUT Configuration on Test

The following equipments are installed on conducted emission test to meet FCC PART 18 requirement and operating in a manner which tends to maximize its emission characteristics in a normal application.

3.5 Operating Condition of EUT

- 3.5.1 Setup the EUT and simulators as shown in Section 3.1.
- 3.5.2 Turn on the power of all equipments.
- 3.5.3 Let the EUT work in test modes and test it.

3.6 Test Procedure

The EUT is put on the ground and connected to the AC mains through a Artificial Mains Network (AMN). This provided a 50ohm coupling impedance for the tested equipments. Both sides of AC line are checked to find out the maximum conducted emission levels according to the **FCC PART 18** regulations during conducted emission test.

The bandwidth of the test receiver (R&S Test Receiver ESCI) is set at 10KHz.
The frequency range from 150 KHz to 30 MHz is investigated.

3.7 Test Result

PASS


Please refer to the following page.

Shenzhen ZKT Technology Co., Ltd.

1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China




Conducted Emission At The Mains Terminals Test Data			
Temperature:	24.5 °C	Relative Humidity:	54%
Pressure:	1009hPa	Phase :	Line
Test Voltage :	AC 120V/60Hz	Test Mode:	charging



No.	Freq MHz	Cable Loss dB	AMN Factor dB	Receiver Reading dB μ V	Emission Level dB μ V	Limit dB μ V	Over Limit dB	Remark
1	0.158	0.22	10.02	23.40	33.64	55.56	-21.92	Average
2	0.158	0.22	10.02	34.28	44.52	65.56	-21.04	QP
3	0.242	0.32	10.20	21.81	32.33	52.04	-19.71	Average
4	0.242	0.32	10.20	30.68	41.20	62.04	-20.84	QP
5	0.318	0.38	10.32	21.22	31.92	49.75	-17.83	Average
6	0.318	0.38	10.32	30.15	40.85	59.75	-18.90	QP
7	0.398	0.40	10.41	15.52	26.33	47.90	-21.57	Average
8	0.398	0.40	10.41	24.33	35.14	57.90	-22.76	QP
9	0.479	0.42	10.49	19.40	30.31	46.36	-16.05	Average
10	0.479	0.42	10.49	29.46	40.37	56.36	-15.99	QP
11	0.555	0.43	10.55	19.97	30.95	46.00	-15.05	Average
12	0.555	0.43	10.55	30.53	41.51	56.00	-14.49	QP





Conducted Emission At The Mains Terminals Test Data			
Temperature:	24.5 °C	Relative Humidity:	54%
Pressure:	1009hPa	Phase :	Neutral
Test Voltage :	AC 120V/60Hz	Test Mode:	charging



No.	Freq MHz	Cable Loss dB	AMN Factor dB	Receiver Reading dB μ V	Emission Level dB μ V	Limit dB μ V	Over Limit dB	Remark
1	0.158	0.22	10.02	22.93	33.17	55.56	-22.39	Average
2	0.158	0.22	10.02	33.29	43.53	65.56	-22.03	QP
3	0.242	0.32	10.20	23.72	34.24	52.04	-17.80	Average
4	0.242	0.32	10.20	31.28	41.80	62.04	-20.24	QP
5	0.318	0.38	10.32	23.04	33.74	49.75	-16.01	Average
6	0.318	0.38	10.32	30.21	40.91	59.75	-18.84	QP
7	0.481	0.43	10.49	19.99	30.91	46.32	-15.41	Average
8	0.481	0.43	10.49	28.67	39.59	56.32	-16.73	QP
9	0.558	0.43	10.55	20.40	31.38	46.00	-14.62	Average
10	0.558	0.43	10.55	29.66	40.64	56.00	-15.36	QP
11	1.519	0.47	10.81	16.75	28.03	46.00	-17.97	Average
12	1.519	0.47	10.81	26.43	37.71	56.00	-18.29	QP

4. RADIATION EMISSION TEST

4.1 Block Diagram of Test Setup



4.2 Test Standard

FCC PART 18

4.3 Radiation Limit

Limits for frequency below 30MHz

Except as provided elsewhere in this Subpart 18.305 (b), the field strength levels of emissions which lie outside the bands specified in § 18.301, unless otherwise indicated, shall not exceed the following table:

Frequency MHz	Distance Meters	Field Strengths Limit	
		dB μ V/m	Remark
0.009~30MHz	3	103.5	Quasi-peak



Remark: (1) Emission level dB V/m for 0.009~30MHz = 20log (15) + 40log (300/3) dB V/m; (2) Calculated according FCC 18.305. (3) The smaller limit shall apply at the cross point between two frequency bands. (4) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Limits for frequency Above 30MHz

FREQUENCY (MHz)	DISTANCE (Meters)	FIELD STRENGTHS LIMITS (dB μ V/m)
30 ~ 1000	3	63.5

(1) Emission level dB V/m for above 30MHz = 20log (15) + 20log (300/3) dB V/m

4.4 EUT Configuration on Test

The FCC PART 18 regulations test method must be used to find the maximum emission during radiated emission test. The configuration of EUT is the same as used in conducted emission test. Please refer to Section 2.2.

4.5 Operating Condition of EUT

Same as conducted emission test, which is listed in Section 2.2 except the test set up replaced as Section 4.1.

4.6 Test Procedure

1) Sequence of testing 9 kHz to 30 MHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions.

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna height is 2.0 meter.

--- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

--- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

Sequence of testing 30 MHz to 1 GHz Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 4 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find



the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.

--- The final measurement will be done with QP detector with an EMI receiver.

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored


4.7 Test Result

PASS

Please refer to the following page.




Radiation Emission Test Data			
Temperature:	26°C	Relative Humidity:	54%
Pressure:	1009hPa	Phase :	/
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Freq	Cable Loss	ANT Factor	Receiver Reading	Emission Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB μ V	dB μ V/m	dB μ V/m	dB	
1	0.074	0.30	23.57	37.18	61.05	103.50	-42.45	QP
2	1.096	0.32	23.12	19.70	43.14	103.50	-60.36	QP
3	1.934	0.32	23.09	23.58	46.99	103.50	-56.51	QP
4	5.971	0.33	21.63	22.26	44.22	103.50	-59.28	QP
5	13.116	0.42	20.19	21.42	42.03	103.50	-61.47	QP
6	22.222	0.51	20.01	22.58	43.10	103.50	-60.40	QP




Radiation Emission Test Data			
Temperature:	26°C	Relative Humidity:	54%
Pressure:	1009hPa	Phase :	Horizontal
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Receiver Reading dB μ V	Preamp Gain dB	Emission Level dB μ V/m	Limit dB μ V/m	Over Limit dB	Remark
1	84.999	0.39	8.10	38.08	28.40	18.17	63.50	-45.33	QP
2	92.139	0.41	9.58	37.35	28.41	18.93	63.50	-44.57	QP
3	121.976	0.44	8.82	36.45	28.43	17.28	63.50	-46.22	QP
4	178.133	0.63	9.20	49.98	28.44	31.37	63.50	-32.13	QP
5	281.008	0.85	12.96	49.13	28.43	34.51	63.50	-28.99	QP
6	768.748	1.35	20.96	34.24	27.79	28.76	63.50	-34.74	QP



Radiation Emission Test Data			
Temperature:	26°C	Relative Humidity:	54%
Pressure:	1009hPa	Phase :	Vertical
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Receiver Reading dB μ V	Preamp Gain dB	Emission Level dB μ V/m	Limit dB μ V/m	Over Limit dB	Remark
1	84.999	0.39	8.10	40.08	28.40	20.17	63.50	-43.33	QP
2	125.007	0.45	8.70	34.26	28.43	14.98	63.50	-48.52	QP
3	181.920	0.63	9.44	48.06	28.44	29.69	63.50	-33.81	QP
4	227.691	0.70	11.69	38.92	28.44	22.87	63.50	-40.63	QP
5	261.058	0.81	12.60	51.35	28.43	36.33	63.50	-27.17	QP
6	768.748	1.35	20.96	34.08	27.79	28.60	63.50	-34.90	QP




5. EUT PHOTOGRAPHS

Reference to the appendix II for details.





6. EUT TEST PHOTOGRAPHS

CE



RE





***** END OF REPORT *****