



RADIO TEST REPORT

Report No: STS2206091H01

Issued for

HANNQI Innovation Manufactory Co., Ltd.

19-6, Building 1, No. 3, Tongjing Road, Nan'an District,
Chongqing, China

Product Name:	Voltmeter Meters or Battery Tester
Brand Name:	JUWEIAT
Model Name:	J7-c
Series Model:	UD24, UD24P, DL24, DT24, AT24, JL24, UC96, U96, S1, S3, S4, S5, S6, S7, S8, S9, AT4P, AT2P, AT1P, DT2P, DT4P, DL150, UD18, A3, T18, P30, UL18, UL24, DL24, DL24M, DLB150W, DLB300W, DLB450W, DLB600W, DLB1200W, C1, C2, C3, C4, C5, C6, C7, C8, C9
FCC ID:	2A7LH-HQ168
Test Standard:	FCC 47CFR §2.1093

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd.

A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





Test Report Certification

Applicant's Name : HANNQI Innovation Manufactory Co., Ltd.

Address : 19-6, Building 1, No. 3, Tongjing Road, Nan'an District, Chongqing, China

Manufacturer's Name : HANNQI Innovation Manufactory Co., Ltd.

Address : 19-6, Building 1, No. 3, Tongjing Road, Nan'an District, Chongqing, China

Product Description

Product Name : Voltmeter Meters or Battery Tester

Brand Name : JUWEIAT

Model Name : J7-c

Series Model : UD24, UD24P, DL24, DT24, AT24, JL24, UC96, U96, S1, S3, S4, S5, S6, S7, S8, S9, AT4P, AT2P, AT1P, DT2P, DT4P, DL150, UD18, A3, T18, P30, UL18, UL24, DL24, DL24M, DLB150W, DLB300W, DLB450W, DLB600W, DLB1200W, C1, C2, C3, C4, C5, C6, C7, C8, C9

Standards : FCC 47CFR §2.1093

447498 D04 Interim General RF Exposure Guidance v01

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test :

Date of receipt of test item : 14 June 2022

Date (s) of performance of tests : 14 June 2022 ~ 23 June 2022

Date of Issue : 23 June 2022


Test Result : **Pass**

Testing Engineer : 

(Chris Chen)

Technical Manager : 

(Sean She)

Authorized Signatory : 

(Bovey Yang)





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	5
2. FCC 47CFR §2.1093 REQUIREMENT	6
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 TEST RESULT	9



**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	23 June 2022	STS2206091H01	ALL	Initial Issue





1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Voltmeter Meters or Battery Tester									
Brand Name	JUWEIAT									
Model Name	J7-c									
Series Model	UD24, UD24P, DL24, DT24, AT24, JL24, UC96, U96, S1, S3, S4, S5, S6, S7, S8, S9, AT4P, AT2P, AT1P, DT2P, DT4P, DL150, UD18, A3, T18, P30, UL18, UL24, DL24, DL24M, DLB150W, DLB300W, DLB450W, DLB600W, DLB1200W, C1, C2, C3, C4, C5, C6, C7, C8, C9									
Model Difference	The internal structure and design of the product are completely the same, Only appearance is different.									
Product Description	<p>The EUT is Voltmeter Meters or Battery Tester</p> <table border="1"><tr><td>Operation Frequency:</td><td>2402~2480 MHz</td></tr><tr><td>Modulation Type:</td><td>GFSK</td></tr><tr><td>Antenna gain:</td><td>-0.58dBi</td></tr><tr><td>Antenna Designation:</td><td>PCB</td></tr></table>		Operation Frequency:	2402~2480 MHz	Modulation Type:	GFSK	Antenna gain:	-0.58dBi	Antenna Designation:	PCB
Operation Frequency:	2402~2480 MHz									
Modulation Type:	GFSK									
Antenna gain:	-0.58dBi									
Antenna Designation:	PCB									
Rating	Input: DC 3.6V-32V 0-5.1A									
Hardware version number	P1.0.11									
Software version number	V1.0.15									

1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



2. FCC 47CFR §2.1093 REQUIREMENT

2.1 TEST STANDARDS

Follow the maximum permissible exposure (MPE) limits specified in 447498 D04 Interim General Radio Frequency Exposure Guidelines v01. The gain of the antenna used in the product was extracted from the supplied antenna data sheet and the maximum total power input to the antenna was also measured. Calculate the distance from the product to the MPE limit by the formula.

2.2 LIMIT

For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);



(C) Or using below table and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency (MHz)	Threshold ERP(watts)
0.3-1.34	1,920 R ² .
1.34-30	3,450 R ² /f ² .
30-300	3.83 R ² .
300-1,500	0.0128 R ² f.
1,500-100,000	19.2R ² .



For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of Part 1.1307 for $P_{th,i}$, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of Part 1.1307 for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$ = the exemption threshold power ($P_{th,i}$) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i .

ERP_j = the ERP of fixed, mobile, or portable RF source j .

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph (b)(3)(i)(C) of Part 1.1307.

$Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure\ Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k , as applicable from § 1.1310.



2.3 TEST RESULT

Turn up

Mode	Detector	Turn up Power
BT	AV	-5±1dBm
BLE	AV	-8±1dBm

Protocol	Fre. (GHz)	Separation distance (cm)	Max Turn up power (dBm)	ANT Gain (dBi)	Max EIRP (dBm)	Max EIRP (mW)	Limit (mW)	Ratio	Result
BT	2.48	0.5	-4	-0.58	-4.58	0.348	2.717	0.128	Pass
BLE	2.48	0.5	-7	-0.58	-7.58	0.175	2.717	0.064	Pass

*****END OF THE REPORT*****