



TEST REPORT

Reference No...... : WTZ22F06125172W
FCC ID : 2A7MY-BCD35AW
Applicant..... : Foshan Shunde QINGZHOU Electric Appliances Co.,Ltd
Address..... : Room 2901, Building 18, Vanke Jinyu Binjiang Plaza, No. 13 Desheng
Middle Road, Dehe Community, Daliang Street, Shunde District,
Foshan, Guangdong
Manufacturer : The same as above
Address..... : The same as above
Product Name..... : Car Refrigerator
Model No..... : BCD35AW
Test specification..... : FCC CFR47 Part 1 Subpart 2 (Section2.1091): 2020
KDB 447498 D01 v06
Date of Receipt sample : 2022-05-11
Date of Test : 2022-06-16
Date of Issue..... : 2022-07-25
Test Report Form No. : WEW-MPE-01A
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Foshan) Co., Ltd.

Address: No.13-19, 2/F., 2nd Building, Sunlink International Machinery City,
Chencun, Shunde District, Foshan, Guangdong, China

Tel:+86-757-23811398

Fax:+86-757-23811381

E-mail:info@waltek.com.cn

Tested by:

Roy Hong

Approved by:

Danny Zhou



1 Revision History

Test Report No.	Date of Issue	Description	Status
WTZ22F06125172W	2022-07-25	Original	Valid

WALTEK



2 Contents

	Page
1 REVISION HISTORY.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 GENERAL DESCRIPTION OF E.U.T	4
3.2 TECHNICAL CHARACTERISTICS OF EUT (BT MODE)	4
3.3 TECHNICAL CHARACTERISTICS OF EUT (BLE MODE)	4
3.4 DISCLAIMER.....	4
4 MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	5
4.1 STANDARD APPLICABLE.....	5
4.2 MPE CALCULATION METHOD.....	6
4.3 MPE CALCULATION RESULT.....	6

WALTEK



3 General Information

3.1 General Description of E.U.T

Product Name : Car Refrigerator
Model No. : BCD35AW
Model Description : ---
Rated Voltage..... : DC 12/24V, 45W
Battery Capacity : ---
Power Adapter : GRT60-145410
Input: 100-240V~, 50/60Hz, 1.5A Max
Output: DC 14.5V, 4.1A, 59.45W

3.2 Technical Characteristics of EUT (BT mode)

Bluetooth Version : V5.1(BR+EDR mode)
Frequency Range : 2402-2480MHz
Max. RF Output Power : -11.44dBm (Conducted)
Modulation : GFSK , $\pi/4$ DQPSK
Data Rate : 1Mbps, 2Mbps
Quantity of Channels : 79
Channel Separation..... : 1MHz
Type of Antenna : MIFA Antenna
Antenna Gain : 1.6dBi
Lowest Oscillation..... : 24MHz

3.3 Technical Characteristics of EUT (BLE mode)

Bluetooth Version : V5.1(BLE mode)
Frequency Range : 2402-2480MHz
RF Output Power : -11.49dBm (Conducted)
Modulation : GFSK
Data Rate : 1Mbps
Quantity of Channels : 40
Channel Separation..... : 2MHz
Type of Antenna : MIFA Antenna
Antenna Gain : 1.6dBi
Lowest Oscillation..... : 24MHz

3.4 Disclaimer

The antenna gain information is provided by the customer. The laboratory is not responsible for the accuracy of the antenna gain information.

Waltek Testing Group (Foshan) Co., Ltd.
<http://www.waltek.com.cn>



4 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

4.1 Standard Applicable

This estimation follows the general guidelines for RF Exposure according to KDB 447498.

As noted in §2.1091(b) a mobile device is defined as “a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.”

According to §2.1091(c) the limits to be used for evaluation are defined in §1.1310.

As specified in §1.1310(d)(2) at operating frequencies less than or equal to 6 GHz, the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in Table 1 of §1.1310(e) may be used.

Table 1 below shows the limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz; * = Plane-wave equivalents power density



4.2 MPE Calculation Method

$$S = (30 \cdot P \cdot G) / (377 \cdot R^2)$$

S = power density (in appropriate units, e.g., mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

4.3 MPE Calculation Result

Prediction distance (mm)	Mode	Antenna Gain (dBi)	Numeric gain	Maximum Tune-up output power (dBm)	Maximum peak output power (mW)	PD (mW/cm ²)	Limit (mW/cm ²)
>200	BT	1.6	1.45	-11.0	0.0794	0.0000228	1.0
>200	BLE	1.6	1.45	-11.5	0.0701	0.0000202	1.0

Note: Tune-up tolerance is 2dB

Result: Pass

=====End of Report=====

WALTEK