



TEST REPORT

FCC ID. :	2A7O2-V5	
Test Report No..... :	TCT220812E029	
Date of issue..... :	Sep. 22, 2022	
Testing laboratory	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name..... :	Shenzhen Lessmore Innovation Technology Ltd	
Address..... :	2206, Taojing Business Building, Longhua New District, Shenzhen, China	
Manufacturer's name ... :	Shenzhen Lessmore Innovation Technology Ltd	
Address..... :	2206, Taojing Business Building, Longhua New District, Shenzhen, China	
Standard(s)	FCC CFR Title 47 Part 1.1310 KDB 680106 D01 RF Exposure Wireless Charging App v03r01	
Product Name..... :	Vertical Lamp	
Trade Mark	N/A	
Model/Type reference..... :	V5	
Rating(s)..... :	AC 120V/60Hz Rechargeable Li-ion Battery DC 7.4V	
Date of receipt of test item	Aug. 12, 2022	
Date (s) of performance of test..... :	Aug. 12, 2022 ~ Sep. 22, 2022	
Tested by (+signature) ... :	Aaron MO	
Check by (+signature).... :	Beryl ZHAO	
Approved by (+signature):	Tomsin	

**General disclaimer:**

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
2. Facilities and Accreditations	4
2.1. Facilities	4
2.2. Location	4
3. Test Results and Measurement Data	5
3.1. Requirements.....	5
3.2. Test Setup	6
3.3. Test Procedure	6
3.4. Test Equipment List	6
3.5. Test Result	7
3.6. Test Set-up Photo.....	9

1. General Product Information

1.1. EUT description

Product Name.....:	Vertical Lamp
Model/Type reference.....:	V5
Sample Number.....:	TCT220812E028-0101
Operation Frequency	117.31kHz ~ 174.36kHz
Modulation Type	Load modulation
Max. Wireless Output Power:	5W
Antenna Type.....:	Inductive loop coil Antenna
Rating(s).....:	AC 120V/60Hz Rechargeable Li-ion Battery DC 7.4V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

None.

2. Facilities and Accreditations

2.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

2.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

3. Test Results and Measurement Data

3.1. Requirements

According to the item 5.b of KDB 680106 D01v03:

Inductive wireless power transfer applications with supporting field strength results and meeting all of the following requirements are not required to submit a KDB inquiry for devices approved using SDoC or a PAG for equipment approved using certification to address RF exposure compliance. However, the responsible party is required to keep a copy of the test report in accordance with KDB 865664 D02. A copy of the test report is to be submitted with the application if the device is approved using certification.

- (1) Power transfer frequency is less than 1 MHz.
- (2) Output power from each primary coil is less than or equal to 15 watts.
- (3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
- (4) Client device is placed directly in contact with the transmitter.
- (5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
- (6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Limits For Maximum Permissible Exposure (MPE)


Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

3.2. Test Setup



Note: Measurements should be made from all sides and the top of the primary/client pair, with the 15cm measured from the center of the probe(s) to the edge of the device.

3.3. Test Procedure

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at 15 cm surrounding the device and 20 cm above the top surface of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- 4) The EUT was measured according to the dictates of KDB 680106 D01 v03. Remark;
The EUT's test position A, B, C, D and E is valid for the E and H field measurements.

3.4. Test Equipment List

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due
Magnetic field meter	NARDA	ELT-400	N-0925	Feb. 24, 2023
Field Probe	NARDA	ELT-400	C-0371	Feb. 24, 2023
Mobile Phone	SAMSUNG	SM-G9350	R28HA2ER3GT	/

3.5. Test Result

E-Filed Strength 15 cm surrounding the device and 20 cm above the top surface of the EUT (V/m)

Frequency Range (KHz)	Operation condition	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Limits Test (V/m)
117.31 ~ 174.36	Full load	1.51	1.65	1.68	1.83	1.57	614
117.31 ~ 174.36	Half load	1.39	1.60	1.62	1.74	1.51	614
117.31 ~ 174.36	No load	1.31	1.44	1.51	1.53	1.48	614

H-Filed Strength 15 cm surrounding the device and 20 cm above the top surface of the EUT (uT)

Frequency Range (KHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E
117.31 ~ 174.36	0.251	0.249	0.254	0.250	0.243
117.31 ~ 174.36	0.248	0.239	0.240	0.244	0.235
117.31 ~ 174.36	0.240	0.231	0.238	0.239	0.228

H-Filed Strength 15 cm surrounding the device and 20 cm above the top surface of the EUT (A/m)

Frequency Range (KHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limits Test (A/m)	Limits Test ((A/m)
117.31 ~ 174.36	0.201	0.199	0.203	0.200	0.194	0.815	1.63
117.31 ~ 174.36	0.198	0.191	0.192	0.195	0.188	0.815	1.63
117.31 ~ 174.36	0.192	0.185	0.190	0.191	0.182	0.815	1.63


Note: $uT=1.25*(A/m)$, $1mT=1000uT$

According to KDB 680106 D01 v03 section 5, b, satisfy the following conditions.


Requirement of KDB 680106 D01	Yes/No	Description
Power transfer frequency is less than 1MHz	Yes	The device operate in the frequency range 117.31kHz ~ 174.36kHz
Output power from each primary coil is less than or equal to 15 watts	Yes	The maximum output power of the primary coil is 5W.
The transfer system includes only single primary and secondary coils. This includes charging system that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.	Yes	The transfer system includes only single coil that is able to detect receiver device.
Client device is placed directly in contact with the transmitter.	Yes	Client device is placed directly in contact with the transmitter.
Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes	Mobile exposure conditions only
The aggregate H-field strengths at 15 cm surrounding the device and 20cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Yes	The EUT H-field strengths at 15 cm surrounding the device and 20cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

3.6. Test Set-up Photo


Front



Back



Left



Right



TOP



*******END OF REPORT*******