## **MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

## **Applicable Standard**

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Report No.: 2504R28083E-RF-00D-M1

Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)					
0.3-1.34	614	1.63	*(100)	30					
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30					
30-300	27.5	0.073	0.2	30					
300-1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

f = frequency in MHz

## Result

## **Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Mode	Frequency (MHz)	Antenna Gain		Tune Up Conducted Power		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
5G WIFI	5250	6.98	4.99	14.8	30.20	20	0.0300	1.0
	5350	7.56	5.70	14.9	30.90	20	0.0351	1.0
	5725	8.50	7.08	16.3	42.66	20	0.0601	1.0
	5850	8.81	7.60	17.6	57.54	20	0.0870	1.0

Note 1: The tune-up conducted power is declared by the applicant.

Note 2: Antenna Gain: 5G WIFI Band 1: Directional gain=3.98dBi\*+3dBi\*=6.98dBi

5G WIFI Band 2: Directional gain=4.56dBi<sup>#</sup>+3dBi<sup>#</sup>=7.56dBi

5G WIFI Band 3: Directional gain=5.50dBi<sup>#</sup>+3dBi<sup>#</sup>=8.50dBi

5G WIFI Band 4: Directional gain=5.81dBi<sup>#</sup>+3dBi<sup>#</sup>=8.81dBi

Note 3: The Bluetooth and WIFI can't transmission simultaneously.

Note 4: The 2.4G Wi-Fi function can't transmit at the same time with the 5G Wi-Fi function.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Compliance** 

<sup>\* =</sup> Plane-wave equivalent power density

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.