



FCC RF EXPOSURE REPORT

FCC ID: 2A7R3-ASIMOUNT3

Test Report No.: RF250328004-01-004

Product(s) Name.: ASI Mount

Model(s).: AM3

Trade Mark.: ZWO

Applicant.: SUZHOU ZWO CO., LTD.

Address.: Building 2, Peninsula Life Plaza, Moon bay road 6 SuZhou Industrial Park, JiangSu, China

Receipt Date.: 2025.04.02

Test Date.: 2025.04.10~2025.05.08

Issued Date.: 2025.05.12

Standards.: CFR47 FCC Part 1: Section 1.1310; CFR47 FCC Part 2: Section 2.1091

FCC KDB Publication 447498 D01v06

Testing Laboratory.: Shenzhen Haiyun Standard Technical Co., Ltd.

Prepared By:	Checked By:	Approved By:	
Jason Huang	Tim Zhang	Misue Su	
Jason Huang	Black Ding	Tim.zhang	



海蕴
HAIYUN

History of this test report

Original Report Issue Date: 2025.05.12

- No additional attachment
- Additional attachments were issued following record

1.. TEST FACILITY

Company:	Shenzhen Haiyun Standard Technical CO., Ltd.
Address:	No. 110-113, 115, 116, Block B, Jinyuan Business Building, Bao'an District, Shenzhen, China
CNAS Registration Number:	CNAS L18252
CAB identifier:	CN0145
A2LA Certificate Number:	6823.01
Telephone:	0755-26024411

2.. MPE CALCULATION METHOD

➤ Product Classification

This device defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

➤ Radio Frequency Exposure Limit

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)
300-1,500	--	--	f/1500
1,500-100,000	--	--	1.0

➤ Radio Frequency Exposure Calculation Formula

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

or:

$$S = \frac{EIRP}{4\pi R^2}$$

where: EIRP = equivalent (or effective) isotropically radiated power

➤ **Table for Filed Antenna**

For BLE & 2.4G WIFI

Ant.	Brand	Antenna Type	Connector	Gain (dBi)
1	N/A	PCB	N/A	0.23

3.. TEST RESULTS

Worst case as below

For Antenna type3(Model name: 2108792-2)

Operating Mode	Freq.	Maximum conducted output power	Directional Antenna Gain	Calculated maximum EIRP		MPE Limit	MPE Value
	(MHz)	(dBm)	(dBi)	(dBm)	(mW)		
BLE	2402-2480	3.29	0.23	3.52	2.25	1	0.0004

Note:

Note: 1. The calculated distance is 20 cm.

➤ **Conclusion**

Result: Complies

Statement

1. The report is invalid without the official seal or special seal of Shenzhen Haiyun Standard Technical Co., Ltd. (hereinafter referred to as the unit).
2. The report is invalid without the signature of the approver.
3. The report is invalid if altered arbitrarily.
4. The report shall not be partially copied without the written approval of the unit.
5. The reported test results are only valid for the tested samples.
6. If there is any objection to the test report, it shall be submitted to the test unit within 15 days from the date of receiving the report, and the overdue shall not be accepted.

Shenzhen Haiyun Standard Technical Co., Ltd.

Address: Room 110, 111, 112, 113, 115, 116, Block B, Jinyuan Business Building, No. 302, Xixiang Avenue, Labor Community, Xixiang Street, Baoan District, Shenzhen, China

Tel: 0755-26024411

Email: service@hy-lab.cn

(END OF REPORT)