



# MAXIMUM PERMISSIBLE EXPOSURE EVALUATION REPORT

**Applicant:** SUZHOU ZWO CO., LTD.

**Address:** Building 2, Peninsula Life Plaza, Moon bay road 6 SuZhou  
Industrial Park, JiangSu, China

**Product Name:** Smart Telescope

**FCC ID:** 2A7R3-SEESTARS30

**Standard(s):** 47 CFR §1.1310, 47 CFR §2.1091,  
47 CFR §15.247(i), 47 CFR §15.407(f)

**Report Number:** 2402Y99315E-RF-00E

**Report Date:** 2024/12/5

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

**Reviewed By:** Pedro Yun

Title: Project Engineer

**Approved By:** Gavin Xu

Title: RF Supervisor

---

**Bay Area Compliance Laboratories Corp. (Dongguan)**  
No.12, Pulong East 1<sup>st</sup> Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

[www.baclcorp.com.cn](http://www.baclcorp.com.cn)

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

## CONTENTS

<b>DOCUMENT REVISION HISTORY .....</b>	<b>3</b>
<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
<b>1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....</b>	<b>4</b>
<b>1.2 ACCESSORY INFORMATION.....</b>	<b>4</b>
<b>1.3 ANTENNA INFORMATION DETAIL ^ .....</b>	<b>4</b>
<b>1.4 EQUIPMENT MODIFICATIONS .....</b>	<b>4</b>
<b>2. RF EXPOSURE EVALUATION (MPE).....</b>	<b>5</b>
<b>2.1 RF EXPOSURE EVALUATION .....</b>	<b>5</b>
2.1.1 Applicable Standard.....	5
2.1.2 Calculation formula: .....	5
2.1.3 Calculated Data:.....	6
<b>EXHIBIT A - EUT PHOTOGRAPHS.....</b>	<b>7</b>

**DOCUMENT REVISION HISTORY**

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2402Y99315E-RF-00E	Original Report	2024/12/5

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

<b>EUT Name:</b>	Smart Telescope
<b>Trade Name:</b>	Seestar
<b>EUT Model:</b>	Seestar S30
<b>Rated Input Voltage:</b>	DC 3.7V From Battery or DC 5~12V From Type-C
<b>Serial Number:</b>	2SWA-1
<b>EUT Received Date:</b>	2024/10/16
<b>EUT Received Status:</b>	Good

### 1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
Type-C Cable	/	/	Unshielded without Ferrite Core, 1.0 meter
Tripod	/	/	/
Solar Filter	/	/	/

### 1.3 Antenna Information Detail▲

Antenna Type	Input Impedance (Ohm)	Frequency Range	Antenna Gain
PCB	50	2.4-2.5GHz	3.27dBi
		5.15~5.25GHz	5.33dBi
		5.70~5.85 GHz	4.23dBi

### 1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

## 2. RF EXPOSURE EVALUATION (MPE)

### 2.1 RF Exposure Evaluation

#### 2.1.1 Applicable Standard

According to subpart 15.247(i), 15.407(f) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

#### 2.1.2 Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

### 2.1.3 Calculated Data

Mode	Frequency Range (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
BDR/EDR	2402-2480	3.27	2.123	5.0	3.16	20	0.001	1.00
BLE	2402-2480	3.27	2.123	4.0	2.51	20	0.001	1.00
2.4GHz WIFI	2412-2462	3.27	2.123	23.0	199.53	20	0.084	1.00
5.2GHz WIFI	5180-5240	5.33	3.412	14.0	25.12	20	0.017	1.00
5.8GHz WIFI	5745-5825	4.23	2.649	15.0	31.62	20	0.017	1.00

Note:

1. The Conducted output power including Tune-up Tolerance provided by manufacturer.
2. The Bluetooth BDR/EDR, BLE and WIFI can't transmit simultaneously.
3. The distance from observation point to the antenna is 20cm.

**Result: Compliant.**

---

## **EXHIBIT A - EUT PHOTOGRAPHS**

---

Please refer to the attachment 2402Y99315E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2402Y99315E -RF-INP EUT INTERNAL PHOTOGRAPHS.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***