

Reelables User Manual for N-Label/0001



Use with barcode printers:

Step 1. Download Reelables Desktop app and ensure software connects to thermal barcode printer with barcode scanner.

Step 2. Load Reelables N-Labels into thermal barcode printer.

Step 3. Scan a barcode, QR code or other serialisation already printed on an inventory item. A Reelables N-Label is instantly printed with the same serialisation.

Step 4. Peel label backing and stick Reelables N-Label to box.

Use with Android or iPhone:

Step 1. Simply scan NFC in corner of N-Label with an iPhone or Android.

Step 2. A weblink will pop-up on the screen. Open in a web browser and enter a shipment reference such as a shipping tracking number or descriptive name.

Step 3. Peel label backing and stick Reelables N-Label to box.



Per FCC 15.19(a)(3) and (a)(4) This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Per FCC 15.21, Changes or modifications not expressly approved by the responsible party for compliance could void the user's authority to operate the equipment.

Per FCC 15.105, Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help



This device is exempt from RF Exposure human safety routine evaluation according to FCC Rule 47 CFR 1.1307(b)(3)(i) as a low power transmitter and is inherently safe for usage at any distance