

## RF Exposure Evaluation

For

SHENZHEN DAYBETTER OPTO-ELECTRONICS CO.,LTD

Strip light

Test Model: D32108B

Prepared for : SHENZHEN DAYBETTER OPTO-ELECTRONICS CO.,LTD  
Address : 4F,BUILDING 2, ANTUOSHAN HI-TECH PARK BAOAN DISTRICT,  
SHENZHEN, China

Prepared by : Guangzhou LCS Compliance Testing Laboratory Ltd.  
Address : No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou,  
Guangdong, China

Tel : (+86) 020-39166689  
Fax : (+86) 020-39166619  
Web : [www.LCS-cert.com](http://www.LCS-cert.com)  
Mail : [webmaster@LCS-cert.com](mailto:webmaster@LCS-cert.com)

Date of receipt of test sample : September 16, 2025  
Number of tested samples : 2  
Sample No. : C250904015-1, C250904015-2  
Serial number : Prototype  
Date of Test : September 16, 2025 ~ September 23, 2025  
Date of Report : September 25, 2025

## RF Exposure Evaluation

**Report Reference No. .... : LCSC09045024EB**

Date of Issue..... : September 25, 2025

**Testing Laboratory Name..... : Guangzhou LCS Compliance Testing Laboratory Ltd.**

Address..... : No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China

Testing Location/ Procedure..... : Full application of Harmonised standards  Partial application of Harmonised standards  Other standard testing method

**Applicant's Name..... : SHENZHEN DAYBETTER OPTO-ELECTRONICS CO.,LTD**

Address..... : 4F,BUILDING 2, ANTUOSHAN HI-TECH PARK BAOAN DISTRICT, SHENZHEN, China

### **Test Specification**

Standard..... : FCC KDB publication 447498 D01 General RF Exposure Guidance v06  
FCC CFR 47 part1 1.1310  
FCC CFR 47 part2 2.1091

**Test Report Form No..... : TRF-4-E-214 A/0**

TRF Originator..... : Guangzhou LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

### **Guangzhou LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Guangzhou LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Guangzhou LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**EUT Description..... : Strip light**


Trade Mark..... : N/A

Test Model..... : D32108B

Ratings..... : Please Refer to Page 6


Result ..... : **Pass**

**Compiled by:**




Lifeng Le / File administrators

**Supervised by:**



Justin Zhu / Technique Director

**Approved by:**



Gavin Liang/ Manager

## RF Exposure Evaluation

|                          |                       |                           |
|--------------------------|-----------------------|---------------------------|
| <b>Test Report No. :</b> | <b>LCSC09045024EB</b> | <u>September 25, 2025</u> |
|                          |                       | Date of issue             |

|                          |   |
|--------------------------|---|
| Test Model.....          | : D32108B   |
| EUT.....                 | : Strip light   |
| <b>Applicant.....</b>    | <b>: SHENZHEN DAYBETTER OPTO-ELECTRONICS CO.,LTD</b>                    |
| Address.....             | : 4F,BUILDING 2, ANTUOSHAN HI-TECH PARK BAOAN DISTRICT, SHENZHEN, China |
| Telephone.....           | : /   |
| Fax.....                 | : /   |
| <b>Manufacturer.....</b> | <b>: SHENZHEN DAYBETTER OPTO-ELECTRONICS CO.,LTD</b>                    |
| Address.....             | : 4F,BUILDING 2, ANTUOSHAN HI-TECH PARK BAOAN DISTRICT, SHENZHEN, China |
| Telephone.....           | : /   |
| Fax.....                 | : /   |
| <b>Factory.....</b>      | <b>: SHENZHEN DAYBETTER OPTO-ELECTRONICS CO.,LTD</b>                    |
| Address.....             | : 4F,BUILDING 2, ANTUOSHAN HI-TECH PARK BAOAN DISTRICT, SHENZHEN, China |
| Telephone.....           | : /   |
| Fax.....                 | : /   |

|                    |             |
|--------------------|-------------|
| <b>Test Result</b> | <b>Pass</b> |
|--------------------|-------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Revision History

| Report Version | Issue Date         | Revision Content | Revised By |
|----------------|--------------------|------------------|------------|
| 000            | September 25, 2025 | Initial Issue    | ---        |
|                |                    |                  |            |
|                |                    |                  |            |

## TABLE OF CONTENTS

| Description                            | Page |
|--|------|
| 1. Product Information .....           | 6    |
| 2. Evaluation Method .....             | 6    |
| 3. Limit .....                         | 6    |
| 4. MPE Calculation Method .....        | 8    |
| 5. Antenna Information .....           | 8    |
| 6. Conducted Power .....               | 8    |
| 7. Manufacturing Tolerance .....       | 8    |
| 8. Measurement Results .....           | 8    |
| 9. Conclusion .....                    | 9    |
| 10. Description of Test Facility ..... | 9    |
| 11. Measurement Uncertainty .....      | 9    |

## 1. Product Information

|                     |   |
|---------------------|---|
| EUT                 | : Strip light                                 |
| Test Model          | : D32108B                                     |
| Power Supply        | : Input: DC 5V<br>Output: DC 24V              |
| Hardware Version    | : VER1.1.0                                    |
| Software Version    | : VER1.0.0                                    |
| Bluetooth           | :   |
| Frequency Range     | : 2402MHz~2480MHz                             |
| Channel Number      | : 40 channels for Bluetooth V5.0 (DTS)        |
| Channel Spacing     | : 2MHz for Bluetooth V5.0 (DTS)               |
| Modulation Type     | : GFSK for Bluetooth V5.0 (DTS)               |
| Bluetooth Version   | : V5.0  |
| Antenna Description | : PCB Antenna, 2.499dBi(Max.)                 |
| Exposure category   | : General population/uncontrolled environment |
| EUT Type            | : Production Unit                             |
| Device Type         | : Mobile Device                               |

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

## 2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

## 3. Limit

### 3. 1 Refer Evaluation Method

[ANSI C95.1–2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

### 3. 2 Limit

#### Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

| Frequency Range(MHz)                        | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minute) |
|---|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for Occupational/Controlled Exposure |                              |                              |                                     |                         |
| 0.3 – 3.0                                   | 614                          | 1.63                         | (100) *                             | 6                       |
| 3.0 – 30                                    | 1842/f                       | 4.89/f                       | (900/f <sup>2</sup> )*              | 6                       |
| 30 – 300                                    | 61.4                         | 0.163                        | 1.0                                 | 6                       |
| 300 – 1500                                  | /                            | /                            | f/300                               | 6                       |
| 1500 – 100,000                              | /                            | /                            | 5                                   | 6                       |

#### Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

| Frequency Range(MHz)                          | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minute) |
|---|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for Occupational/Uncontrolled Exposure |                              |                              |                                     |                         |
| 0.3 – 3.0                                     | 614                          | 1.63                         | (100) *                             | 30                      |
| 3.0 – 30                                      | 824/f                        | 2.19/f                       | (180/f <sup>2</sup> )*              | 30                      |
| 30 – 300                                      | 27.5                         | 0.073                        | 0.2                                 | 30                      |
| 300 – 1500                                    | /                            | /                            | f/1500                              | 30                      |
| 1500 – 100,000                                | /                            | /                            | 1.0                                 | 30                      |

F=frequency in MHz

\*=Plane-wave equivalent power density

#### 4. MPE Calculation Method

Predication of MPE limit at a given distance  
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

#### 5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

| Internal/External Identification | Antenna type and antenna number | Operate frequency band | Maximum antenna gain | Notes         |
|----------------------------------|---------------------------------|------------------------|----------------------|---------------|
| Internal Antenna                 | PCB Antenna                     | 2400-2500 MHz          | 2.499dBi             | BT LE Antenna |

#### 6. Conducted Power

[BLE]

| Mode | Channel | Frequency (MHz) | Peak Conducted Output Power (dBm) |
|------|---------|-----------------|-----------------------------------|
| BLE  | 0       | 2402            | 1.47                              |
|      | 19      | 2440            | 0.22                              |
|      | 39      | 2480            | -0.87                             |

#### 7. Manufacturing Tolerance

| BLE (Peak)           |           |            |            |
|----------------------|-----------|------------|------------|
| Channel              | Channel 0 | Channel 19 | Channel 39 |
| Target (dBm)         | 1.0       | 0          | 0          |
| Tolerance $\pm$ (dB) | 1.0       | 1.0        | 1.0        |

#### 8. Measurement Results

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r = 20\text{cm}$ , as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

| Modulation Type | Output power |        | Antenna Gain (dBi) | Antenna Gain (linear) | MPE (mW/cm <sup>2</sup> ) | MPE Limits (mW/cm <sup>2</sup> ) |
|-----------------|--------------|--------|--------------------|-----------------------|---------------------------|----------------------------------|
|                 | dBm          | mW     |                    |                       |                           |                                  |
| GFSK            | 2.0          | 1.5849 | 2.499              | 1.7779                | 0.0006                    | 1.0000                           |

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

## 9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

## 10. Description of Test Facility

CNAS Registration Number is L11555

A2LA Certificate Number: 5099.01

FCC Designation Number is CN1379

Test Firm Registration Number: 729882

## 11. Measurement Uncertainty

| Test Item      | Frequency Range | Uncertainty | Note |
|----------------|-----------------|-------------|------|
| Output power : | 1GHz-40GHz      | ±0.57dB     | (1)  |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

-----THE END OF REPORT-----