

Appendix A

RF Test Data for BT LE (Conducted Measurement)

Product Name: Strip light
Test Model: D43209-30B

Environmental Conditions


Temperature:	23.9°C
Relative Humidity:	52.4%
ATM Pressure:	100.0 kPa
Test Engineer:	Suichao Lai
Supervised by:	Yan Chen

A.1 -6dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.659	≥ 0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.662	≥ 0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.664	≥ 0.5	Pass


Test Graphs

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1




-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1






A.2 Maximum Peak Conducted Output Power


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	0.06	30	Pass
NVNT	BLE 1M	2440	Ant1	0.54	30	Pass
NVNT	BLE 1M	2480	Ant1	-0.38	30	Pass






A.3 Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant1	-16.49	8	Pass
NVNT	BLE 1M	2440	Ant1	-16.07	8	Pass
NVNT	BLE 1M	2480	Ant1	-17.06	8	Pass






A.4 Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-57.07	-20	Pass
NVNT	BLE 1M	2480	Ant1	-55.87	-20	Pass


Test Graphs

Band Edge NVNT BLE 1M 2402MHz Ant1 Ref




Band Edge NVNT BLE 1M 2402MHz Ant1 Emission







A.5 Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-54.7	-20	Pass
NVNT	BLE 1M	2440	Ant1	-55.34	-20	Pass
NVNT	BLE 1M	2480	Ant1	-54.97	-20	Pass









A.6 Duty Cycle


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant1	87.39	0.59	0.61
NVNT	BLE 1M	2440	Ant1	87.41	0.58	0.61
NVNT	BLE 1M	2480	Ant1	87.39	0.59	0.61






A.7 Restrict Band

Condition	Mode	Frequency (MHz)	Antenna	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	Duty Factor (dB)	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
NVNT	BLE 1M	2402	Ant1	2310	-51.1	2	-	46.16	Peak	74	Pass
NVNT	BLE 1M	2402	Ant1	2310	-59.02	2	0.59	38.83	Average	54	Pass
NVNT	BLE 1M	2402	Ant1	2386.032	-47.32	2	-	49.94	Peak	74	Pass
NVNT	BLE 1M	2402	Ant1	2371.152	-58.26	2	0.59	39.59	Average	54	Pass
NVNT	BLE 1M	2402	Ant1	2390	-51.23	2	-	46.03	Peak	74	Pass
NVNT	BLE 1M	2402	Ant1	2390	-58.61	2	0.59	39.24	Average	54	Pass
NVNT	BLE 1M	2480	Ant1	2483.5	-49.44	2	-	47.82	Peak	74	Pass
NVNT	BLE 1M	2480	Ant1	2483.5	-57.8	2	0.59	40.05	Average	54	Pass
NVNT	BLE 1M	2480	Ant1	2483.752	-46.26	2	-	51.00	Peak	74	Pass
NVNT	BLE 1M	2480	Ant1	2483.704	-57.68	2	0.59	40.17	Average	54	Pass
NVNT	BLE 1M	2480	Ant1	2500	-49.94	2	-	47.32	Peak	74	Pass
NVNT	BLE 1M	2480	Ant1	2500	-58.32	2	0.59	39.53	Average	54	Pass



Restrict Band NVNT BLE 1M 2480MHz Ant1 Peak



Restrict Band NVNT BLE 1M 2480MHz Ant1 Average

