FCC ID: 2A7XM-WE-001

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] * [$\sqrt{f(GHz)}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is \leq 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT DSS:

| Transmit Frequency (GHz) | Mode | Max Conducted Power (dBm) | tune up maximum power(dBm) | Result calculation | 1-g SAR |
|--------------------------|------------|------------------------------|----------------------------|--------------------|---------|
| 2.402 | GFSK | 1.84 | 3 | 0.618 | 3 |
| 2.441 | GFSK | 2.07 | 3 | 0.623 | 3 |
| 2.480 | GFSK | 1.82 | 3 | 0.628 | 3 |
| 2.402 | pi/4-DQPSK | 2.7 | 3 | 0.618 | 3 |
| 2.441 | pi/4-DQPSK | 2.89 | 3 | 0.623 | 3 |
| 2.480 | pi/4-DQPSK | 2.65 | 3 | 0.628 | 3 |
| 2.402 | 8DPSK | 3.11 | 4 | 0.779 | 3 |
| 2.441 | 8DPSK | 3.28 | 4 | 0.785 | 3 |
| 2.480 | 8DPSK | 3.03 | 4 | 0.791 | 3 |

BLE DTS

| Transmit Frequency (GHz) | Mode | Max Conducted Power (dBm) | tune up maximum power(dBm) | Result calculation | 1-g SAR |
|-----------------------------|------|---------------------------|----------------------------|--------------------|---------|
| 2402(1M) | GFSK | 2.01 | 3 | 0.618 | 3 |
| 2440(1M) | GFSK | 2.16 | 3 | 0.623 | 3 |
| 2480(1M) | GFSK | 1.88 | 3 | 0.628 | 3 |
| 2402(2M) | GFSK | 2.03 | 3 | 0.618 | 3 |
| 2440(2M) | GFSK | 2.19 | 3 | 0.623 | 3 |
| 2480(2M) | GFSK | 1.93 | 3 | 0.628 | 3 |

Conclusion:

For the max result: 0.791≤ 3.0 for 1-g SAR extremity SAR, No SAR is required.

Signature: Date: 2022.9.17

NAME AND TITLE (Please print or type): Lisa Wang/Manager COMPANY (Please print or type): Shenzhen EMTEK Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China