



FCC RF Exposure Evaluation

1. Product Information

Product name	:	Notebook
Test Model	:	WWN17V2C4SL128
Additional Model No.	:	WWN17V2C4WH128, WWN17V2C8SL256, WN17V2C8WH256, WWN17V2C8SL512, WWN17V2C8WH512
Model Declaration	:	PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Power Supply	:	Input: 12V $\pm$ 3.0A For AC Adapter Input: 100-240V~, 50/60Hz, 1.5A Adapter Output: 12.0V $\pm$ 3.0A 36.0W DC 7.6V by Rechargeable Li-ion Battery, 6000mAh
Hardware Version	:	G133JA REV01
Software Version	:	09-18-2022
Bluetooth		
Frequency Range	:	2402MHz~2480MHz
Channel Number	:	40 channels for Bluetooth V4.2 (DTS)
Channel Spacing	:	2MHz for Bluetooth V4.2 (DTS)
Modulation Type	:	GFSK for Bluetooth V4.2 (DTS)
Bluetooth Version	:	V4.2
Antenna Description	:	Antenna 1: PIFA Antenna, 1.59dBi(Max.)
WIFI(2.4G Band)		
Frequency Range	:	2412MHz~2462MHz
Channel Spacing	:	5MHz
Channel Number	:	11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	:	Antenna 1: PIFA Antenna, 1.59dBi(Max.) Antenna 2: PIFA Antenna, 1.42dBi(Max.)
5.2G WLAN		
Frequency Range	:	5180MHz~5240MHz
Channel Number	:	4 channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)
Modulation Type	:	IEEE 802.11a/n/ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	:	Antenna 1: PIFA Antenna, 1.38dBi(Max.) Antenna 2: PIFA Antenna, 1.32dBi(Max.)
5.8G WLAN		



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Frequency Range	:	5745MHz~5825MHz
Channel Number	:	5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz) 1 channels for 80MHz bandwidth(5775MHz)
Modulation Type	:	IEEE 802.11a/n/ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	:	Antenna 1: PIFA Antenna, 1.45dBi(Max.) Antenna 2: PIFA Antenna, 1.43dBi(Max.)
Exposure category	:	General population/uncontrolled environment
EUT Type	:	Production Unit
Device Type	:	Portable Device

2. Evaluation method and Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.22 The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc."

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f} (\text{GHz})] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

When one of the following test exclusion conditions is satisfied for all combinations of simultaneous transmission configurations, further equipment approval is not required to incorporate transmitter modules in host devices that operate in the mixed mobile and portable host platform exposure conditions. The grantee is responsible for documenting this according to Class I permissive change requirements. Antennas that qualify for standalone SAR test exclusion must apply the estimated standalone SAR to determine simultaneous transmission test exclusion.

a) The $\sum$ of (the highest measured or estimated SAR for each standalone antenna configuration,



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



adjusted for maximum tune-up tolerance) / 1.6 W/kg] + [Σ of MPE ratios] is ≤ 1.0.

b) The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all ≤ 0.04, and the [Σ of MPE ratios] is ≤ 1.0.

3. Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



4. Conducted Power Results

[BLE]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	-3.87
	19	2440	-2.49
	39	2480	-4.17

[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11B	1	2412	6.86	6.91
	6	2437	6.90	6.65
	11	2462	6.73	6.15
11G	1	2412	6.61	6.10
	6	2437	6.72	6.17
	11	2462	6.30	6.64
11N20 SISO	1	2412	6.91	6.89
	6	2437	6.28	6.21
	11	2462	6.49	6.57
11N40 SISO	3	2422	6.68	6.49
	6	2437	6.88	6.74
	9	2452	6.75	6.61

[5.2G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11A	36	5180	6.87	6.67
	40	5200	6.58	6.85
	48	5240	6.99	6.51
11N20 SISO	36	5180	6.71	6.53
	40	5200	6.69	6.68
	48	5240	6.45	6.39
11N40 SISO	38	5190	6.76	6.46
	46	5230	6.55	6.50
11AC20 SISO	36	5180	6.68	6.44
	40	5200	6.55	6.48
	48	5240	6.49	6.41
11AC40 SISO	38	5190	6.76	6.47
	46	5230	6.56	6.46
11AC80 SISO	42	5210	6.70	6.59



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.8G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11A	149	5745	6.40	6.66
	157	5785	6.45	6.65
	165	5825	6.39	6.39
11N20 SISO	149	5745	6.29	6.54
	157	5785	6.26	6.46
	165	5825	6.27	6.88
11N40 SISO	151	5755	6.92	6.57
	159	5795	6.12	6.63
11AC20 SISO	149	5745	6.27	6.53
	157	5785	6.58	6.62
	165	5825	6.26	6.31
11AC40 SISO	151	5755	6.88	6.58
	159	5795	6.87	6.59
11AC80 SISO	155	5775	6.18	6.28



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



5. Manufacturing Tolerance

[BLE]

BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-3.0	-2.0	-3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WIFI Ant1]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WIFI Ant2]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.2G WIFI Ant1]

11A (Peak)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Peak)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Peak)			
Channel	Channel 38	Channel 46	
Target (dBm)	7.0	7.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Peak)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Peak)			
Channel	Channel 38	Channel 46	
Target (dBm)	6.0	6.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80(Peak)			
Channel	Channel 42		
Target (dBm)	6.0		
Tolerance $\pm$ (dB)	1.0		



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.2G WIFI Ant2]

11A (Peak)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Peak)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Peak)			
Channel	Channel 38	Channel 46	
Target (dBm)	6.0	6.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Peak)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Peak)			
Channel	Channel 38	Channel 46	
Target (dBm)	6.0	6.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80(Peak)			
Channel	Channel 42		
Target (dBm)	6.0		
Tolerance $\pm$ (dB)	1.0		



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.8G WIFI Ant1]

11A (Peak)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Peak)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Peak)			
Channel	Channel 151	Channel 159	
Target (dBm)	6.0	6.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Peak)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Peak)			
Channel	Channel 151	Channel 159	
Target (dBm)	6.0	6.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80(Peak)			
Channel	Channel 155		
Target (dBm)	6.0		
Tolerance $\pm$ (dB)	1.0		



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.8G WIFI Ant2]

11A (Peak)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Peak)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Peak)			
Channel	Channel 151	Channel 159	
Target (dBm)	6.0	6.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Peak)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	6.0	6.0	6.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Peak)			
Channel	Channel 151	Channel 159	
Target (dBm)	6.0	6.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80(Peak)			
Channel	Channel 155		
Target (dBm)	6.0		
Tolerance $\pm$ (dB)	1.0		



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



6. Evaluation Results

6.1 Standalone Evaluation

[BLE]

Band/Mode		Frequency (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
				dBm	mW		
BLE	GFSK	2.440	5	-1.0	0.7943	0.2482< 3.0	Yes

[2.4G WIFI Ant1]

Band/Mode		Frequency (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
				dBm	mW		
IEEE 802.11b		2.462	5	7.0	5.0119	1.5728< 3.0	Yes
IEEE 802.11g		2.462	5	7.0	5.0119	1.5728< 3.0	Yes
IEEE 802.11n HT20		2.462	5	7.0	5.0119	1.5728< 3.0	Yes
IEEE 802.11n HT40		2.452	5	7.0	5.0119	1.5696< 3.0	Yes

[2.4G WIFI Ant2]

Band/Mode		Frequency (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
				dBm	mW		
IEEE 802.11b		2.462	5	7.0	5.0119	1.5728< 3.0	Yes
IEEE 802.11g		2.462	5	7.0	5.0119	1.5728< 3.0	Yes
IEEE 802.11n HT20		2.462	5	7.0	5.0119	1.5728< 3.0	Yes
IEEE 802.11n HT40		2.452	5	7.0	5.0119	1.5696< 3.0	Yes

[5.2G WIFI Ant1]

Band/Mode		Frequency (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
				dBm	mW		
IEEE 802.11a		5.240	5	7.0	5.0119	2.2945< 3.0	Yes
IEEE 802.11n HT20		5.240	5	7.0	5.0119	2.2945< 3.0	Yes
IEEE 802.11n HT40		5.230	5	7.0	5.0119	2.2923< 3.0	Yes
IEEE 802.11ac VHT20		5.240	5	7.0	5.0119	2.2945< 3.0	Yes
IEEE 802.11ac VHT40		5.230	5	7.0	5.0119	2.2923< 3.0	Yes
IEEE 802.11ac VHT80		5.210	5	7.0	5.0119	2.2880< 3.0	Yes



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.2G WIFI Ant2]

Band/Mode	Frequency (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
IEEE 802.11a	5.240	5	7.0	5.0119	2.2945< 3.0	Yes
IEEE 802.11n HT20	5.240	5	7.0	5.0119	2.2945< 3.0	Yes
IEEE 802.11n HT40	5.230	5	7.0	5.0119	2.2923< 3.0	Yes
IEEE 802.11ac VHT20	5.240	5	7.0	5.0119	2.2945< 3.0	Yes
IEEE 802.11ac VHT40	5.230	5	7.0	5.0119	2.2923< 3.0	Yes
IEEE 802.11ac VHT80	5.210	5	7.0	5.0119	2.2880< 3.0	Yes

[5.8G WIFI Ant1]

Band/Mode	Frequency (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
IEEE 802.11a	5.825	5	7.0	5.0119	2.4192< 3.0	Yes
IEEE 802.11n HT20	5.825	5	7.0	5.0119	2.4192< 3.0	Yes
IEEE 802.11n HT40	5.795	5	7.0	5.0119	2.4130< 3.0	Yes
IEEE 802.11ac VHT20	5.825	5	7.0	5.0119	2.4192< 3.0	Yes
IEEE 802.11ac VHT40	5.795	5	7.0	5.0119	2.4130< 3.0	Yes
IEEE 802.11ac VHT80	5.775	5	7.0	5.0119	2.4088< 3.0	Yes

[5.8G WIFI Ant2]

Band/Mode	Frequency (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
IEEE 802.11a	5.825	5	7.0	5.0119	2.4192< 3.0	Yes
IEEE 802.11n HT20	5.825	5	7.0	5.0119	2.4192< 3.0	Yes
IEEE 802.11n HT40	5.795	5	7.0	5.0119	2.4130< 3.0	Yes
IEEE 802.11ac VHT20	5.825	5	7.0	5.0119	2.4192< 3.0	Yes
IEEE 802.11ac VHT40	5.795	5	7.0	5.0119	2.4130< 3.0	Yes
IEEE 802.11ac VHT80	5.775	5	7.0	5.0119	2.4088< 3.0	Yes

Remark:

1. Output power including tune up tolerance;
2. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



6.2 Simultaneous Transmission for SAR Exclusion

The sample support one BLE/2.4GWIFI/5.2G WIFI/5.8GWIFI antenna and one 2.4GWIFI/5.2G WIFI/5.8GWIFI antenna, they supports difference antenna, need consider simultaneous transmission;
 Σ of (the highest measured or estimated SAR_{Ant1}+SAR_{Ant2})/1.6=(0.3226+0.3226)/1.6=0.4<1.0;

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

.....THE END OF REPORT.....



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity