

Testing Report

Customer Name: Shenzhen Moday Cultural Creation Co., Ltd


Product Name: Electronic lighting Dice

Sample Model: D20

Reference Standard: *GB/T 9410-2008; ANSI/IEEE Std 149-1979*

Issue Date: 2022.10.19

Engineer: Jackson	Date: 2022.10.19
Auditor: Eason	Date: 2022.10.19
Approver: Janson	Date: 2022.10.19

A circular blue seal with a serrated edge. The outer ring contains the text "Shenzhen RFI-LAB Communication Technology Co., Ltd." in white. The center of the seal is dark blue with the text "RFI-LAB" in white.

Version

Version No.	Date	Description	Formulate	Approval
A0	2022.10.19	For the first time, formulate	Jackson	Eason

Contents

1.General Information	3
1.1 General information of testing institutions	3
1.2 Testing principle	3
1.3 Test equipment	4
1.4 Test environment	4
1.5 Statement	4
2.Sample Information	5
2.1 Client information	5
2.2 Description of EUT(S)	5
2.3 EUT appearance	6
2.4 DUT setup photo of free space OTA testing	6
3.Test Results	7
3.1 Test standard	7
3.2 Test uncertainty	7
3.3 Test data	8
3.3.1 Typical free space efficiency and gain	8
3.3.2 Typical free space radiation pattern	8
(The following is blank)	9

1.General Information


1.1 General information of testing institutions

Name	Shenzhen RFI-LAB Communication Technology Co., Ltd.
Address	10/F A, Lingyun Bld, Liufang Rd, Baoan District, SZ
Tel	13798473001
E-mail	lait@tech-now.com
Equipment	All the equipment used in the report is fixed in 10/F A, Lingyun Bld, Liufang Rd, Baoan District, SZ

1.2 Testing principle



Multi-Probe OTA Measurement System



1.3 Test equipment

Equipment	Model No.	Serial No.	Manufacturer	Calibration date	Next calibration date
16 probe microwave chamber	3*3*2.5	RFI-LAB-RF-A00	SUNYIELD	2021.3.15	2023.3.14
Network Analyzer	E5071C	RFI-LAB-RF-A02	Agilent	2022.5.13	2023.5.12

1.4 Test environment

Temperature	24.3°C
Humidity	59%RH
Pressure	100.11kPa

1.5 Statement

- (1) The test results in the report are only applicable to the tested samples and the tested samples work under the environment described in the report.
- (2) Only Shenzhen RFI-LAB Communication Technology Co., Ltd. have the right to modify the report, and the modification information shall be annotated in the revision form.
- (3) Any objection to this report shall be raised within 30 days after formal confirmation of the report.
- (4) This report is invalid if there is any evidence that the sample information provided is falsified.
- (5) The report is invalid without the signature of the auditor and approver.

2.Sample Information



2.1 Client information

Name	Shenzhen Moday Cultural Creation Co., Ltd
Address	Room 1516, Block B, Tianxia International Center, No.8 Taoyuan Road, Dawangshan Community, Nantou Street, Nanshan District, Shenzhen
Contacts	xiaobo
Tel	18923443357
E-mail	240280479@qq.com
manufacturer	Dongguan Fortune Electronic Technology Co., Ltd

2.2 Description of EUT(S)

Product Name	Electronic lighting Dice
Sample Model	D20
Size	/
Serial No.	/
Test Item	Gain; Efficiency; Radiation pattern
Frequency Range	2400-2500MHz
Received Date	2022.10.18
Test Date	2022.10.19
Remark	/

2.3 EUT appearance




2.4 DUT setup photo of free space OTA testing

Planform



Front view



3. Test Results

3.1 Test standard

Name	Parameter	Method	Standard no.
Mobile communication antenna	Antenna gain	Generic specification for antennas used in the mobile communications	GB/T 9410-2008
	Radiation pattern		
Antenna	Radiation efficiency	IEEE Standard Test Procedures for Antennas	ANSI/IEEE Std 149-1979
	Gain and directivity		

3.2 Test uncertainty

The uncertainty was calculated on the basis of the GUM published by ISO, using the inclusion factor of $K=2$ and the 95% confidence level to express the extended uncertainty.

Item	Uncertainty
Antenna gain	$\pm 1\text{dB}$
Radiation efficiency	$\pm 10\%$

3.3 Test data


3.3.1 Typical free space efficiency and gain

Frequency/MHz	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Peak Gain/dBi	-1.01	-0.96	-0.87	-0.38	-0.69	-0.13	-0.28	0.38	0.11	0.73	0.57
Efficiency/%	14.62	14.94	15.56	17.14	16.55	18.64	18.47	21.70	20.08	23.09	21.83

3.3.2 Typical free space radiation pattern


(1) 2400-2500MHz X-Z Plane:

V Phi=0




(2) 2400-2500MHz Y-Z Plane:

V Phi=90




(3) 2400-2500MHz X-Y Plane:

H Theta=90



(4) Typical Free Space 3D Radiation Pattern at 2.45GHz:



End

(The following is blank)