

RF TEST REPORT

For

CDI HONG KONG HOLDINGS LIMITED
Product Name: Bendable wearable
Test Model(s).: C6814

Report Reference No. : POCE240329004EC001
FCC ID : 2A833-C6814

Applicant's Name : CDI HONG KONG HOLDINGS LIMITED
Address : Flat A, 16 Floor, Easy Tower, 609 Tai Nan West Street, Cheung Sha Wan, Kowloon, Hong Kong

Testing Laboratory : Shenzhen POCE Technology Co., Ltd.
Address : 101-102 Building H5 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China

Test Specification Standard : 47 CFR Part 15.231 & ANSI C63.10-2013

Date of Receipt : March 29, 2024
Date of Test : March 29, 2024 to April 3, 2024
Date of Issue : April 3, 2024
Result : Pass

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen POCE Technology Co., Ltd. This document may be altered or revised by Shenzhen POCE Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Revision History Of Report

Version	Description	REPORT No.	Issue Date
V1.0	Original	POCE240329004EC001	April 3, 2024

NOTE1:

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Compiled by:

Keren Huang

Keren Huang / Test Engineer

Supervised by:

Stone Yin

Stone Yin / Project Engineer

Approved by:

Tom Chen

Tom Chen / Manager

CONTENTS

1	TEST SUMMARY	4
1.1	TEST STANDARDS	4
1.2	SUMMARY OF TEST RESULT	4
2	GENERAL INFORMATION	5
2.1	CLIENT INFORMATION	5
2.2	DESCRIPTION OF DEVICE (EUT).....	5
2.3	DESCRIPTION OF TEST MODES.....	5
2.4	DESCRIPTION OF SUPPORT UNITS	5
2.5	EQUIPMENTS USED DURING THE TEST	6
2.6	STATEMENT OF THE MEASUREMENT UNCERTAINTY	7
2.7	IDENTIFICATION OF TESTING LABORATORY	7
2.8	ANNOUNCEMENT	8
3	EVALUATION RESULTS (EVALUATION).....	9
3.1	ANTENNA REQUIREMENT.....	9
3.1.1	Conclusion:.....	9
4	RADIO SPECTRUM MATTER TEST RESULTS (RF).....	10
4.1	CONDUCTED EMISSION AT AC POWER LINE	10
4.1.1	E.U.T. Operation:.....	10
4.1.2	Test Setup Diagram:.....	10
4.1.3	Test Data:	11
4.2	20dB BANDWIDTH.....	13
4.2.1	E.U.T. Operation:.....	13
4.2.2	Test Setup Diagram:.....	14
4.2.3	Test Data:	14
4.3	DUTY CYCLE	15
4.3.1	E.U.T. Operation:.....	15
4.3.2	Test Setup Diagram:.....	15
4.3.3	Test Data:	16
4.4	AVERAGE FACTOR	17
4.4.1	E.U.T. Operation:.....	17
4.4.2	Test Setup Diagram:.....	17
4.4.3	Test Data:	18
4.5	RADIATED EMISSION (BELOW 1GHz).....	20
4.5.1	E.U.T. Operation:.....	21
4.5.2	Test Setup Diagram:.....	21
4.5.3	Test Data:	22
4.6	RADIATED EMISSION (ABOVE 1GHz)	24
4.6.1	E.U.T. Operation:.....	25
4.6.2	Test Setup Diagram:.....	25
4.6.3	Test Data:	26
5	TEST SETUP PHOTOS	28
6	PHOTOS OF THE EUT	30

1 TEST SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15.231: Periodic operation in the band 40.66-40.70 MHz and above 70 MHz

1.2 Summary of Test Result

Item	Method	Requirement	Result
Antenna requirement	/	47 CFR 15.203	Pass
Conducted Emission at AC power line	ANSI C63.10-2013 section 6.2	47 CFR 15.207(a)	Pass
20dB Bandwidth	ANSI C63.10-2013, section 6.9.2	47 CFR 15.231(c)	Pass
Dwell Time	ANSI C63.10-2013, Section 7.4	47 CFR 15.231(a)(1) & (a)(2)	Pass
Duty Cycle	ANSI C63.10-2013, Section 7.5	47 CFR 15.231(b) & (e)	Pass
Field Strength of The Fundamental Signal	ANSI C63.10-2013, Section 6.5	47 CFR 15.231(b)	Pass
Radiated Emission (below 1GHz)	ANSI C63.10-2013, Section 6.5	47 CFR 15.231	Pass
Radiated Emission (above 1GHz)	ANSI C63.10-2013, Section 6.6	47 CFR 15.231	Pass

2 GENERAL INFORMATION

2.1 Client Information

Applicant's Name : CDI HONG KONG HOLDINGS LIMITED
Address : Flat A, 16 Floor, Easy Tower, 609 Tai Nan West Street, Cheung Sha Wan, Kowloon, Hong Kong

Manufacturer : CDI HONG KONG HOLDINGS LIMITED
Address : Flat A, 16 Floor, Easy Tower, 609 Tai Nan West Street, Cheung Sha Wan, Kowloon, Hong Kong

2.2 Description of Device (EUT)

Product Name:	Bendable wearable
Model/Type reference:	C6814
Series Model:	6814T, 6814, 6814C
Model difference:	Their electrical circuit design, layout, components used and internal wiring are identical, The product name is slightly different according to the needs, but it will not affect any EMC/RF performance of the product .
Trade Mark:	N/A
Product Description:	Bendable wearable
Power Supply:	DC3.7V from battery
Operation Frequency:	433.92MHz
Number of Channels:	1
Modulation Type:	ASK
Antenna Type:	PCB ANTENNA
Antenna Gain:	0.58dBi
Hardware Version:	V1.0
Software Version:	N/A

2.3 Description of Test Modes

No	Title	Description
TM1	TM1	Continuous TX

2.4 Description of Support Units

Title	Manufacturer	Model No.	Serial No.
AC-DC adapter	HUAWEI	P0005	/

2.5 Equipments Used During The Test

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
loop antenna	EVERFINE	LLA-2	80900L-C	2024-02-19	2025-02-18
Power absorbing clamp	SCHWARZ BECK	MESS-ELEKTRONIK	/	2023-12-12	2024-12-11
Electric Network	SCHWARZ BECK	CAT5 8158	CAT5 8158#207	/	/
Cable	SCHWARZ BECK	/	/	2023-12-27	2024-12-26
Pulse Limiter	SCHWARZ BECK	VTSD 9561-F Pulse limiter 10dB Ateennator	561-G071	2023-12-12	2024-12-11
50ΩCoaxial Switch	Anritsu	MP59B	M20531	/	/
Test Receiver	Rohde & Schwarz	ESPI TEST RECEIVER	ID:1164.6607 K03-102109-MH	2023-06-13	2024-06-12
L.I.S.N	R&S	ESH3-Z5	831.5518.52	2023-12-12	2024-12-11

Duty Cycle 20dB Bandwidth Dwell Time					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	Tachoy Information	RTS-01	V2.0.0.0	/	/
RF Sensor Unit	Tachoy Information	TR1029-2	000001	/	/
Vector signal generator	Keysight	N5181A	MY48180415	2023-11-09	2024-11-08
Signal generator	Keysight	N5182A	MY50143455	2023-11-09	2024-11-08
Spectrum Analyzer	Keysight	N9020A	MY53420323	2023-12-12	2024-12-11

Field Strength of The Fundamental Signal
Radiated Emission (below 1GHz)
Radiated Emission (above 1GHz)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	V1.1.42	/	/
Positioning Controller	/	MF-7802	/	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2022-04-05	2025-04-04
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2023-04-05	2025-04-04
Loop antenna	ZHINAN	ZN30900C	ZN30900C	2021-07-05	2024-07-04
Cable(LF)#2	Schwarzbeck	/	/	2024-02-19	2025-02-18
Cable(LF)#1	Schwarzbeck	/	/	2024-02-19	2025-02-18
Cable(HF)#2	Schwarzbeck	AK9515E	96250	2024-02-19	2025-02-18
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2024-02-19	2025-02-18
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2023-06-13	2024-06-12
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2023-06-13	2024-06-12
Spectrum Analyzer	R&S	FSP30	1321.3008K40 -101729-jR	2023-06-14	2024-06-13
Horn Antenna	Sunol Sciences	DRH-118	A091114	2023-05-13	2025-05-12
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2023-05-21	2025-05-20
Test Receiver	R&S	ESCI	102109	2023-06-13	2024-06-12

2.6 Statement Of The Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Disturbance (0.15~30MHz)	±3.41dB
Occupied Bandwidth	±3.63%
Duty cycle	±3.1%
Radiated Emission (Below 1GHz)	±5.79dB
Radiated Emission (Above 1GHz)	±5.46dB

Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.7 Identification of Testing Laboratory

Company Name:	Shenzhen POCE Technology Co., Ltd.
Address:	101-102 Building H5 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252

Identification of the Responsible Testing Location

Company Name:	Shenzhen POCE Technology Co., Ltd.
---------------	------------------------------------

Address:	101-102 Building H5 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252
FCC Registration Number:	0032847402
Designation Number:	CN1342
Test Firm Registration No.:	778666
A2LA Certificate Number:	6270.01

2.8 Announcement


- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by POCE and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) We hereby declare that the laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant. the laboratory is not responsible for the accuracy of the information provided by the client. When the information provided by the customer may affect the effectiveness of the results, the responsibility lies with the customer, and the laboratory does not assume any responsibility.

3 Evaluation Results (Evaluation)

3.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

3.1.1 Conclusion:



4 Radio Spectrum Matter Test Results (RF)


4.1 Conducted Emission at AC power line

Test Requirement:	<p>Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN).</p>			
Test Limit:	Frequency of emission (MHz)		Conducted limit (dB μ V)	
		Quasi-peak	Average	
	0.15-0.5	66 to 56*	56 to 46*	
	0.5-5	56	46	
	5-30	60	50	
*Decreases with the logarithm of the frequency.				
Test Method:	ANSI C63.10-2013 section 6.2			
Procedure:	Refer to ANSI C63.10-2013 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices			

4.1.1 E.U.T. Operation:


Operating Environment:					
Temperature:	22.3 °C	Humidity:	50 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.1.2 Test Setup Diagram:




4.1.3 Test Data:

TM1 / Line: Line



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.3100	3.01	10.02	13.03	49.97	-36.94	AVG	
2		0.3420	20.30	10.01	30.31	59.15	-28.84	QP	
3		0.4880	17.80	9.98	27.78	56.24	-28.46	QP	
4	*	0.4940	12.52	9.98	22.50	46.10	-23.60	AVG	
5		1.1140	17.93	9.90	27.83	56.00	-28.17	QP	
6		1.2059	8.26	9.92	18.18	46.00	-27.82	AVG	
7		1.5260	18.59	9.93	28.52	56.00	-27.48	QP	
8		1.5580	9.51	9.94	19.45	46.00	-26.55	AVG	
9		7.4680	7.55	10.28	17.83	60.00	-42.17	QP	
10		7.9020	-2.96	10.30	7.34	50.00	-42.66	AVG	
11		16.2340	-0.47	10.48	10.01	50.00	-39.99	AVG	
12		17.3819	16.29	10.50	26.79	60.00	-33.21	QP	

TM1 / Line: Neutral



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.1539	24.15	10.04	34.19	65.78	-31.59		QP	
2	0.1780	6.90	10.03	16.93	54.57	-37.64		AVG	
3	*	0.3480	22.09	10.01	32.10	59.06	-26.96	QP	
4	0.4940	6.45	9.98	16.43	46.10	-29.67		AVG	
5	1.1100	17.05	9.90	26.95	56.00	-29.05		QP	
6	1.1180	5.02	9.90	14.92	46.00	-31.08		AVG	
7	1.8620	14.08	9.96	24.04	56.00	-31.96		QP	
8	1.8820	-0.23	9.96	9.73	46.00	-36.27		AVG	
9	4.7619	-2.43	10.13	7.70	46.00	-38.30		AVG	
10	4.7880	10.51	10.13	20.64	56.00	-35.36		QP	
11	10.5900	0.81	10.44	11.25	50.00	-38.75		AVG	
12	10.6340	12.81	10.44	23.25	60.00	-36.75		QP	

4.2 20dB Bandwidth


Test Requirement:	47 CFR 15.231(c)
Test Limit:	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.
Test Method:	ANSI C63.10-2013, section 6.9.2
Procedure:	<p>a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.</p> <p>b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.</p> <p>c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.</p> <p>d) Steps a) through c) might require iteration to adjust within the specified tolerances.</p> <p>e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 Db OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.</p> <p>f) Set detection mode to peak and trace mode to max hold.</p> <p>g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).</p> <p>h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.</p> <p>i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).</p> <p>j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “ixx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “ixx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.</p> <p>k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).</p>

4.2.1 E.U.T. Operation:

Operating Environment:				
Temperature:	23.4 °C	Humidity:	48.2 %	Atmospheric Pressure: 101 kPa
Pretest mode:	TM1			

Final test mode:	TM1
------------------	-----

4.2.2 Test Setup Diagram:



4.2.3 Test Data:

Condition	Antenna	Frequency (MHz)	20dB BW(kHz)	limit(MHz)	Result
NVNT	ANT1	433.92	17.31	1.0848	Pass




4.3 Duty Cycle


Test Requirement:	47 CFR 15.231(b) & (e)
Test Limit:	No limit, only for Report Use.
Test Method:	ANSI C63.10-2013, Section 7.5
Procedure:	<p>a) Adjust and configure any EUT switches, controls, or input data streams to ensure that the EUT is transmitting or encoded to obtain the “worst-case” pulse ON time.</p> <p>b) Couple the final radio frequency output signal to the input of a spectrum analyzer. This may be performed by a radiated, direct connection (i.e., conducted) or by a “near-field” coupling method. The signal received shall be of sufficient level to trigger adequately the spectrum analyzer sweep display.</p> <p>NOTE—If the bandwidth of the pulse is greater than the RBW of the spectrum analyzer, then a similar measurement may be performed using a wideband digital storage oscilloscope (DSO).</p> <p>c) Adjust the center frequency of the spectrum analyzer to the center of the RF signal.</p> <p>d) Set the spectrum analyzer for ZERO SPAN.</p> <p>e) Adjust the SWEEP TIME to obtain at least a 100 ms period of time on the horizontal display axis of the spectrum analyzer.</p> <p>f) If the pulse train is periodic (i.e., consists of a series of pulses that repeat in a characteristic pattern over a constant time period), and the period (T) is less than or equal to 100 ms, then:</p> <ol style="list-style-type: none"> 1) Set the TRIGGER on the spectrum analyzer to capture at least one period of the pulse train, including any blanking intervals. 2) Determine the total maximum pulse “ON time” (t_{ON}) over one period of the pulse train. An example of a periodic pulse train and the associated period is shown in Figure 14. If the pulse train contains pulses of different widths, then t_{ON} is determined by summing the duration of all of the pulses within the pulse train [i.e., $t_{ON} = \sum(t_1 + t_2 + \dots + t_n)$]. 3) The duty cycle is then determined by dividing the total maximum “ON time” by the period of the pulse train (t_{ON}/T). <p>g) If the pulse train is nonperiodic or is periodic with a period that exceeds 100 ms, or as an alternative to step f), then:</p> <ol style="list-style-type: none"> 1) Set the TRIGGER on the spectrum analyzer to capture the greatest amount of pulse “ON time” over 100 ms. 2) Find the 100 ms period that contains the maximum “on time”; this may require summing the duration of multiple pulses as described in step f2). 3) Determine the duty cycle by dividing the total maximum “ON time” by 100 ms ($t_{ON}/100 \text{ ms}$).

4.3.1 E.U.T. Operation:

Operating Environment:				
Temperature:	23.4 °C	Humidity:	48.2 %	Atmospheric Pressure: 101 kPa
Pretest mode:	TM1			
Final test mode:	TM1			


4.3.2 Test Setup Diagram:





4.3.3 Test Data:

Condition	Antenna	Frequency (MHz)	Dwell time(s)	limit(s)	Result
NVNT	ANT1	433.92	0.3s	5s	Pass




4.4 Average Factor

Procedure:	<p>The output field strengths of specification in accordance with the FCC rules specify measurements with an average detector. During the test, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.</p> <p>The duty cycle is measured in 100 ms or the repetition cycle period, whichever is a shorter time frame. The duty cycle is measured by placing the spectrum analyzer to set zero span at 100kHz resolution bandwidth.</p>
Factor:	<p>Averaging factor in dB =$20\log(\text{duty cycle})$ The duration of one cycle =44ms The duty cycle is simply the on-time divided the duration of one cycle $\text{Duty Cycle} = (13*1.02 + 13*0.510)/44 = 19.89/44 = 0.45205$ Therefore, the averaging factor is found by $20*\log(0.45205) = -6.90\text{dB}$ Test plot as follows: Note: During the 100ms, the amount of pulse and on-time of pulse are the same for every pulse train.</p>


4.4.1 E.U.T. Operation:

Operating Environment:				
Temperature:	22.3 °C	Humidity:	51.7 %	Atmospheric Pressure: 102 kPa
Pre test mode:	TM1			
Final test mode:	TM1			

4.4.2 Test Setup Diagram:



4.4.3 Test Data:





4.5 Radiated Emission (below 1GHz)

Test Requirement:	47 CFR 15.231		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>			
Test Method:	ANSI C63.10-2013, Section 6.5		
Procedure:	<p>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel, the middle channel, the Highest channel.</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p> <p>Remark:</p> <ol style="list-style-type: none"> 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been 		


	displayed.
--	------------

4.5.1 E.U.T. Operation:

Operating Environment:


Temperature:	23.4 °C	Humidity:	48.2 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.5.2 Test Setup Diagram:



4.5.3 Test Data:

TM1 / Polarization: Horizontal / BW: 0.02 / CH: M




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	30.2110	23.91	-2.92	20.99	40.00	-19.01	peak			P	
2	113.7142	24.58	-5.07	19.51	40.00	-20.49	peak			P	
3	150.0107	25.02	-3.73	21.29	40.00	-18.71	peak			P	
4	355.4272	24.45	1.72	26.17	47.00	-20.83	peak			P	
5 *	434.0650	84.85	1.21	86.06	100.8	-14.74	peak			P	Fundamental
6 X	869.1301	52.06	7.20	59.26	80.80	-21.54	peak			P	

Frequency (MHz)	Level (dBuV/m)	AV factor (dB)	Final Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Result
434.0650	86.06	/	86.06	100.8	-14.74	PK	Pass
434.0650	/	-6.90	79.16	80.80	-1.64	AV	Pass
869.1301	59.26	/	59.26	80.80	-21.54	PK	Pass
869.1301	/	-6.90	52.36	60.80	-8.44	AV	Pass

AV Level =PK Level + AV factor, Margin= Final Level - Limit

TM1 / Polarization: Vertical / BW: 0.02 / CH: M



Frequency (MHz)	Level (dBuV/m)	AV factor (dB)	Final Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Result
434.0650	85.45	/	85.45	100.8	-15.35	PK	Pass
434.0650	/	-6.90	78.55	80.80	-2.25	AV	Pass
869.1301	65.83	/	65.83	80.80	-14.97	PK	Pass
869.1301	/	-6.90	58.93	60.80	-1.87	AV	Pass

AV Level =PK Level + AV factor, Margin= Final Level - Limit

4.6 Radiated Emission (above 1GHz)


Test Requirement:	47 CFR 15.231		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>			
Test Method:	ANSI C63.10-2013, Section 6.6		
Procedure:	<p>a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel, the middle channel, the Highest channel.</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p> <p>Remark:</p> <ol style="list-style-type: none"> 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not 		

	exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	---

4.6.1 E.U.T. Operation:


Operating Environment:			
Temperature:	23.4 °C	Humidity:	48.2 %
Pretest mode:	TM1		
Final test mode:	TM1		

4.6.2 Test Setup Diagram:



4.6.3 Test Data:


TM1 / Polarization: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	1300.000	57.68	-2.31	55.37	74.00	-18.63	peak			P	
2	1735.000	56.38	0.20	56.58	74.00	-17.42	peak			P	
3	2170.000	55.44	1.71	57.15	74.00	-16.85	peak			P	
4	3035.000	57.04	-2.46	54.58	74.00	-19.42	peak			P	
5 *	3470.000	61.50	-0.52	60.98	74.00	-13.02	peak			P	
6	3905.000	57.31	0.85	58.16	74.00	-15.84	peak			P	

Frequency (MHz)	Level (dBuV/m)	AV factor (dB)	Final Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Result
1300.00	55.37	/	55.37	80.8	-25.43	PK	Pass
1300.00	/	-6.9	48.47	60.8	-12.33	AV	Pass
1735.00	56.58	/	56.58	80.8	-24.22	PK	Pass
1735.00	/	-6.9	49.68	60.8	-11.12	AV	Pass
2170.00	57.15	/	57.15	80.8	-23.65	PK	Pass
2170.00	/	-6.9	50.25	60.8	-10.55	AV	Pass
3035.00	54.58	/	54.58	80.8	-26.22	PK	Pass
3035.00	/	-6.9	47.68	60.8	-13.12	AV	Pass
3470.00	60.98	/	60.98	80.8	-19.82	PK	Pass
3470.00	/	-6.9	54.08	60.8	-6.72	AV	Pass
3905.00	58.16	/	58.16	80.8	-22.64	PK	Pass
3905.00	/	-6.9	51.26	60.8	-9.54	AV	Pass



TM1 / Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	1735.000	60.50	-1.66	58.84	74.00	-15.16	peak			P	
2 *	2605.000	59.55	1.98	61.53	74.00	-12.47	peak			P	
3	3035.000	62.34	-2.39	59.95	74.00	-14.05	peak			P	
4	3475.000	59.10	-0.82	58.28	74.00	-15.72	peak			P	
5	3905.000	54.23	0.70	54.93	74.00	-19.07	peak			P	
6	4340.000	51.82	2.18	54.00	74.00	-20.00	peak			P	

Frequency (MHz)	Level (dBuV/m)	AV factor (dB)	Final Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Result
1735.00	58.84	/	58.84	80.8	-21.96	PK	Pass
1735.00	/	-6.9	51.94	60.8	-8.86	AV	Pass
2605.00	61.53	/	61.53	80.8	-19.27	PK	Pass
2605.00	/	-6.9	54.63	60.8	-6.17	AV	Pass
3035.00	59.95	/	59.95	80.8	-20.85	PK	Pass
3035.00	/	-6.9	53.05	60.8	-7.75	AV	Pass
3475.00	58.28	/	58.28	80.8	-22.52	PK	Pass
3475.00	/	-6.9	51.38	60.8	-9.42	AV	Pass
3905.00	54.93	/	54.93	80.8	-25.87	PK	Pass
3905.00	/	-6.9	48.03	60.8	-12.77	AV	Pass
4340.00	54.00	/	54.00	80.8	-26.8	PK	Pass
4340.00	/	-6.9	47.1	60.8	-13.7	AV	Pass

5 TEST SETUP PHOTOS

Radiated Emission (below 1GHz)**Radiated Emission (above 1GHz)**

Conducted Emission



6 PHOTOS OF THE EUT

External










Internal







***** End of Report *****