

1. RF Exposure Requirements

1.1 General Information

Client Information

Applicant: Xiamen Comfier Technology Co.,Ltd
Address of applicant: 2/F,3/F,4/F,5/F, No. 65 Sunban South Road, JiMei District, Xiamen, China

Manufacturer: Xiamen Anmmacare Science & Technology CO., LTD
Address of manufacturer: Building C, 99-2, Tongfu Road, Tongan District, Xiamen City

General Description of EUT:

Product Name: MASSAGE CHAIR
Trade Name: COMFIER
Model No.: CF-9216
Adding Model(s): /
Rated Voltage: AC120V
Battery Capacity: /
FCC ID: 2A835CF-9216
Equipment Type: Fixed device

Technical Characteristics of EUT:

Bluetooth

Bluetooth Version: V4.0 (BR/EDR mode)
Frequency Range: 2402-2480MHz
RF Output Power: 2.48dBm (Conducted)
Data Rate: 1Mbps, 2Mbps
Modulation: GFSK, $\pi/4$ DQPSK
Quantity of Channels: 79
Channel Separation: 1MHz
Type of Antenna: PCB Antenna
Antenna Gain: -7.24dBi

1.2 RF Exposure Exemption

According to §1.1307(b)(3) and 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Option A: FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

Option B: FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option C: FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$
1.34-30	$3,450 R^2/f^2$
30-300	$3.83 R^2$
300-1,500	$0.0128 R^2 f$
1,500-100,000	$19.2 R^2$

For Multiple RF sources: FCC Rule Part 1.1307(b)(3)(ii):

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).

(B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

1.3 Calculated Result

Radio Access Technology	Min. Frequency	Max. Output Power	Max. Tune-Up Output Power	Antenna Gain	Duty Cycle	Tune-Up EIRP
	(MHz)	(dBm)	(dBm)	(dBi)	(%)	(dBm)
Bluetooth	2402	2.48	3.00	-7.24	100	-4.24

Frequency	Option	Min. Distance	Tune-Up ERP		Exposure Limit	Ratio	Result
		(cm)	(dBm)	(mW)	(mW)		Pass/Fail
2402	B	0.5	-6.39	0.23	2.79	0.08	Pass

Note: 1. $ERP = EIRP - 2.15dB$; $EIRP = Output\ Power + Antenna\ gain$

2. Option A, B and C refers as clause 1.2.
3. For option B, $P_{th}(mW)$ convert to $Exposure\ Limit(mW)$; For option C, $ERP(W)$ convert to $Exposure\ Limit(mW)$.
4. $Ratio = Tune-Up\ ERP(mW) / Exposure\ Limit(mW)$

Mode for Simultaneous Multi-band Transmission:

Radio Access Technology	Ratio 1	Ratio 2	Simultaneous Ratio	Limit	Result
					Pass/Fail
--	--	--	--	--	--

Result: Pass