



1938 Occidental Ave South, Suite C, Seattle, WA 98134

Federal Communications Commission
Authorization and Evaluation Division
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, MD 21046

May 8, 2023

Re: Declaration concerning Antenna Specification for:

Product name: GFD200 with FCC ID 2A83C-BZQ6R

To Whom It May Concern:

It is hereby declared that the product fulfils the requirement in FCC tests relating to the antenna type.

Evaluation criteria

47 CFR Part 15, Subpart C (Specific rule part §15.203) state that the subject device must meet at least one of the following criteria:

- (a) Antenna must be permanently attached to the unit.
- (b) Antenna must use a unique type of connector to attach the unit.
- (c) Unit must be professionally installed. Installer shall be responsible for verifying that the correct antenna is employed with the unit.

The device specified above confirms to the FCC recommendations for Internal antenna type described below:

Model No. of antenna: PRO-OB-440

Evaluation criteria: a

Type of antenna: Surface Mount PCBA mounted antennas

Gain of the antenna: §15.247: <5.0 dBi

Frequency range: §15.247: 2400-2483.5MHz

Please see attached **Exhibit A** for photograph of the antenna within the product and **Exhibit B** for specifications.


Please contact me if there is any information you may need.

Sincerely,



Nick Woolger, Principal Electrical Engineer
Glowforge Inc.

Exhibit A:
Photograph of Antenna



Shared BT, Wi-Fi and BLE Antenna - 2.4 GHz

Exhibit B:
Specifications
(See next pages.)

OnBoard 2.4 GHz SMD - Antenna



PRO-OB-440

Request Samples



Check Inventory



13.75 x 5.23 x 3.53 mm
RoHS/RoHS II Compliant
MSL Level = 1


Features

- Compact
- Low Cost
- Mixed Linear Polarization
- Peak Gain of less than 5 dBi
- Efficiency > 65%
- Surface Mount
- Durable-Shelf life of up to 10 years

Applications

- 2.4 GHz - Wi-Fi/BT/BLE/ZigBee/ISM
- IoT, M2M
 - Industrial IoT
 - Consumer IoT
 - Medical IoT
- Telemetry
- Wireless Remote Control
- Personal Area Networks (PAN)
- Industrial/Commercial Equipments

Product Image



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-01-22

ABRACON IS
ISO9001-2015
CERTIFIED

OnBoard 2.4 GHz SMD - Antenna



PRO-OB-440

[Request Samples](#)[Check Inventory](#)

13.75 x 5.23 x 3.53 mm
RoHS/RoHS II Compliant
MSL Level = 1

Electrical Specification

Parameter	Specification	Unit
Operating Frequency	2400 - 2500	MHz
Center Frequency	2450	
Return Loss	< -6.9	dB
Polarization	Mixed Linear	-
Maximum Gain	< 5.0	dBi
Efficiency	> 65	%
Impedance	50	Ω

Note: All measurements were conducted on the evaluation board in free space. Performance will vary depending on the ground plane, application, and environment.

Mechanical Specification

Parameter	Specification
Antenna Dimension	13.75 x 5.23 x 3.53 mm
Evaluation board Dimension	100 x 50 mm
Mounting Type	Surface Mount

Environmental Specification

Parameter	Specification
Operating Temperature	-40°C to +125°C
Storage Temperature	
Maximum Temperature	400°C
RoHS Compliance	Yes Compliant with EU directive 2011/65/EU and 2015/863
Shelf life	10 years
MSL	Level 1, unlimited
Mechanical resistance	Immunity to vibrations IEC/EN 60068-2-6, Fc test Immunity to shock IEC/EN 60068-2-27, Ea test

OnBoard 2.4 GHz SMD - Antenna



PRO-OB-440

Request Samples




Check Inventory




13.75 x 5.23 x 3.53 mm
RoHS/RoHS II Compliant
MSL Level = 1

Product Dimension



Unit : mm

Antenna pins and keep-out block



Unit : mm



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-01-22

ABRACON IS
ISO9001-2015
CERTIFIED

OnBoard 2.4 GHz SMD - Antenna



PRO-OB-440

Request Samples



Check Inventory



13.75 x 5.23 x 3.53 mm
RoHS/RoHS II Compliant
MSL Level = 1

PCB layout and antenna pin numbering


The antenna uses PIFA technology and should thus be mounted on a ground plane. If there are several layers in the PCB, there is an advantage to add vias for smooth interconnection of the ground areas to avoid splits in the ground plane. It is also important that there is a ground clearance around the NC pads and the RF feed pad, through all layers of the PCB. It is recommended to implement a matching network to optimize the antenna impedance in your application. The components can be positioned under the antenna. See recommendations in the figures below.

3 ■ ■ 1
■ 2



4 ■

1 = GND
2 = RF FEED
3 = NC
4 = NC

Pin configuration



PCB Layout (from evaluation board)



Clearance through all layers

Unit : mm



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-01-22

ABRACON IS
ISO9001-2015
CERTIFIED

OnBoard 2.4 GHz SMD - Antenna



PRO-OB-440

Request Samples




Check Inventory



13.75 x 5.23 x 3.53 mm
RoHS/RoHS II Compliant
MSL Level = 1

Measurement Setup

The antenna measurements were all done in free space with the OnBoard SMD 2400 evaluation board (PRO-EB-450) that has a PCB size of 100 x 50 mm.



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-01-22

ABRACON IS
ISO9001-2015
CERTIFIED

OnBoard 2.4 GHz SMD - Antenna



PRO-OB-440

Request Samples




Check Inventory




13.75 x 5.23 x 3.53 mm
RoHS/RoHS II Compliant
MSL Level = 1


Reflection Characteristics – Return Loss



Total Radiation Efficiency



Maximum Radiation Gain



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-01-22

ABRACON IS
ISO9001-2015
CERTIFIED

OnBoard 2.4 GHz SMD - Antenna



PRO-OB-440

Request Samples




Check Inventory




13.75 x 5.23 x 3.53 mm
RoHS/RoHS II Compliant
MSL Level = 1

Radiation Characteristics – 2D Pattern (2400 MHz)



VP: Vertical Polarization
HP: Horizontal Polarization

Unit: dBi



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-01-22

ABRACON IS
ISO9001-2015
CERTIFIED

OnBoard 2.4 GHz SMD - Antenna



PRO-OB-440

Request Samples




Check Inventory




13.75 x 5.23 x 3.53 mm
RoHS/RoHS II Compliant
MSL Level = 1

Radiation Characteristics – 2D Pattern (2500 MHz)



VP: Vertical Polarization
HP: Horizontal Polarization

Unit: dBi



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-01-22

ABRACON IS
ISO9001-2015
CERTIFIED

OnBoard 2.4 GHz SMD - Antenna



PRO-OB-440

Request Samples




Check Inventory



13.75 x 5.23 x 3.53 mm
RoHS/RoHS II Compliant
MSL Level = 1


Evaluation Board Outline & Matching Circuit

The evaluation board (PRO-EB-450) is developed to simplify antenna testing and evaluation. It has an arbitrary size of 100 x 50 mm and includes an SMA connector. The purpose is to give a reference design for an optimal antenna implementation. The evaluation board can also be used to test other implementations by cutting and soldering the PCB into any device.



Evaluation board outline

The evaluation board has a matching circuit implemented next to the antenna. This is aimed to enable optimization possibilities for the user. The component positions are sized for 0402 (1005 metric) SMD components.



Matching circuit

The antenna needs a matching circuit to adjust the resonant frequency balance. When delivered, the evaluation board is tuned for optimum balance at the 2.4 GHz frequency band using the following (can be replaced by equivalent):

$$C1 = 1.5 \text{ nH (LQW15AN1N5B00D)} \quad C2 = 0.5 \text{ pF (GRM1555C1HR50WA01D)} \quad C3 = \text{N/A}$$

However, it is common that the resonant frequency will shift during implementation in an arbitrary device. Therefore, this matching may be changed with other values/components/brands for compensation of such effects. This is further described in the General Implementation Guidelines section below.



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-01-22

ABRACON IS
ISO9001-2015
CERTIFIED




PRO-OB-440

[Request Samples](#)[Check Inventory](#)

13.75 x 5.23 x 3.53 mm
RoHS/RoHS II Compliant
MSL Level = 1

General Implementation Guidelines

The antenna can be positioned in different ways, although there are some positions which are more beneficial. Below picture shows a typical PCB with examples on different antenna positions. The optimal position is option 1 or 4.



The antenna should be aligned with the PCB edge if possible, preferably with the GND pin(s) close to a corner.

The antenna enables that small electrical components are mounted inside the antenna keep-out block. This is a space-efficient solution which has very little influence on the performance. It may have an impact on the antenna tuning, but is fully possible if there is limited space on the PCB.

Another general aspect on surface mounted antennas is regarding the PCB population. If other electrical components are positioned in the surrounding area of the antenna, some impact on the antenna tuning and radiated performance may be expected. It is recommended that such components are distributed below a topographical slope that starts on PCB level at the antenna keep-out block, and slowly increases the height.

It shall also be highlighted that plastic and metal parts in the near proximity of antennas may influence the antenna tuning and/or performance. This aspect should be noted as a general guideline for all antennas. The effects are difficult to estimate without detailed information, but it is common that a plastic housing above the antenna shifts the resonant frequency down. It is recommended to measure the antenna in the actual device after implementation.


OnBoard 2.4 GHz SMD - Antenna

**PRO-OB-440**[Request Samples](#)[Check Inventory](#)

13.75 x 5.23 x 3.53 mm
RoHS/RoHS II Compliant
MSL Level = 1

Packaging

The antenna is delivered on tape and reel according to following specifications. The quantity per 13" reel is 1000 pcs.



Unit: mm (unless otherwise noted)



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-01-22

ABRACON IS
ISO9001-2015
CERTIFIED

OnBoard 2.4 GHz SMD - Antenna



PRO-OB-440

Request Samples



Check Inventory



13.75 x 5.23 x 3.53 mm
RoHS/RoHS II Compliant
MSL Level = 1

Part Marking

The top marking of the antenna is arranged according to the following illustration.

Abracon

440


Product part number

YYWW

Date code

YY=Year

WW=Week



Example top marking

There will be a transition period for the part marking until production batches after 2222 (YYWW). Produced batches before 2222 are marked according to the below illustration.

(YYWW) *Date code*
Proant *YY=Year*
(P/N) *WW=Production week*

Product part number



Example top marking

Ordering Information

Part number	Part name	Details
PRO-OB-440	OnBoard SMD 2400	Antenna for 2.4-2.5 GHz.
PRO-EB-450	Evaluation board, Onboard SMD 2400	Evaluation board with PRO-OB-440 for 2.4 - 2.5 GHz (Wi-Fi/BT/BLE/Zigbee) applications.

ATTENTION: Abracon LLC's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon LLC is required. Please contact Abracon LLC for more information.



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-01-22

ABRACON IS
ISO9001-2015
CERTIFIED

Title	Glowforge Inc. - Antenna_info_5-8-2023
File name	Glowforge Inc. - ...info_5-8-2023.pdf
Document ID	b22dd8e71e0c24633d5f7593f1d10b729b9268ae
Audit trail date format	MM / DD / YYYY
Status	● Signed

Document History

 SENT	05 / 09 / 2023 19:19:20 UTC	Sent for signature to Nick Woolger (nickw@glowforge.com) from leslie.clark@glowforge.com IP: 76.34.211.123
 VIEWED	05 / 10 / 2023 00:59:11 UTC	Viewed by Nick Woolger (nickw@glowforge.com) IP: 75.172.67.99
 SIGNED	05 / 10 / 2023 01:00:03 UTC	Signed by Nick Woolger (nickw@glowforge.com) IP: 75.172.67.99
 COMPLETED	05 / 10 / 2023 01:00:03 UTC	The document has been completed.