

# TEST REPORT

<b>FCC ID.</b> .....	2A84O-LSEM003	
<b>Test Report No.</b> .....	TCT221010E009	
<b>Date of issue</b> .....	Oct. 25, 2022	
<b>Testing laboratory</b> .....	SHENZHEN TONGCE TESTING LAB	
<b>Testing location/ address:</b>	2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
<b>Applicant's name</b> .....	shen zhen shi xin yu shi ye you xian gong si	
<b>Address</b> .....	shi yan jie dao shi long she qu xing ye lu 1 hao xing guang gong ye qu A dong 3 ceng shen zhen China	
<b>Manufacturer's name</b> .....	shen zhen shi xin yu shi ye you xian gong si	
<b>Address</b> .....	shi yan jie dao shi long she qu xing ye lu 1 hao xing guang gong ye qu A dong 3 ceng shen zhen China	
<b>Standard(s)</b> .....	FCC CFR Title 47 Part 2.1091	
<b>Product Name</b> .....	Eye massager	
<b>Trade Mark</b> .....	BOQUBOO, fmlave, TIHONI, huhubol	
<b>Model/Type reference</b> .....	LS-EM003	
<b>Rating(s)</b> .....	DC 5V from adapter	
<b>Date of receipt of test item</b> .....	Oct. 10, 2022	
<b>Date (s) of performance of test</b> .....	Oct. 11, 2022- Oct. 25, 2022	
<b>Tested by (+signature)</b> .....	Onnado YE	Onnado YE 
<b>Check by (+signature)</b> .....	Beryl ZHAO	Beryl ZHAO 
<b>Approved by (+signature)</b> :	Tomsin	Tomsin 

## General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

## Table of Contents

<b>1. General Product Information .....</b>	<b>3</b>
1.1. EUT description .....	3
1.2. Model(s) list.....	3
<b>2. Facilities and Accreditations .....</b>	<b>4</b>
2.1. Facilities .....	4
2.2. Location .....	4
<b>3. Test Results and Measurement Data .....</b>	<b>5</b>

## 1. General Product Information

### 1.1. EUT description

Test item description .....	Eye massager
Model/Type reference.....	LS-EM003
Sample Number.....	TCT221010E008-0101
Operation Frequency .....	2402MHz~2480MHz
Modulation Type .....	GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Type.....	PCB Antenna
Antenna Gain .....	-0.68dBi
Rating(s).....	DC 5V from adapter

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

### 1.2. Model(s) list

None.

## 2. Facilities and Accreditations

### 2.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098  
SHENZHEN TONGCE TESTING LAB  
Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1  
SHENZHEN TONGCE TESTING LAB  
CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

### 2.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China  
TEL: +86-755-27673339

### 3. Test Results and Measurement Data

KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

#### Assessment Result

Passed

Not Applicable

Type	Frequency (MHz)	Conducted Power (dBm)	Maximum Tune-up (dBm)	Calculating data	Limit	Result
BT-EDR	2402	0.60	1.00	0.39	3.0	Pass

Note: The exposure evaluation safety distance is 5mm.

\*\*\*\*\*END OF REPORT\*\*\*\*\*