



Maximum Permissible Exposure Evaluation

FCC ID: 2A84X-KAODCPPROV4

1. Client Information

Applicant	:	KICKASS PRODUCTS USA, LLC
Address	:	C/O MKC LAW, MIN CHAI 9070 IRVINE CTR DR. STE. 135 IRVINE, CA 92618
Manufacturer	:	KICKASS PRODUCTS USA, LLC
Address	:	C/O MKC LAW, MIN CHAI 9070 IRVINE CTR DR. STE. 135 IRVINE, CA 92618

2. General Description of EUT

EUT Name	:	Multimedia Projector
Models No.	:	KAODCPPROV4
Model Difference	:	----
Sample ID	:	RW-C-202209-0179-1-1#&RW-C-202209-0179-1-2#
Product Description	:	Operation Frequency: Bluetooth 5.0: 2402MHz~2480MHz Bluetooth 5.0(BLE): 2402MHz~2480MHz 802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
Power Rating	:	Adapter (FJ-SW528G1204000U) Input: 100-240V~ 50/60Hz 1.5A MAX Output: 12V=4A
Software Version	:	1.9.a_20220902
Hardware Version	:	R033_D66LVD_813 20210302
Connecting I/O Port(S)	:	Please refer to the User's Manual
Remark	:	the MPE report used the EUT-2(RW-C-202209-0179-1-2#).

MPE Calculations

1. Antenna Gain:

Antenna	Brand	Model Name	Type	Antenna Gain(dBi)
Bluetooth	N/A	N/A	PCB	1.53

Antenna	Brand	Model Name	Type	Antenna Gain(dBi)
2.4G WIFI	N/A	N/A	FPC	1.53

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Simultaneous transmission MPE Considerations

According to KDB447498: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

This means that:

$$\sum \text{ of MPE ratios } \leq 1.0$$



5. Standalone MPE Evaluation:

Bluetooth Worst Maximum MPE Result								
Mode	N _{TX}	Freq. (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
GFSK	1	2402	2.78	2±1	3	1.53	20	0.0006
		2441	2.23	2±1	3	1.53	20	0.0006
		2480	1.35	1±1	2	1.53	20	0.0004
π /4-DQPSK	1	2402	3.32	3±1	4	1.53	20	0.0007
		2441	2.78	2±1	3	1.53	20	0.0006
		2480	1.93	1±1	2	1.53	20	0.0004

Note:
N_{TX}= Number of Transmit Antennas
RF Output power specifies that Maximum Conducted Peak Output Power.

Bluetooth LE Worst Maximum MPE Result								
Mode	N _{TX}	Freq. (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
GFSK	1	2402	2.72	2±1	3	1.53	20	0.0006
		2440	2.19	2±1	3	1.53	20	0.0006
		2480	1.09	1±1	2	1.53	20	0.0004

Note:
N_{TX}= Number of Transmit Antennas
RF Output power specifies that Maximum Conducted Peak Output Power.



2.4G WiFi Worst Maximum MPE Result

Mode	N _{TX}	Freq. (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
802.11b	1	2412	11.95	11±1	12	1.53	20	0.0044
		2437	12.15	12±1	13	1.53	20	0.0056
		2462	12.47	12±1	13	1.53	20	0.0056
802.11g	1	2412	13.92	13±1	14	1.53	20	0.0071
		2437	13.61	13±1	14	1.53	20	0.0071
		2462	13.67	13±1	14	1.53	20	0.0071
802.11n (HT20)	1	2412	13.45	13±1	14	1.53	20	0.0071
		2437	12.62	12±1	13	1.53	20	0.0056
		2462	12.71	12±1	13	1.53	20	0.0056
802.11n (HT40)	1	2422	12.42	12±1	13	1.53	20	0.0056
		2437	12.89	12±1	13	1.53	20	0.0056
		2452	12.91	12±1	13	1.53	20	0.0056

Note:

N_{TX}= Number of Transmit Antennas

RF Output power specifies that Maximum Conducted Peak Output Power.

Remark:

1. Output power including turn-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.
4. Only the worst power was evaluated for each wireless function



6. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

7. Summary simultaneous transmission information

The sample supports two antennas for Bluetooth and WLAN. The Bluetooth and WLAN can transmit simultaneous. The Bluetooth and WLAN with two different antenna. According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;
 Σ of MPE ratios ≤ 1.0

8. Summary simultaneous transmission results

Bluetooth + 2.4G Wifi Maximum Simultaneous transmission MPE Ratios is
 $0.0007+0.0071=0.0078 \leq 1.0$.

9. Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----END OF REPORT-----

