

FCC §1.1307 (b) (3) & §2.1091- MPE-Based Exemption

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemptionfrom further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

| RF Source frequency (MHz) | Threshold ERP (watts) |
|---------------------------|--|
| 0.3-1.34 | 1,920 R ² . |
| 1.34-30 | 3,450 R ² /f ² . |
| 30-300 | 3.83 R ² . |
| 300-1,500 | 0.0128 R ² f. |
| 1,500-100,000 | 19.2R ² . |

R is the minimum separation distance in meters

f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Result

| Mode | Frequency (MHz) | Tune up conducted power | Antenna Gain | | ERP | | Evaluation Distance (m) | ERP Limit (W) |
|------------|-----------------|-------------------------|--------------|-------|-------|-------|-------------------------|---------------|
| | | (dBm) | (dBi) | (dBd) | (dBm) | (W) | | |
| BT | 2402-2480 | 1.0 | 2.12 | -0.03 | 0.97 | 0.001 | 0.2 | 0.768 |
| BLE | 2402-2480 | 5.5 | 2.12 | -0.03 | 5.47 | 0.004 | 0.2 | 0.768 |
| 2.4G Wi-Fi | 2412-2462 | 20.0 | 2.12 | -0.03 | 19.97 | 0.099 | 0.2 | 0.768 |
| 5G Wi-Fi | 5150-5250 | 15.0 | 2.48 | 0.33 | 15.33 | 0.034 | 0.2 | 0.768 |
| | 5250-5350 | 15.5 | 2.48 | 0.33 | 15.83 | 0.038 | 0.2 | 0.768 |
| | 5470-5725 | 11.5 | 2.48 | 0.33 | 11.83 | 0.015 | 0.2 | 0.768 |
| | 5725-5850 | 13.0 | 2.48 | 0.33 | 13.33 | 0.022 | 0.2 | 0.768 |

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.
 2. The BT can transmit at the same time with the Wi-Fi, the 2.4G Wi-Fi and 5G Wi-Fi cannot
 Simultaneous transmitting
 3. 0dBd=2.15dBi

Simultaneous transmitting consideration (worst case):

The ratio=ERP_{BLE}/limit+ERP_{Wi-Fi}/limit=0.004/0.768+0.099/0.768=0.134<1.0, so simultaneous exposure is compliant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.