

RF EXPOSURE EVALUATION

EUT Specification

EUT	Smart Plug Gen2
Model Number	3RSP02028BZ
FCC ID	2A898-3RSP02028BZ
Antenna gain (Max)	1.62dBi
Operation Frequency	2405-2480MHz
Input Rating	AC 100-120V, 15A MAX
Max. output power	11.35dBm(0.0136W)

Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF)

Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

11.1 Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm=20cm


Under the limit of MPE, $1\text{mW}/\text{cm}^2$. If we know the maximum gain of the antenna total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

Antenna gain: 1.62dBi

Mode	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (Numeric)	Evaluation result (mW/cm^2)	Power density Limits (mW/cm^2)
O-QPSK	2405	11.35	11±1	12	1.452	0.004578	1
O-QPSK	2440	11.11	11±1	12	1.452	0.004578	1
O-QPSK	2480	10.75	11±1	12	1.452	0.004578	1

Signature:



Tiger Xu

Date: 2022-11-14